



Pneumatic Catalogue 2012

Quick Coupling Systems for
Pneumatic and Fluid Handling

aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



ENGINEERING YOUR SUCCESS.

Structure of Part Numbers

Hose Connection

TF = Hose Barb
 TH = Hose Barb 45°
 TR = Hose Barb 90°
 TZ = Straight shaft parallel
 TP = for Parker plug-in Hose
 TS = Panel Mount with Hose Barb
 TD = Hose Barb DIN EN 560
 TE = Front Panel Installation, Hose Barb Panel Mount

Plastic Tube Connection

KO = with Hose Nut, without spring guard
 KR = 90° KO - connection
 KS = Panel mounted, without spring guard
 KK = with spring guard
 KE = Front panel installation with KO - connection
 KP = Plastic tube connection
 (hard plastic hoses, only for RECTUCHEM)

Other Connections

KL = Insert for plug-in connection
 PV = Fixing connection for PVC hoses
 DS = Double plug-in nipple
 PH = Parker 45°

Male Thread

AW = Whitworth pipe thread ISO 228 parallel
 AM = Metric thread DIN 13
 AK = Whitworth pipe thread DIN 2999 tapered
 AN = NPT thread ANSI B 1.20.1 tapered
 AD = Metric thread DIN 2353 (ISO 8434-1)
 WP = Whitworth pipe thread ISO 228 Serto Plan
 MP = Metric thread DIN 13 Serto Plan
 SW = Panel mount Whitworth pipe thread
 ISO 228 Serto Plan
 SM = Panel mount metric thread DIN 13 Serto Plan
 AL = Whitworth pipe thread ISO 228 parallel left
 AR = 90° Whitworth pipe thread DIN 2999 tapered
 AE = Front Panel Installation with Whitworth pipe
 thread ISO 228 parallel
 AJ = UNF thread (JIC) with 37° cone by SAE J 514

Female Thread

IW = Whitworth pipe thread ISO 228 parallel
 IM = Metric thread DIN 13
 IK = Whitworth pipe thread ISO 7 corresponding
 DIN 2999 tapered
 IN = NPSF-thread ANSI B 1.20.3
 IT = NPT thread tapered ANSI B 1.20.1
 IF = UNF-thread
 IL = Whitworth pipe thread ISO 228
 parallel left

Adding 1

S = Marking for special
 version
 0 = RECTUKey round
 3 = RECTUKey triangle
 6 = RECTUKey hexagon
 8 = RECTUKey octagon

21 KA AW 13 M P X X X

Series No:

Couplings

KA = Single Shut-Off
 KB = Double Shut-Off
 KF = Straight-Through
 KL = Dry-Break (double shut-off)
 KE = Self-Venting System
 KS = Safety (single shut-off)
 KD = Safety (double shut-off)
 KR = Safety (straight through)

Plugs

SF = Straight-Through
 SB = Double Shut-Off
 SL = Dry-Break (double shut-off)
 SS = Safety (straight-through)
 SD = Safety (double shut-off)
 SR = Recoil Eliminator

Metric Thread

05 = M5
 10 = M10 x 1
 12 = M12 x 1,5
 14 = M14 x 1,5
 16 = M16 x 1,5
 18 = M18 x 1,5

Thread Sizes

10 = 1/8"
 13 = 1/4"
 17 = 3/8"
 21 = 1/2"
 26 = 3/4"
 33 = 1"
 38 = 1 1/8"
 42 = 1 1/4"
 48 = 1 1/2"
 54 = 1 3/4"
 60 = 2"

Hose Connection

03 = for 3 mm LW (1/8")
 04 = for 4 mm LW (3/16")
 06 = for 5 mm LW (1/4")
 08 = for 8 mm LW (5/16")
 09 = for 9 mm LW (3/8")
 13 = for 13 mm LW (1/2")
 19 = for 19 mm LW (3/4")
 25 = for 25 mm LW (1")

Plastic Hose

04 = for 3 x 4 mm
 05 = for 3 x 5 mm
 36 = for 3 x 6,3 mm
 06 = for 4 x 6 mm
 46 = for 4 x 6,3 mm
 08 = for 6 x 8 mm
 10 = for 8 x 10 mm
 12 = for 9 x 12 mm
 16 = for 13 x 16 mm

Material

M = Brass CuZn39Pb3
 2.0401 (except sleeve)
 B = Brass CuZn39Pb3
 2.0401 (completely)
 S = Steel 9SMnPb28K
 1.0718
 R = Stainless Steel
 AISI 303
 H = Stainless Steel
 AISI 316 LMO
 E = Stainless Steel
 AISI 316 L
 K = Thermoplastics
 D = POM (Delrin)
 F = PVDF

Surface

X = without surface treatment
 N = Nickel plated
 C = Chrome plated
 Z = Zinc plated
 D = Durnicoated (chemic. zinc plated)
 B = Browning (steel black)
 G = Zinc plated and yellow chromated
 P = Passivated
 P = Pressure springs made of PEEK
 (only for RECTUCHEM+)
 F = chemically nickel plated and
 chrome plated (Flashchrome)
 S = zinc plated and black chromated

Seal

X = without seal
 P = Perbunan NBR
 V = FKM/FPM
 E = Ethylene-Propylene
 EPDM
 S = Silicone
 K = FFKM

Adding 2 Color coding for plastic

B = Blue
 G = Green
 R = Red
 Y = Yellow

Key to Symbols in Application Area



Machinery Construction



Electrical Engineering



Medical Technology



Mobile Hydraulics



Food Technology



Aeronautics



Safety Technology



Trade



Chemical Technology



Automotive

Important Notes:

- Please note that the technical data, specifications and drawings in the catalogue are not binding. This information is subject to change without notice in the interest of improvement.
- We reserve the right to make technical modifications for the purposes of improvement.
- April 2012: With the actual catalogue the older versions are no longer valid.
- The interchangeability is guaranteed under the assumption that the manufacturer of the relevant product has not changed any functional part in the meantime.
- You will find important safety instructions on pages 12 and 13.

ARE YOU HOPING TO FIND WITHOUT LOOKING? THEN WE HAVE JUST THE THING FOR YOU!

Low Pressure Systems

This chapter provides information on all coupling systems and accessory parts for use with pressures of up to 35 bar. These are primarily Rectus brand products – for use in the area of liquid and gaseous media.

Here you will also find our wide range of hoses for various applications.



Page 22 to 181

Brass/Steel

- Single Shut-Off Page 22 to 119
- Double Shut-Off Page 120 to 161
- Dry-Break Page 162 to 181

Page 182 to 235

Stainless Steel

- Single Shut-Off Page 182 to 199
- Double Shut-Off Page 200 to 221
- Dry-Break Page 222 to 235

Page 236 to 265

Thermoplastics

Page 266 to 299

Safety

- Single Shut-Off Page 266 to 275
- Double Shut-Off Page 276 to 279
- Self-Venting Page 280 to 295
- Breathing Air Page 296 to 299

Page 300 to 309

Coded Systems

Page 310 to 311

Measuring Systems

Page 312 to 339

Accessories

Page 340 to 359

Hoses and Tubing

- Nylon 12 Page 344 to 347
- Polyurethane Page 348 to 354
- PVC Page 355
- PVDF Page 356
- Accessories Page 357 to 359

YOU CAN NEVER HAVE TOO MANY GOOD CONNECTIONS.



Decades of experience in the construction and production of high quality coupling systems for the widest variety of media for pneumatic and fluid handling – that is what our customers value about us.


With the internationally established Rectus and Tema product brands, you can be certain that the know-how of our engineers is always available and reliable.



For decades, Rectus quick connect couplings have been a name for the highest precision and reliability. The low pressure systems are used in many sectors, primarily for compressed air, but also for connections with liquid media.



THE RIGHT SOLUTION FOR EVERY SECTOR!



Whether under water, in aerospace, on the high seas, on the street, or in industry – our quick connect coupling systems are at home in many domains and represent the right solution in numerous technical applications.


The modular structure of our series allows you to benefit from a wide standard range, which includes a suitable system for most applications – just-in-time goes without saying.



YOU KNOW YOUR APPLICATIONS, WE KNOW THE RIGHT COUPLING SYSTEM!

Industrial Sectors/ Application Areas	Straight Through KF	Single Shut-Off KA	Double Shut-Off KB	Dry-Break KL	Thermoplastic Couplings POM/PVDF	Stainless Steel Couplings	Safety Couplings	FlatFace Couplings
Compressed Air	●	●	○	○	○	○	●	○
Air	●	●	○	○	○	○	●	○
Breathing Air	○	○	●	○	○	○	●	○
Gases	○	○	●	○	○	○	●	○
Liquid Gases	○	○	●	○	○	○	●	○
Water*	●	●	●	●	○	○	○	○
Liquid Media	○	○	●	○	○	○	○	○
Aggressive Media	○	○	●	○	○	○	○	○
Chemicals	○	○	●	○	○	○	○	○
Machinery/Systems Manufacturing	○	○	○	○	○	○	○	○
Welding	○	○	○	○	○	○	○	○
Molding	○	○	○	○	○	○	○	○
Automation	○	○	○	○	○	○	○	○
Robotics	○	○	○	○	○	○	○	○
Textile Industry	○	○	○	○	○	○	○	○
Medical Equipment	○	○	○	○	○	○	○	○
Food and Beverage Industry	○	○	○	○	○	○	○	○
Chemical Industry	○	○	○	○	○	○	○	○
Pharmaceutical Industry	○	○	○	○	○	○	○	○
Laboratory	○	○	○	○	○	○	○	○
Analysis Technology	○	○	○	○	○	○	○	○
Steel Manufacturing	○	○	○	○	○	○	○	○
Raffineries	○	○	○	○	○	○	○	○
Paper Production	○	○	○	○	○	○	○	○
Rescue and Safety	○	○	○	○	○	○	○	○
Aerospace Technology	○	○	○	○	○	○	○	○
Shipyards	○	○	○	○	○	○	○	○
Semiconductor Technology	○	○	○	○	○	○	○	○
Laser Technology	○	○	○	○	○	○	○	○
Nuclear Power	○	○	○	○	○	○	○	○

* only systems with valve and sleeve made of brass



COUPLING QUICKLY AND SAFELY WITH ONE HAND!


The development of the single-hand quick connect coupling made a decisive contribution to improving work safety and functionality. In order to create a connection, the plug is simply pushed into the coupling. This causes

the sleeve to spring forward and lock automatically. When uncoupling, the sleeve is pushed back with one hand and the disconnection is easy. The following valve designs are available for selection for different applications:

Straight-Through

These coupling systems work with no shut-off valve, which means they can achieve the greatest possible flow. Further, turbulence which can occur with integrated valves is


completely eradicated. Straight-through couplings are ideally suited to liquid media – e.g. water applications. Before unlocking, the flow must be stopped.



Single Shut-Off

On our single shut-off systems, the plug is designed straight-through – although the coupling shuts off immediately when the connection is broken.


Appearance of on-flow media in the line is effectively prevented. An ideal solution for operating compressed air tools.



Double Shut-Off

On our double shut-off systems, after disconnection, the flow stops both in the coupling and in the plug.

The medium remains in the hose in both connecting lines, the pressure is held constant and not released.



Dry-Break Design

Our leak-free coupling systems have valves on the coupling and plug that build up no dead-space volume. Thus, when the connection is broken, no drops of the medium can

escape. This variant is especially suitable for transferring aggressive media or in sensitive environments such as cleanrooms.



WE SET STANDARDS IN QUALITY AND SAFETY.



Around the world highly qualified specialists are working to secure and optimise the quality of our products. Nothing will deter them from the high demands which they set themselves – as all employees know, we can only retain our top international position by constant top performance. With the help of controlled manufacturing processes and up to the minute precision technology, it is the person - as a creative and experienced

technical, sales man and customer adviser – who is responsible for this. All stages of production are subject to proven and comprehensive quality management. Certificates and test reports from the most important independent institutes confirm our excellent functionality and production quality. For our customers, this means: greater safety and reliability – even in extreme conditions.



DIN EN ISO 9001:2000
Reg.Nr. 1070
Qualitätsmanagementsystem





FROM STANDARD PRODUCT TO BESPOKE SYSTEM SOLUTION.


Our standard catalogue range offers the right coupling for most application areas. Many of these standard items come from previous special solutions which we later integrated into serial production. Developing special solutions for particular tasks is one of our strengths – and an advantage which you can use at any time. Our competent specialists will be pleased to visit you to establish your

specific requirements and wishes. We will then recommend adaptation of one of our standard products, or new design of a bespoke individual solution for you. At the end, we will provide you with a functional system that is exactly suited to your requirements – both technologically and economically. Get in touch – we will be pleased to advise you specifically.



From Mini to Maxi

Our innovations are impressive: from the smallest quick connect coupling in the world to the large ISO-B-Couplingsysteme in nominal diameter 20 mm.



SEALING AND ACCURACY.

A coupling system is always as good as its sealing components. That is why we only use top quality, proven standards, which have been tried and tested time and again. For special applications, please also ask our specialist advisers, as an important criterium

for functionality of an O-ring is the type of medium in relation to its temperature. In accordance with these parameters, we can recommend the right type of seal and will be pleased to carry out specific tests with you.

The most important sealants

Sealing-Material	Brand	Temperature-Range	Features
NBR Acrylonitrile-Butadiene Rubber	Buna N	-20°C - +100°C	Can be used for compressed air. Resistant to heat and many liquids, e.g. mineral oils, fuel (no environmental diesel), water glycol and grease.
EPDM Ethylene Propylene Diene Rubber		-50°C - +150°C	Heat resistant and specially suited to hot water and steam. Good resistance to brake oils, glycol and fire-resistant oils. Not suitable for mineral-based oils and petrol.
FKM Fluorocarbon Rubber	Viton® ¹⁾	-15°C - +200°C	Very high resistance to heat and liquids inc. petrol, oils, environmental diesel, grease and aromatic oils.
FFKM Perfluoro Rubber	Kalrez® ²⁾	-25°C - +240°C	Universal chemical resistance, good for aggressive media, high thermal resistance. Lowest source values for all media.

¹⁾ Viton® is a registered trademark of DuPont Dow Elastomers.

²⁾ Kalrez® is a registered trademark of DuPont Dow Elastomers.

WITH US, YOU CAN WORK IN ANY UNITS.

Conversion of temp. units

°F	→ °C	°C	→ °F
-40	-40,0	-40	-40
-35	-37,2	-35	-31
-30	-34,4	-30	-22
-25	-31,7	-25	-13
-20	-28,9	-20	-4
-15	-26,1	-17,8	0
-10	-23,3	-15	+5
-5	-20,6	-10	+14
0	-17,8	-5	+23
+5	-15,01	0	+32
+10	-12,2	+5	+41
+15	-9,4	+10	+50
+20	-6,7	+15	+59
+25	-3,9	+20	+68
+30	-1,1	+25	+77
+32	0,0	+30	+86
+35	+1,7	+35	+95
+40	+4,4	+40	+104
+45	+7,2	+45	+113
+50	+10,0	+50	+122
+55	+12,8	+55	+131
+60	+15,6	+60	+140
+65	+18,3	+65	+149
+70	+21,1	+70	+158
+75	+23,9	+75	+167
+80	+26,7	+80	+176
+85	+29,4	+85	+185
+90	+32,2	+90	+194
+95	+35,0	+95	+203
+100	+37,8	+100	+212
+105	+40,6	+105	+221
+110	+43,3	+110	+230
+115	+46,1	+115	+239
+120	+48,9	+120	+248
+125	+51,7	+125	+257
+130	+54,4	+130	+266
+135	+57,2	+135	+275
+140	+60,0	+140	+284
+145	+62,8	+145	+293
+150	+65,6	+150	+302
+155	+68,3	+155	+311
+160	+71,1	+160	+320
+165	+73,9	+165	+329
+170	+76,7	+170	+338
+175	+79,4	+175	+347
+180	+82,2	+180	+356
+185	+85,0	+185	+365
+190	+87,8	+190	+374
+195	+90,6	+195	+383
+200	+93,3	+200	+392
+205	+96,1	+205	+401
+210	+98,9	+210	+410
+215	+101,7	+215	+419
+220	+104,4	+220	+428
+225	+107,2	+225	+437
+230	+110,0	+230	+446
+235	+112,8	+235	+455
+240	+115,6	+240	+464
+245	+118,3	+245	+473
+250	+121,1	+250	+482

Conversion of flow rate units

l/min	→ Cfm	→ m³/h
100	4	6
200	7	12
300	11	18
400	14	24
600	21	36
800	28	48
1000	35	60
1200	42	72
1400	49	84
1600	57	96
1800	64	108
2000	71	120
2200	78	132
2400	85	144
2600	92	156
2800	99	168
3000	106	180
3300	117	198
3600	127	216
3900	138	234
4200	148	252
4500	159	270
4800	170	288
5100	180	306
5400	191	324
5700	201	342
6000	212	360
6300	222	378
6600	233	396
6900	244	414
7200	254	432
7500	265	450
7800	275	468
8000	283	480

Thread dimensions in mm

Pipe thread according to ISO 228

Nominal thread size	Outer-Ø d (mm)	Core-Ø d ₁ (mm)
1/16	7,723	6,561
1/8	9,728	8,566
1/4	13,157	11,445
3/8	16,662	14,950
1/2	20,955	18,631
5/8	22,911	20,587
3/4	26,441	24,117
7/8	30,201	27,877
1	33,249	30,291
1 1/8	37,897	34,939
1 1/4	41,910	38,952
1 1/2	47,803	44,845
1 3/4	53,746	50,788
2	59,614	56,656
2 1/4	65,710	62,752
2 1/2	75,184	72,226
2 3/4	81,534	78,576

Conversion of pressure units

bar	PSI	MPa	PSI	bar	MPa
1	14,5	0,1	15	1,0	0,10
3	43,5	0,3	50	3,5	0,35
6	87,0	0,6	75	5,2	0,52
8	116,0	0,8	100	6,9	0,69
10	145,0	1,0	125	8,6	0,86
12	174,0	1,2	150	10,3	1,03
15	217,5	1,5	175	12,1	1,21
20	290,0	2,0	200	13,8	1,38
25	363,0	2,5	250	17,2	1,72
30	435,0	3,0	300	20,7	2,07
35	508,0	3,5	400	27,6	2,76
50	725,0	5,0	500	34,5	3,45
70	1015,0	7,0	750	51,7	5,17
100	1450,0	10,0	1000	69,0	6,90
150	2175,0	15,0	1500	103,4	10,34
200	2900,0	20,0	2000	137,9	13,79
250	3625,0	25,0	3000	206,8	20,68

Vacuum units

Vacuum (%)	Absolute press. (mbar)	Neg. press. (mbar)	Neg. press. (mm Hg)
0	1000	0	0
10	900	-100	-75
13,3	867	-133	-100
20	800	-200	-150
26,7	733	-267	-200
30	700	-300	-225
40	600	-400	-300
50	500	-500	-375
53,3	467	-533	-400
60	400	-600	-450
66,7	333	-667	-500
70	300	-700	-525
80	200	-800	-600
90	100	-900	-675
92	80	-920	-690
100	0	-1000	-760

SAFETY GUIDE FOR SELECTING AND USING QUICK CONNECT COUPLINGS AND RELATED ACCESSORIES

DANGER: failure or improper selection or improper use of quick connect couplings or related accessories can cause death, personal injury and property damage. Possible consequences of failure or

- Couplings or parts thrown off at high speed
- High velocity fluid discharge
- Contact with suddenly moving or falling objects that are to be held in position or moved by the conveyed fluid
- Dangerously whipping hose

improper selection or improper use of quick connect couplings or related accessories include but are not limited to:

- Explosion or burning of the conveyed fluid
- Contact with conveyed fluids that may be hot, cold, toxic, or otherwise injurious
- Sparking or explosion while paint or flammable liquid spraying

Before selecting or using any Parker RectusTema quick connect couplings or related accessories, it is important that you read and follow the following instructions.

1.0 GENERAL INSTRUCTIONS

1.1 Scope: this catalogue provides instructions for selecting and using (including installing connecting, disconnecting, and maintaining) quick connect couplings and related accessories (including caps, plugs, hoses, blow guns). This safety instruction is a supplement to and is to be used with the specific Parker publications for the specific quick connect couplings and related accessories that are being considered for use.

1.2 Fail-Safe: quick connect couplings or the hose they are attached to can fail without warning for many reasons. Design all systems and equipment in a fail-safe mode, so that failure of the quick connect coupling or hose will not endanger persons or property.

1.3 Distribution: provide a copy of this safety guide to each person who is responsible for selecting or using quick connect coupling products. Do not select or use quick connect couplings without thoroughly reading and understanding this safety guide as well as the specific Parker publications for the products considered or selected.

1.4 User responsibility: due to the wide variety of operating conditions and uses for quick connect couplings, Parker RectusTema and its distributors do not represent or warrant that any particular coupling system is suitable for any specific end use system. This safety instructions do not analyse all technical parameters that must be considered in selecting a product. The user, through its own analysis and testing, is solely responsible for:

- Making the final selection of the quick connect couplings.
- Assuring that the user's requirements are met and that the use presents no health or safety hazards.
- Providing all appropriate health and safety warnings on the equipment on which the quick connect couplings are used.

1.5 Additional questions: call the appropriate Parker customer service department if you have any questions or require any additional information. For the telephone numbers of the appropriate customer service department, see the Parker publication for the product being considered or used.

2.0 SELECTION INSTRUCTIONS

2.1 Pressure: quick connect couplings selection must be made so that the published rated pressure of the coupling is equal to or greater than the maximum system pressure. Pressure surges in the system higher than the rated pressure of the coupling will shorten the quick connect coupling's life. Do not confuse burst pressure or other pressure values with rated pressure and do not use burst pressure or other pressure values for this purpose.

2.2 Fluid compatibility: quick connect couplings selection must assure compatibility of the body and seal materials with the fluid media used. See the fluid compatibility chart.

2.3 Temperature: be certain that fluid and ambient temperatures, both steady and transient, do not exceed the limitations of the quick connect couplings. Use caution and hand protection when connecting or disconnecting quick connect couplings that are heated or cooled by the media they are conducting or by their environment.

2.4 Size: transmission or power by means of pressurised liquid varies with pressure and rate of flow. The size of the quick connect couplings and other components of the system must be adequate to keep pressure losses to a minimum and avoid damage due to heat generation or excessive fluid velocity.

2.5 Pressurised connection or disconnection: if connecting or disconnecting under pressure is a requirement, use only quick connect couplings designed for that purpose. The rated operating pressure of a quick connect coupling may not be the pressure at which it may be safely connected or disconnected.

2.6 Environment: care must be taken to ensure that quick connect couplings are either compatible with or protected from the environment (that is, surrounding conditions) to which they are exposed. Environmental conditions including but not limited to ultraviolet radiation, ozone, moisture, water, salt water, chemicals, and air pollutants can cause degradation and premature failure.



2.7 Locking means: ball locking quick connect couplings can unintentionally disconnect if they are dragged over obstructions on the end of a hose or if the sleeve is bumped or moved enough to cause disconnection. Sleeves designed with flanges to provide better gripping for oily or gloved hands are especially susceptible to accidental disconnection and should not be used where these conditions exist. Sleeve lock or union (threaded) sleeve designs should be considered where there is a potential for accidental uncoupling.

2.8 Mechanical loads: external forces can significantly reduce quick connect couplings' life or cause failure. Mechanical loads which must be considered include excessive tensile or side loads and vibration. Unusual applications may require special testing prior to quick connect couplings selection.

2.9 Specifications and standards: when selecting quick connect couplings, government, industry and Parker specifications must be reviewed and followed as applicable.

2.10 Vacuum: not all quick connect couplings are suitable or recommended for vacuum service. Quick connect couplings used for vacuum applications must be selected to ensure that the quick connect couplings will withstand the vacuum and pressure of the system.

2.11 Fire resistant fluids: some fire resistant fluids require seals other than the standard NBR (nitrile) used in many coupling systems.

2.12 Radiant heat: quick connect couplings can be heated to destruction or loss of sealing without contact by such nearby items as hot manifolds or molten metal. The same heat source may then initiate a fire. This can occur despite the presence of cool air around the quick connect couplings.

2.13 Welding and brazing: heating of plated parts, including quick connect couplings and port adapters, above 450 °F (232 °C) such as during welding, brazing, or soldering may emit deadly gases and may cause coupling seal damage.

3.0 INSTALLATION INSTRUCTIONS

3.1 Pre-installation inspection: before installing a quick connect coupling, visually inspect it and check for correct style, body material, seal material, and catalogue number. Before final installation, coupling halves should be connected and disconnected with a sample of the mating half with which they will be used.

3.2 Quick connect coupling halves from other manufacturers: if a quick connect coupling assembly is made up of one Parker RectusTema half and one half from another manufacturer, the lowest pressure rating of the two halves should not be exceeded.

3.3 Fitting installation: use a thread sealant, when assembling taper pipe thread joints in quick connect couplings. Be sure the sealant is compatible with the system fluid or gas. To avoid system contamination, use a liquid or paste type sealant rather than a tape style. Use the flats provided to hold the quick connect coupling when installing fittings. Do not use pipe wrenches or a vice on other parts of the coupling to hold it when installing or a removing fittings as damage or loosening of threaded joints in the coupling assembly could result. Do not apply excessive torque to taper pipe threads because cracking or splitting of the female component can result.

3.4 Caps and plugs: use dust caps and plugs when quick connect couplings are not coupled to exclude dirt and contamination and to protect critical surfaces from damage.

3.5 Coupling location: locate quick connect couplings where they can be reached for connection or disconnection without exposing the operator to slipping, falling, getting sprayed or coming in contact with hot or moving parts.

3.6 Hose whips: use a hose whip (a short length of hose between the tool and the coupling half) instead of rigidly mounting a coupling half on hand tools or other devices. This reduces the potential for coupling damage if the tool is dropped and provides some isolation from mechanical vibration which could cause uncoupling.

4.0 MAINTENANCE INSTRUCTIONS

4.1 Even with proper selection and installation, quick connect coupling life may be significantly reduced without a continuing maintenance program. Frequency should be determined by the severity of the application and risk potential. A maintenance program must be established and followed by the user and must include the following as a minimum:

4.2 Visual inspection of quick connect couplings: any of the following conditions require immediate shut down and replacement of the quick connect coupling:

- Cracked, damaged, or corroded quick connect couplings parts.
- Leaks at the fitting, valve or mating seal.
- Broken coupling mounting hardware, especially breakaway clamps.

4.3 Visual inspection all other:

- Leaking seals or port connections.
- Excess dirt build-up on the coupling locking means or on the interface area of either coupling half.
- Defective clamps, guards, and shields.
- System fluid level, fluid type and any entrapment.

4.4 Functional test: operate the system at maximum operating pressure and check for possible malfunctions and freedom from leaks. Personnel must avoid potential hazardous areas while testing and using the system.

4.5 Replacement intervals: specific replacement intervals must be considered based on previous service life, government or industry recommendations, or when failures could result in unacceptable downtime, damage or injury risk. See instruction 1.2 above.

LOW PRESSURE SYSTEMS. PROVEN, TOP QUALITY RECTUS SOLUTIONS.

Depending on the design, our connecting elements for the low pressure range up to 35 bar are suitable for gaseous (compressed air) or liquid media (water, chemistry). In our standard range, you will find solutions for the widest variety of applications.

e. g. Rectus Series 21KA

This successful small-dimensioned coupling is available as a single-hand quick connect system in numerous design and material qualities.

Nominal Diameter/Flow

The nominal diameter corresponds to the free internal diameter of the coupling or plug. Normally, the internal diameter of the front plug area is measured. Due to the integrated valve, plugs on double shut-off couplings have a smaller internal diameter than the coupling, thus the effective nominal diameter is smaller. The nominal diameter gives a rough idea of size for flow in a coupling-plug combination. The real flow is always dependent on the nominal diameter, in connection with the flowpreferential shape of a system.

up to **35** bar



Material Properties

Brass:

Corrosion resistant for compressed air and water applications, medium strength, anti-magnetic, high resistance to organic liquids, good surface quality, exemplary recyclability.

Steel:

High surface hardness, curable material for high loads, magnetic.

Stainless steel AISI 303 (V2A):

Corrosion resistant, good strength, only slightly magnetic.

Stainless steel AISI 316 L (V4A):

Highly corrosion resistant, good strength, only slightly magnetic.

POM thermoplastics:

Good strength and resistance for standard applications.

PVDF thermoplastics:

Medium strength with good general resistance. Especially good temperature and UV resistance, easy to sterilise (autoclave).

PVDF+ thermoplastics:

The springs in these PVDF couplings are made of the material PEEK. The mechanical properties are significantly improved, the size of the springs can be reduced. Pressure range from 1 bar.

Brass/Steel

from page 22

- Single Shut-Off Page 22 to 119
- Double Shut-Off Page 120 to 161
- Dry-Break Page 162 to 181

Stainless steel

from page 182

- Single Shut-Off Page 182 to 199
- Double Shut-Off Page 200 to 221
- Dry-Break Page 222 to 235

Thermoplastics

Single/Double Shut-Off

from page 236

Safety

from page 266

- Single Shut-Off Page 266 to 275
- Double Shut-Off Page 276 to 279
- Self-Venting Page 280 to 295
- Breathing Air Page 296 to 299

Coded Systems

Single/Double Shut-Off

from page 300

Measuring Systems

from page 310

Accessories

from page 312

Hoses and Tubing

from page 340

- Nylon 12 Page 344 to 347
- Polyurethane Page 348 to 354
- PVC Page 355
- PVDF Page 356
- Accessories Hoses Page 357 to 359

ALL OUR PERFORMANCE CAPACITY AT A GLANCE.

Using this flow quantity diagram, find the right Rectus coupling series for your application – and at a glance! At the same time, we demonstrate the profile-specific compatibility/interchangeability with other Rectus products and foreign makes.

- Single Shut-Off
- Double Shut-Off
- Dry-Break Version


Flow quantity – air
Litres/minute*


*(Measurement data generated in accordance with ISO 6358; CCTOP RP50P at input pressure 6 bar, pressure drop 0.5 bar)

- Thermo-oil
- Mold Connections/Straight-Through

Flow quantity – oil/water
Litres/minute*

*(Measurement data generated in accordance with ISO 7241/2:2000, pressure drop 0.5 bar)





Series
Nominal Plug Bore


- Brass/Steel
- Stainless Steel
- Thermo-plastics
- Safety
- Thermo-oil

Interchangeable with

FROM PLUG TO BEST COUPLING SYSTEM.

Using the plug profiles shown below, the corresponding coupling systems are easy to determine.

RECTUS Plug Profiles





206SL

31SF

**51SF
51SB**

**52SF
52SB**

48SF

**25SF
26SF
25SB
26SB
26SL
25SL**

95SS

96SS



32SF

34SF

28SS

37SF

57SF

**38SF
38SB**

**39SF
39SB
39SL**

ABOVE ALL ELSE, OUR SYSTEMS OFFER YOU GREATER SAFETY.

Safety-Couplings

We consider that protecting people and material surfaces is an important issue. For use mainly in danger areas with high safety requirements, we have developed coupling systems with safety locks.




Self-Venting-Couplings

A patented single-hand self-venting technique with 2 separate locking systems makes it possible to vent automatically before uncoupling. Plastic sleeves prevent surface scratches. Application area exclusive to compressed air.




Valves


Depending on application area, our coupling systems are available with free flow, single or double shut-off, and in leak free design. A test of various valve types is recommended before ordering large quantities.



RectuLoc


With the introduction of this innovative sealing system, we have finally eliminated laborious sealing with angel hair or plastic tape. Ball threads can be coated with RectuLoc on request, cylindrical threads can be supplied with a RectuLoc seal.






RectuKey

This coded coupling system completely eliminates confusion of different media. The structure and color of the couplings and plugs is differentiated – this makes wrong coupling impossible.



UltraFlo

The flow-favourable UltraFlo valve is a Rectus development, which increases the flow by up to 80% compared with conventional systems. Supply to compressed air tools is improved and energy costs are reduced. Can be supplied e.g. with the series 25 and 27 premium coupling systems.




Materials

For almost all application cases, Rectus supplies the ideal combination of material and technology. Brass/steel products, various stainless steels, thermoplastics or mixed materials such as steel/plastic are all in the range and can be ordered specifically for the application.



Surfaces

Our coupling systems can be supplied with additional coating refinements, resistant to corrosion or aggressive media and specific to your requirements. Please ask your specialist adviser for special requirement profiles. We will test the appropriate solution for you.



Nominal Diameter

1,5 = 1,8 mm²

RECTUS Series

02KA



actual size



Technical Description

Smallest mini industrial coupling, suitable for air and gas applications. Primarily in medicine, didactics and model building. Specific application for liquids due to size.

Advantages

Single handed operation.
Extremely small dimensions.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor 4 to 1.

Interchangeability



RECTUS Design

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug


Plug

Brass


Brass, Nickel Plated

Couplings

RECTUS Series 02KA



Male Thread





Female Thread

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
Male Thread	M 3	6	19	6,5	3					Standard	02KA AM03 MPX
										Nickel Plated	02KA AM03MPN
Female Thread	M 3	6	19	6,5	3					Standard	02KA IM03 MPX
										Nickel Plated	02KA IM03 MPN



Couplings

RECTUS Series 02KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	2 mm	6	21	6,5	5,5					Standard	02KA TF02 MPX
										Nickel Plated	02KA TF02 MPN
	3 mm	6	22	6,5	6,5					Standard	02KA TF03 MPX
										Nickel Plated	02KA TF03 MPN
 <p>Panel Mount, Hose Barb</p>	2 mm	7	29	6,5	5,5	8	7	3	M 5	Standard	02KA TS02 MPX
										Nickel Plated	02KA TS02 MPN
	3 mm	7	30	6,5	6,5	8	7	3	M 5	Standard	02KA TS03 MPX
										Nickel Plated	02KA TS03 MPN



Plugs


RECTUS Series 02KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	2 mm		12	4	5,5					Standard	02SF TF02 MXX
										Nickel Plated	02SF TF02 MXN
	3 mm		13	5	6,5					Standard	02SF TF03 MXX
 <p>Panel Mount, Hose Barb</p>	2 mm	7	22		5,5	8	7	3	M 5	Standard	02SF TS02 MXX
										Nickel Plated	02SF TS02 MXN
	3 mm	7	23		6,5	8	7	3	M5	Standard	02SF TS03 MXX
										Nickel Plated	02SF TS03 MXN

Plugs

RECTUS Series 02KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	M 3	6	11		3					Standard	02SF AM03 MXX
										Nickel Plated	02SF AM03 MXN
 <p>Female Thread</p>	M 3	6	10		3					Standard	02SF IM03 MXX
										Nickel Plated	02SF IM03 MXN



Nominal Diameter

2,5 = 5 mm²

RECTUS Series

50KA



actual size



Technical Description

Mini industrial coupling, can be used with various media. Extremely easy to operate.

Advantages

Single handed operation. Small installation dimensions.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability



WALTHER LP002

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug


Plug

Brass

Brass, Nickel Plated

Couplings

RECTUS Series 50KA



Male Thread



Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	36	16	7					Standard	50KA AW10 MPXS
									Nickel Plated	50KA AW10 MPNS
G 1/4	17	38	16	9					Standard	50KA AW13 MPXS
									Nickel Plated	50KA AW13 MPNS

Couplings

RECTUS Series 50KA


Brass/Steel

Low Pressure

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 1/8	14	36	16	9					Standard	50KA IW10 MPXS
										Nickel Plated	50KA IW10 MPNS
	G 1/4	17	38	16	9					Standard	50KA IW13 MPXS
										Nickel Plated	50KA IW13 MPNS
 <p>Hose Barb</p>	4 mm	14	46	16	17					Standard	50KA TF04 MPXS
										Nickel Plated	50KA TF04 MPNS
	6 mm	14	46	16	17					Standard	50KA TF06 MPXS
										Nickel Plated	50KA TF06 MPNS
	9 mm	14	46	16	17					Standard	50KA TF09 MPXS
										Nickel Plated	50KA TF09 MPNS
	10 mm	14	46	16	17					Standard	50KA TF10 MPXS
										Nickel Plated	50KA TF10 MPNS



Plugs

RECTUS Series 50KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	4 mm	7	35		13					Standard	50SF TF04 MXX
										Nickel Plated	50SF TF04 MXN
	6 mm	7	35		13					Standard	50SF TF06 MXX
										Nickel Plated	50SF TF06 MXN

Plugs

RECTUS Series 50KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14	30		7					Standard	50SF AW10 MXX
										Nickel Plated	50SF AW10 MXN
 <p>Female Thread</p>	G 1/8	14	30		7					Standard	50SF IW10 MXX
										Nickel Plated	50SF IW10 MXN

⚠ Please consider our security advices on the pages 12/13 ⚠



Nominal Diameter

2,7 = 6 mm²

RECTUS Series

20KA



actual size



Technical Description

Mini industrial coupling, internationally used profile. Notable for a high flow and numerous application options with various media. Frequent use in mini-pneumatics, medical technology and chemistry/pharmacy.

Advantages

Single handed operation.
Small dimensions.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability



RECTUS 91
WALTHER 06-003

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Double Shut-off P. 120
- ▶ Stainless Steel P. 182

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug

Brass

Brass, Nickel Plated

Couplings

RECTUS Series 20KA






	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	M 5	9	26	10	5					Standard	20KA AM05 MPX
										Nickel Plated	20KA AM05 MPN
<p>Female Thread</p>	G 1/8	11	28	10	7					Standard	20KA AW10 MPX
										Nickel Plated	20KA AW10 MPN
	M 5	9	26	10	5					Standard	20KA IM05 MPX
										Nickel Plated	20KA IM05 MPN
	G 1/8	12	28	10	7					Standard	20KA IW10 MPX
										Nickel Plated	20KA IW10 MPN

Couplings

RECTUS Series 20KA





Brass/Steel



Low Pressure


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	3 mm		35	10	13					Standard	20KA TF03 MPX
										Nickel Plated	20KA TF03 MPN
	4 mm		35	10	13					Standard	20KA TF04 MPX
										Nickel Plated	20KA TF04 MPN
	5 mm		34	10	13					Standard	20KA TF05 MPX
										Nickel Plated	20KA TF05 MPN
 <p>Plastic Hose Connection</p>	3 x 4 mm	9	34	10	7	5		M 7 x 0,5	Standard	20KA KO04 MPX	
										Nickel Plated	20KA KO04 MPN
	3 x 5 mm	9	34	10	7	5		M 7 x 0,5	Standard	20KA KO05 MPX	
										Nickel Plated	20KA KO05 MPN
	4 x 6 mm	9	34	10	7	5		M 8 x 0,5	Standard	20KA KO06 MPX	
										Nickel Plated	20KA KO06 MPN
 <p>Panel Mount, Plastic Hose Connection</p>	3 x 4 mm	12	45	10	7	17	11	3	M 7 x 0,5	Standard	20KA KS04 MPX
										Nickel Plated	20KA KS04 MPN
	3 x 5 mm	12	45	10	7	17	11	3	M 7 x 0,5	Standard	20KA KS05 MPX
										Nickel Plated	20KA KS05 MPN
	4 x 6 mm	12	45	10	7	12	11	3	M 8 x 0,5	Standard	20KA KS06 MPX
										Nickel Plated	20KA KS06 MPN
 <p>Panel Mount, Hose Barb</p>	3 mm	12	51	10	13	17	11	3	M 7 x 0,5	Standard	20KA TS03 MPX
										Nickel Plated	20KA TS03 MPN
	4 mm	12	51	10	13	17	11	3	M 7 x 0,5	Standard	20KA TS04 MPX
										Nickel Plated	20KA TS04 MPN
	6 mm	12	51	10	13	17	12	3	M 10 x 1	Standard	20KA TS06 MPX
										Nickel Plated	20KA TS06 MPN
 <p>Push-In</p>	4 mm	10	35	10						Standard	20KA RP04 MPN

Plugs

RECTUS Series 20KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	3 mm		24	7	13					Standard	20SF TF03 MXX
										Nickel Plated	20SF TF03 MXN
	4 mm		24	7	13					Standard	20SF TF04 MXX
										Nickel Plated	20SF TF04 MXN
	5 mm		22	9	13					Standard	20SF TF05 MXX
										Nickel Plated	20SF TF05 MXN
 <p>Plastic Hose Connection</p>	3 x 4 mm	7	25		7	5			M 7 x 0,5	Standard	20SF KO04 MXX
										Nickel Plated	20SF KO04 MXN
	3 x 5 mm	7	25		7	5			M 7 x 0,5	Standard	20SF KO05 MXX
										Nickel Plated	20SF KO05 MXN
	4 x 6 mm	8	25		7	5			M 8 x 0,5	Standard	20SF KO06 MXX
										Nickel Plated	20SF KO06 MXN
 <p>Panel Mount, Plastic Hose Connection</p>	3 x 4 mm	11	38		7	17	11	3	M 7 x 0,5	Standard	20SF KS04 MXX
										Nickel Plated	20SF KS04 MXN
	3 x 5 mm	11	38		7	17	11	3	M 7 x 0,5	Standard	20SF KS05 MXX
										Nickel Plated	20SF KS05 MXN
	4 x 6 mm	12	38		7	17	12	3	M 8 x 0,5	Standard	20SF KS06 MXX
										Nickel Plated	20SF KS06 MXN
 <p>Panel Mount, Hose Barb</p>	3 mm	12	45		13	18	11	3,5	M 7 x 0,5	Standard	20SF TS03 MXX
										Nickel Plated	20SF TS03 MXN
	4 mm	12	45		13	17	11	3	M 7 x 0,5	Standard	20SF TS04 MXX
										Nickel Plated	20SF TS04 MXN
	4 mm	10	35	10						Nickel Plated	20SF RP04 MPN

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	M 5	7	18		5					Standard	20SF AM05 MXX
										Nickel Plated	20SF AM05 MXN
	G 1/8	11	20		7					Standard	20SF AW10 MXX
										Nickel Plated	20SF AW10 MXN
	M 5	7	17		5					Standard	20SF IM05 MXX
										Nickel Plated	20SF IM05 MXN
 <p>Female Thread</p>	G 1/8	12	19		7					Standard	20SF IW10 MXX
										Nickel Plated	20SF IW10 MXN



Nominal Diameter

2,7 = 6 mm²

RECTUS Series

91KA



actual size

**Technical Description**

The 91 series is a variation of the 20 series couplings. The valve has been shortened in respect that the plug seals before the coupling valve opens. In spite of the short valve the well-proven single hand operation is retained, as the ball-lock is replaced by a pin-lock. This extends the external diameter of the sleeve from 10 to 13 mm.

Advantages

Single handed operation. No loss through leakage during coupling.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.



Interchangeability

RECTUS 20
WALTHER 06-003

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart**Material****Coupling**

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Pins
Seals

Standard

Brass
Brass
Brass
Brass
AISI 303
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug

Brass





Brass, Nickel Plated

Couplings**RECTUS Series 91KA**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	M 5	9	26	13	5					Standard	91KA AM05 MPX
										Nickel Plated	91KA AM05 MPN
	G 1/8	11	28	13	7					Standard	91KA AW10 MPX
										Nickel Plated	91KA AW10 MPN
<p>Female Thread</p>	M 5	9	25	13	5					Standard	91KA IM05 MPX
										Nickel Plated	91KA IM05 MPN
	G 1/8	12	28	13	7					Standard	91KA IW10 MPX
										Nickel Plated	91KA IW10 MPN
<p>Hose Barb</p>	4 mm		35	13	13					Standard	91KA TF04 MPX
										Nickel Plated	91KA TF04 MPN



Plugs


RECTUS Series 91KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Hose Barb</p>	3 mm		24	7	13					Standard	20SF TF03 MXX	
										Nickel Plated	20SF TF03 MXN	
	4 mm		24	7	13					Standard	20SF TF04 MXX	
										Nickel Plated	20SF TF04 MXN	
	5 mm		22	9	13					Standard	20SF TF05 MXX	
										Nickel Plated	20SF TF05 MXN	
 <p>Plastic Hose Connection</p>	3 x 4 mm	7	25		7	5			M 7 x 0,5	Standard	20SF KO04 MXX	
										Nickel Plated	20SF KO04 MXN	
	3 x 5 mm	7	25		7	5			M 7 x 0,5	Standard	20SF KO05 MXX	
										Nickel Plated	20SF KO05 MXN	
	4 x 6 mm	8	25		7	5			M 8 x 0,5	Standard	20SF KO06 MXX	
										Nickel Plated	20SF KO06 MXN	
 <p>Panel Mount Plastic Hose Connection</p>	3 x 4 mm	11	38		7	17	11	3	M 7 x 0,5	Standard	20SF KS04 MXX	
										Nickel Plated	20SF KS04 MXN	
	3 x 5 mm	11	38		7	17	11	3	M 7 x 0,5	Standard	20SF KS05 MXX	
										Nickel Plated	20SF KS05 MXN	
	4 x 6 mm	12	38		7	17	12	3	M 8 x 0,5	Standard	20SF KS06 MXX	
										Nickel Plated	20SF KS06 MXN	
 <p>Panel Mount, Hose Barb</p>	3 mm	12	45		13	18	11	4	M 7 x 0,5	Standard	20SF TS03 MXX	
										Nickel Plated	20SF TS03 MXN	
	4 mm	12	45		13	17	11	3	M 7 x 0,5	Standard	20SF TS04 MXX	
										Nickel Plated	20SF TS04 MXN	

Plugs

RECTUS Series 20SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	M 5	7	18		5					Standard	20SF AM05 MXX
										Nickel Plated	20SF AM05 MXN
	G 1/8	11	20		7					Standard	20SF AW10 MXX
										Nickel Plated	20SF AW10 MXN
 <p>Female Thread</p>	M 5	7	17		5				Standard	20SF IM05 MXX	
										Nickel Plated	20SF IM05 MXN
	G 1/8	12	19		7					Standard	20SF IW10 MXX
										Nickel Plated	20SF IW10 MXN



Nominal Diameter

5 = 20 mm²

RECTUS Series

17KA



actual size



Technical Description

English profile industrial coupling with UltraFlo technology, giving high flow performance. Specially suited to compressed air applications. Brass/steel design developed for industry. Compact dimensions and single handed operation make it suitable for numerous applications.

Advantages

Single handed operation. Small dimensions, light weight. High flow valve.

Working Pressure



PB = 35 bar, maximum static working pressure with safety factor 4 to 1.

Interchangeability
SCHRADER NW 5

Working Temperature*
-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



Material

- Coupling
- Back Body
- Valve Body
- Sleeve
- Valve
- Inner Sleeve
- Spring Plate
- Spring and Locking Ring
- Locking Balls
- Seals

Standard


- Brass, Nickel Plated
- Steel Hardened and Nickel Plated
- Steel Hardened and Nickel Plated
- Brass
- Brass
- Brass
- AISI 303
- AISI 420
- NBR

Plug


- Plug
- Steel Hardened, Nickel Plated

Couplings

RECTUS Series 17KA



Male Thread



Female Thread


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/4	19	63	23	12					Standard	17KA AK13 SPN
R 3/8	19	62	23	12					Standard	17KA AK17 SPN
R 1/2	22	63	23	17					Standard	17KA AK21 SPN
G 1/4	19	58	23	9					Standard	17KA IW13 SPN
G 3/8	19	57	23	9					Standard	17KA IW17 SPN
G 1/2	24	60	23	12					Standard	17KA IW21 SPN

Couplings

RECTUS Series 17KA

Brass/Steel


Low Pressure



Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	19	76	23	25					Standard	17KA TF06 SPN
8 mm	19	76	23	25					Standard	17KA TF08 SPN
10 mm	19	76	23	25					Standard	17KA TF10 SPN
13 mm	19	76	23	25					Standard	17KA TF13 SPN

Plugs


RECTUS Series 17KA




Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm		58	12	25					Standard	17SF TF06 SXN
8 mm		52	12	25					Standard	17SF TF08 SXN
10 mm		52	12	25					Standard	17SF TF10 SXN

Plugs


RECTUS Series 17KA



Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/8	11	37		9					Standard	17SF AK10 SXN
R 1/4	14	42		12					Standard	17SF AK13 SXN



G 1/8	14	33		7					Standard	17SF IW10 SXN
G 1/4	17	36		9					Standard	17SF IW13 SXN



Nominal Diameter

5 = 20 mm²



RECTUS Series

21KA

actual size





Technical Description

Mini industrial coupling, the world's most commonly used profile. Above average flow performance for liquid and gaseous media. Large band width in materials and valve variants.

Dust Caps (P. 331) for coupling Part.-No. SK16S

Chart



Advantages

Single handed operation. Small dimensions. All versions interchangeable.

Interchangeability

RECTUS 90
CAMOZZI
EWO
KANI

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to + 200°C (FKM)
0°C up to +316°C (FFKM) depending on the medium.

*At a temperature below -20°C and above + 100°C special seals are available on request.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug

Brass


Brass, Nickel Plated

You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Double Shut-off P. 125
- ▶ Stainless Steel P. 185
- ▶ Thermoplastics P. 242
- ▶ Safety P. 266
- ▶ Coded Systems S. 300

Couplings

RECTUS Series 21KA



Male Thread




Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 mm	B mm	G mm	Version	Part Number
G 1/8	14	36	16	7					Standard	21KA AW10 MPX
									Nickel Plated	21KA AW10 MPN
G 1/4	17	38	16	9					Standard	21KA AW13 MPX
									Nickel Plated	21KA AW13 MPN
G 3/8	19	38	16	9					Standard	21KA AW17 MPX
									Nickel Plated	21KA AW17 MPN
M 12 x 1,5	17	39	16	10					Standard	21KA AD12 MPX
									Nickel Plated	21KA AD12 MPN

Couplings

RECTUS Series 21KA






Brass/Steel

Low Pressure

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Male Thread</p>	M 14 x 1,5	17	39	16	10					Standard	21KA AD14 MPX	
										Nickel Plated	21KA AD14 MPN	
 <p>Female Thread</p>	G 1/8	14	36	16	9					Standard	21KA IW10 MPX	
										Nickel Plated	21KA IW10 MPN	
		G 1/4	17	38	16	9					Standard	21KA IW13 MPX
											Nickel Plated	21KA IW13 MPN
		G 3/8	19	38	16	9					Standard	21KA IW17 MPX
											Nickel Plated	21KA IW17 MPN
	 <p>Hose Barb</p>	M 12 x 1,5	17	38	16	6					Standard	21KA IM12 MPX
										Nickel Plated	21KA IM12 MPN	
		M 14 x 1,5	17	38	16	6					Standard	21KA IM14 MPX
											Nickel Plated	21KA IM14 MPN
		4 mm	14	46	16	17					Standard	21KA TF04 MPX
											Nickel Plated	21KA TF04 MPN
	6 mm	14	46	16	17					Standard	21KA TF06 MPX	
										Nickel Plated	21KA TF06 MPN	
	8 mm	14	46	16	17					Standard	21KA TF08 MPX	
										Nickel Plated	21KA TF08 MPN	
	9 mm	14	46	16	17					Standard	21KA TF09 MPX	
										Nickel Plated	21KA TF09 MPN	
	10 mm	14	46	16	17					Standard	21KA TF10 MPX	
										Nickel Plated	21KA TF10 MPN	
	6 mm Parker	14	50	16	20					Standard	21KA TP06 MPX	
										Nickel Plated	21KA TP06 MPN	




Couplings

RECTUS Series 21KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Plastic Hose Connection</p>	4 x 6 mm	14	42	16	7	6			M 10 x 1	Standard	21KA KO06 MPX	
										Nickel Plated	21KA KO06 MPN	
	6 x 8 mm	14	42	16	7	6				M 12 x 1	Standard	21KA KO08 MPX
											Nickel Plated	21KA KO08 MPN
 <p>Panel Mount, Plastic Hose Connection</p>	4 x 6 mm	14	54	16	7	18	12	3	M 10 x 1	Standard	21KA KS06 MPX	
										Nickel Plated	21KA KS06 MPN	
	6 x 8 mm	17	54	16	7	18	17	4		M 12 x 1	Standard	21KA KS08 MPX
											Nickel Plated	21KA KS08 MPN
 <p>Front Panel Installation, Plastic Hose Panel Mount</p>	4 x 6 mm	22	42	24	7	16	24	5	M 20 x 1	Standard	21KA KE06 MPX	
										Nickel Plated	21KA KE06 MPN	
	6 x 8 mm	22	42	24	7	16	24	5		M 20 x 1	Standard	21KA KE08 MPX
											Nickel Plated	21KA KE08 MPN
 <p>Front Panel Installation, Hose Barb Panel Mount</p>	4 mm	22	46	24	17	16	24	5	M 20 x 1	Standard	21KA TE04 MPX	
										Nickel Plated	21KA TE04 MPN	
	6 mm	22	46	24	17	16	24	5		M 20 x 1	Standard	21KA TE06 MPX
											Nickel Plated	21KA TE06 MPN
	8 mm	22	46	24	17	16	24	5		M 20 x 1	Standard	21KA TE08 MPX
											Nickel Plated	21KA TE08 MPN
	9 mm	22	46	24	17	16	24	5		M 20 x 1	Standard	21KA TE09 MPX
											Nickel Plated	21KA TE09 MPN
10 mm	22	46	24	17	16	24	5		M 20 x 1	Standard	21KA TE10 MPX	
										Nickel Plated	21KA TE10 MPN	
 <p>Panel Mount, Hose Barb</p>	4 mm	12	60	16	17	14	12	4	M 10 x 1	Standard	21KA TS04 MPX	
										Nickel Plated	21KA TS04 MPN	
	5 mm	17	60	16	17	14	17	4		M 12 x 1	Standard	21KA TS05 MPX
											Nickel Plated	21KA TS05 MPN
	6 mm	17	60	16	17	14	17	4		M 12 x 1	Standard	21KA TS06 MPX
											Nickel Plated	21KA TS06 MPN
8 mm	17	60	16	17	14	17	4		M 12 x 1	Standard	21KA TS08 MPX	
										Nickel Plated	21KA TS08 MPN	


Couplings

RECTUS Series 21KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Panel Mount, Hose Barb</p>	9 mm	17	60	16	17	14	19	4	M 12 x 1	Standard	21KA TS09 MPX
										Nickel Plated	21KA TS09 MPN
	10 mm	17	60	16	17	14	19	4	M 14 x 1	Standard	21KA TS10 MPX
										Nickel Plated	21KA TS10 MPN
 <p>Plastic Hose Connection with Spring Guard</p>	4 x 6 mm	14	125	16	7	6			M 10 x 1	Standard	21KA KK06 MPX
										Nickel Plated	21KA KK06 MPN
	6 x 8 mm	14	130	16	7	6			M 10 x 1	Standard	21KA KK08 MPX
										Nickel Plated	21KA KK08 MPN
 <p>Push-In</p>	6 mm	14	43,5	16,15						Nickel Plated	21KA RP06 MPN
	8 mm	17	48	16,15						Nickel Plated	21KA RP08 MPN






Plugs


RECTUS Series 21KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
	4 mm		32	9	17					Standard	21SF TF04 MXX
										Nickel Plated	21SF TF04 MXN
	5 mm		32	9	17					Standard	21SF TF05 MXX
										Nickel Plated	21SF TF05 MXN
	6 mm		32	9	17					Standard	21SF TF06 MXX
										Nickel Plated	21SF TF06 MXN
	8 mm		32	9	17					Standard	21SF TF08 MXX
										Nickel Plated	21SF TF08 MXN
 <p>Hose Barb</p>	9 mm		33	10	17					Standard	21SF TF09 MXX
										Nickel Plated	21SF TF09 MXN
	10 mm		33	12	17					Standard	21SF TF10 MXX
										Nickel Plated	21SF TF10 MXN
	6 mm Parker		36	16	20					Standard	21SF TP06 MXX
										Nickel Plated	21SF TP06 MXN


Plugs

RECTUS Series 21KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Plastic Hose Connection</p>	4 x 6 mm		32	10	6	6			M 10 x 1	Standard	21SF KO06 MXX
										Nickel Plated	21SF KO06 MXN
	6 x 8 mm		32	12	6	6			M 12 x 1	Standard	21SF KO08 MXX
										Nickel Plated	21SF KO08 MXN
	8 x 10 mm	17	36		9	8			M 16 x 1	Standard	21SF KO10 MXX
										Nickel Plated	21SF KO10 MXN
 <p>Panel Mount, Plastic Hose Connection</p>	4 x 6 mm	14	43		7	18	12	3	M 10 x 1	Standard	21SF KS06 MXX
										Nickel Plated	21SF KS06 MXN
	6 x 8 mm	14	44		7	18	17	4	M 12 x 1	Standard	21SF KS08 MXX
										Nickel Plated	21SF KS08 MXN
	4 mm	14	50		17	14	14	4	M 10 x 1	Standard	21SF TS04 MXX
										Nickel Plated	21SF TS04 MXN
 <p>Panel Mount, Hose Barb</p>	5 mm	14	50		17	14	17	4	M 12 x 1	Standard	21SF TS05 MXX
										Nickel Plated	21SF TS05 MXN
	6 mm	14	50		17	14	17	4	M 12 x 1	Standard	21SF TS06 MXX
										Nickel Plated	21SF TS06 MXN
	8 mm	14	50		17	14	17	4	M 12 x 1	Standard	21SF TS08 MXX
										Nickel Plated	21SF TS08 MXN
	9 mm	14	50		17	14	17	4	M 12 x 1	Standard	21SF TS09 MXX
										Nickel Plated	21SF TS09 MXN
	10 mm	17	50		17	14	19	4	M 14 x 1	Standard	21SF TS10 MXX
										Nickel Plated	21SF TS10 MXN
 <p>Plastic Hose Connection with Spring Guard</p>	4 x 6 mm		115		6	6			M 10 x 1	Standard	21SF KK06 MXX
										Nickel Plated	21SF KK06 MXN
	6 x 8 mm		120		6	6			M 12 x 1	Standard	21SF KK08 MXX
										Nickel Plated	21SF KK08 MXN
 <p>Push-In</p>	6 mm	14	32,8		13,2					Nickel Plated	21SF RP06 MPN
	8 mm	17	37		15,4					Nickel Plated	21SF RP08 MPN




Male Thread



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	25		7					Standard	21SF AW10 MXX
									Nickel Plated	21SF AW10 MXN
G 1/4	17	28		9					Standard	21SF AW13 MXX
									Nickel Plated	21SF AW13 MXN
G 3/8	17	28		9					Standard	21SF AW17 MXX
									Nickel Plated	21SF AW17 MXN
M 10 x 1	14	26		8					Standard	21SF AD10 MXX
									Nickel Plated	21SF AD10 MXN
M 12 x 1,5	17	28		10					Standard	21SF AD12 MXX
									Nickel Plated	21SF AD12 MXN
M 14 x 1,5	17	28		10					Standard	21SF AD14 MXX
									Nickel Plated	21SF AD14 MXN
G 1/8	14	25		8					Standard	21SF IW10 MXX
									Nickel Plated	21SF IW10 MXN
G 1/4	17	25		9					Standard	21SF IW13 MXX
									Nickel Plated	21SF IW13 MXN
G 3/8	19	26		9					Standard	21SF IW17 MXX
									Nickel Plated	21SF IW17 MXN
M 10 x 1	14	26		9					Standard	21SF IM10 MXX
									Nickel Plated	21SF IM10 MXN
M 12 x 1,5	17	27		10					Standard	21SF IM12 MXX
									Nickel Plated	21SF IM12 MXN
M 14 x 1,5	17	27		10					Standard	21SF IM14 MXX
									Nickel Plated	21SF IM14 MXN



Nominal Diameter

5 = 20 mm²

RECTUS Series

90KA



actual size



Technical Description

Small, splash-protected industrial coupling, specially developed for liquid media as the plug profile acts as a seal before the coupling valve is opened. Series 90 is a variant of series 21. Pin locking. Enlarged external sleeve diameter of 20 mm.

Advantages

Single handed operation. No loss through leakage during coupling.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability



RECTUS 21
CAMOZZI
EWO
KANI

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
0°C up to +316° (FFKM)
depending on the medium

*At a temperature below -20°C and above +100°C specials seals are available on request.

Chart



Material

Coupling

Back Body Brass
Valve Body Brass
Sleeve Brass
Valve Brass
Spring and Locking Ring AISI 301
Locking Pins AISI 420
Seals NBR

Standard

Nickel Plated


Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug (21 Series)


Plug Brass Nickel Plated

Couplings

RECTUS Series 90KA



Male Thread



Female Thread


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	36	20	7					Standard	90KA AW10 MPX
									Nickel Plated	90KA AW10 MPN
G 1/4	17	38	20	9					Standard	90KA AW13 MPX
									Nickel Plated	90KA AW13 MPN
G 3/8	19	39	20	9					Standard	90KA AW17 MPX
									Nickel Plated	90KA AW17 MPN
G 1/4	17	38	20	9					Standard	90KA IW13 MPX
									Nickel Plated	90KA IW13 MPN
G 3/8	19	38	20	9					Standard	90KA IW17 MPX
									Nickel Plated	90KA IW17 MPN

Couplings

RECTUS Series 90KA

Brass/Steel

Low Pressure




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	14	46	20	17					Standard	90KA TF06 MPX
									Nickel Plated	90KA TF06 MPN
8 mm	14	46	20	17					Standard	90KA TF08 MPX
									Nickel Plated	90KA TF08 MPN
9 mm	14	46	20	17					Standard	90KA TF09 MPX
									Nickel Plated	90KA TF09 MPN
10 mm	14	46	20	17					Standard	90KA TF10 MPX
									Nickel Plated	90KA TF10 MPN


Plugs

RECTUS Series 21SF




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
4 mm		32	9	17					Standard	21SF TF04 MXX
									Nickel Plated	21SF TF04 MXN
5 mm		32	9	17					Standard	21SF TF05 MXX
									Nickel Plated	21SF TF05 MXN
6 mm		32	9	17					Standard	21SF TF06 MXX
									Nickel Plated	21SF TF06 MXN
8 mm		32	9	17					Standard	21SF TF08 MXX
									Nickel Plated	21SF TF08 MXN
9 mm		33	10	17					Standard	21SF TF09 MXX
									Nickel Plated	21SF TF09 MXN
10 mm		33	12	17					Standard	21SF TF10 MXX
									Nickel Plated	21SF TF10 MXN
4 x 6 mm		32	10	6	6			M 10 x 1	Standard	21SF KO06 MXX
									Nickel Plated	21SF KO06 MXN
6 x 8 mm		32	12	6	6			M 12 x 1	Standard	21SF KO08 MXX
									Nickel Plated	21SF KO08 MXN
8 x 10 mm	17	36		9	8			M 16 x 1	Standard	21SF KO10 MXX
									Nickel Plated	21SF KO10 MXN
8 x 12 mm	17	36		9	8			M 16 x 1	Standard	21SF KO12 MXXS
									Nickel Plated	21SF KO12 MXNS
4 x 6 mm	14	43		7	18	12	3	M 10 x 1	Standard	21SF KS06 MXX
									Nickel Plated	21SF KS06 MXN
4 x 6 mm	14	44		7	18	17	4	M 12 x 1	Standard	21SF KS08 MXX
									Nickel Plated	21SF KS08 MXN





Plastic Hose Connection



Panel Mount, Plastic Hose Connection


Plugs


RECTUS Series 21SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW	B mm	G mm	Version	Part Number
 <p>Panel Mount Hose Barb</p>	4 mm	14	50		17	14	14	4	M 10 x 1	Standard	21SF TS04 MXX
										Nickel Plated	21SF TS04 MXN
	5 mm	14	50		17	14	17	4	M 12 x 1	Standard	21SF TS05 MXX
										Nickel Plated	21SF TS05 MXN
	6 mm	14	50		17	14	17	4	M 12 x 1	Standard	21SF TS06 MXX
										Nickel Plated	21SF TS06 MXN
	8 mm	14	50		17	14	17	4	M 12 x 1	Standard	21SF TS08 MXX
										Nickel Plated	21SF TS08 MXN
	9 mm	14	50		17	14	17	4	M 12 x 1	Standard	21SF TS09 MXX
										Nickel Plated	21SF TS09 MXN
	10 mm	17	50		17	14	19	4	M 14 x 1	Standard	21SF TS10 MXX
										Nickel Plated	21SF TS10 MXN
 <p>Plastic Hose Connection with Spring Guard</p>	4 x 6 mm		115		6	6			M 10 x 1	Standard	21SF KK06 MXX
										Nickel Plated	21SF KK06 MXN
	6 x 8 mm		120		6	6			M 12 x 1	Standard	21SF KK08 MXX
										Nickel Plated	21SF KK08 MXN

Plugs

RECTUS Series 21SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14	25		7					Standard	21SF AW10 MXX
										Nickel Plated	21SF AW10 MXN
	G 1/4	17	28		9					Standard	21SF AW13 MXX
										Nickel Plated	21SF AW13 MXN
	G 3/8	19	28		9					Standard	21SF AW17 MXX
										Nickel Plated	21SF AW17 MXN
ISO 8434-1	M 10 x 1	14	26		8					Standard	21SF AD10 MXX
										Nickel Plated	21SF AD10 MXN
ISO 8434-1	M 12 x 1,5	17	28		10					Standard	21SF AD12 MXX
										Nickel Plated	21SF AD12 MXN
ISO 8434-1	M 14 x 1,5	19	28		10					Standard	21SF AD14 MXX
										Nickel Plated	21SF AD14 MXN



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	25		8					Standard	21SF IW10 MXX
									Nickel Plated	21SF IW10 MXN
G 1/4	17	25		9					Standard	21SF IW13 MXX
									Nickel Plated	21SF IW13 MXN
G 3/8	19	26		9					Standard	21SF IW17 MXX
									Nickel Plated	21SF IW17MXN
M 10 x 1	14	26		9					Standard	21SF IM10 MXX
									Nickel Plated	21SF IM10 MXN
M 12 x 1,5	17	27		10					Standard	21SF IM12 MXX
									Nickel Plated	21SF IM12 MXN
M 14 x 1,5	17	27		10					Standard	21SF IM14 MXX
									Nickel Plated	21SF IM14 MXN



Nominal Diameter

5,5 = 25 mm²

RECTUS Series

14KA



actual size

**Technical Description**

Robust brass coupling. Numerous connection options. Preferred application: compressed air technology and water connections.

Advantages

Single handed operation. Plug design optimised through greater insert depth.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.



Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Interchangeability

RECTUS 22
ARO 210
PARKER 50
CEJN 300
ORION 44510
JWL 552 + JWL 532
various Swiss Products

Chart

You will find the following alternative versions in our current catalogue on page:

► Safety Self-Venting

P. 280

Material**Coupling**

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Pins
Seals

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug

Steel Hardened, Nickel Plated or
Brass and Brass, Nickel Plated

Couplings**RECTUS Series 14KA**


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/4	22	43	25	9					Standard	14KA AW13 MPX
										Nickel Plated	14KA AW13 MPN
	G 3/8	22	43	25	9					Standard	14KA AW17 MPX
										Nickel Plated	14KA AW17 MPN
<p>Female Thread</p>	G 1/2	22	46	25	12					Standard	14KA AW21 MPX
										Nickel Plated	14KA AW21 MPN
	G 1/4	22	43	25	9					Standard	14KA IW13 MPX
										Nickel Plated	14KA IW13 MPN
	G 3/8	22	43	25	9					Standard	14KA IW17 MPX
										Nickel Plated	14KA IW17 MPN
	G 1/2	24	46	25	12					Standard	14KA IW21 MPX
										Nickel Plated	14KA IW21 MPN

Couplings

RECTUS Series 14KA

Brass/Steel

Low Pressure




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	21	60	25	25					Standard	14KA TF06 MPX
									Nickel Plated	14KA TF06 MPN
8 mm	21	60	25	25					Standard	14KA TF08 MPX
									Nickel Plated	14KA TF08 MPN
9 mm	21	60	25	25					Standard	14KA TF09 MPX
									Nickel Plated	14KA TF09 MPN
10 mm	21	60	25	25					Standard	14KA TF10 MPX
									Nickel Plated	14KA TF10 MPN
13 mm	21	60	25	25					Standard	14KA TF13 MPX
									Nickel Plated	14KA TF13 MPN

Plugs

RECTUS Series 22SF




Hose Barb


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm		49	12	25					Standard	22SF TF06 SXN
									Brass	22SF TF06 MXX
									Nickel Plated	22SF TF06 MXN
8 mm		49	12	25					Standard	22SF TF08 SXN
									Brass	22SF TF08 MXX
									Nickel Plated	22SF TF08 MXN
10 mm		49	12	25					Standard	22SF TF10 SXN
									Brass	22SF TF10 MXX
									Nickel Plated	22SF TF10 MXN
13 mm		49	15	25					Standard	22SF TF13 SXN
									Brass	22SF TF13 MXX
									Nickel Plated	22SF TF13 MXN

Plugs

RECTUS Series 22SF



Male Thread



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/4	14	41		12					Standard	22SF AK13 SXN
									Brass	22SF AK13 MXX
									Nickel Plated	22SF AK13 MXN
R 3/8	17	41		12					Standard	22SF AK17 SXN
									Brass	22SF AK17 MXX
									Nickel Plated	22SF AK17 MXN
R 1/2	22	46		17					Standard	22SF AK21 SXN
									Brass	22SF AK21 MXX
									Nickel Plated	22SF AK21 MXN
G 1/4	17	35		9					Standard	22SF IW13 SXN
									Brass	22SF IW13 MXX
									Nickel Plated	22SF IW13 MXN
G 3/8	19	35		10					Standard	22SF IW17 SXN
									Brass	22SF IW17 MXX
									Nickel Plated	22SF IW17 MXN

⚠ Please consider our security advices on the pages 12/13 ⚠



Nominal Diameter

5,5 = 25 mm²

RECTUS Series

18KA



actual size





Technical Description

ISO 6150 C industrial coupling with UltraFlo technology. Robust design. The steel sleeve counters oscillating forces. System has limited use for liquids (steel sleeve/zinc die cast valve).

Dust Caps (P. 331) for coupling Part.-No. SK23S

Chart



Advantages

Single handed operation. Innovative valve technology. Plug design optimised through greater insert depth. High flow valve.

Interchangeability

CEJN 291
OETIKER
ISO 6150 C

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Material

Coupling
Back Body
Valve Body
Sleeve
Valve
Inner Sleeve
Spring Plate
Spring and Locking Ring
Locking Balls
Seals

Standard

Brass, Nickel Plated
Brass, Nickel Plated
Steel Hardened, Nickel Plated
Zinc Diecasting, Nickel Plated
Brass
Brass
AISI 301
AISI 420
NBR

Plug


Plug
Steel Hardened, Nickel Plated

You will find the following alternative versions in our current catalogue on page:


► Safety Self-Venting P. 282

Couplings

RECTUS Series 18KA



Male Thread



Female Thread


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/4	19	63	23	12					Standard	18KA AK13 MPN
R 3/8	19	62	23	12					Standard	18KA AK17 MPN
R 1/2	22	63	23	17					Standard	18KA AK21 MPN
G 1/4	19	58	23	9					Standard	18KA IW13 MPN
G 3/8	19	57	23	9					Standard	18KA IW17 MPN
G 1/2	24	60	23	12					Standard	18KA IW21 MPN

Couplings

RECTUS Series 18KA

Brass/Steel

Low Pressure




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	19	76	23	25					Standard	18KA TF06 MPN
8 mm	19	76	23	25					Standard	18KA TF08 MPN
10 mm	19	76	23	25					Standard	18KA TF10 MPN
13 mm	19	76	23	25					Standard	18KA TF13 MPN

Plugs

RECTUS Series 18KA




Hose Barb


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm		59	12	25					Standard	18SF TF06 SXN
8 mm		59	12	25					Standard	18SF TF08 SXN
10 mm		59	12	25					Standard	18SF TF10 SXN

Plugs

RECTUS Series 18KA




Male Thread



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/4	17	41		9					Standard	18SF AW13 SXN
G 3/8	19	41		9					Standard	18SF AW17 SXN
G 1/4	17	43		9					Standard	18SF IW13 SXN
G 3/8	19	44		9					Standard	18SF IW17 SXN




Nominal Diameter

5,5 = 25 mm²

RECTUS Series

19KA



actual size



Technical Description

English industrial profile with UltraFlo technology. Compact dimensions. Robust coupling for compressed air applications. The steel sleeve counters oscillating forces.

Advantages

Single handed operation. Plug design optimised through greater insert depth. High flow valve.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability

PCL 60 (UK)

Working Temperature*



-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 0°C up to +316°C (FFKM)
 depending on the medium.

Dust Caps (P. 331)

for coupling Part.-No. SK23S



Chart



Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Inner Sleeve
- Spring Plate
- Spring and Locking Ring
- Locking Balls
- Seals

Standard

- Brass, Nickel Plated
- Brass, Nickel Plated
- Steel Hardened, Nickel Plated
- Zinc Diecasting, Nickel Plated
- Brass
- Brass
- AISI 301
- AISI 420
- NBR

Plug

Plug

Steel Hardened, Nickel Plated

Couplings **RECTUS Series 19KA**


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	63	23	12					Standard	19KA AK13 MPN
	R 3/8	19	62	23	12					Standard	19KA AK17 MPN
	R 1/2	22	68	23	17					Standard	19KA AK21 MPN
<p>Female Thread</p>	G 1/4	19	58	23	9					Standard	19KA IW13 MPN
	G 3/8	19	58	23	9					Standard	19KA IW17 MPN
	G 1/2	24	60	23	12					Standard	19KA IW21 MPN

Couplings

RECTUS Series 19KA

Brass/Steel

Low Pressure




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	19	76	23	25					Standard	19KA TF06 MPN
8 mm	19	76	23	25					Standard	19KA TF08 MPN
10 mm	19	76	23	25					Standard	19KA TF10 MPN
13 mm	19	76	23	25					Standard	19KA TF13 MPN

Plugs

RECTUS Series 19KA




Hose Barb


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm		60	12	25					Standard	19SF TF06 SXN
8 mm		60	12	25					Standard	19SF TF08 SXN
10 mm		60	12	25					Standard	19SF TF10 SXN

Plugs

RECTUS Series 19KA



Male Thread



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/4	14	50		12					Standard	19SF AK13 SXN
R 3/8	17	50		12					Standard	19SF AK17 SXN
G 1/4	17	46		9					Standard	19SF IW13 SXN
G 3/8	19	47		9					Standard	19SF IW17 SXN



Nominal Diameter

5,5 = 25 mm²

RECTUS Series

22KA



actual size



**Technical Description**

Industrial coupling with high flow performance from UltraFlo technology. Specially suited to use with gaseous media in industry. The steel sleeve counters oscillating forces. Special variant with brass valve for use with liquids.

Dust Caps (P. 331)

for coupling

Part.-No. SK23S

**Chart****Advantages**

Single handed operation. Plug design optimised through greater insert depth. High flow valve.

Interchangeability

RECTUS 14
ARO 210
PARKER 50
CEJN 300
ORION 44510
JWL 522 + JWL 532
various Swiss products

Material**Coupling**

Back Body
Valve Body
Sleeve
Valve
Inner Sleeve
Spring Plate
Spring and Locking Ring
Locking Balls
Seals

Plug

Plug

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Standard

Brass, Nickel Plated
Brass, Nickel Plated
Steel Hardened, Nickel Plated
Zinc Diecasting, Nickel Plated
Brass
Brass
AISI 301
AISI 420
NBR



Steel Hardened, Nickel Plated or
Brass and Brass, Nickel Plated

Couplings**RECTUS Series 22KA**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	61	23	12					Standard	22KA AK13 MPN
	R 3/8	19	60	23	12					Standard	22KA AK17 MPN
	R 1/2	22	61	23	17					Standard	22KA AK21 MPN
<p>Female Thread</p>	G 1/4	19	56	23	9					Standard	22KA IW13 MPN
	G 3/8	19	55	23	9					Standard	22KA IW17 MPN
	G 1/2	24	58	23	9					Standard	22KA IW21 MPN
<p>Hose Barb</p>	6 mm	19	74	23	25					Standard	22KA TF06 MPN
	8 mm	19	74	23	25					Standard	22KA TF08 MPN
	9 mm	19	74	23	25					Standard	22KA TF09 MPN
	10 mm	19	74	23	25					Standard	22KA TF10 MPN
	13 mm	19	74	23	25					Standard	22KA TF13 MPN


Couplings

RECTUS Series 22KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Plastic Hose Connection</p>	6 x 8 mm	19	61	23	7	6			M 12 x 1	Standard	22KA KO08 MPN
	8 x 10 mm	19	65	23	9	8			M 16 x 1	Standard	22KA KO10 MPN
 <p>Plastic Hose Connection w. Spring Guard</p>	6 x 8 mm	19	126	23	7	6			M 12 x 1	Standard	22KA KK08 MPN



Plugs

RECTUS Series 22KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Hose Barb</p>	6 mm		49	12	25					Standard	22SF TF06 SXN	
										Brass	22SF TF06 MXX	
										Brass, Nickel P.	22SF TF06 MXN	
	8 mm		49	12	25						Standard	22SF TF08 SXN
											Brass	22SF TF08 MXX
											Brass, Nickel P.	22SF TF08 MXN
	10 mm		49	12	25						Standard	22SF TF10 SXN
											Brass	22SF TF10 MXX
											Brass, Nickel P.	22SF TF10 MXN
13 mm		49	15	25						Standard	22SF TF13 SXN	
										Brass	22SF TF13 MXX	
										Brass, Nickel P.	22SF TF13 MXN	


Plugs

RECTUS Series 22KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Male Thread</p>	R 1/4	14	41		12					Standard	22SF AK13 SXN	
										G 1/4	Brass	22SF AK13 MXX
	R 3/8	17	41		12						Standard	22SF AK17 SXN
											G 3/8	Brass
											Brass, Nickel P.	22SF AK17 MXN
	R 1/2	22	46		17						Standard	22SF AK21 SXN
 <p>Female Thread</p>	G 1/4	17	35		9					Standard	22SF IW13 SXN	
										Brass	22SF IW13 MXX	
										Brass, Nickel P.	22SF IW13 MXN	
	G 3/8	19	35		10						Standard	22SF IW17 SXN
											Brass	22SF IW17 MXX
											Brass, Nickel P.	22SF IW17 MXN
G 1/2	24	35		12						Standard	22SF IW21 SXN	

⚠ Please consider our security advices on the pages 12/13 ⚠

Brass/Steel
Low Pressure



Nominal Diameter

5,5 = 25 mm²

RECTUS Series

23KA



actual size



Technical Description



1/4" industrial coupling with UltraFlo technology in accordance with ISO 6150 B and US Mil. Spec. 4109. Especially suitable for use with gaseous media in industry. Steel sleeve counters oscillating forces. Special variants with brass valve for use with liquids.

Dust Caps (P. 331)

for coupling Part.-No. SK23S



Chart



Advantages

High flow performance with low pressure drop and a multitude of connection options.

Interchangeability

INDUSTR. INTERCHANGE 1/4"
US-MIL-SPEC-C-4109
ISO 6150 B
RECTUS 24, RECTUS 1400/1423
TEMA 1400
CEJN 310, HANSEN 3000,
FASTER, GROMELLE 600
PARKER 20 1/4" + 30 1/4"
JWL 521 + JWL 531

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Inner Sleeve
Spring Plate
Spring and Locking Ring
Locking Balls
Seals

Plug

Plug

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Standard

Brass, Nickel Plated
Brass, Nickel Plated
Steel Hardened, Nickel Plated
Zinc Diecasting, Nickel Plated
Brass
Brass
AISI 301
AISI 420
NBR

Steel Hardened, Nickel Plated or Brass

You will find the following alternative versions in our current catalogue on page:

► Safety Self-Venting

P. 284



Couplings

RECTUS Series 23KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	61	23	12					Standard	23KA AK13 MPN
	R 3/8	19	60	23	12					Standard	23KA AK17 MPN
	R 1/2	22	61	23	17					Standard	23KA AK21 MPN
<p>Female Thread</p>	G 1/4	19	56	23	9					Standard	23KA IW13 MPN
	G 3/8	19	54	23	9					Standard	23KA IW17 MPN
	G 1/2	24	58	23	9					Standard	23KA IW21 MPN
<p>Hose Barb</p>	6 mm	19	74	23	25					Standard	23KA TF06 MPN
	8 mm	19	74	23	25					Standard	23KA TF08 MPN
	9 mm	19	74	23	25					Standard	23KA TF09 MPN
	10 mm	19	74	23	25					Standard	23KA TF10 MPN
	13 mm	19	74	23	25					Standard	23KA TF13 MPN


Couplings

RECTUS Series 23KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Plastic Hose Connection</p>	8 x 10 mm	19	64	23	9	8			M 16 x 1	Standard	23KA KO10 MPN
 <p>Plastic Hose Connection with Spring Guard</p>	9 x 12 mm	19	163	23	9	8			M 16 x 1	Standard	23KA KK12 MPN




Plugs

RECTUS Series 23KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	4 mm		51	14	25					Brass, Nickel P.	23SF TF04 MXN
	6 mm		51	14	25					Standard	23SF TF06 SXN
										Brass	23SF TF06 MXX
	8 mm		51	14	25					Standard	23SF TF08 SXN
										Brass	23SF TF08 MXX
	9 mm		51	14	25					Standard	23SF TF09 SXN
										Brass	23SF TF09 MXX
	10 mm		51	14	25					Standard	23SF TF10 SXN
										Brass	23SF TF10 MXX
	13 mm		51	14	25					Standard	23SF TF13 SXN

Plugs

RECTUS Series 23KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/8	13	39		9					Standard	23SF AK10 SXN
	R 1/4	14	42		12					Standard	23SF AK13 SXN
	G 1/4									Brass	23SF AW13 MXX
	R 3/8	17	42		12					Standard	23SF AK17 SXN
	G 3/8									Brass	23SF AW17 MXX
 <p>Female Thread</p>	R 1/2	22	48		17					Standard	23SF AK21 SXN
	G 1/8	14	36		9					Standard	23SF IW10 SXN
	G 1/4	17	36		9					Standard	23SF IW13 SXN
										Brass	23SF IW13 MXX
	G 3/8	19	36		9					Standard	23SF IW17 SXN
									Brass	23SF IW17 MXX	
 <p>Flex Joint, Male Thread</p>	G 1/2	24	39		12					Standard	23SF IW21 SXN
	R 1/4	17	68		11					Brass	23FA AK13 SPN



Nominal Diameter

5,5 = 25 mm²

RECTUS Series

1400KA



actual size





Technical Description

Rectus Tema premium industrial coupling – the know-how from both brands combined in one system. 1/4" coupling conforming to ISO 6150 B with high grade valve technology, optimum flow performance and minimum coupling forces.

Dust Caps (P. 331) for coupling Part.-No. SK23S

Chart



Advantages

Single handed operation. High flow valve. Minimum coupling forces.

Interchangeability

RECTUS 23 + 24, RECTUS 1423 TEMA 1400 INDUSTR. INTERCHANGE 1/4" US-MIL-SPEC-C-4109, ISO 6150 B CEJN 310, HANSEN 3000, FASTER, GROMELLE 600 PARKER 20 1/4" + 30 1/4" JWL 521 + JWL 531

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring
Locking Ring and
Locking Balls
Seals

Plug

Plug

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Standard

Brass, Nickel Plated
Steel, QPQ treated
Brass, Nickel Plated
Brass
AISI 301
AISI 420

NBR

Steel Hardened and Nickel Plated

You will find the following alternative versions in our current catalogue on page:

► Safety Self-Venting P. 284

Couplings

RECTUS Series 1400KA


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	65	23	12					Standard	1400KA AK13 SPN
	R 3/8	19	65	23	12					Standard	1400KA AK17 SPN
	R 1/2	22	59,5	23	17					Standard	1400KA AK21 SPN
<p>Female Thread</p>	G 1/4	19	59	23	9					Standard	1400KA IW13 SPN
	G 3/8	19	59	23	9					Standard	1400KA IW17 SPN
	G 1/2	24	62	23	12					Standard	1400KA IW21 SPN

Couplings

RECTUS Series 1400KA

Brass/Steel

Low Pressure




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	19	80	23	25					Standard	1400KA TF06 SPN
8 mm	19	80	23	25					Standard	1400KA TF08 SPN
10 mm	19	80	23	25					Standard	1400KA TF10 SPN
13 mm	19	80	23	25					Standard	1400KA TF13 SPN

Plugs

RECTUS Series 23SF




Hose Barb


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
4 mm		51	14	25					Brass, Nickel P.	23SF TF04 MXN
6 mm		51	14	25					Standard	23SF TF06 SXN
									Brass	23SF TF06 MXX
8 mm		51	14	25					Standard	23SF TF08 SXN
									Brass	23SF TF08 MXX
9 mm		51	14	25					Standard	23SF TF09 SXN
									Brass	23SF TF09 MXX
10 mm		51	14	25					Standard	23SF TF10 SXN
									Brass	23SF TF10 MXX
13 mm		51	15	25					Standard	23SF TF13 SXN

Plugs


RECTUS Series 23SF



Male Thread




Female Thread



Flex Joint, Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/8	13	39		9					Standard	23SF AK10 SXN
R 1/4	14	42		12					Standard	23SF AK13 SXN
G 1/4									Brass	23SF AW13 MXX
R 3/8	17	42		12					Standard	23SF AK17 SXN
G 3/8									Brass	23SF AW17 MXX
R 1/2	22	48		17					Standard	23SF AK21 SXN
G 1/8	14	36		9					Standard	23SF IW10 SXN
G 1/4	17	36		9					Standard	23SF IW13 SXN
									Brass	23SF IW13 MXX
G 3/8	19	36		9					Standard	23SF IW17 SXN
									Brass	23SF IW17 MXX
G 1/2	24	39		12					Standard	23SF IW21 SXN
R 1/4	17	68		11					Standard	23FA AK13 SPN

⚠ Please consider our security advices on the pages 12/13 ⚠



Nominal Diameter

5,5 = 25 mm²

RECTUS Series

1423KA



actual size



Technical Description



Rectus Tema premium industrial coupling - the know-how from both brands combined in one system. 1/4" coupling conforming to ISO 6150 B with high grade valve technology, optimum flow performance and minimum coupling forces. Especially robust 2-component plastic sleeve.

Dust Caps (P. 331)

for coupling Part.-No. SK23S



Chart



Advantages

Single handed operation. High flow valve. Minimum coupling forces.

Interchangeability

RECTUS 23 + 24,
RECTUS 1400
TEMA 1400
INDUSTR. INTERCHANGE 1/4"
US-MIL-SPEC-C-4109,
ISO 6150 B
CEJN 310, HANSEN 3000,
FASTER, GROMELLE 600
PARKER 20 1/4" + 30 1/4"
JWL 521 + JWL 531

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring
Locking Ring and
Locking Balls
Seals

Plug

Plug

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +80°C (NBR)
-20°C up to +80°C (EPDM)
-20°C up to +80°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +80°C special seals are available on request.

Standard

Brass, Nickel Plated
Steel, QPQ treated
PA6 + TPE
Brass
AISI 301
AISI 420

NBR

Steel Hardened and
Nickel Plated

You will find the following alternative versions in our current catalogue on page:

► Safety Self-Venting

P. 284

Couplings


RECTUS Series 1423KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	65	26	12					Standard	1423KA AK13 SPN
	R 3/8	19	65	26	12					Standard	1423KA AK17 SPN
	R 1/2	22	59,5	26	17					Standard	1423KA AK21 SPN
<p>Female Thread</p>	G 1/4	19	59	26	9					Standard	1423KA IW13 SPN
	G 3/8	19	59	26	9					Standard	1423KA IW17 SPN
	G 1/2	24	62	26	12					Standard	1423KA IW21 SPN

Couplings

RECTUS Series 1423KA

Brass/Steel
Low Pressure




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	19	80	26	25					Standard	1423KA TF06 SPN
8 mm	19	80	26	25					Standard	1423KA TF08 SPN
9 mm	19	80	26	25					Standard	1423KA TF09 SPN
10 mm	19	80	26	25					Standard	1423KA TF10 SPN
13 mm	19	80	26	25					Standard	1423KA TF13 SPN

Plugs

RECTUS Series 23SF




Hose Barb


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
4 mm		51	14	25					Brass, Nickel P.	23SF TF04 MXN
6 mm		51	14	25					Standard	23SF TF06 SXN
									Brass	23SF TF06 MXX
8 mm		51	14	25					Standard	23SF TF08 SXN
									Brass	23SF TF08 MXX
9 mm		51	14	25					Standard	23SF TF09 SXN
									Brass	23SF TF09 MXX
10 mm		51	14	25					Standard	23SF TF10 SXN
									Brass	23SF TF10 MXX
13 mm		51	14	25					Standard	23SF TF13 SXN

Plugs


RECTUS Series 23SF



Male Thread




Female Thread



Flex Joint, Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/8	13	39		9					Standard	23SF AK10 SXN
R 1/4	14	42		12					Standard	23SF AK13 SXN
G 1/4									Brass	23SF AW13 MXX
R 3/8	17	42		12					Standard	23SF AK17 SXN
G 3/8									Brass	23SF AW17 MXX
R 1/2	22	48		17					Standard	23SF AK21 SXN
G 1/8	14	36		9					Standard	23SF IW10 SXN
G 1/4	17	36		9					Standard	23SF IW13 SXN
									Brass	23SF IW13 MXX
G 3/8	19	36		9					Standard	23SF IW17 SXN
									Brass	23SF IW17 MXX
G 1/2	24	39		12					Standard	23SF IW21 SXN
R 1/4	17	68		11					Standard	23FA AK13 SPN

⚠ Please consider our security advices on the pages 12/13 ⚠



Nominal Diameter

5,5 = 25 mm²

RECTUS Series

24KA



actual size



Technical Description

1/4" Industrial brass coupling conforming to ISO 6150B and US Mil. Spec 4109. Notable for brass mass design and corresponding sleeve design. Hardened steel plug counters vibrations and effects of external forces.

Advantages

Single handed operation.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability



RECTUS 23
RECTUS 1400/1423
TEMA 1400
INDUSTR. INTERCHANGE 1/4"
US-MIL-SPEC-C-4109,
ISO 6150 B
CEJN 310, HANSEN 3000,
FASTER, GROMELLE 600
PARKER 20 1/4" + 30 1/4"
JWL 521 + JWL 531

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



You will find the following alternative versions in our current catalogue on page:

- Safety Self-Venting P. 286

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Pins
Seals

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug

Steel Hardened, Nickel Plated or Brass


Couplings

RECTUS Series 24KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/4	22	43	25	9					Standard	24KA AW13 MPX
										Nickel Plated	24KA AW13 MPN
	G 3/8	22	43	25	9					Standard	24KA AW17 MPX
										Nickel Plated	24KA AW17 MPN
<p>Female Thread</p>	G 1/2	22	46	25	12					Standard	24KA AW21 MPX
										Nickel Plated	24KA AW21 MPN
	G 1/4	22	43	25	11					Standard	24KA IW13 MPX
										Nickel Plated	24KA IW13 MPN
	G 3/8	22	43	25	9					Standard	24KA IW17 MPX
										Nickel Plated	24KA IW17 MPN
	G 1/2	22	46	25	12					Standard	24KA IW21 MPX
										Nickel Plated	24KA IW21 MPN

Couplings

RECTUS Series 24KA




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	21	60	25	25					Standard	24KA TF06 MPX
8 mm	21	60	25	25					Standard Nickel Plated	24KA TF08 MPX 24KA TF08 MPN
9 mm	21	60	25	25					Standard	24KA TF09 MPX
10 mm	21	60	25	25					Standard	24KA TF10 MPX
13 mm	21	60	25	25					Standard	24KA TF13 MPX

Plugs

RECTUS Series 23SF




Hose Barb


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
4 mm		51	14	25					Brass, Nickel P.	23SF TF04 MXN
6 mm		51	14	25					Standard Brass	23SF TF06 SXN 23SF TF06 MXX
8 mm		51	14	25					Standard Brass	23SF TF08 SXN 23SF TF08 MXX
9 mm		51	14	25					Standard Brass	23SF TF09 SXN 23SF TF09 MXX
10 mm		51	14	25					Standard Brass	23SF TF10 SXN 23SF TF10 MXX
13 mm		51	15	25					Standard	23SF TF13 SXN

Plugs


RECTUS Series 23SF



Male Thread




Female Thread



Flex Joint, Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/8	13	39		9					Standard	23SF AK10 SXN
R 1/4	14	42		12					Standard	23SF AK13 SXN
G 1/4									Brass	23SF AW13 MXX
R 3/8	17	42		12					Standard	23SF AK17 SXN
G 3/8									Brass	23SF AW17 MXX
R 1/2	22	48		17					Standard	23SF AK21 SXN
G 1/8	14	36		9					Standard	23SF IW10 SXN
G 1/4	17	36		9					Standard Brass	23SF IW13 SXN 23SF IW13 MXX
G 3/8	19	36		9					Standard Brass	23SF IW17 SXN 23SF IW17 MXX
G 1/2	24	39		12					Standard	23SF IW21 SXN
R 1/4	17	68		11					Standard	23FA AK13 SPN



Nominal Diameter

6 = 30 mm²

RECTUS Series

31KA



actual size



Technical Description



Steel industrial coupling with high flow due to UltraFlo technology. Widely used in the Scandinavian market. Specially suited to use with gaseous media in industry.

Dust Caps (P. 331)

for coupling Part.-No. SK23S
for plug Part.-No. SK12S



Chart



Advantages

Single handed operation. Extremely high flow performance from optimum valve design. High flow valve.

Interchangeability

TEMA 1300 (single shut-off)
Cejn 303

Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring Plate
- Spring and Locking
- Ring
- Locking Balls
- Seals

Plug

- Plug

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

- 20°C up to +100°C (NBR)
 - 40°C up to +120/150°C (EPDM)
 - 15°C up to +200°C (FKM)
- depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Standard

- Brass, Nickel Plated,
- Steel, Black Nitrided
- Brass, Nickel Plated
- Brass
- Brass
- Spring Plate
- AISI 301
- AISI 420
- NBR

- Steel Hardened,
- Zinc Chromatized

Couplings RECTUS Series 31KA


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	58	22	12					Standard	31KA AK13 SPN
	R 3/8	19	56	22	12					Standard	31KA AK17 SPN
	R 1/2	23	57	26	14					Standard	31KA AK21 SPN
<p>Female Thread</p>	G 1/4	19	55	22	11					Standard	31KA IW13 SPN
	G 3/8	20	55	22	10					Standard	31KA IW17 SPN

Couplings

RECTUS Series 31KA

Brass/Steel

Low Pressure




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	19	78	22	23					Standard	31KA TF06 SPN
8 mm	19	78	22	23					Standard	31KA TF08 SPN
10 mm	19	78	22	23					Standard	31KA TF10 SPN
13 mm	19	77	22	24					Standard	31KA TF13 SPN

Plugs

RECTUS Series 31KA




Hose Barb


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm		44	12	23					Standard	31SF TF06 SXZ
8 mm		44	12	23					Standard	31SF TF08 SXZ
10 mm		44	12	24					Standard	31SF TF10 SXZ
13 mm		47	12	24					Standard	31SF TF13 SXZ

Plugs

RECTUS Series 31KA




Male Thread



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/8	13	35		9					Standard	31SF AK10 SXZ
R 1/4	14	38		12					Standard	31SF AK13 SXZ
R 3/8	17	38		12					Standard	31SF AK17 SXZ
R 1/2	22	40		14					Standard	31SF AK21 SXZ
G 1/8	13	32		8,5					Standard	31SF IW10 SXZ
G 1/4	16	36		10					Standard	31SF IW13 SXZ
G 3/8	20	36		10					Standard	31SF IW17 SXZ

⚠ Please consider our security advices on the pages 12/13 ⚠



Nominal Diameter

6 = 30 mm²

RECTUS Series

51KB



actual size



Technical Description



German industrial profile with UltraFlo technology. Small dimensions. Robust steel coupling for compressed air applications, especially with oscillating forces due to the greater insert depth of the plug profile and steel sleeve.

Dust Caps (P. 331)

for coupling Part.-No. SK23S



Chart



Advantages

Single handed operation. Ergonomic design. High flow valve.

Interchangeability

WALTHER SP006

Working Pressure

PB = 50 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Spring Plate

Standard

Brass, Nickel Plated
Steel, Nickel Plated
Steel Hardened, Nickel Plated
Brass, Nickel Plated
AISI 301
AISI 420
NBR
Brass

Plug

Plug


Steel Hardened, Nickel Plated

You will find the following alternative versions in our current catalogue on page:


► Brass/Steel Double Shut-off P. 130

Couplings

RECTUS Series 51KB



Male Thread



Female Thread



Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/4	22	61	22	9					Standard	51KB AW13 SPN
G 3/8	22	61	22	9					Standard	51KB AW17 SPN
G 1/2	22	61	22	12					Standard	51KB AW21 SPN
G 1/4	22	63	22	12					Standard	51KB IW13 SPN

Couplings

RECTUS Series 51KB


Brass/Steel

Low Pressure

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 3/8	22	63	22	12					Standard	51KB IW17 SPN
	G 1/2	24	64	22	13					Standard	51KB IW21 SPN
	6 mm	21	78	22	25					Standard	51KB TF06 SPN
 <p>Hose Barb</p>	9 mm	21	78	22	25				Standard	51KB TF09 SPN	
	13 mm	21	78	22	25					Standard	51KB TF13 SPN



Plugs

RECTUS Series 51KB


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm		46	11	25					Standard	51SF TF06 SXN
	9 mm		46	11	25					Standard	51SF TF09 SXN

Plugs

RECTUS Series 51KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/4	17	35		9					Standard	51SF AW13 SXN
	G 3/8	19	36		9					Standard	51SF AW17 SXN
 <p>Female Thread</p>	G 1/4	17	34		11					Standard	51SF IW13 SXN
	G 3/8	19	34		11					Standard	51SF IW17 SXN

⚠ Please consider our security advices on the pages 12/13 ⚠




Nominal Diameter

6 = 30 mm²

RECTUS Series

52KB



actual size



Technical Description



German industrial profile with UltraFlo technology. Small dimensions. Robust steel coupling for compressed air applications, especially with oscillating forces due to the greater insert depth of the plug profile and steel sleeve.

Dust Caps (P. 331)

for coupling Part.-No. SK23S
for plug Part.-No. SK12S



Chart



Advantages

Single handed operation.
Ergonomic design. High flow valve.

Interchangeability

WALTHER LP006

Working Pressure

PB = 50 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Inner Sleeve
Spring Plate

Standard

Brass, Nickel Plated
Steel, Nickel Plated
Steel Hardened, Nickel Plated
Brass, Nickel Plated
AISI 301
AISI 420
NBR
Brass
Brass

Plug

Plug


Steel Hardened, Nickel Plated

You will find the following alternative versions in our current catalogue on page:


► Brass/Steel Double Shut-off P. 132

Couplings

RECTUS Series 52KB



Male Thread



Female Thread



Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/4	22	62	25	9					Standard	52KB AW13 SPN
G 3/8	22	62	25	9					Standard	52KB AW17 SPN
G 1/2	22	62	25	12					Standard	52KB AW21 SPN
G 1/4	22	62	25	10					Standard	52KB IW13 SPN

Couplings

RECTUS Series 52KB


Brass/Steel

Low Pressure

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 3/8	22	60	25	10					Standard	52KB IW17 SPN
	G 1/2	22	65	25	13					Standard	52KB IW21 SPN
 <p>Hose Barb</p>	6 mm	21	79	25	25					Standard	52KB TF06 SPN
	9 mm	21	80	25	25					Standard	52KB TF09 SPN
	10 mm	21	80	25	25					Standard	52KB TF110 SPN
	11 mm	21	80	25	25					Standard	52KB TF11 SPN
	13 mm	21	79	25	25					Standard	52KB TF13 SPN



Plugs

RECTUS Series 52KB


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm		46	12	25					Standard	52SF TF06 SXN
	9 mm		46	12	25					Standard	52SF TF09 SXN
	11 mm		53	12	30					Standard	52SF TF11 SXN
	13 mm		53	12	30					Standard	52SF TF13 SXN

Plugs

RECTUS Series 52KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14	32		7					Standard	52SF AW10 SXN
	G 1/4	17	35		9					Standard	52SF AW13 SXN
	G 3/8	19	35		9					Standard	52SF AW17 SXN
	G 1/2	24	38		12					Standard	52SF AW21 SXN
 <p>Female Thread</p>	G 1/8	14	31		7					Standard	52SF IW10 SXN
	G 1/4	17	33		9					Standard	52SF IW13 SXN
	G 3/8	19	33		9					Standard	52SF IW17 SXN
	G 1/2	24	36		12					Standard	52SF IW21 SXN

⚠ Please consider our security advices on the pages 12/13 ⚠



Nominal Diameter

7,2 = 40 mm²

RECTUS Series

26KA



actual size



Technical Description

European standard industrial profile. Universal brass coupling. Small mass size. Ergonomic sleeve design prevents dirt on the valve body. Series 26 plugs in brass. Series 25 steel plugs recommended for oscillating forces.

Advantages

Single handed operation. European standard.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability



RECTUS 25
RECTUS 1600/1625
TEMA 1600
CEJN 320
JWL 520 + JWL 530
and various German products

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Double Shut-off P. 136
- ▶ Stainless Steel P. 189
- ▶ Safety Self-Venting P. 288

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Pins
Seals

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug


Plug

Brass

Brass, Nickel Plated





Couplings

RECTUS Series 26KA





Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	22	43	25	9					Standard	26KA AW10 MPX
									Nickel Plated	26KA AW10 MPN
G 1/4	22	39	25	9					Standard	26KA AW13 MPX
									Nickel Plated	26KA AW13 MPN
G 3/8	22	41	25	9					Standard	26KA AW17 MPX
									Nickel Plated	26KA AW17 MPN
G 1/2	22	44	25	12					Standard	26KA AW21 MPX
									Nickel Plated	26KA AW21 MPN
G 1/2	24	42	25	10					Standard	26KA AW21 MPXS_36
									Nickel Plated	26KA AW21 MPNS_09

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Male Thread</p>	M 14 x 1,5	22	42	25	10					Standard	26KA AD14 MPX	
										Nickel Plated	26KA AD14 MPN	
	M 16 x 1,5	22	43	25	11					Standard	26KA AD16 MPX	
										Nickel Plated	26KA AD16 MPN	
	M 18 x 1,5	22	43	25	11					Standard	26KA AD18 MPX	
										Nickel Plated	26KA AD18 MPN	
 <p>Female Thread</p>	G 1/4	22	41	25	9					Standard	26KA IW13 MPX	
										Nickel Plated	26KA IW13 MPN	
	G 3/8	22	41	25	9					Standard	26KA IW17 MPX	
										Nickel Plated	26KA IW17 MPN	
	G 1/2	24	44	25	10					Standard	26KA IW21 MPX	
										Nickel Plated	26KA IW21 MPN	
	M 14 x 1,5	22	44	25	9					Standard	26KA IM14 MPX	
										Nickel Plated	26KA IM14 MPN	
	M 16 x 1,5	22	44	25	9					Standard	26KA IM16 MPX	
										Nickel Plated	26KA IM16 MPN	
 <p>Hose Barb</p>	6 mm	21	58	25	25					Standard	26KA TF06 MPX	
										Nickel Plated	26KA TF06 MPN	
	8 mm	21	58	25	25					Standard	26KA TF08 MPX	
										Nickel Plated	26KA TF08 MPN	
	9 mm	21	58	25	25					Standard	26KA TF09 MPX	
										Nickel Plated	26KA TF09 MPN	
	10 mm	21	58	25	25					Standard	26KA TF10 MPX	
										Nickel Plated	26KA TF10 MPN	
	13 mm	21	58	25	25					Standard	26KA TF13 MPX	
										Nickel Plated	26KA TF13 MPN	
	6 mm Parker	21	58	25	20,5					Standard	26KA TP06 MPX	
										Nickel Plated	26KA TP06 MPN	
	10 mm Parker	21	58	25	24					Standard	26KA TP10 MPX	
										Nickel Plated	26KA TP10 MPN	
 <p>Plastic Hose Connection</p>	4 x 6 mm	21	58	25	7	6		M 10 x 1	Standard	26KA KO06 MPX		
										Nickel Plated	26KA KO06 MPN	
	6 x 8 mm	21	45	25	7	6		M 12 x 1	Standard	26KA KO08 MPX		
										Nickel Plated	26KA KO08 MPN	
	8 x 10 mm	21	49	25	9	8		M 16 x 1	Standard	26KA KO10 MPX		
										Nickel Plated	26KA KO10 MPN	
	9 x 12 mm	21	49	25	9	8		M 16 x 1	Standard	26KA KO12 MPX		
										Nickel Plated	26KA KO12 MPN	



Couplings

RECTUS Series 26KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Panel Mount Hose Barb</p>	6 mm	21	60	25	17	10	17	4	M 12 x 1	Standard	26KA TS06 MPX
										Nickel Plated	26KA TS06 MPN
	8 mm	21	63	25	17	14	17	4	M 12 x 1	Standard	26KA TS08 MPX
										Nickel Plated	26KA TS08 MPN
	10 mm	21	72	25	25	14	17	4	G 1/4	Standard	26KA TS10 MPX
										Nickel Plated	26KA TS10 MPN
 <p>Plastic Hose Connection</p>	6 x 8 mm	21	132	25	7	6			M 12 x 1	Standard	26KA KK08 MPX
										Nickel Plated	26KA KK08 MPN
	8 x 10 mm	21	143	25	9	8			M 16 x 1	Standard	26KA KK10 MPX
										Nickel Plated	26KA KK10 MPN
	9 x 12 mm	21	150	25	9	8			M 16 x 1	Standard	26KA KK12 MPX
										Nickel Plated	26KA KK12 MPN



Plugs

RECTUS Series 26KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	4 mm		48	12	25					Standard	26SF TF04 MXX
										Nickel Plated	26SF TF04 MXN
	6 mm		48	12	25						26SF TF06 MXX
										Nickel Plated	26SF TF06 MXN
	8 mm		48	12	25					Standard	26SF TF08 MXX
										Nickel Plated	26SF TF08 MXN
	9 mm		48	12	25					Standard	26SF TF09 MXX
										Nickel Plated	26SF TF09 MXN
	10 mm		48	12	25					Standard	26SF TF10 MXX
										Nickel Plated	26SF TF10 MXN
	13 mm		48	15	25					Standard	26SF TF13 MXX
										Nickel Plated	26SF TF13 MXN
	6 mm Parker		43	16	20,5					Standard	26SF TP06 MXX
										Nickel Plated	26SF TP06 MXN
	10 mm Parker		46	22	24					Standard	26SF TP10 MXX
										Nickel Plated	26SF TP10 MXN
	13 mm Parker		50	24	28					Standard	26SF TP13 MXX
										Nickel Plated	26SF TP13 MXN
 <p>Plastic Hose Connection</p>	4 x 6 mm		34	12	7	6			M 10 x 1	Standard	26SF KO06 MXX
										Nickel Plated	26SF KO06 MXN
	6 x 8 mm		34	12	7	6			M 12 x 1	Standard	26SF KO08 MXX
										Nickel Plated	26SF KO08 MXN
	8 x 10 mm	17	42		9	6			M 16 x 1	Standard	26SF KO10 MXX
										Nickel Plated	26SF KO10 MXN
	9 x 12 mm	17	42		9	8			M 16 x 1	Standard	26SF KO12 MXX
										Nickel Plated	26SF KO12 MXN



Plugs

RECTUS Series 26KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Panel Mount Hose Barb</p>	6 mm	14	56		17	14	17	4	M 12 x 1	Standard	26SF TS06 MXX
										Nickel Plated	26SF TS06 MXN
	8 mm	17	56		17	14	17	4	M 12 x 1	Standard	26SF TS08 MXX
										Nickel Plated	26SF TS08 MXN
	10 mm	17	56		17	14	19	4	M 14 x 1	Standard	26SF TS10 MXX
										Nickel Plated	26SF TS10 MXN
 <p>Plastic Hose Connection with Spring Guard</p>	4 x 6 mm		120	12	7	6			M 10 x 1	Standard	26SF KK06 MXX
										Nickel Plated	26SF KK06 MXN
	6 x 8 mm		127	12	7	6			M 12 x 1	Standard	26SF KK08 MXX
										Nickel Plated	26SF KK08 MXN
	8 x 10 mm	17	135		9	8			M 16 x 1	Standard	26SF KK10 MXX
										Nickel Plated	26SF KK10 MXN
	9 x 12 mm	17	142		9	8			M 16 x 1	Standard	26SF KK12 MXX
										Nickel Plated	26SF KK12 MXN

Plugs


RECTUS Series 26KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14	31		7					Standard	26SF AW10 MXX
										Nickel Plated	26SF AW10 MXN
	G 1/4	17	33		9					Standard	26SF AW13 MXX
										Nickel Plated	26SF AW13 MXN
	G 3/8	19	33		9					Standard	26SF AW17 MXX
										Nickel Plated	26SF AW17 MXN
	G 1/2	24	38		12					Standard	26SF AW21 MXX
										Nickel Plated	26SF AW21 MXN
	M 14 x 1,5	17	35		10					Standard	26SF AD14 MXX
										Nickel Plated	26SF AD14 MXN
	M 16 x 1,5	19	36		11					Standard	26SF AD16 MXX
										Nickel Plated	26SF AD16 MXN
	M 18 x 1,5	22	37		11					Standard	26SF AD18 MXX
										Nickel Plated	26SF AD18 MXN
 <p>Female Thread</p>	G 1/8	14	30		7					Standard	26SF IW10 MXX
										Nickel Plated	26SF IW10 MXN
	G 1/4	17	33		10					Standard	26SF IW13 MXX
										Nickel Plated	26SF IW13 MXN
	G 3/8	19	33		10					Standard	26SF IW17 MXX
										Nickel Plated	26SF IW17 MXN
	G 1/2	24	35		12					Standard	26SF IW21 MXX
										Nickel Plated	26SF IW21 MXN
	M 14 x 1,5	17	33		10					Standard	26SF IM14 MXX
										Nickel Plated	26SF IM14 MXN
	M 16 x 1,5	19	33		10					Standard	26SF IM16 MXX
										Nickel Plated	26SF IM16 MXN
	M 18 x 1,5	22	36		13					Standard	26SF IM18 MXX
										Nickel Plated	26SF IM18 MXN

⚠ Please consider our security advices on the pages 12/13 ⚠


Plugs


RECTUS Series 26KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Flex Joint, Male Thread</p>	R 1/4	17	64		11					Nickel Plated	25FA AK13 SPN

Recoil Eliminator

RECTUS Series 26KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Hose Barb</p>	6 mm	21	60		25					Standard	26SR TF06 MXX	
										Nickel Plated	26SR TF06 MXN	
	8 mm	21	60		25						Standard	26SR TF08 MXX
											Nickel Plated	26SR TF08 MXN
	9 mm	21	60		25						Standard	26SR TF09 MXX
											Nickel Plated	26SR TF09 MXN
	10 mm	21	60		25						Standard	26SR TF10 MXX
											Nickel Plated	26SR TF10 MXN
	13 mm	21	60		25						Standard	26SR TF13 MXX
											Nickel Plated	26SR TF13 MXN



Technical Description

Japanese industrial profile. Robust brass coupling with above average flow volumes and structure resistant to the effects of external forces.

Advantages

Single handed operation. Anti-corrosive.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability

RECTUS 03
NITTO-KOHKI 200
CEJN 314
CEJN 315



Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.



Chart



Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Pins
Seals

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug
Steel Hardened, Nickel Plated


Couplings

RECTUS Series 13KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	22	49	27	12					Standard	13KA AK13 MPX
										Nickel Plated	13KA AK13 MPN
	R 3/8	22	49	27	12					Standard	13KA AK17 MPX
										Nickel Plated	13KA AK17 MPN
<p>Female Thread</p>	R 1/2	22	53	27	17					Standard	13KA AK21 MPX
										Nickel Plated	13KA AK21 MPN
	G 1/4	22	45	27	9					Standard	13KA IW13 MPX
										Nickel Plated	13KA IW13 MPN
	G 3/8	22	45	27	9					Standard	13KA IW17 MPX
										Nickel Plated	13KA IW17 MPN
	G 1/2	24	48	27	12					Standard	13KA IW21 MPX
										Nickel Plated	13KA IW21 MPN

Couplings

RECTUS Series 13KA




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	21	62	27	25					Standard	13KA TF06 MPX
									Nickel Plated	13KA TF06 MPN
8 mm	21	62	27	25					Standard	13KA TF08 MPX
									Nickel Plated	13KA TF08 MPN
10 mm	21	62	27	25					Standard	13KA TF10 MPX
									Nickel Plated	13KA TF10 MPN
13 mm	21	62	27	25					Standard	13KA TF13 MPX
									Nickel Plated	13KA TF13 MPN

Plugs

RECTUS Series 13KA




Hose Barb


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm		48	15	25					Standard	13SF TF06 SXN
8 mm		48	15	25					Standard	13SF TF08 SXN
10 mm		48	15	25					Standard	13SF TF10 SXN
13 mm		48	15	25					Standard	13SF TF13 SXN

Plugs

RECTUS Series 13KA



Male Thread



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/4	14	37		12					Standard	13SF AK13 SXN
R 3/8	17	37		12					Standard	13SF AK17 SXN
R 1/2	22	44		17					Standard	13SF AK21 SXN
G 1/4	17	34		9					Standard	13SF IW13 SXN
G 3/8	19	34		9					Standard	13SF IW17 SXN



Technical Description



3/8" – 1/2" European industrial profile with UltraFlo technology. High flow performance. Notable for robust design and steel sleeve used with large pneumatic consumers. Also available in brass design.

Dust Caps (P. 331)

for coupling Part.-No. SK23S
for plug Part.-No. SK12S



Chart



Advantages

Single handed operation.
Tough construction.
UltraFlo technology.

Interchangeability

RECTUS 26
RECTUS 1600/1625
TEMA 1600
CEJN 320
JWL 520 + JWL 530
and various German products

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Inner Sleeve
Spring Plate
Spring and Locking Ring
Locking Balls
Seals

Plug

Plug

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Standard

Brass, Nickel Plated
Brass, Nickel Plated
Steel Hardened, Nickel Plated
Zinc Diecasting, Nickel Plated
Brass
Brass
AISI 301
AISI 420
NBR

Steel Hardened, Zinc Plated

actual size



You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Double Shut-off P. 139
- ▶ Stainless Steel P. 192
- ▶ Safety P. 270
- ▶ Safety Self-Venting P. 290
- ▶ Coded Systems P. 303





Couplings





RECTUS Series 25KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	60	23	12					Standard	25KA AK13 MPN
	R 3/8	19	60	23	12					Standard	25KA AK17 MPN
	R 1/2	22	61	23	17					Standard	25KA AK21 MPN
	M 14 x 1,5	19	59	23	10					Standard	25KA AD14 MPN
	M 16 x 1,5	19	60	23	11					Standard	25KA AD16 MPN
	M 18 x 1,5	19	60	23	11					Standard	25KA AD18 MPN
<p>Female Thread</p>	G 1/4	19	56	23	10					Standard	25KA IW13 MPN
	G 3/8	19	55	23	9					Standard	25KA IW17 MPN
	G 1/2	24	58	23	12					Standard	25KA IW21 MPN
	M 14 x 1,5	19	55	23	9					Standard	25KA IM14 MPN
	M 16 x 1,5	19	55	23	9					Standard	25KA IM16 MPN
	M 18 x 1,5	22	56	23	9					Standard	25KA IM18 MPN

Couplings




RECTUS Series 25KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm	19	74	23	25					Standard	25KA TF06 MPN
	8 mm	19	74	23	25					Standard	25KA TF08 MPN
	9 mm	19	74	23	25					Standard	25KA TF09 MPN
	10 mm	19	74	23	25					Standard	25KA TF10 MPN
	13 mm	19	74	23	25					Standard	25KA TF13 MPN
	6 mm Parker	19	69	23	20					Standard	25KA TP06 MPN
	10 mm Parker	19	73	23	24					Standard	25KA TP10 MPN
	13 mm Parker	19	76	23	28					Standard	25KA TP13 MPN
 <p>Plastic Hose Connection</p>	6 x 8 mm	19	61	23	7	6				Standard	25KA KO08 MPN
	8 x 10 mm	19	65	23	9	8				Standard	25KA KO10 MPN
	9 x 12 mm	19	65	23	9	8				Standard	25KA KO12 MPN
 <p>Panel Mount, Hose Barb</p>	6 mm	19	76	23	17	10	17	4	M 12 x 1	Standard	25KA TS06 MPN
	8 mm	19	80	23	17	14	17	4	M 12 x 1	Standard	25KA TS08 MPN
	10 mm	19	87	23	25	14	17	4	G 1/4	Standard	25KA TS10 MPN
 <p>Plastic Hose Connection with Spring Guard</p>	6 x 8 mm	19	144	23	7	6				Standard	25KA KK08 MPN
	8 x 10 mm	19	155	23	9	8				Standard	25KA KK10 MPN
	9 x 12 mm	19	162	23	9	8				Standard	25KA KK12 MPN

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number		
 <p>Hose Barb</p>	6 mm		48	12	25					Standard	25SF TF06 SXZ		
	8 mm		48	12	25					Standard	25SF TF08 SXZ		
	9 mm		48	12	25					Standard	25SF TF09 SXZ		
	10 mm		48	12	25					Standard	25SF TF10 SXZ		
	13 mm		48	15	25					Standard	25SF TF13 SXZ		
 <p>Plastic Hose Connection</p>	4 x 6 mm		34	12	7	6		M 10 x 1	Standard	26SF KO06 MXX	Nickel Plated	26SF KO06 MXN	
	6 x 8 mm		34	12	7	6		M 12 x 1	Standard	26SF KO08 MXX	Nickel Plated	26SF KO08 MXN	
	8 x 10 mm	17	42		9	8		M 16 x 1	Standard	26SF KO10 MXX	Nickel Plated	26SF KO10 MXN	
	9 x 12 mm	17	42		9	8		M 16 x 1	Standard	26SF KO12 MXX	Nickel Plated	26SF KO12 MXN	
	6 mm	14	56		17	14	17	4	M 12 x 1	Standard	26SF TS06 MXX	Nickel Plated	26SF TS06 MXN
	8 mm	14	56		17	14	17	4	M 12 x 1	Standard	26SF TS08 MXX	Nickel Plated	26SF TS08 MXN
 <p>Panel Mount, Hose Barb</p>	10 mm	17	56		17	14	19	4	M 14 x 1	Standard	26SF TS10 MXX	Nickel Plated	26SF TS10 MXN
	4 x 6 mm		111	12	7	6			M 10 x 1	Standard	26SF KK06 MXX	Nickel Plated	26SF KK06 MXN
 <p>Plastic Hose Connection with Spring Guard</p>	6 x 8 mm		120	12	7	6		M 10 x 1	Standard	26SF KK08 MXX	Nickel Plated	26SF KK08 MXN	
	8 x 10 mm	17	132		9	8		M 16 x 1	Standard	26SF KK10 MXX	Nickel Plated	26SF KK10 MXN	
	9 x 12 mm	17	139		9	8		M 16 x 1	Standard	26SF KK12 MXX	Nickel Plated	26SF KK12 MXN	


Plugs

RECTUS Series 25KA


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/8	13	33		9					Standard	25SF AK10 SXZ
	R 1/4	14	36,5		12					Standard	25SF AK13 SXZ
	R 3/8	17	37		12					Standard	25SF AK17 SXZ
	R 1/2	22	43		17					Standard	25SF AK21 SXZ
	M 14 x 1,5	17	35		10					Standard	25SF AD14 SXZ
	M 16 x 1,5	19	36		10					Standard	25SF AD16 SXZ
	M 18 x 1,5	22	37		13					Standard	25SF AD18 SXZ
 <p>Female Thread</p>	G 1/8	14	30		5					Standard	25SF IW10 SXZ
	G 1/4	17	38,5		12					Standard	25SF IW13 SXZ
	G 3/8	19	39,5		12					Standard	25SF IW17 SXZ
	G 1/2	24	44		14					Standard	25SF IW21 SXZ
	M 14 x 1,5	17	33		8					Standard	25SF IM14 SXZ
	M 16 x 1,5	19	33		10					Standard	25SF IM16 SXZ
	M 18 x 1,5	22	36		13					Standard	25SF IM18 SXZ
 <p>Flex Joint, Male Thread</p>	R 1/4	17	64		11					Standard	25FA AK13 SPN

Recoil Eliminator


RECTUS Series 25KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Hose Barb</p>	6 mm	21	60	25						Standard	26SR TF06 MXX	
										Nickel Plated	26SR TF06 MXN	
	8 mm	21	60	25							Standard	26SR TF08 MXX
											Nickel Plated	26SR TF08 MXN
	9 mm	21	60	25							Standard	26SR TF09 MXX
											Nickel Plated	26SR TF09 MXN
	10 mm	21	60	25							Standard	26SR TF10 MXX
											Nickel Plated	26SR TF10 MXN
	13 mm	21	60	25							Standard	26SR TF13 MXX
											Nickel Plated	26SR TF13 MXN

1600KA



48 mm² = 7,8



Technical Description



Rectus Tema premium industrial coupling – the know-how from both brands combined in one system. European standard profile. High grade valve technology with optimum flow performance and minimum coupling forces. Suitable for compressed air applications with above average air consumption.

Dust Caps (P. 331)

for coupling Part.-No. SK23S
for plug Part.-No. SK12S



Chart



Advantages

Single handed operation. High flow valve. Minimum coupling forces.

Interchangeability

RECTUS 25 + 26
RECTUS 1625
TEMA 1600
CEJN 320
JWL 520 + JWL 530
various German products

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring
Locking Ring and
Locking Balls
Seals

Plug

Plug

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Standard

Brass, Nickel Plated
Steel, QPQ treated
Brass, Nickel Plated
Brass
AISI 301
AISI 420

NBR

Steel Hardened and
Zinc-Plated



actual size

You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel P. 192
- ▶ Safety Self-Venting P. 290


Couplings

RECTUS Series 1600KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	65	23	12					Standard	1600KA AK13 SPN
	R 3/8	19	65	23	12					Standard	1600KA AK17 SPN
	R 1/2	22	59,5	23	17					Standard	1600KA AK21 SPN
<p>Female Thread</p>	G 1/4	19	59	23	9					Standard	1600KA IW13 SPN
	G 3/8	19	59	23	9					Standard	1600KA IW17 SPN
	G 1/2	24	62	23	12					Standard	1600KA IW21 SPN



Couplings

RECTUS Series 1600KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm	19	80	23	25					Standard	1600KA TF06 SPN
	8 mm	19	80	23	25					Standard	1600KA TF08 SPN
	9 mm	19	80	23	25					Standard	1600KA TF09 SPN
	10 mm	19	80	23	25					Standard	1600KA TF10 SPN
	13 mm	19	80	23	25					Standard	1600KA TF13 SPN


Plugs


RECTUS Series 25SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/8	13	33		9					Standard	25SF AK10 SXZ
	R 1/4	14	37		12					Standard	25SF AK13 SXZ
	R 3/8	17	37		12					Standard	25SF AK17 SXZ
	R 1/2	22	43		17					Standard	25SF AK21 SXZ
 <p>Female Thread</p>	G 1/8	14	30		7					Standard	25SF IW10 SXZ
	G 1/4	17	38,5		9					Standard	25SF IW13 SXZ
	G 3/8	19	39,5		9					Standard	25SF IW17 SXZ
	G 1/2	24	44		12					Standard	25SF IW21 SXZ

Plugs

RECTUS Series 25SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm		48	12	25					Standard	25SF TF06 SXZ
	8 mm		48	12	25					Standard	25SF TF08 SXZ
	9 mm		48	12	25					Standard	25SF TF09 SXZ
	10 mm		48	12	25					Standard	25SF TF10 SXZ
	13 mm		48	15	25					Standard	25SF TF13 SXZ



Technical Description



Rectus Tema premium industrial coupling – the know-how from both brands combined in one system. European standard profile. High grade valve technology with optimum flow performance and minimum coupling forces. Extremely robust 2-component thermoplastic sleeve. Suitable for compressed air applications with above average air consumption.

Dust Caps (P. 331)

for coupling Part.-No. SK23S
for plug Part.-No. SK12S



Chart



Advantages

Single handed operation. High flow valve. Minimum coupling forces.

Interchangeability

RECTUS 25 + 26
RECTUS 1600
TEMA 1600
CEJN 320
JWL 520 + JWL 530
various German products

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +40°C (NBR)
-20°C up to +40°C (EPDM)
-20°C up to +40°C (FKM)
depending on the medium.

*At a temperature below -20°C and above 40°C special seals are available on request.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring
Locking Ring and Locking Balls
Seals

Standard

Brass, Nickel Plated Steel, QPQ treated
PA6 + TPE
Brass
AISI 301
AISI 420

NBR

Plug

Plugs

Steel Hardened and Zinc-Plated



actual size

You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel P. 192
- ▶ Safety Self-Venting P. 290


Couplings

RECTUS Series 1625KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	65	26	12					Standard	1625KA AK13 SPN
	R 3/8	19	65	26	12					Standard	1625KA AK17 SPN
	R 1/2	22	59,5	26	17					Standard	1625KA AK21 SPN
<p>Female Thread</p>	G 1/4	19	59	26	9					Standard	1625KA IW13 SPN
	G 3/8	19	59	26	9					Standard	1625KA IW17 SPN
	G 1/2	24	62	26	12					Standard	1625KA IW21 SPN



Couplings

RECTUS Series 1625KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm	19	80	26	25					Standard	1625KA TF06 SPN
	8 mm	19	80	26	25					Standard	1625KA TF08 SPN
	9 mm	19	80	26	25					Standard	1625KA TF09 SPN
	10 mm	19	80	26	25					Standard	1625KA TF10 SPN
	13 mm	19	80	26	25					Standard	1625KA TF13 SPN


Plugs


RECTUS Series 25SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/8	13	33		9					Standard	25SF AK10 SXZ
	R 1/4	14	37		12					Standard	25SF AK13 SXZ
	R 3/8	17	37		12					Standard	25SF AK17 SXZ
	R 1/2	22	43		17					Standard	25SF AK21 SXZ
 <p>Female Thread</p>	G 1/8	14	30		7					Standard	25SF IW10 SXZ
	G 1/4	17	38,5		9					Standard	25SF IW13 SXZ
	G 3/8	19	39,5		9					Standard	25SF IW17 SXZ
	G 1/2	24	44		12					Standard	25SF IW21 SXZ

Plugs

RECTUS Series 25SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm		48	12	25					Standard	25SF TF06 SXZ
	8 mm		48	12	25					Standard	25SF TF08 SXZ
	9 mm		48	12	25					Standard	25SF TF09 SXZ
	10 mm		48	12	25					Standard	25SF TF10 SXZ
	13 mm		48	15	25					Standard	25SF TF13 SXZ



Technical Description

Steel industrial coupling with high flow performance due to UltraFlo technology. Interchangeable with Atlas Copco profile. Specially suited to use with gaseous media in industry.

Advantages

Single handed operation. Extremely high flow performance from optimum valve design.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*



-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

* At a temperature below -20°C and above +100°C special seals are available on request.

Interchangeability

Atlas Copco QIC 10

Chart



Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Inner Sleeve
- Spring Plate
- Spring and Locking Ring
- Locking Balls
- Seals

Plug

Plug

Standard

- Brass, Nickel Plated
- Steel, Zinc Plated
- Steel Hardened, Nickel Plated
- Brass
- Brass
- Brass
- AISI 301
- AISI 420
- NBR

Steel Hardened, Zinc-Plated



Couplings


RECTUS Series 33KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	60	23	12					Standard	33KA AK13 SPN
	R 3/8	19	59	23	12					Standard	33KA AK17 SPN
	R 1/2	22	60	23	17					Standard	33KA AK21 SPN
<p>Female Thread</p>	G 1/4	19	55	23	10					Standard	33KA IW13 SPN
	G 3/8	19	54	23	9					Standard	33KA IW17 SPN
	G 1/2	24	57	23	12					Standard	33KA IW21 SPN

Couplings

RECTUS Series 33KA

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	19	73	23	25					Standard	33KA TF06 SPN
8 mm	19	73	23	25					Standard	33KA TF08 SPN
10 mm	19	73	23	25					Standard	33KA TF10 SPN
13 mm	19	73	23	25					Standard	33KA TF13 SPN




Hose Barb

Plugs

RECTUS Series 33KA

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm		52	14	25					Standard	33SF TF06 SXN
8 mm		52	14	25					Standard	33SF TF08 SXN
10 mm		52	15	25					Standard	33SF TF10 SXN
13 mm		52	15	25					Standard	33SF TF13 SXN




Hose Barb


Plugs

RECTUS Series 33KA


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/8	14	40		9					Standard	33SF AK10 SXN
R 1/4	14	42		12					Standard	33SF AK13 SXN
R 3/8	17	42		12					Standard	33SF AK17 SXN
R 1/2	22	47		17					Standard	33SF AK21 SXN
G 1/8	14	34		7					Standard	33SF IW10 SXN
G 1/4	17	37		9					Standard	33SF IW13 SXN
G 3/8	17	37		9					Standard	33SF IW17 SXN
G 1/2	24	42		12					Standard	33SF IW21 SXN



Male Thread



Female Thread



Technical Description



Extremely high flow values from UltraFlo technology. Optimum plug design due to greater insert depth and 6-way ball locking.

Dust Caps (P. 331)

for coupling Part.-No. SK27S
for plug Part.-No. SK12S



Chart



Advantages

Single handed operation. Optimum plug locking. Limited pressure loss. High flow valve.

Interchangeability

ISO 6150 C

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR) depending on the medium.

* At a temperature below -20°C and above +100°C special seals are available on request.

Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Inner Sleeve
- Spring Plate
- Spring and Locking Ring
- Locking Balls
- Seals

Plug

Plug

Standard

- Brass, Nickel Plated
- Steel, Nickel Plated
- Steel Hardened, Nickel Plated
- Brass
- Brass
- Brass
- AISI 301
- AISI 420
- NBR

Steel Hardened, Nickel Plated

80% of actual size




Couplings

RECTUS Series 84KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/4	27	83	29	12					Standard	84KA AW13 SPN
	G 3/8	27	83	29	12					Standard	84KA AW17 SPN
	G 1/2	27	83	29	15					Standard	84KA AW21 SPN
<p>Female Thread</p>	G 3/8	27	81	29	14					Standard	84KA IW17 SPN

Couplings

RECTUS Series 84KA




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
8 mm	27	97	29	25					Standard	84KA TF08 SPN
9 mm	27	97	29	25					Standard	84KA TF09 SPN
10 mm	27	97	29	25					Standard	84KA TF10 SPN
13 mm	27	97	29	25					Standard	84KA TF13 SPN
16 mm	27	97	29	25					Standard	84KA TF16 SPN

Plugs

RECTUS Series 84KA




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
8 mm		65	16	25					Standard	84SF TF08 SXN
9 mm		65	16	25					Standard	84SF TF09 SXN
10 mm		65	16	25					Standard	84SF TF10 SXN
13 mm		65	16	25					Standard	84SF TF13 SXN
16 mm		65	16	25					Standard	84SF TF16 SXN


Plugs

RECTUS Series 84KA




Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/4	17	57		12					Standard	84SF AW13 SXN
G 3/8	21	59		12					Standard	84SF AW17 SXN
G 1/2	21	64		15					Standard	84SF AW21 SXN



Female Thread

G 1/4	17	53		9					Standard	84SF IW13 SXN
G 3/8	19	54		9					Standard	84SF IW17 SXN



Technical Description

Modular coupling and plug without an integrated locking system for installation in multi-coupling systems (Series 08). Special coupling body with PTFE coating giving greater robustness, lower coupling forces, and resistance to liquid media.

Interchangeability

RECTUS Design

Working Pressure

PB = 15 bar, maximum static working pressure with safety factor of 4 to 1.



Working Temperature*

-15°C up to +100°C (NBR)
 -30°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM*)
 0°C up to +316°C (FFKM*)
 depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.



Chart



Material

Coupling

Back Body
 Valve Body

Valve
 Spring and Locking Ring
 Seals

Standard

Brass, Nickel Plated
 Steel Hardened and
 PTFE coated

Brass
 AISI 301
 FKM

Plug

Plug Profile

Back Body
 Valve
 Spring and Locking Ring
 Seal

Steel Hardened and
 PTFE coated

Brass, Nickel Plated
 Brass
 AISI 301
 FKM

You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Dry-Break P. 174



Couplings

RECTUS Series 93KF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 1/2	24	48		10,1					Standard	93KF IW21 SVN
<p>Hose Barb</p>	13 mm	24	62		17					Standard	93KF TF13 SVN



Valved Plugs

RECTUS Series 93KF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 1/2	24	57,5		10,1					Standard	93SF IW21 SXN
 <p>Hose Barb</p>	13 mm	24	68,5		25					Standard	93SF TF13 SXN

Locking Coupling and Bolt

RECTUS Series 93KF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Locking Couplings</p>			45								94KX
 <p>Locking Bolts</p>		24	58		13						94SX



Technical Description

Multi-coupling system as plate or individual components for connecting hose combinations. Special coupling body with PTFE coating giving greater robustness, lower coupling forces, and resistance to liquid media. The standard version consists of a floating plate fitted with 8 quick connect couplings, 2 handles and 2 locking couplings as well as a fixed plate fitted with 8 plugs and 2 locking bolts. The layout is asymmetrical to avoid mixing up the circulation systems.

Advantages

The safety locking system prevents unintentional disconnection.

Interchangeability

RECTUS Design

Material Coupling

- Plate with 2 Handles
- 8 Multi Couplings
 - Back Body
 - Valve Body
 - Inner Parts
 - Springs
 - Seals
 - Locking Rings
- 2 Locking Couplings

Plug

- Plate
- 8 Multi-Plugs
 - Back Body
 - Plug
 - Inner Parts
 - Springs
 - Seals
 - Locking Rings
- 2 Locking Bolts

Working Pressure

PB = 15 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

- 20°C up to +100°C (NBR)
- 40°C up to +120/150°C (EPDM)
- 15°C up to +200°C (FKM)
- 0°C up to 316°C (FFKM)

*At a temperature below -15°C and above +200°C special seals are available on request.

Standard

- Aluminium, elox.
- Brass, Nickel Plated
- Steel Hardened, DNC-PTFE-coated
- Brass
- AISI 301
- FKM
- AISI 301
- Steel Hardened, Nickel Plated

- Aluminium, elox.
- Brass, Nickel Plated
- Steel Hardened, DNC-PTFE-coated
- Brass
- AISI 301
- FKM
- AISI 301
- Steel Hardened, Nickel Plated



You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Dry-Break P. 176



Couplings


RECTUS Series 08KF

	Connection A	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L mm	Version	Part Number
<p>Female Thread</p>	G 1/2	170	100	50	30	18					Standard	08KF IW21 SVN
<p>Hose Barb</p>	13 mm	170	100	50	44	18					Standard	08KF TF13 SVN

Plugs

RECTUS Series 08KF

	Connection	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L mm	Version	Part Number
 <p>Female Thread</p>	G 1/2	170	100	50	30	27					Standard	08SF IW21 SXN
 <p>Hose Barb</p>	13 mm	170	100	50	44	27					Standard	08SF TF13 SXN



Technical Description

Brass coupling without valve. Application area for pressures up to 150 bar. Especially suitable for applications with non-aggressive liquids.

Advantages

Anti-corrosive. High flow. Minimum pressure drop.

Working Pressure

PB = 150 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

* At a temperature below -20°C and above +100°C special seals are available on request.

Interchangeability

PARKER
HANSEN

Material

Coupling


Back Body
Sleeve
Spring and Locking Rings
Locking Balls
Seals

Standard

Brass
Brass
AISI 301
AISI 420
NBR



Chart





Plug

Plug

Steel Hardened, Nickel Plated



Couplings


RECTUS Series 45KF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 Male Thread	G 1/4	24	43	28	13,5					Standard	45KF AW13 MPX
	G 3/8	24	43	28	13,5					Standard	45KF AW17 MPX
	G 1/4	24	37	28	13,5					Standard	45KF IW13 MPX
 Female Thread	G 3/8	24	37	28	14					Standard	45KF IW17 MPX

Plugs

RECTUS Series 45KF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/4	19	42		13,5					Standard	45SF AW13 SXN
 <p>Female Thread</p>	G 3/8	22	42		13,5					Standard	45SF AW17 SXN
	G 1/4	19	40		14					Standard	45SF IW13 SXN
	G 3/8	22	40		14					Standard	45SF IW17 SXN



Technical Description

3/8" US steel coupling system conforming to US Mil. Spec 4109. Robust design, steel valve bodies. Optimum plug design due to greater insert depth.

Advantages

Steel valve body for robust applications.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability

Industrial. Interchange 3/8"
US-MIL-SPEC-C-4109
ISO 6150 B
GROMELLE 900
ARO
HANSEN 4000
PARKER 30 3/8"



Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.



Chart



Material

Coupling

Back Body
Valve Body

Sleeve
Valve

Spring and Locking Ring
Pins
Seals

Plug

Plug

Standard

Brass
Steel, Zinc
Chromatized

Brass
Brass
AISI 301
AISI 420
NBR

Steel Hardened, Nickel Plated

Nickel Plated

Brass, Nickel Plated
Steel, Zinc
Chromatized

Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR


Couplings

RECTUS Series 30KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/4	22	49	30	9					Standard	30KA AW13 SPX
										Nickel Plated	30KA AW13 SPN
	G 3/8	22	49	30	9					Standard	30KA AW17 SPX
										Nickel Plated	30KA AW17 SPN
<p>Female Thread</p>	G 1/2	22	52	30	12					Standard	30KA AW21 SPX
										Nickel Plated	30KA AW21 SPN
	G 1/4	22	49	30	11					Standard	30KA IW13 SPX
										Nickel Plated	30KA IW13 SPN
	G 3/8	22	49	30	9					Standard	30KA IW17 SPX
										Nickel Plated	30KA IW17 SPN
	G 1/2	22	52	30	12					Standard	30KA IW21 SPX
										Nickel Plated	30KA IW21 SPN

Couplings

RECTUS Series 30KA




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	21	66	30	25					Standard	30KA TF06 SPX
									Nickel Plated	30KA TF06 SPN
8 mm	21	66	30	25					Standard	30KA TF08 SPX
									Nickel Plated	30KA TF08 SPN
10 mm	21	66	30	25					Standard	30KA TF10 SPX
									Nickel Plated	30KA TF10 SPN
13 mm	21	66	30	25					Standard	30KA TF13 SPX
									Nickel Plated	30KA TF13 SPN

Plugs

RECTUS Series 30KA




Hose Barb


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm		55	16	25					Standard	30SF TF06 SXN
8 mm		55	16	25					Standard	30SF TF08 SXN
10 mm		55	16	25					Standard	30SF TF10 SXN
13 mm		55	16	25					Standard	30SF TF13 SXN

Plugs

RECTUS Series 30KA




Male Thread



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/4	17	42		9					Standard	30SF AW13 SXN
G 3/8	19	42		9					Standard	30SF AW17 SXN
G 1/2	24	46		12					Standard	30SF AW21 SXN
G 1/4	17	40		10					Standard	30SF IW13 SXN
G 3/8	19	42		10					Standard	30SF IW17 SXN
G 1/2	24	43		12					Standard	30SF IW21 SXN



Technical Description

Brass coupling system produced for raw applications. Ergonomic sleeve design prevents dirt on the valve body. The system is suitable for use with non-aggressive liquid media.

Advantages

Single handed operation.
Anti-corrosive.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability

ARO 310
ORION 44520
ORION 44530



Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium

*At a temperature below -20°C and above +100°C special seals are available on request.



Chart



Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Pins
Seals

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR


Plug

Plug
Steel Hardened, Nickel Plated

Couplings

RECTUS Series 40KA


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 3/8	27	46	32	10					Standard	40KA IW17 MPX
									Nickel Plated	40KA IW17 MPN
G 1/2	27	46	32	11					Standard	40KA IW21 MPX
									Nickel Plated	40KA IW21 MPN



Female Thread



Plugs


RECTUS Series 40KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm		51	16	25					Standard	40SF TF06 SXN
	8 mm		51	16	25					Standard	40SF TF08 SXN
	10 mm		51	16	25					Standard	40SF TF10 SXN
	13 mm		51	16	25					Standard	40SF TF13 SXN
	19 mm		51	21	25					Standard	40SF TF19 SXN

Plugs

RECTUS Series 40KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 3/8	16	40		12					Standard	40SF AK17 SXN
	R 1/2	16	46		17					Standard	40SF AK21 SXN
	R 3/4	16	51		19					Standard	40SF AK26 SXN
 <p>Female Thread</p>	G 3/8	19	35		9					Standard	40SF IW17 SXN
	G 1/2	24	39		12					Standard	40SF IW21 SXN



Technical Description



1/2" European industrial profile with UltraFlo technology. High flow performance. Notable for robust design with steel sleeve in use with large pneumatic consumers. Also available in brass.

Dust Caps (P. 331)

for coupling Part.-No. SK27S
for plug Part.-No. SK16S



Chart



Advantages

Single handed operation. Low pressure drop. No damage to the valve body from binding design. High flow valve.

Interchangeability

RECTUS 41
RECTUS 1700
RECTUS 1727
TEMA 1700
CEJN 410

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM*)
0°C up to +316°C (FFKM*)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Inner Sleeve
Spring Plate
Spring and Locking Ring
Locking Balls
Seals

Standard

Brass, Nickel Plated
Brass, Nickel Plated
Steel Hardened, Nickel Plated
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Plug

Plug

Steel Hardened, Nickel Plated



You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Double Shut-off P. 145
- ▶ Stainless Steel P. 196
- ▶ Safety Self-Venting P. 292


Couplings

RECTUS Series 27KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	24	63	27	12					Standard	27KA AK13 MPN
	R 3/8	24	63	27	12					Standard	27KA AK17 MPN
	R 1/2	24	65	27	17					Standard	27KA AK21 MPN
	R 3/4	27	65	27	17					Standard	27KA AK26 MPN
<p>Female Thread</p>	G 1/4	24	56	27	10					Standard	27KA IW13 MPN
	G 3/8	24	56	27	11					Standard	27KA IW17 MPN
	G 1/2	24	56	27	12					Standard	27KA IW21 MPN
	G 3/4	27	60	27	16					Standard	27KA IW26 MPN


Couplings

RECTUS Series 27KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm	24	76	27	25					Standard	27KA TF06 MPN
	8 mm	24	76	27	25					Standard	27KA TF08 MPN
	9 mm	24	76	27	25					Standard	27KA TF09 MPN
	10 mm	24	76	27	25					Standard	27KA TF10 MPN
	13 mm	24	76	27	25					Standard	27KA TF13 MPN
	16 mm	24	76	27	20					Standard	27KA TF16 MPN
	19 mm	24	76	27	25					Standard	27KA TF19 MPN



Plugs



RECTUS Series 27KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm		48	15	25					Standard	27SF TF06 SXN
	8 mm		48	15	25					Standard	27SF TF08 SXN
	9 mm		48	15	25					Standard	27SF TF09 SXN
	10 mm		48	15	25					Standard	27SF TF10 SXN
	13 mm		48	15	25					Standard	27SF TF13 SXN
	16 mm		48	18	25					Standard	27SF TF16 SXN
	19 mm		49	21	25					Standard	27SF TF19 SXN

Plugs

RECTUS Series 27KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/4	17	40		12					Standard	27SF AK13 SXN
	R 3/8	17	40		12					Standard	27SF AK17 SXN
	R 1/2	22	45		17					Standard	27SF AK21 SXN
	R 3/4	27	48		19					Standard	27SF AK26 SXN
 <p>Female Thread</p>	G 1/4	17	33		9					Standard	27SF IW13 SXN
	G 3/8	19	33		12					Standard	27SF IW17 SXN
	G 1/2	24	37		12					Standard	27SF IW21 SXN
	G 3/4	32	42		16					Standard	27SF IW26 SXN



Technical Description

Premium industrial coupling in nominal diameter 10 with high grade valve technology and unprecedented flow values and minimum coupling forces. Especially suited to compressed air applications with above average air consumption.

Dust Caps (P. 331)

for coupling Part.-No. SK27S
for plug Part.-No. SK16S



Advantages

Single handed operation.
High flow valve. Minimum coupling forces.

Interchangeability

RECTUS 27
RECTUS 1727
TEMA 1700
CEJN 410

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring
Locking Ring and Locking Balls
Seals

Standard

Brass, Nickel Plated
Steel, QPQ treated
Brass, Nickel Plated
Brass
AISI 301
AISI 420

NBR

Plug


Plug
Steel Hardened, Zinc-Plated



You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Double Shut-off P. 148
- ▶ Stainless Steel P. 196
- ▶ Safety Self-Venting P. 292

Chart




Couplings

RECTUS Series 1700KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 3/8	24	70	27	12					Standard	1700KA AK17 SPN
	R 1/2	24	75	27	17					Standard	1700KA AK21 SPN
	R 3/4	27	64	27	17					Standard	1700KA AK26 SPN
<p>Female Thread</p>	G 3/8	24	64,5	27	10					Standard	1700KA IW17 SPN
	G 1/2	24	68	27	11					Standard	1700KA IW21 SPN
	G 3/4	32	69	27	14					Standard	1700KA IW26 SPN


Couplings

RECTUS Series 1700KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	10 mm	24	80	27	21					Standard	1700KA TF10 SPN
	13 mm	24	80	27	21					Standard	1700KA TF13 SPN
	16 mm	24	80	27	21					Standard	1700KA TF16 SPN



Plugs



RECTUS Series 27SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm		48	15	25					Standard	27SF TF06 SXN
	8 mm		48	15	25					Standard	27SF TF08 SXN
	9 mm		48	15	25					Standard	27SF TF09 SXN
	10 mm		48	15	25					Standard	27SF TF10 SXN
	13 mm		48	15	25					Standard	27SF TF13 SXN
	16 mm		48	18	25					Standard	27SF TF16 SXN
	19 mm		49	21	25					Standard	27SF TF19 SXN

Plugs

RECTUS Series 27SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/4	17	40		12					Standard	27SF AK13 SXN
	R 3/8	17	40		12					Standard	27SF AK17 SXN
	R 1/2	22	45		17					Standard	27SF AK21 SXN
	R 3/4	27	48		19					Standard	27SF AK26 SXN
 <p>Female Thread</p>	G 1/4	17	33		9					Standard	27SF IW13 SXN
	G 3/8	19	33		12					Standard	27SF IW17 SXN
	G 1/2	24	37		12					Standard	27SF IW21 SXN
	G 3/4	32	42		16					Standard	27SF IW26 SXN



Technical Description

Premium industrial coupling in nominal diameter 10 with high grade, resistant 2-component thermoplastic sleeve. Valve technology with unprecedented flow values and minimum coupling forces. Especially suited to compressed air applications with above average air consumption.

Dust Caps (P. 331)

for coupling Part.-No. SK27S
for plug Part.-No. SK16S



Advantages

Single handed operation. High flow valve. Minimum coupling forces. Ergonomic thermo-plastic sleeve.

Interchangeability

RECTUS 27
RECTUS 1700
TEMA 1700
CEJN 410

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*


-20°C up to +40°C (NBR)
-20°C up to +40°C (EPDM)
-20°C up to +40°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +40°C special seals are available on request.

80% of actual size



Chart



Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring
Locking Ring and
Locking Balls
Seals

Standard

Brass, Nickel Plated
Steel, QPQ treated
PA6 + TPE
Brass
AISI 301
AISI 420

NBR

Plug

Plug

Steel Hardened and
Zinc-Plated

You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Double Shut-off P. 145
- ▶ Stainless Steel P. 196
- ▶ Safety Self-Venting P. 292


Couplings

RECTUS Series 1727KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 3/8	24	70	30	12					Standard	1727KA AK17 SPN
	R 1/2	24	75	30	17					Standard	1727KA AK21 SPN
	R 3/4	27	64	30	17					Standard	1727KA AK26 SPN
<p>Female Thread</p>	G 3/8	24	64,5	30	10					Standard	1727KA IW17 SPN
	G 1/2	24	68	30	12					Standard	1727KA IW21 SPN
	G 3/4	32	69	30	14					Standard	1727KA IW26 SPN


Couplings

RECTUS Series 1727KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	10 mm	24	80	30	21					Standard	1727KA TF10 SPN
	13 mm	24	80	30	21					Standard	1727KA TF13 SPN
	16 mm	24	80	30	21					Standard	1727KA TF16 SPN



Plugs


RECTUS Series 27SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm		48	15	25					Standard	27SF TF06 SXN
	8 mm		48	15	25					Standard	27SF TF08 SXN
	9 mm		48	15	25					Standard	27SF TF09 SXN
	10 mm		48	15	25					Standard	27SF TF10 SXN
	13 mm		48	15	25					Standard	27SF TF13 SXN
	16 mm		48	18	25					Standard	27SF TF16 SXN
	19 mm		49	21	25					Standard	27SF TF19 SXN

Plugs

RECTUS Series 27SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/4	17	40		12					Standard	27SF AK13 SXN
	R 3/8	17	40		12					Standard	27SF AK17 SXN
	R 1/2	22	45		17					Standard	27SF AK21 SXN
	R 3/4	27	48		19					Standard	27SF AK26 SXN
 <p>Female Thread</p>	G 1/4	17	33		9					Standard	27SF IW13 SXN
	G 3/8	19	33		12					Standard	27SF IW17 SXN
	G 1/2	24	37		12					Standard	27SF IW21 SXN
	G 3/4	32	42		16					Standard	27SF IW26 SXN



Technical Description



Industrial coupling with UltraFlo technology demonstrates high flow performance. Used widely in the Scandinavian market. Especially suitable for use with liquid and gaseous media in the industrial area.

Dust Caps (P. 331)

for coupling Part.-No. SK27S
for plug Part.-No. SK16S



Chart



Advantages

Single handed operation.
Extremely high flow performance.

Interchangeability

TEMA 1800 (Single Shut-Off)
CEJN 408

Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Inner Sleeve
- Spring Plate
- Spring and Locking Ring
- Pins
- Seals

Plug

Plug

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

- 20°C up to +100°C (NBR)
 - 40°C up to +120/150°C (EPDM)
 - 15°C up to +200°C (FKM)
- depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Standard

- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass
- Brass
- Brass
- AISI 301
- AISI 420 C
- NBR

Steel Hardened,
Zinc Chromatized

85% of actual size




Couplings

RECTUS Series 32KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/2	23	69	27	13					Standard	32KA AK21 MPN
<p>Female Thread</p>	G 3/8	23	65	27	10					Standard	32KA IW17 MPN
	G 1/2	25	65	27	7					Standard	32KA IW21 MPN

Couplings

RECTUS Series 32KA




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
10 mm	24	82	27	23					Standard	32KA TF10 MPN
13 mm	24	82	27	24					Standard	32KA TF13 MPN
16 mm	24	82	27	24					Standard	32KA TF16 MPN
19 mm	24	82	27	24					Standard	32KA TF19 MPN

Plugs

RECTUS Series 32KA




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm		44	16	23					Standard	32SF TF06 SXZ
8 mm		44	16	23					Standard	32SF TF08 SXZ
10 mm		44	16	23					Standard	32SF TF10 SXZ
13 mm		44	16	24					Standard	32SF TF13 SXZ
16 mm		44	18	24					Standard	32SF TF16 SXZ
19 mm		44	21	24					Standard	32SF TF19 SXZ


Plugs

RECTUS Series 32KA




Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/4	16	39		12					Standard	32SF AK13 SXZ
R 3/8	17	38		12					Standard	32SF AK17 SXZ
R 1/2	22	40		14					Standard	32SF AK21 SXZ
R 3/4	27	43		16					Standard	32SF AK26 SXZ



Female Thread

G 1/4	16	36		10					Standard	32SF IW13 SXZ
G 3/8	20	36		10					Standard	32SF IW17 SXZ
G 1/2	25	39		12					Standard	32SF IW21 SXZ



Technical Description



Industrial profile with UltraFlo technology. Interchangeable with Atlas Copco profiles. High flow performance. The robust design and steel sleeve make it optimal for use with large pneumatic consumers.

Dust Caps (P. 331)

for coupling Part.-No. SK27S



Chart



Advantages

Single handed operation.
Low pressure drop. No damage to the valve body from binding design.

Interchangeability

Atlas Copco QIC 15

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Inner Sleeve
Spring Plate
Spring and Locking Ring
Locking Balls
Seals

Plug

Plug

Standard

Brass, Nickel Plated
Steel, Nickel Plated
Steel Hardened, Nickel Plated
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Steel Hardened, Nickel Plated

85% of actual size



Couplings


RECTUS Series 34KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/2	24	70	28	12					Standard	34KA AK13 SPN
	R 3/8	24	70	28	12					Standard	34KA AK17 SPN
	R 1/2	24	72	28	12					Standard	34KA AK21 SPN
	R 3/4	27	72	28	12					Standard	34KA AK26 SPN
<p>Female Thread</p>	G 1/4	24	64	28	9					Standard	34KA IW13 SPN
	G 3/8	24	64	28	12					Standard	34KA IW17 SPN
	G 1/2	24	64	28	12					Standard	34KA IW21 SPN

Couplings

RECTUS Series 34KA

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	24	84	28	25					Standard	34KA TF06 SPN
8 mm	24	84	28	25					Standard	34KA TF08 SPN
10 mm	24	84	28	25					Standard	34KA TF10 SPN
13 mm	24	84	28	25					Standard	34KA TF13 SPN
16 mm	24	84	28	25					Standard	34KA TF16 SPN
19 mm	24	84	28	25					Standard	34KA TF19 SPN



Hose Barb

Plugs

RECTUS Series 34KA

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm		55	15	25					Standard	34SF TF06 SXN
10 mm		55	15	25					Standard	34SF TF10 SXN
13 mm		55	15	25					Standard	34SF TF13 SXN
16 mm		55	18	25					Standard	34SF TF16 SXN




Hose Barb


Plugs

RECTUS Series 34KA

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/4	17	46		12					Standard	34SF AK13 SXN
R 3/8	19	46		12					Standard	34SF AK17 SXN
R 1/2	22	52		17					Standard	34SF AK21 SXN
G 3/8	19	40		9					Standard	34SF IW17 SXN
G 1/2	24	44		12					Standard	34SF IW21 SXN



Male Thread



Female Thread



Technical Description

Brass coupling without valve. Application area for pressures up to 35 bar. Especially suitable for applications with non-aggressive liquids.

Advantages

Anti-corrosive. High flow. Minimum pressure drop.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Interchangeability

RECTUS 27
CEJN 417

Material

Coupling

Back Body
Sleeve
Spring and Locking Ring
Locking balls
Seals

Standard

Brass, Nickel Plated
Brass, Nickel Plated
AISI 301
AISI 420
NBR

Plug


Plug

Brass, Nickel Plated

85% of actual size



Chart




Couplings

RECTUS Series 41KF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/2		31	25	8					Standard	41KF AW21 MPN
	G 3/4		32,5	25	9					Standard	41KF AW26 MPN
<p>Female Thread</p>	G 1/2	24	32,5	25	10					Standard	41KF IW21 MPN
	G 3/4	30	32,5	25	10					Standard	41KF IW26 MPN
	M 22 x 1	24	32,5	25	10					Standard	41KF IM22 MPN




Couplings

RECTUS Series 41KF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	10 mm		48,5	25	25					Standard	41KF TF10 MPN
	13 mm		48,5	25	25					Standard	41KF TF13 MPN
	16 mm		48,5	25	25					Standard	41KF TF16 MPN
	19 mm		48,5	25	25					Standard	41KF TF19 MPN

Plugs

RECTUS Series 41KF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	8 mm		48	15	25					Standard	41SF TF08 MXN
	10 mm		48	15	25					Standard	41SF TF10 MXN
	13 mm		48	15	25					Standard	41SF TF13 MXN
	16 mm		48	18	25					Standard	41SF TF16 MXN
	19 mm		48	21	25					Standard	41SF TF19 MXN
 <p>Male Thread</p>	G 1/2	24	40	12						Standard	41SF AW21 MXN
	G 3/4	32	45	16						Standard	41SF AW26 MXN
 <p>Female Thread</p>	G 1/2	24	37	12						Standard	41SF IW21 MXN
	G 3/4	32	42	16						Standard	41SF IW26 MXN
	M 22 x 1	24	36	12						Standard	41SF IM22 MXN



Technical Description

Brass coupling without valve. Application area for pressures up to 35 bar. Especially suitable for applications with non-aggressive liquids. Chrome plated standard design.

Advantages

Anti-corrosive. High flow. Minimum pressure drop.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability

ABA

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Material

Coupling

Back Body
Sleeve
Spring and Locking Ring
Locking Pins
Seals

Standard

Brass, Chrome Plated
Brass, Chrome Plated
AISI 301
AISI 304
NBR


Plug

Plug

Brass, Chrome Plated



Chart




Couplings RECTUS Series 42KF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/2		49	32	7,5					Standard	42KF AW21 MPC
	G 3/4		49	32	7,5					Standard	42KF AW26 MPC
<p>Female Thread</p>	G 1/2		34	32	8					Standard	42KF IW21 MPC
	G 3/4		34	32	8					Standard	42KF IW26 MPC




Couplings



RECTUS Series 42KF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	9 mm		55	32	25					Standard	42KF TF09 MPC
	13 mm		55	32	25					Standard	42KF TF13 MPC
	19 mm		55	32	25					Standard	42KF TF19 MPC

Plugs

RECTUS Series 42KF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	9 mm		48	15	25					Standard	42SF TF09 MXC
	13 mm		48	15	25					Standard	42SF TF13 MXC
	19 mm		48	15	25					Standard	42SF TF19 MXC
 <p>Male Thread</p>	G 1/2	24	35,5	12						Standard	42SF AW21 MXC
	G 3/4	32	42,5	16						Standard	42SF AW26 MXC
 <p>Female Thread</p>	G 1/2		31,5	30	8					Standard	42SF IW21 MXC
	G 3/4		31,5	30	8					Standard	42SF IW26 MXC



Technical Description

1/2" Coupling-System according to US-MIL-Spec. C-4109 made of brass. Plug design optimised through greater insert depth.

Advantages

Single handed operation. Tough construction.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability



Industrial Interchange 1/2" US-MIL-Spec. C-4109 1/2" ISO 6150-B-17 GROMELLE 1300 HANSEN 5000

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Pins
Seals

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug

Steel Hardened, Nickel Plated

70% of actual size



You will find the following alternative versions in our current catalogue on page:


► Safety Self-Venting

P. 294

Couplings

RECTUS Series 37KA



	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
	G 3/8	30	70,5	35	9					Standard	37KA AW17 MPX
										Nickel Plated	37KA AW17 MPN
	1/2 NPT	30	79	35	17					Standard	37KA AN21 MPX
										Nickel Plated	37KA AN21 MPN
	G 1/2	30	76,5	35	12					Standard	37KA AW21 MPX
										Nickel Plated	37KA AW21 MPN
	3/4 NPT	30	81	35	19					Standard	37KA AN26 MPX
										Nickel Plated	37KA AN26 MPN
	G 3/4	30	77,5	35	13					Standard	37KA AW26 MPX
										Nickel Plated	37KA AW26 MPN



Male Thread


Couplings

RECTUS Series 37KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	3/8 NPSF	30	76	35	14					Standard	37KA IN17 MPX
										Nickel Plated	37KA IN17 MPN
	1/2 NPSF	30	83	35	23					Standard	37KA IN21 MPX
										Nickel Plated	37KA IN21 MPN
	3/4 NPSF	32	84	35	24					Standard	37KA IN26 MPX
										Nickel Plated	37KA IN26 MPN
 <p>Hose Barb</p>	10 mm	30	86	35	25					Standard	37KA TF10 MPX
										Nickel Plated	37KA TF10 MPN
	13 mm	30	86	35	25					Standard	37KA TF13 MPX
										Nickel Plated	37KA TF13 MPN
	16 mm	30	86	35	25					Standard	37KA TF16 MPX
										Nickel Plated	37KA TF16 MPN
	19 mm	30	86	35	25					Standard	37KA TF19 MPX
										Nickel Plated	37KA TF19 MPN



Plugs


RECTUS Series 37KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	10 mm		62	17	25					Nickel Plated	37SF TF10 SXN
	13 mm		62	17	25					Nickel Plated	37SF TF13 SXN
	16 mm		62	18	25					Nickel Plated	37SF TF16 SXN
	19 mm		72	21	35					Nickel Plated	37SF TF19 SXN

Plugs

RECTUS Series 37KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 3/8	17	53		12					Nickel Plated	37SF AK17 SXN
	R 1/2	22	60		17					Nickel Plated	37SF AK21 SXN
	R 3/4	27	61		19					Nickel Plated	37SF AK26 SXN
 <p>Female Thread</p>	R 3/8	19	56		19					Nickel Plated	37SF IN17 SXN
	G 1/2	24	50		10					Nickel Plated	37SF IW21 SXN
	G 3/4	32	57		14					Nickel Plated	37SF IW26 SXN



Technical Description

German industrial profile with UltraFlo technology. Optimum structure with respect to size and performance. Robust coupling in compressed air applications, especially for oscillating forces due to steel sleeve and steel valve bodies.

Advantages

Single handed operation. Low pressure drop. UltraFlo technology. No damage to the valve body from binding design. High flow valve.

Interchangeability

WALTHER LP012

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*



-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

55% of actual size



Chart



Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring Plate
Spring and Locking Ring
Locking Balls
Seals

Plug

Plug

Standard

Brass, Nickel Plated
Steel Hardened, Nickel Plated
Steel Hardened, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
AISI 301
AISI 420
NBR

Steel Nickel Plated

You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Double Shut-off P. 152

Couplings


RECTUS Series 57KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/2	34	98	40	12					Standard	57KB AW21 SPN
	G 3/4	34	100	40	16					Standard	57KB AW26 SPN
	G 1	41	100	40	19					Standard	57KB AW33 SPN
<p>Female Thread</p>	G 1/2	34	100	40	19					Standard	57KB IW21 SPN
	G 3/4	34	100	40	16					Standard	57KB IW26 SPN
	G 1	41	101	40	20					Standard	57KB IW33 SPN

Couplings

RECTUS Series 57KB

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
16 mm	34	122	40	36					Standard	57KB TF16 SPN
19 mm	34	122	40	36					Standard	57KB TF19 SPN




Hose Barb

Plugs

RECTUS Series 57SF

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
13 mm		63	28	28					Standard	57SF TF13 SXN
16 mm		71	28	36					Standard	57SF TF16 SXN
19 mm		71	28	36					Standard	57SF TF19 SXN




Hose Barb

Plugs

RECTUS Series 57SF


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 3/8	27	49		12					Standard	57SF AW17 SXN
G 1/2	27	52		15					Standard	57SF AW21 SXN
G 3/4	32	55		17					Standard	57SF AW26 SXN
G 1	41	60		20					Standard	57SF AW33 SXN
G 1/2	27	48		15					Standard	57SF IW21 SXN
G 3/4	32	54		20					Standard	57SF IW26 SXN



Male Thread



Female Thread



Technical Description

Extremely robust steel coupling system with UltraFlo technology. Especially suitable in building or mining. Compact design prevents extreme dirtying on the sleeve and plug profile.

Advantages

Single handed operation. Low pressure drop. High flow valve.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability

RECTUS Design

Working Temperature*

-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 depending on the medium.


*At a temperature below -20°C and above +100°C special seals are available on request.

65% of actual size




Chart

Air



Water



Material

Coupling

- Back Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals

Standard

- Steel, Zinc Plated
- Steel Hardened, Zinc Plated
- Brass
- AISI 301
- AISI 420
- NBR

Plug


Plug

Steel Hardened, Zinc Plated

Couplings

RECTUS Series 29KA


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
	G 1/2	32	78	40	13					Standard	29KA IW21 SPZ
	G 3/4	32	78	40	16					Standard	29KA IW26 SPZ



Female Thread



Plugs

RECTUS Series 29KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	13 mm		76	22	49					Standard	29SF TF13 SPZ
	19 mm	34	122	40	36					Standard	29SF TF19 SPZ



Plugs


RECTUS Series 29KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/2	24	48		13					Standard	29SF AW21 SPZ
	G 3/4	32	48		14					Standard	29SF AW26 SPZ
 <p>Female Thread</p>	G 1/2	27	44		12					Standard	29SF IW21 SPZ
	G 3/4	32	48		16					Standard	29SF IW26 SPZ

Recoil Eliminator

RECTUS Series 29KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	13 mm	32	93		28					Standard	29SR TF13 SPZ
	19 mm	32	101		36					Standard	29SR TF19 SPZ
 <p>Plastic Hose Connection</p>	13 x 16 mm	32	83		11	8	24	M 22 x 1		Standard	29SR KO16 SPZ



Technical Description

Brass industrial profile with UltraFlo technology. Compact dimensions with high performance characteristics. Coupling can be used with numerous gaseous and liquid media.

Advantages

Compact construction. Extremely high flow performance due to the Rectus UltraFlo valve.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability

HANSEN 6000

Working Temperature*



-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 0°C up to +316°C (FFKM)
 depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

60% of actual size



Chart



Material

Coupling

Back Body
 Valve Body
 Sleeve
 Valve
 Inner Sleeve
 Spring Plate
 Spring and Locking Ring
 Locking Balls
 Seals

Standard

Brass
 Brass
 Brass
 Brass
 Brass
 Brass
 Brass
 AISI 301
 AISI 420
 NBR

Nickel Plated

Brass, Nickel Plated
 Brass, Nickel Plated
 Brass, Nickel Plated
 Brass
 Brass
 Brass
 AISI 301
 AISI 420
 NBR

Plug

Plug

Brass

Brass, Nickel Plated

You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Double Shut-off P. 156


Couplings

RECTUS Series 38 KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/2	34	89	40	12					Standard	38KB AW21 MPX
										Nickel Plated	38KB AW21 MPN
	G 3/4	34	91	40	16					Standard	38KB AW26 MPX
										Nickel Plated	38KB AW26 MPN
<p>Female Thread</p>	G 1	41	91	40	19					Standard	38KB AW33 MPX
										Nickel Plated	38KB AW33 MPN
	G 1/2	34	95	40	20					Standard	38KB IW21 MPX
										Nickel Plated	38KB IW21 MPN
	G 3/4	34	91	40	14					Standard	38KB IW26 MPX
										Nickel Plated	38KB IW26 MPN
	G 1	41	92	40	20					Standard	38KB IW33 MPX
										Nickel Plated	38KB IW33 MPN


Couplings

RECTUS Series 38KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	13 mm	34	105	40	28					Standard	38KB TF13 MPX
										Nickel Plated	38KB TF13 MPN
	16 mm	34	113	40	36					Standard	38KB TF16 MPX
										Nickel Plated	38KB TF16 MPN
	19 mm	34	113	40	36					Standard	38KB TF19 MPX
										Nickel Plated	38KB TF19 MPN
	25 mm	34	109	40	36					Standard	38KB TF25 MPX
										Nickel Plated	38KB TF25 MPN



Plugs


RECTUS Series 38SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	13 mm		65	30	28					Standard	38SF TF13 MXX
										Nickel Plated	38SF TF13 MXN
	16 mm		73	30	36					Standard	38SF TF16 MXX
										Nickel Plated	38SF TF16 MXN
	19 mm		73	30	36					Standard	38SF TF19 MXX
										Nickel Plated	38SF TF19 MXN
	25 mm		76	30	36					Standard	38SF TF25 MXX
										Nickel Plated	38SF TF25 MXN

Plugs

RECTUS Series 38SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/2	24	54		12					Standard	38SF AW21 MXX
										Nickel Plated	38SF AW21 MXN
	G 3/4	27	58		16					Standard	38SF AW26 MXX
										Nickel Plated	38SF AW26 MXN
	G 1	36	63		19					Standard	38SF AW33 MXX
										Nickel Plated	38SF AW33 MXN
 <p>Female Thread</p>	G 1/2	24	49		12					Standard	38SF IW21 MXX
										Nickel Plated	38SF IW21 MXN
	G 3/4	30	54		18					Standard	38SF IW26 MXX
										Nickel Plated	38SF IW26 MXN
	G 1	41	61		24					Standard	38SF IW33 MXX
										Nickel Plated	38SF IW33 MXN



Technical Description

Brass industrial profile with UltraFlo technology. Compact dimensions with high performance characteristics. Coupling can be used with numerous gaseous and liquid media.

Advantages

Compact construction. Extremely high flow performance due to the Rectus UltraFlo valve.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*



-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 0°C up to +316°C (FFKM)
 depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Interchangeability

HANSEN 7000

Chart



Material

Back Body
 Valve Body
 Sleeve
 Valve
 Inner Sleeve
 Spring Plate
 Spring and Locking Ring
 Locking Balls
 Seals

Standard

Brass
 Brass
 Brass
 Brass
 Brass
 Brass
 Brass
 AISI 301
 AISI 420
 NBR

Nickel Plated

Brass, Nickel Plated
 Brass, Nickel Plated
 Brass, Nickel Plated
 Brass
 Brass
 Brass
 AISI 301
 AISI 420
 NBR

Plug

Plug

Brass

Brass, Nickel Plated

50% of actual size



You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Double Shut-off P. 158
- ▶ Brass/Steel Dry-Break P. 180

Couplings


RECTUS Series 39KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 3/4	41	95	46	16					Standard	39KB AW26 MPX
										Nickel Plated	39KB AW26 MPN
	G 1	41	98	46	19					Standard	39KB AW33 MPX
										Nickel Plated	39KB AW33 MPN
<p>Female Thread</p>	G 1 1/4	46	98	46	19					Standard	39KB AW42 MPX
										Nickel Plated	39KB AW42 MPN
	G 3/4	41	99	46	20					Standard	39KB IW26 MPX
										Nickel Plated	39KB IW26 MPN
	G 1	41	100	46	22					Standard	39KB IW33 MPX
										Nickel Plated	39KB IW33 MPN
	G 1 1/4	50	105	46	22					Standard	39KB IW42 MPX
										Nickel Plated	39KB IW42 MPN

Couplings

RECTUS Series 39KB

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version		Part Number
									Standard	Nickel Plated	
19 mm	41	115	46	36					Standard		39KB TF19 MPX
									Nickel Plated		39KB TF19 MPN
25 mm	41	125	46	48					Standard		39KB TF25 MPX
									Nickel Plated		39KB TF25 MPN




Hose Barb

Plugs

RECTUS Series 39SF

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version		Part Number
									Standard	Nickel Plated	
19 mm		75	35	36					Standard		39SF TF19 MXX
									Nickel Plated		39SF TF19 MXN
25 mm		87	35	48					Standard		39SF TF25 MXX
									Nickel Plated		39SF TF25 MXN




Hose Barb


Plugs

RECTUS Series 39SF

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version		Part Number
									Standard	Nickel Plated	
G 3/4	30	60		16					Standard		39SF AW26 MXX
									Nickel Plated		39SF AW26 MXN
G 1	34	65		19					Standard		39SF AW33 MXX
									Nickel Plated		39SF AW33 MXN
G 1 1/4	46	68		19					Standard		39SF AW42 MXX
									Nickel Plated		39SF AW42 MXN
G 3/4	32	58		16					Standard		39SF IW26 MXX
									Nickel Plated		39SF IW26 MXN
G 1	41	68		24					Standard		39SF IW33 MXX
									Nickel Plated		39SF IW33 MXN
G 1 1/4	50	70		26					Standard		39SF IW42 MXX
									Nickel Plated		39SF IW42 MXN




Male Thread



Female Thread



Life is already hard enough.



The design of RectusTema series 1600KA and 1625KA allows operation of the coupling systems with very little exertion. The innovative high-flow valve also ensures optimum flow.






Nominal Diameter

2,7 = 5 mm²

RECTUS Series

20KB



actual size



Technical Description

Mini industrial coupling, internationally used profile. Notable for a high flow and numerous application options with various media. Frequent use in medical technology and chemistry/pharmacy.

Advantages

Single handed operation.
Small dimensions.
Minimal pressure drop.

Working Pressure



PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Single Shut-off P. 26
- ▶ Stainless Steel P. 200

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
(Sleeve made of Aluminium, elox. on request)

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug Profile
Back Body
Valve
Spring
Seal

Brass
Brass
Brass
AISI 301
NBR

Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
NBR

Couplings

RECTUS Series 20KB





	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	M5	9	26	10	5					Standard	20KB AM05 MPX
										Nickel Plated	20KB AM05 MPN
<p>Female Thread</p>	G 1/8	11	28	10	7					Standard	20KB AW10 MPX
										Nickel Plated	20KB AW10 MPN
	M5	9	26	10	5					Standard	20KB IM05 MPX
										Nickel Plated	20KB IM05 MPN
	G 1/8	12	28	10	7					Standard	20KB IW10 MPX
										Nickel Plated	20KB IW10 MPN

Couplings

RECTUS Series 20KB


Brass/Steel

Low Pressure

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	3 mm		35	10	13					Standard	20KB TF03 MPX
										Nickel Plated	20KBTF03MPN
	4 mm		35	10	13					Standard	20KB TF04 MPX
										Nickel Plated	20KB TF04 MPN
	5 mm		34	10	13					Standard	20KB TF05 MPX
										Nickel Plated	20KB TF05 MPN
 <p>Plastic Hose Connection</p>	3 x 4 mm	9	34	10	7	5				Standard	20KB KO04 MPX
										Nickel Plated	20KB KO04 MPN
	3 x 5 mm	9	34	10	7	5				Standard	20KB KO05 MPX
										Nickel Plated	20KB KO05 MPN
	4 x 6 mm	9	34	10	7	5				Standard	20KB KO06 MPX
										Nickel Plated	20KB KO06 MPN
 <p>Panel Mount, Plastic Hose Connection</p>	3 x 4 mm	12	45	10	7	17	11	3	M 7 x 0,5	Standard	20KB KS04 MPX
										Nickel Plated	20KB KS04 MPN
	3 x 5 mm	12	45	10	7	17	11	3	M 7 x 0,5	Standard	20KB KS05 MPX
										Nickel Plated	20KB KS05 MPN
	4 x 6 mm	12	45	10	7	17	12	3,5	M 8 x 0,5	Standard	20KB KS06 MPX
										Nickel Plated	20KB KS06 MPN
 <p>Panel Mount, Hose Barb</p>	3 mm	12	51	10	13	17	11	3	M 7 x 0,5	Standard	20KB TS03 MPX
										Nickel Plated	20KB TS03 MPN
	4 mm	12	51	10	13	17	11	3	M 7 x 0,5	Standard	20KB TS04 MPX
										Nickel Plated	20KB TS04 MPN

Valved Plugs




RECTUS Series 20KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	3 mm	8	36		13					Standard	20SB TF03 MPX
										Nickel Plated	20SB TF03 MPN
	4 mm	8	36		13					Standard	20SB TF04 MPX
										Nickel Plated	20SB TF04 MPN
	5 mm	8	36		13					Standard	20SB TF05 MPX
										Nickel Plated	20SB TF05 MPN

⚠ Please consider our security advices on the pages 12/13 ⚠



Valved Plugs

RECTUS Series 20KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Plastic Hose Connection</p>	3 x 4 mm	9	30,5		7	5			M 7 x 0,5	Standard	20SB KO04 MPX
										Nickel Plated	20SB KO04 MPN
	3 x 5 mm	9	30,5		7	5			M 7 x 0,5	Standard	20SB KO05 MPX
										Nickel Plated	20SB KO05 MPN
	4 x 6 mm	9	30,5		7	5			M 8 x 0,5	Standard	20SB KO06 MPX
										Nickel Plated	20SB KO06 MPN
 <p>Panel Mount, Plastic Hose Connection</p>	3 x 4 mm	12	46,5		7	17	11	3	M 7 x 0,5	Standard	20SB KS04 MPX
										Nickel Plated	20SB KS04 MPN
	3 x 5 mm	12	46,5		7	17	11	3	M 7 x 0,5	Standard	20SB KS05 MPX
										Nickel Plated	20SB KS05 MPN
	4 x 6 mm	12	46,5		7	17	12	3,5	M 8 x 0,5	Standard	20SB KS06 MPX
										Nickel Plated	20SB KS06 MPN
 <p>Panel Mount, Hose Barb</p>	3 mm	12	52,5		13	17	11	3	M 7 x 0,5	Standard	20SB TS03 MPX
										Nickel Plated	20SB TS03 MPN
	4 mm	12	52,5		13	17	11	3	M 7 x 0,5	Standard	20SB TS04 MPX
										Nickel Plated	20SB TS04 MPN
	6 mm	12	46,5		13	17	12	3	M 10 x 1	Standard	20SB TS06 MPX
										Nickel Plated	20SB TS06 MPN

Valved Plugs

RECTUS Series 20KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	M 5	9	28		5					Standard	20SB AM05 MPX
										Nickel Plated	20SB AM05 MPN
	G 1/8	11	30		7					Standard	20SB AW10 MPX
										Nickel Plated	20SB AW10 MPN
 <p>Female Thread</p>	M 5	9	26		5					Standard	20SB IM05 MPX
										Nickel Plated	20SB IM05 MPN
	G 1/8	12	30		7					Standard	20SB IW10 MPX
										Nickel Plated	20SB IW10 MPN



Nominal Diameter

4,3 = 15 mm²

RECTUS Series

71KB



actual size



You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel P. 216
- ▶ Thermoplastic P. 256

Technical Description

The 71KB series plug profile conforms to ISO Standard 7241-1 series B and is compatible with other makes of the same standard.

Advantages

This is a coupling to be operated with two hands, i.e. the unlocking sleeve must be pushed back manually when coupling.

Working Pressure

PB = 250 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +200°C special seals are available on request.

Material

Coupling

- Coupling Body
- Sleeve
- Valve
- Springs
- Locking Balls
- Seals
- Valve Holder

Brass Version


- Brass
- Brass
- Brass
- AISI 301
- AISI 420 C
- NBR
- AISI 301

Plug

- Plug Body
- Valve
- Springs
- Seals
- Valve Holder

- Brass
- Brass
- AISI 301
- NBR
- AISI 301

Chart



Couplings

RECTUS Series 71KB

	Connection A	Hex SW	L mm	L1 mm	D mm	Working press. connected	Version	Seal	Part Number
 Female Thread	G 1/8	14	48,5	7	25	250 bar	Brass	NBR	71KB IW10 MPX

Plugs

RECTUS Series 71KB

	Connection A	Hex SW	L mm	L1 mm	D mm	Working press. connected	Version	Seal	Part Number
 Female Thread	G 1/8	14	29,5	7	25	250 bar	Brass	NBR	71SB IW10 MPX



Technical Description



Mini industrial coupling, internationally the most common profile for this nominal diameter, in double shut-off design. Above average flow performance for liquid and gaseous media. Large band width in materials and valve variants.

Dust Caps (P. 331)

for coupling Part.-No. SK16S



Chart



Advantages

Single handed operation. Small dimensions. Reliable design.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Materials

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug Profile
Back Body
Valve
Spring
Seal

Brass
Brass
Brass
AISI 301
NBR

Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
NBR

actual size




You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Single Shut-off P. 34
- ▶ Brass/Steel Dry-Break P. 164
- ▶ Stainless Steel P. 205
- ▶ Thermoplastics P. 242
- ▶ Safety P. 276
- ▶ Coded Systems P. 300

Couplings

RECTUS Series 21KB











Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version		Part Number
									Standard	Nickel Plated	
G 1/8	14	36	16	7					Standard	Nickel Plated	21KB AW10 MPX 21KB AW10 MPN
G 1/4	17	38	16	9					Standard	Nickel Plated	21KB AW13 MPX 21KB AW13 MPN
G 3/8	19	38	16	9					Standard	Nickel Plated	21KB AW17 MPX 21KB AW17 MPN
M 10 x 1	14	37	16	8					Standard	Nickel Plated	21KB AD10 MPX 21KB AD10 MPN
M 12 x 1,5	17	39	16	10					Standard	Nickel Plated	21KB AD12 MPX 21KB AD12 MPN
M 14 x 1,5	17	39	16	10					Standard	Nickel Plated	21KB AD14 MPX 21KB AD14 MPN

Couplings






RECTUS Series 21KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Female Thread</p>	G 1/8	14	36	16	9					Standard	21KB IW10 MPX	
										Nickel Plated	21KB IW10 MPN	
	G 1/4	17	38	16	9					Standard	21KB IW13 MPX	
										Nickel Plated	21KB IW13 MPN	
	G 3/8	19	38	16	9					Standard	21KB IW17 MPX	
										Nickel Plated	21KB IW17 MPN	
	M 12 x 1,5	17	38	16	6					Standard	21KB IM12 MPX	
										Nickel Plated	21KB IM12 MPN	
	M 14 x 1,5	17	38	16	6					Standard	21KB IM14 MPX	
										Nickel Plated	21KB IM14 MPN	
	 <p>Hose Barb</p>	4 mm	14	46	16	17					Standard	21KB TF04 MPX
											Nickel Plated	21KB TF04 MPN
5 mm		14	46	16	17					Standard	21KB TF05 MPX	
										Nickel Plated	21KB TF05 MPN	
6 mm		14	46	16	17					Standard	21KB TF06 MPX	
										Nickel Plated	21KB TF06 MPN	
8 mm		14	46	16	17					Standard	21KB TF08 MPX	
										Nickel Plated	21KB TF08 MPN	
9 mm		14	46	16	17					Standard	21KB TF09 MPX	
										Nickel Plated	21KB TF09 MPN	
10 mm		14	46	16	17					Standard	21KB TF10 MPX	
										Nickel Plated	21KB TF10 MPN	
 <p>Plastic Hose Connection</p>	4 x 6 mm	14	42	16	7	6			M 10 x 1	Standard	21KB KO06 MPX	
										Nickel Plated	21KB KO06 MPN	
	6 x 8 mm	14	42	16	7	6				M 12 x 1	Standard	21KB KO08 MPX
										Nickel Plated	21KB KO08 MPN	
 <p>Panel Mount, Plastic Hose Connection</p>	4 x 6 mm	14	54	16	7	18	14	4	M 10 x 1	Standard	21KB KS06 MPX	
										Nickel Plated	21KB KS06 MPN	
	6 x 8 mm	17	54	16	7	18	17	4	M 12 x 1	Standard	21KB KS08 MPX	
										Nickel Plated	21KB KS08 MPN	


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Front Panel Installation Plastic Hose Panel Mount</p>	4 x 6 mm	22	42	24	7	16	24	5	M 20 x 1	Standard	21KB KE06 MPX
										Nickel Plated	21KB KE06 MPN
	6 x 8 mm	22	42	24	7	16	24	5	M 20 x 1	Standard	21KB KE08 MPX
										Nickel Plated	21KB KE08 MPN
 <p>Front Panel Installation, Hose Barb Panel Mount</p>	4 mm	22	46	24	17	16	24	5	M 20 x 1	Standard	21KB TE04 MPX
										Nickel Plated	21KB TE04 MPN
	6 mm	22	46	24	17	16	24	5	M 20 x 1	Standard	21KB TE06 MPX
										Nickel Plated	21KB TE06 MPN
	9 mm	22	46	24	17	16	24	5	M 20 x 1	Standard	21KB TE09 MPX
										Nickel Plated	21KB TE09 MPN
	10 mm	22	46	24	17	16	24	5	M 20 x 1	Standard	21KB TE10 MPX
										Nickel Plated	21KB TE10 MPN
 <p>Panel Mount, Hose Barb</p>	4 mm	14	60	16	17	14	14	4	M 10 x 1	Standard	21KB TS04 MPX
										Nickel Plated	21KB TS04 MPN
	5 mm	17	60	16	17	14	17	4	M 12 x 1	Standard	21KB TS05 MPX
										Nickel Plated	21KB TS05 MPN
	6 mm	17	60	16	17	14	17	4	M 12 x 1	Standard	21KB TS06 MPX
										Nickel Plated	21KB TS06 MPN
	8 mm	17	60	16	17	14	17	4	M 12 x 1	Standard	21KB TS08 MPX
										Nickel Plated	21KB TS08 MPN
	9 mm	17	60	16	17	14	19	4	M 12 x 1	Standard	21KB TS09 MPX
										Nickel Plated	21KB TS09 MPN
 <p>Plastic Hose Connection with Spring Guard</p>	4 x 6 mm	14	125	16	7	6			M 10 x 1	Standard	21KB KK06 MPX
										Nickel Plated	21KB KK06 MPN
	6 x 8 mm	14	130	16	7	6			M 10 x 1	Standard	21KB KK08 MPX
										Nickel Plated	21KB KK08 MPN

Valved Plugs


RECTUS Series 21KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	4 mm	14	50	17						Standard	21SB TF04 MPX
										Nickel Plated	21SB TF04 MPN
	5 mm	14	50	17						Standard	21SB TF05 MPX
										Nickel Plated	21SB TF05 MPN
	6 mm	14	50	17						Standard	21SB TF06 MPX
										Nickel Plated	21SB TF06 MPN
	8 mm	14	50	17						Standard	21SB TF08 MPX
										Nickel Plated	21SB TF08 MPN
	9 mm	14	50	17						Standard	21SB TF09 MPX
										Nickel Plated	21SB TF09 MPN
	10 mm	14	50	17						Standard	21SB TF10 MPX
										Nickel Plated	21SB TF10 MPN
	6 mm Parker	14	54	20						Standard	21SB TP06 MPX
										Nickel Plated	21SB TP06 MPN
 <p>Plastic Hose Connection</p>	4 x 6 mm	14	46	7	6			M 10 x 1	Standard	21SB KO06 MPX	
										Nickel Plated	21SB KO06 MPN
	6 x 8 mm	14	46	7	6			M 12 x 1	Standard	21SB KO08 MPX	
										Nickel Plated	21SB KO08 MPN
 <p>Panel Mount, Plastic Hose Connection</p>	4 x 6 mm	14	58	7	18	12	3	M 10 x 1	Standard	21SB KS06 MPX	
										Nickel Plated	21SB KS06 MPN
	6 x 8 mm	17	58	7	18	17	4	M 12 x 1	Standard	21SB KS08 MPX	
										Nickel Plated	21SB KS08 MPN
 <p>Panel Mount, Hose Barb</p>	4 mm	14	64	17	14	14	4	M 10 x 1	Standard	21SB TS04 MPX	
										Nickel Plated	21SB TS04 MPN
	6 mm	14	64	17	14	17	4	M 12 x 1	Standard	21SB TS06 MPX	
										Nickel Plated	21SB TS06 MPN
	8 mm	14	64	17	14	17	4	M 12 x 1	Standard	21SB TS08 MPX	
										Nickel Plated	21SB TS08 MPN
	10 mm	14	64	17	14	19	4	M 14 x 1	Standard	21SB TS10 MPX	
										Nickel Plated	21SB TS10 MPN
	 <p>Plastic Hose Connection with Spring Guard</p>	4 x 6 mm	14	130	7	6			M 10 x 1	Standard	21SB KK06 MPX
											Nickel Plated
6 x 8 mm		14	135	7	6			M 12 x 1	Standard	21SB KK08 MPX	
										Nickel Plated	21SB KK08 MPN


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	40		7					Standard	21SB AW10 MPX
									Nickel Plated	21SB AW10 MPN
G 1/4	17	42		9					Standard	21SB AW13 MPX
									Nickel Plated	21SB AW13 MPN
G 3/8	19	42		9					Standard	21SB AW17 MPX
									Nickel Plated	21SB AW17 MPN
M 10 x 1	14	41		8					Standard	21SB AD10 MPX
									Nickel Plated	21SB AD10 MPN
M 12 x 1,5	17	43		10					Standard	21SB AD12 MPX
									Nickel Plated	21SB AD12 MPN
M 14 x 1,5	17	43		10					Standard	21SB AD14 MPX
									Nickel Plated	21SB AD14 MPN
G 1/8	14	40		7					Standard	21SB IW10 MPX
									Nickel Plated	21SB IW10 MPN
G 1/4	17	42		7					Standard	21SB IW13 MPX
									Nickel Plated	21SB IW13 MPN
G 3/8	19	42		7					Standard	21SB IW17 MPX
									Nickel Plated	21SB IW17 MPN
M 12 x 1,5	17	42		7					Standard	21SB IM12 MPX
									Nickel Plated	21SB IM12 MPN
M 14 x 1,5	17	42		7					Standard	21SB IM14 MPX
									Nickel Plated	21SB IM14 MPN



Male Thread



Female Thread



Nominal Diameter

6 = 30 mm²

RECTUS Series

51KB



actual size

Technical Description



German industrial profile with UltraFlo technology. Slim design. Robust steel coupling for compressed air applications – especially for oscillating forces, due to greater insert depth of plug profile and steel sleeve.

Dust Caps (P. 331)

for coupling Part.-No. SK23S



Chart



Advantages

Single handed operation. Ergonomic design. High flow valve.

Working Pressure

PB = 50 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium

*At a temperature below -20°C and above +100°C special seals are available on request.

Material

Coupling
Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Spring Plate

Standard

Brass, Nickel Plated
Brass, Nickel Plated
Steel Hardened, Nickel Plated
Brass, Nickel Plated
AISI 301
AISI 420
NBR
Brass

Plug

Plug Profile
Back Body
Valve
Spring
Seal
Spring Plate

Steel Hardened, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
AISI 301
NBR
Brass

You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Single Shut-off P. 62

Couplings

RECTUS Series 51KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/4	22	61	22	9					Standard	51KB AW13 SPN
	G 3/8	22	61	22	9					Standard	51KB AW17 SPN
	G 1/2	22	61	22	12					Standard	51KB AW21 SPN
<p>Female Thread</p>	G 1/4	22	61	22	12					Standard	51KB IW13 SPN
	G 3/8	22	61	22	12					Standard	51KB IW17 SPN
	G 1/2	22	61	22	13					Standard	51KB IW21 SPN


Couplings

RECTUS Series 51KB

Brass/Steel

Low Pressure

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	21	78	22	25					Standard	51KB TF06 SPN
9 mm	21	78	22	25					Standard	51KB TF09 SPN
13 mm	21	78	22	25					Standard	51KB TF13 SPN




Hose Barb

Valved Plugs

RECTUS Series 51KB

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	21	65,5		25					Standard	51SB TF06 SPN
9 mm	21	65,5		25					Standard	51SB TF09 SPN
13 mm	21	65,5		25					Standard	51SB TF13 SPN




Hose Barb


Valved Plugs

RECTUS Series 51KB


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/4	19	54		8					Standard	51SB AW13 SPN
G 3/8	22	49,5		9					Standard	51SB AW17 SPN
G 1/2	22	49,5		12					Standard	51SB AW21 SPN
G 1/4	22	51,5		12					Standard	51SB IW13 SPN
G 3/8	22	51,5		12					Standard	51SB IW17 SPN



Male Thread



Female Thread



Nominal Diameter

6 = 30 mm²

RECTUS Series

52KB



actual size

Technical Description



German industrial profile with UltraFlo technology. Slim design. Robust steel coupling for compressed air applications – especially for oscillating forces, due to greater insert depth of plug profile and steel sleeve.

Dust Caps (P. 331)

for coupling Part.-No. SK23S
for plug Part.-No. SK12S



Chart



Advantages

Single handed operation. Ergonomic design. High flow valve.

Working Pressure

PB = 50 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Material

- Coupling
- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals
- Inner Sleeve
- Spring Plate

Standard

- Brass, Nickel Plated
- Brass, Nickel Plated
- Steel Hardened, Nickel Plated
- Brass, Nickel Plated
- AISI 301
- AISI 420
- NBR
- Brass
- Brass

Plug

- Plug Profile
- Back Body
- Valve
- Spring
- Seal


- Steel Hardened, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- AISI 301
- NBR

You will find the following alternative versions in our current catalogue on page:


► Brass/Steel Single Shut-off P. 64

Couplings

RECTUS Series 52KB



Male Thread



Female Thread


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/4	22	62	25	9					Standard	52KB AW13 SPN
G 3/8	22	62	25	9					Standard	52KB AW17 SPN
G 1/2	22	65	25	12					Standard	52KB AW21 SPN
G 1/4	22	62	25	10					Standard	52KB IW13 SPN
G 3/8	22	60	25	10					Standard	52KB IW17 SPN
G 1/2	22	65	25	13					Standard	52KB IW21 SPN

Couplings

RECTUS Series 52KB

Brass/Steel


Low Pressure



Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	21	79	25	25					Standard	52KB TF06 SPN
9 mm	21	80	25	25					Standard	52KB TF09 SPN
10 mm	21	80	25	25					Standard	52KB TF10 SPN
11 mm	21	80	25	25					Standard	52KB TF11 SPN
13 mm	21	79	25	25					Standard	52KB TF13 SPN

Valved Plugs


RECTUS Series 52KB




Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	21	77,5		25					Standard	52SB TF06 SPN
8 mm	21	77,5		25					Standard	52SB TF08 SPN
9 mm	21	77,5		25					Standard	52SB TF09 SPN
10 mm	21	77,5		25					Standard	52SB TF10 SPN
	21	77,5		25					Standard	52SB TF13 SPN

Valved Plugs


RECTUS Series 52KB



Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/4	22	48		9					Standard	52SB AW13 SPN
G 3/8	22	48		9					Standard	52SB AW17 SPN
G 1/2	22	48		12					Standard	52SB AW21 SPN



G 1/4	22	48		9					Standard	52SB IW13 SPN
G 3/8	22	48		9					Standard	52SB IW17 SPN



Nominal Diameter

6,3 = 31 mm²

RECTUS Series

72KB



90% of actual size



Technical Description

The 72KB series plug profile conforms to ISO Standard 7241-1 series B and is compatible with other makes of the same standard.

Advantages

This is a coupling to be operated with two hands, i.e. the unlocking sleeve must be pushed back manually when coupling.

Working Pressure


PB = 200 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -40°C and above +200°C special seals are available on request.

Chart



Material

Coupling

- Coupling Body
- Sleeve
- Valve
- Springs
- Locking Balls
- Seals
- Valve Holder

Plug

- Plug Body
- Valve
- Springs
- Seals
- Valve Holder

Brass Version

- Brass
- Brass
- Brass
- AISI 301
- AISI 420
- NBR
- AISI 301

- Brass
- Brass
- AISI 301
- NBR
- AISI 301

You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel P. 217
- ▶ Thermoplastic P. 257

Couplings


RECTUS Series 72KB

	Connection A	Hex SW	L mm	L1 mm	D mm	Valve	Working press. connected	Version	Seal	Part Number
<p>Female Thread</p>	G 1/4	19	57,5	10	25	with	200 bar	Brass	NBR	72KB IW13 MPX

Plugs

RECTUS Series 72KB

	Connection A	Hex SW	L mm	L1 mm	D mm	Valve	Working press. connected	Version	Seal	Part Number
<p>Female Thread</p>	G 1/4	19	35	10		with	200 bar	Brass	NBR	72SB IW13 MPX



Nominal Diameter

7,2 = 40 mm²

RECTUS Series

26KB

actual size

**Technical Description**

European standard industrial profile. Universal brass coupling. Small massive design. Ergonomic sleeve design prevents dirt on the valve body.

Advantages

Single handed operation. European standard.



Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart

You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Single Shut-off P. 66
- ▶ Stainless Steel P. 189
- ▶ Safety Self-Venting P. 288

Material**Coupling**

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Pins
Seals
(Sleeves made of thermoplastic on request)

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated


Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug Profile
Back Body
Valve
Spring
Seal




Brass
Brass
Brass
AISI 301
NBR

Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
NBR

Couplings**RECTUS Series 26KB**





Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	22	43	25	9					Standard	26KB AW10 MPX
									Nickel Plated	26KB AW10 MPN
G 1/4	22	39	25	9					Standard	26KB AW13 MPX
									Nickel Plated	26KB AW13 MPN
G 3/8	22	41	25	9					Standard	26KB AW17 MPX
									Nickel Plated	26KB AW17 MPN
G 1/2	24	42	25	10					Standard	26KB AW21 MPX
									Nickel Plated	26KB AW21 MPN



	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Male Thread</p>	M 16 x 1,5	22	43	25	11					Standard	26KB AD16 MPX	
										Nickel Plated	26KB AD16 MPN	
	M 18 x 1,5	22	43	25	11					Standard	26KB AD18 MPX	
										Nickel Plated	26KB AD18 MPN	
 <p>Female Thread</p>	G 1/4	22	41	25	9					Standard	26KB IW13 MPX	
										Nickel Plated	26KB IW13 MPN	
	G 3/8	22	41	25	9					Standard	26KB IW17 MPX	
										Nickel Plated	26KB IW17 MPN	
	G 1/2	24	44	25	10					Standard	26KB IW21 MPX	
										Nickel Plated	26KB IW21 MPN	
	M 16 x 1,5	22	44	25	9					Standard	26KB IM16 MPX	
										Nickel Plated	26KB IM16 MPN	
	M 18 x 1,5	22	44	25	9					Standard	26KB IM18 MPX	
										Nickel Plated	26KB IM18 MPN	
 <p>Hose Barb</p>	6 mm	21	58	25	25					Standard	26KB TF06 MPX	
										Nickel Plated	26KB TF06 MPN	
	8 mm	21	58	25	25					Standard	26KB TF08 MPX	
										Nickel Plated	26KB TF08 MPN	
	9 mm	21	58	25	25					Standard	26KB TF09 MPX	
										Nickel Plated	26KB TF09 MPN	
	10 mm	21	58	25	25					Standard	26KB TF10 MPX	
										Nickel Plated	26KB TF10 MPN	
	13 mm	21	58	25	25					Standard	26KB TF13 MPX	
										Nickel Plated	26KB TF13 MPN	
	6 mm Parker	21	58	25	25					Standard	26KB TP06 MPX	
										Nickel Plated	26KB TP06 MPN	

Couplings

RECTUS Series 26KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Hose Barb</p>	10 mm Parker	21	58	25	24					Standard	26KB TP10 MPX	
										Nickel Plated	26KB TP10 MPN	
	13 mm Parker	21	58	25	28					Standard	26KB TP13 MPX	
										Nickel Plated	26KB TP13 MPN	
 <p>Plastic Hose Connection</p>	6 x 8 mm	21	45	25	7	6			M 12 x 1	Standard	26KB KO08 MPX	
										Nickel Plated	26KB KO08 MPN	
	8 x 10 mm	21	49	25	9	8			M 16 x 1	Standard	26KB KO10 MPX	
										Nickel Plated	26KB KO10 MPN	
	9 x 12 mm	21	49	25	9	8			M 16 x 1	Standard	26KB KO12 MPX	
										Nickel Plated	26KB KO12 MPN	
 <p>Panel Mount, Hose Barb</p>	6 mm	21	60	25	17	10	17	4	M 12 x 1	Standard	26KB TS06 MPX	
										Nickel Plated	26KB TS06 MPN	
	8 mm	21	63	25	17	14	17	4	M 12 x 1	Standard	26KB TS08 MPX	
										Nickel Plated	26KB TS08 MPN	
	10 mm	21	72	25	25	14	17	4	G 1/4	Standard	26KB TS10 MPX	
										Nickel Plated	26KB TS10 MPN	
 <p>Plastic Hose Connection with Spring Guard</p>	6 x 8 mm	21	132	25	7	6			M 12 x 1	Standard	26KB KK08 MPX	
										Nickel Plated	26KB KK08 MPN	
	8 x 10 mm	21	143	25	9	8			M 16 x 1	Standard	26KB KK10 MPX	
										Nickel Plated	26KB KK10 MPN	
	9 x 12 mm	21	150	25	9	8			M 16 x 1	Standard	26KB KK12 MPX	
										Nickel Plated	26KB KK12 MPN	

Valved Plugs for all 26 KB Series (same as 25KB Series!) see page 137.



Technical Description



3/8" - 1/2" brass coupling system with UltraFlo technology. High flow performance. Notable for robust design and steel sleeve used with large pneumatic consumers.

Dust Caps (P. 331)

for coupling Part.-No. SK23S
for plug Part.-No. SK12S



Chart



Advantages

Single handed operation. Robust design. High flow valve. No damage to the valve body due to collar design.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM) depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

actual size



Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Inner Sleeve
Spring Plate

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR
Brass
Brass

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR
Brass
Brass

Plug

Plug Profile
Back Body
Valve
Spring
Seal

Brass
Brass
Brass
AISI 301
NBR


Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
NBR

You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Single Shut-off P. 73
- ▶ Brass/Steel Dry-Break P. 171
- ▶ Stainless Steel P. 209
- ▶ Safety P. 278
- ▶ Safety Self-Venting P. 290
- ▶ Safety Coded P. 303

Couplings

RECTUS Series 25KB








Male Thread




ISO 8434-1

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/4	19	60	23	12					Standard	25KB AK13 BPX
									Nickel Plated	25KB AK13 BPN
R 3/8	19	59	23	10,5					Standard	25KB AK17 BPX
									Nickel Plated	25KB AK17 BPN
R 1/2	22	57,5	23	9					Standard	25KB AK21 BPX
									Nickel Plated	25KB AK21 BPN
M 14 x 1,5	19	59	23	10					Standard	25KB AD14 BPX
									Nickel Plated	25KB AD14 BPN
M 16 x 1,5	19	60	23	11					Standard	25KB AD16 BPX
									Nickel Plated	25KB AD16 BPN
M 18 x 1,5	19	60	23	11					Standard	25KB AD18 BPX
									Nickel Plated	25KB AD18 BPN

Couplings


RECTUS Series 25KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Female Thread</p>	G 1/4	19	56	23	10					Standard	25KB IW13 BPX	
										Nickel Plated	25KB IW13 BPN	
	G 3/8	19	55	23	9					Standard	25KB IW17 BPX	
										Nickel Plated	25KB IW17 BPN	
	G 1/2	24	58	23	12					Standard	25KB IW21 BPX	
										Nickel Plated	25KB IW21 BPN	
	M 16 x 1,5	19	55	23	9					Standard	25KB IM16 BPX	
										Nickel Plated	25KB IM16 BPN	
	M 18 x 1,5	22	56	23	9					Standard	25KB IM18 BPX	
										Nickel Plated	25KB IM18 BPN	
 <p>Hose Barb</p>	6 mm	19	74	23	25					Standard	25KB TF06 BPX	
										Nickel Plated	25KB TF06 BPN	
	8 mm	19	74	23	25					Standard	25KB TF08 BPX	
										Nickel Plated	25KB TF08 BPN	
	9 mm	19	74	23	25					Standard	25KB TF09 BPX	
										Nickel Plated	25KB TF09 BPN	
	10 mm	19	74	23	25					Standard	25KB TF10 BPX	
										Nickel Plated	25KB TF10 BPN	
	13 mm	19	74	23	25					Standard	25KB TF13 BPX	
										Nickel Plated	25KB TF13 BPN	
	10 mm Parker	19	73	23	24					Standard	25KB TP10 BPX	
										Nickel Plated	25KB TP10 BPN	
	13 mm Parker	19	76	23	28					Standard	25KB TP13 BPX	
										Nickel Plated	25KB TP13 BPN	
 <p>Plastic Hose Connection</p>	8 x 10 mm	19	65	23	9	8			M 16 x 1	Standard	25KB KO10 BPX	
										Nickel Plated	25KB KO10 BPN	
	9 x 12 mm	19	65	23	9	8			M 16 x 1	Standard	25KB KO12 BPX	
										Nickel Plated	25KB KO12 BPN	
 <p>Panel Mount, Hose Barb</p>	6 mm	19	76	23	17	10	17	4	M 12 x 1	Standard	25KB TS06 BPX	
										Nickel Plated	25KB TS06 BPN	
	8 mm	19	80	23	17	14	17	4	M 12 x 1	Standard	25KB TS08 BPX	
										Nickel Plated	25KB TS08 BPN	
	10mm	19	76	23	17	10	17	4	M 12 x 1	Standard	25KB TS10 BPX	
										Nickel Plated	25KB TS10 BPN	
 <p>Plastic Hose Connection with Spring Guard</p>	6 x 8 mm	19	144	23	7	6			M 12 x 1	Standard	25KB KK08 BPX	
										Nickel Plated	25KB KK08 BPN	
	9 x 12 mm	19	162	23	9	8			M 16 x 1	Standard	25KB KK12 BPX	

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm	21	60		25					Standard	25SB TF06 MPX
										Nickel Plated	25SB TF06 MPN
	8 mm	21	60		25					Standard	25SB TF08 MPX
										Nickel Plated	25SB TF08 MPN
	9 mm	21	60		25					Standard	25SB TF09 MPX
										Nickel Plated	25SB TF09 MPN
	10 mm	21	60		25					Standard	25SB TF10 MPX
										Nickel Plated	25SB TF10 MPN
	13 mm	21	60		25					Standard	25SB TF13 MPX
										Nickel Plated	25SB TF13 MPN
	6 mm Parker	19	67,5		20,5					Standard	25SB TP06 MPX
										Nickel Plated	25SB TP06 MPN
10 mm Parker	19	71		24					Standard	25SB TP10 MPX	
									Nickel Plated	25SB TP10 MPN	
13 mm Parker	19	83		28					Standard	25SB TP13 MPX	
									Nickel Plated	25SB TP13 MPN	
 <p>Plastic Hose Connection</p>	4 x 6 mm	21	47		7	6			M 10 x 1	Standard	25SB KO06 MPX
										Nickel Plated	25SB KO06 MPN
	6 x 8 mm	21	47		7	6			M 12 x 1	Standard	25SB KO08 MPX
										Nickel Plated	25SB KO08 MPN
	8 x 10 mm	21	51		8,5	8,5			M 16 x 1	Standard	25SB KO10 MPX
										Nickel Plated	25SB KO10 MPN
	9 x 12 mm	21	51		8,5	8,5			M 16 x 1	Standard	25SB KO12 MPX
										Nickel Plated	25SB KO12 MPN
 <p>Panel Mount, Hose Barb</p>	6 mm	21	62		17	10	17	4	M 12 x 1	Standard	25SB TS06 MPX
										Nickel Plated	25SB TS06 MPN
	8 mm	21	65		17	14	17	4	M 12 x 1	Standard	25SB TS08 MPX
										Nickel Plated	25SB TS08 MPN
	10 mm	21	74		25	14	17	3,5	G 1/4	Standard	25SB TS10 MPX
										Nickel Plated	25SB TS10 MPN

Valved Plugs

RECTUS Series 25KB




Plastic Hose Connection with Spring Guard

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
4 x 6 mm	19	120		7	6			M 10 x 1	Standard	25SB KK06 MPX
									Nickel Plated	25SB KK06 MPN
6 x 8 mm	19	135		7	6			M 12 x 1	Standard	25SB KK08 MPX
									Nickel Plated	25SB KK08 MPN
8 x 10 mm	19	145		8,5	8,5			M 16 x 1	Standard	25SB KK10 MPX
									Nickel Plated	25SB KK10 MPN
9 x 12 mm	19	150		8,5	8,5			M 16 x 1	Standard	25SB KK12 MPX
									Nickel Plated	25SB KK12 MPN


Valved Plugs

RECTUS Series 25KB



Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	22	44,5		9					Standard	25SB AW10 MPX
									Nickel Plated	25SB AW10 MPN
G 1/4	22	43		9					Standard	25SB AW13 MPX
									Nickel Plated	25SB AW13 MPN
G 3/8	22	43		9					Standard	25SB AW17 MPX
									Nickel Plated	25SB AW17 MPN
G 1/2	22	46		12					Standard	25SB AW21 MPX
									Nickel Plated	25SB AW21 MPN
M 14 x 1,5	22	44		10					Standard	25SB AD14 MPX
									Nickel Plated	25SB AD14 MPN
M 16 x 1,5	22	45		11					Standard	25SB AD16 MPX
									Nickel Plated	25SB AD16 MPN
M 18 x 1,5	22	45		11					Standard	25SB AD18 MPX
									Nickel Plated	25SB AD18 MPN
G 1/4	22	43		10					Standard	25SB IW13 MPX
									Nickel Plated	25SB IW13 MPN
G 3/8	22	43		9					Standard	25SB IW17 MPX
									Nickel Plated	25SB IW17 MPN
G 1/2	24	46		9					Standard	25SB IW21 MPX
									Nickel Plated	25SB IW21 MPN
M 14 x 1,5	22	43		9					Standard	25SB IM14MPX
									Nickel Plated	25SB IM14 MPN
M 16 x 1,5	22	43		9					Standard	25SB IM16 MPX
									Nickel Plated	25SB IM16 MPN
M 18 x 1,5	22	43		9					Standard	25SB IM18 MPX
									Nickel Plated	25SB IM18 MPN



Female Thread



Nominal Diameter

7,5 = 44 mm²



RECTUS Series

73KB

80% of actual size



Technical Description

The 73KB series plug profile conforms to ISO Standard 7241-1 series B and is compatible with other makes of the same standard.

Advantages

This is a coupling to be operated with two hands, i.e. the unlocking sleeve must be pushed back manually when coupling.

Working Pressure

PB = 200 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*


73KB Series:
 -20°C up to +100°C (NBR)
 -15°C up to +200°C (FKM)
 depending on the medium.

*At a temperature below -40°C and above +200°C special seals are available on request.

You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel P. 218
- ▶ Thermoplastic P. 258

Chart



Material

Coupling

- Coupling Body
- Sleeve
- Valve
- Springs
- Locking Balls
- Seals
- Valve Holder (up to 100°C)
- Valve Holder (over 100°C)

Plug

- Plug Body
- Valve
- Springs
- Seals
- Valve Holder (up to 100°C)
- Valve Holder (over 100°C)

Brass Version


73KB Series

- Brass
- Brass
- Brass
- AISI 301
- AISI 420
- NBR
- Brass
- Brass

- Brass
- Brass
- AISI 301
- NBR
- Brass
- Brass


Couplings

RECTUS Series 73KB

	Connection A	Hex SW	L mm	L1 mm	D mm	Valve	Working press. connected	Version	Seal	Part Number
 <p>Female Thread</p>	G 3/8	22	64	11,5	35	with	200 bar	Brass	NBR	73KB IW17 MPX

Plugs

RECTUS Series 73KB

	Connection A	Hex SW	L mm	L1 mm	D mm	Valve	Working press. connected	Version	Seal	Part Number
 <p>Female Thread</p>	G 3/8	22	39	11,5		with	200 bar	Brass	NBR	73SB IW17 MPX



Technical Description



1/2" European industrial profile with UltraFlo technology. High flow performance. Notable for robust design and steel sleeve in use with large pneumatic consumers.

Dust Caps (P. 331)

for coupling Part.-No. SK27S



Chart



Advantages

Single handed operation. Minimal pressure drop. High flow valve. No damage to the valve body from collar design.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1

Working Temperature*

-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 0°C up to +316°C (FFKM)
 depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Material

Coupling

Back Body
 Valve Body
 Sleeve
 Valve
 Spring and Locking Ring
 Locking Balls
 Seals
 Inner Sleeve
 Spring Plate

Standard

Brass
 Brass
 Brass
 Brass
 AISI 301
 AISI 420
 NBR
 Brass
 Brass

Nickel Plated

Brass, Nickel Plated
 Brass, Nickel Plated
 Brass, Nickel Plated
 Brass
 AISI 301
 AISI 420
 NBR
 Brass
 Brass

Plug

Plug Profile
 Back Body
 Valve
 Spring
 Seal

Brass
 Brass
 Brass
 AISI 301
 NBR

Brass, Nickel Plated
 Brass, Nickel Plated
 Brass, Nickel Plated
 AISI 301
 NBR




actual size

You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Single Shut-off P. 95
- ▶ Stainless Steel P. 213
- ▶ Safety Self-Venting P. 292

Couplings

RECTUS Series 27KB





Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version		Part Number
									Standard	Nickel Plated	
R 1/4	24	63	27	12					Standard	Nickel Plated	27KB AK13 BPX
											27KB AK13 BPN
R 3/8	24	63	27	12					Standard	Nickel Plated	27KB AK17 BPX
											27KB AK17 BPN
R 1/2	24	65	27	17					Standard	Nickel Plated	27KB AK21 BPX
											27KB AK21 BPN
R 3/4	27	65	27	17					Standard	Nickel Plated	27KB AK26 BPX
											27KB AK26 BPN


Couplings

RECTUS Series 27KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 1/4	24	56	27	10					Standard	27KB IW13 BPX
										Nickel Plated	27KB IW13 BPN
	G 3/8	24	56	27	11					Standard	27KB IW17 BPX
										Nickel Plated	27KB IW17 BPN
	G 1/2	24	56	27	12					Standard	27KB IW21 BPX
										Nickel Plated	27KB IW21 BPN
	G 3/4	32	60	27	16					Standard	27KB IW26 BPX
										Nickel Plated	27KB IW26 BPN
 <p>Hose Barb</p>	6 mm	24	76	27	25					Standard	27KB TF06 BPX
										Nickel Plated	27KB TF06 BPN
	8 mm	24	76	27	25					Standard	27KB TF08 BPX
										Nickel Plated	27KB TF08 BPN
	9 mm	24	76	27	25					Standard	27KB TF09 BPX
										Nickel Plated	27KB TF09 BPN
	10 mm	24	76	27	25					Standard	27KB TF10 BPX
										Nickel Plated	27KB TF10 BPN
	13 mm	24	76	27	25					Standard	27KB TF13 BPX
										Nickel Plated	27KB TF13 BPN
	16 mm	24	76	27	25					Standard	27KB TF16 BPX
										Nickel Plated	27KB TF16 BPN
	19 mm	24	76	27	25					Standard	27KB TF19 BPX
										Nickel Plated	27KB TF19 BPN

Valved Plugs

RECTUS Series 27KB


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm	24	74		25					Standard	27SB TF06 MPX
										Nickel Plated	27SB TF06 MPN
	8 mm	24	74		25					Standard	27SB TF08 MPX
										Nickel Plated	27SB TF08 MPN
	9 mm	24	74		25					Standard	27SB TF09 MPX
										Nickel Plated	27SB TF09 MPN

Valved Plugs

RECTUS Series 27KB

Brass/Steel

Low Pressure




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
10 mm	24	74		25					Standard	27SB TF10 MPX
									Nickel Plated	27SB TF10 MPN
13 mm	24	74		25					Standard	27SB TF13 MPX
									Nickel Plated	27SB TF13 MPN
16 mm	24	74		25					Standard	27SB TF16 MPX
									Nickel Plated	27SB TF16 MPN
19 mm	24	74		25					Standard	27SB TF19 MPX
									Nickel Plated	27SB TF19 MPN


Valved Plugs

RECTUS Series 27KB




Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/4	24	60,5		12					Standard	27SB AK13 MPX
									Nickel Plated	27SB AK13 MPN
R 3/8	24	60,5		12					Standard	27SB AK17 MPX
									Nickel Plated	27SB AK17 MPN
R 1/2	24	62,5		17					Standard	27SB AK21 MPX
									Nickel Plated	27SB AK21MPN
R 3/4	27	62,5		17					Standard	27SB AK26 MPX
									Nickel Plated	27SB AK26 MPN



Female Thread

G 1/4	24	54,5		9					Standard	27SB IW13 MPX
									Nickel Plated	27SB IW13 MPN
G 3/8	24	54,5		9					Standard	27SB IW17 MPX
									Nickel Plated	27SB IW17 MPN
G 1/2	24	54,5		12					Standard	27SB IW21 MPX
									Nickel Plated	27SB IW21 MPN
G 3/4	32	58,5		16					Standard	27SB IW26 MPX
									Nickel Plated	27SB IW26 MPN



Nominal Diameter

10 = 80 mm²

RECTUS Series

1700KB



80% of actual size





Technical Description

Premium industrial coupling in nominal diameter 10 with high grade valve technology and unprecedent flow values and minimum connecting forces.

Dust Caps (P. 331) for coupling Part.-No. SK27S

Chart



Advantages

Single handed operation. High flow valve. Easy connecting forces. Easy-grip sleeve design. Increased reliability due to use of high grade materials. Extremely high flow performance.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
0°C up to 316°C (FFKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve, Seat
Springs, Locking Ring
Balls
Seals

Standard Version

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug Profile
Back Body
Valve
Spring
Seal

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
AISI 301
NBR

You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Single Shut-off P. 97

Couplings RECTUS Series 1700KB



	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 3/8	24	64,5	27	7					Standard	1700KB AW17 BPN
	G 1/2	24	69,5	27	12					Standard	1700KB AW21 BPN
	G 3/4	30	73,5	27	16					Standard	1700KB AW26 BPN
<p>Female Thread</p>	G 3/8	24	67,5	27	12					Standard	1700KB IW17 BPN

Couplings

RECTUS Series 1700KB


Brass/Steel

Low Pressure

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 1/2	24	67,5	27	12					Standard	1700KB IW21 BPN
	G 3/4	32	73,5	27	16					Standard	1700KB IW26 BPN
 <p>Hose Barb</p>	10 mm	24	79,5	27	21				Standard	1700KB TF10 BPN	
	13 mm	24	79,5	27	21				Standard	1700KB TF13 BPN	
	16 mm	24	79,5	27	21				Standard	1700KB TF16 BPN	
	19 mm	24	79,5	27	21				Standard	1700KB TF19 BPN	



Valved Plugs


RECTUS Series 27SB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm	24	74		25					Standard	27SB TF06 MPN
	8 mm	24	74		25					Standard	27SB TF08 MPN
	9 mm	24	74		25					Standard	27SB TF09 MPN
	10 mm	24	74		25					Standard	27SB TF10 MPN
	13 mm	24	74		25					Standard	27SB TF13 MPN
	16 mm	24	74		25					Standard	27SB TF16 MPN
19 mm	24	74		25					Standard	27SB TF19 MPN	

Valved Plugs

RECTUS Series 27SB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/4	24	60,5		12					Standard	27SB AK13 MPN
	R 3/8	24	60,5		12					Standard	27SB AK17 MPN
	R 1/2	24	62,5		17					Standard	27SB AK21 MPN
	R 3/4	27	62,5		17					Standard	27SB AK26 MPN
 <p>Female Thread</p>	G 1/4	24	54,5		9					Standard	27SB IW13 MPN
	G 3/8	24	54,5		9					Standard	27SB IW17 MPN
	G 1/2	24	54,5		12					Standard	27SB IW21 MPN
	G 3/4	24	54,5		16					Standard	27SB IW26 MPN



Nominal Diameter

11 = 95 mm²

RECTUS Series

74KB



75% of actual size



Technical Description

The 74KB series plug profile conforms to ISO Standard 7241-1 series B and is compatible with other makes of the same standard.

Advantages

This is a coupling to be operated with two hands, i.e. the unlocking sleeve must be pushed back manually when coupling.

Working Pressure

PB = 150 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -40°C and above +200°C special seals are available on request.

Material

Coupling

Coupling Body
Sleeve
Valve
Springs
Locking Balls
Seals
Valve Holder (up to 100°C)
Valve Holder (over 100°C)

Brass Version


Brass
Brass
Brass
AISI 301
AISI 420
NBR
Brass
Brass

Plug

Plug Body
Valve
Springs
Seals
Valve Holder (up to 100°C)
Valve Holder (over 100°C)

Brass
Brass
AISI 301
NBR
Brass
Brass

Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel P. 219
- ▶ Thermoplastic P. 259

Couplings

RECTUS Series 74KB

	Connection A	Hex SW	L mm	L1 mm	D mm	Valve	Working press. connected	Version	Seal	Part Number
 Female Thread	G 1/2	27	76	16	44,5	with	150 bar	Brass	NBR	74KB IW21 MPX

Plugs

RECTUS Series 74KB

	Connection A	Hex SW	L mm	L1 mm	D mm	Valve	Working press. connected	Version	Seal	Part Number
 Female Thread	G 1/2	27	48	16		with	150 bar	Brass	NBR	74SB IW21 MPX




Nominal Diameter

12 = 115 mm²

RECTUS Series

57KB



65% of actual size



Technical Description

German industrial profile with UltraFlo technology. Optimised structure with respect to size and performance. Robust coupling for compressed air applications. Especially suitable for oscillating forces, due to steel sleeve and steel valve body. Specific application for liquids.

Advantages

Single handed operation. Minimal pressure drop. High flow valve. No damage to the valve body from collar design.

Working Pressure



PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



Material

- Coupling
- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals
- Spring Plate

Standard

- Brass, Nickel Plated
- Steel, Nickel Plated
- Steel Hardened, Nickel Plated
- Brass, Nickel Plated
- AISI 301
- AISI 420
- NBR
- Brass, Nickel Plated

Plug

- Plug Profile
- Back Body
- Valve
- Spring
- Seal
- Spring Plate


- Steel Hardened, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- AISI 301
- NBR
- Brass

You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Single Shut-off P. 111

Couplings

RECTUS Series 57KB



Male Thread



Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/2	34	98	40	12					Standard	57KB AW21 SPN
G 3/4	34	100	40	16					Standard	57KB AW26 SPN
G 1	41	100	40	19					Standard	57KB AW33 SPN

Couplings

RECTUS Series 57KB


Brass/Steel

Low Pressure

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 1/2	34	100	40	19					Standard	57KB IW21 SPN
	G 3/4	34	100	40	16					Standard	57KB IW26 SPN
	G 1	41	101	40	20					Standard	57KB IW33 SPN
 <p>Hose Barb</p>	16 mm	34	122	40	36					Standard	57KB TF16 SPN
	19 mm	34	122	40	36					Standard	57KB TF19 SPN



Valved Plugs

RECTUS Series 57KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	13 mm	34	101		28					Standard	57SB TF13 SPN
	16 mm	34	107		36					Standard	57SB TF16 SPN
	19 mm	34	107		36					Standard	57SB TF19 SPN

Valved Plugs

RECTUS Series 57KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 3/8	34	86		12					Standard	57SB AW17 SPN
	G 1/2	34	83		12					Standard	57SB AW21 SPN
	G 3/4	34	85		16					Standard	57SB AW26 SPN
	G 1	41	85		19					Standard	57SB AW33 SPN
 <p>Female Thread</p>	G 1/2	34	85		19					Standard	57SB IW21 SPN
	G 3/4	34	85		16					Standard	57SB IW26 SPN

⚠ Please consider our security advices on the pages 12/13 ⚠



Nominal Diameter

13 = 133 mm²



RECTUS Series

75KB

55% of actual size



Technical Description

The 75KB series plug profile conforms to ISO Standard 7241-1 series B and is compatible with other makes of the same standard.

Advantages

This is a coupling to be operated with two hands, i.e. the unlocking sleeve must be pushed back manually when coupling.

Working Pressure

PB = 100 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

75KB Series:
-20°C up to +100°C (NBR)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -40°C and above +200°C special seals are available on request.

Material

Coupling

- Coupling Body
- Sleeve
- Valve
- Springs
- Locking Balls
- Seals
- Valve Holder

Brass Version

75KB Series


- Brass
- Brass
- Brass
- AISI 301
- AISI 420
- NBR
- Brass

Plug

- Plug Body
- Valve
- Springs
- Seals
- Valve Holder

- Brass
- Brass
- AISI 301
- NBR
- Brass

Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel P. 220
- ▶ Thermoplastic P. 260

Couplings


RECTUS Series 75KB

	Connection A	Hex SW	L mm	L1 mm	D mm	Valve	Working press. connected	Version	Seal	Part Number
<p>Female Thread</p>	G 3/4	34	96	24	55	with	100 bar	Brass	NBR	75KB IW26 MPX

Plugs

RECTUS Series 75KB

	Connection A	Hex SW	L mm	L1 mm	D mm	Valve	Working press. connected	Version	Seal	Part Number
<p>Female Thread</p>	G 3/4	36	60	24		with	100 bar	Brass	NBR	75SB IW26 MPX



Nominal Diameter

15 = 175 mm²

RECTUS Series

38KB



60% of actual size



Technical Description

Industrial profile in brass, with UltraFlo technology. Compact dimensions with high performance characteristics. Coupling can be used with numerous gaseous and liquid media.

Advantages

Compact dimensions. Extremely high flow performance. High flow valve.

Working Pressure



PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 0°C up to 316°C (FFKM)
 depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Single Shut-off P. 115

Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals
- Inner Sleeve
- Spring Plate

Standard

- Brass
- Brass
- Brass
- Brass
- AISI 301
- AISI 420
- NBR
- Brass
- Brass

Nickel Plated

- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass
- AISI 301
- AISI 420
- NBR
- Brass
- Brass

Plug

- Plug Profile
- Back Body
- Valve
- Spring and Locking Ring
- Seal
- Spring Plate

- Brass
- Brass
- Brass
- AISI 301
- NBR
- Brass

- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass
- AISI 301
- NBR
- Brass



Couplings

RECTUS Series 38KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/2	34	89	40	12					Standard	38KB AW21 MPX
										Nickel Plated	38KB AW21 MPN
	G 3/4	34	91	40	16					Standard	38KB AW26 MPX
										Nickel Plated	38KB AW26 MPN
<p>Female Thread</p>	G 1	41	91	40	19					Standard	38KB AW33 MPX
										Nickel Plated	38KB AW33 MPN
	G 1/2	34	95	40	20					Standard	38KB IW21 MPX
										Nickel Plated	38KB IW21 MPN


Couplings

RECTUS Series 38KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 3/4	34	91	40	14					Standard	38KB IW26 MPX
										Nickel Plated	38KB IW26 MPN
	G 1	41	92	40	20					Standard	38KB IW33 MPX
										Nickel Plated	38KB IW33 MPN
 <p>Hose Barb</p>	13 mm	34	105	40	28					Standard	38KB TF13 MPX
										Nickel Plated	38KB TF13 MPN
	16 mm	34	113	40	36					Standard	38KB TF16 MPX
										Nickel Plated	38KB TF16 MPN
	19 mm	34	113	40	36					Standard	38KB TF19 MPX
										Nickel Plated	38KB TF19 MPN
	25 mm	34	109	40	36					Standard	38KB TF25 MPX
										Nickel Plated	38KB TF25 MPN



Valved Plugs

RECTUS Series 38KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	13 mm	34	103		28					Standard	38SB TF13 MPX
										Nickel Plated	38SB TF13 MPN
	16 mm	34	109		36					Standard	38SB TF16 MPX
										Nickel Plated	38SB TF16 MPN
	19 mm	34	109		36					Standard	38SB TF19 MPX
										Nickel Plated	38SB TF19 MPN
	25 mm	34	105		36					Standard	38SB TF25 MPX
										Nickel Plated	38SB TF25 MPN

Valved Plugs

RECTUS Series 38KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/2	34	85		12					Standard	38SB AW21 MPX
										Nickel Plated	38SB AW21 MPN
	G 3/4	34	87		16					Standard	38SB AW26 MPX
										Nickel Plated	38SB AW26 MPN
 <p>Female Thread</p>	G 1	41	87		19					Standard	38SB AW33 MPX
										Nickel Plated	38SB AW33 MPN
	G 1/2	34	87		16					Standard	38SB IW21 MPX
										Nickel Plated	38SB IW21 MPN
	G 3/4	34	87		16					Standard	38SB IW26 MPX
										Nickel Plated	38SB IW26 MPN
	G 1	41	8		26					Standard	38SB IW33 MPX
										Nickel Plated	38SB IW33 MPN



Nominal Diameter

19 = 300 mm²

RECTUS Series

39KB



40% of actual size



Technical Description

Industrial brass profile with UltraFlo technology. Compact dimensions with high performance characteristics. Coupling can be used with numerous gaseous and liquid media.

Advantages

Compact dimensions. Extremely high flow performance. High flow valve.

Working Pressure



PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 0°C up to 316°C (FFKM)
 depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Single Shut-off P. 117
- ▶ Brass/Steel Dry-Break P. 180

Material

Coupling

Back Body
 Valve Body
 Sleeve
 Valve
 Spring and Locking Ring
 Locking Balls
 Seals
 Inner Sleeve
 Spring Plate

Standard

Brass
 Brass
 Brass
 Brass
 AISI 301
 AISI 420
 NBR
 Brass
 Brass

Nickel Plated

Brass, Nickel Plated
 Brass, Nickel Plated
 Brass, Nickel Plated
 Brass
 AISI 301
 AISI 420
 NBR
 Brass
 Brass

Plug


Plug Profile
 Back Body
 Valve
 Spring and Locking Ring
 Seal
 Spring Plate

Brass
 Brass
 Brass
 AISI 301
 NBR
 Brass


Brass, Nickel Plated
 Brass, Nickel Plated
 Brass
 AISI 301
 NBR
 Brass

Couplings

RECTUS Series 39KB



Male Thread





Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 3/4	41	95	46	16					Standard	39KB AW26 MPX
									Nickel Plated	39KB AW26 MPN
G 1	41	98	46	19					Standard	39KB AW33 MPX
									Nickel Plated	39KB AW33 MPN
G 1 1/4	46	98	46	19					Standard	39KB AW42 MPX
									Nickel Plated	39KB AW42 MPN
G 3/4	41	99	46	20					Standard	39KB IW26 MPX
									Nickel Plated	39KB IW26 MPN


Couplings

RECTUS Series 39KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 1	41	100	46	20					Standard	39KB IW33 MPX
										Nickel Plated	39KB IW33 MPN
	G 1 1/4	50	105	46	22					Standard	39KB IW42 MPX
										Nickel Plated	39KB IW42 MPN
 <p>Hose Barb</p>	19 mm	41	115	46	36					Standard	39KB TF19 MPX
										Nickel Plated	39KB TF19 MPN
	25 mm	41	125	46	48					Standard	39KB TF25 MPX
										Nickel Plated	39KB TF25 MPN



Valved Plugs

RECTUS Series 39KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	19 mm	41	114		36					Standard	39SB TF19 MPX
										Nickel Plated	39SB TF19 MPN
	25 mm	41	124		48					Standard	39SB TF25 MPX
										Nickel Plated	39SB TF25 MPN

Valved Plugs


RECTUS Series 39KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 3/4	41	92		16					Standard	39SB AW26 MPX
										Nickel Plated	39SB AW26 MPN
	G 1	41	95		19					Standard	39SB AW33 MPX
										Nickel Plated	39SB AW33 MPN
 <p>Female Thread</p>	G 1 1/4	46	95		19					Standard	39SB AW42 MPX
										Nickel Plated	39SB AW42 MPN
	G 3/4	41	96		19					Standard	39SB IW26 MPX
										Nickel Plated	39SB IW26 MPN
	G 1	41	97		24					Standard	39SB IW33 MPX
										Nickel Plated	39SB IW33 MPN
	G 1 1/4	50	102		26					Standard	39SB IW42 MPX
										Nickel Plated	39SB IW42 MPN



Nominal Diameter

20 = 490 mm²



RECTUS Series

76KB

50% of actual size



Technical Description

The 76KB series plug profile conforms to ISO Standard 7241-1 series B and is compatible with other makes of the same standard.

Advantages

This is a coupling to be operated with two hands, i.e. the unlocking sleeve must be pushed back manually when coupling.

Working Pressure

PB = 100 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -40°C and above +200°C special seals are available on request.

Material

Coupling

- Coupling Body
- Sleeve
- Valve
- Springs
- Locking Balls
- Seals
- Valve Holder

Brass Version


- Brass
- Brass
- Brass
- AISI 316 Ti
- AISI 420
- NBR
- Brass

Plug

- Plug Body
- Valve
- Springs
- Seals
- Valve Holder

- Brass
- Brass
- AISI 316 Ti
- NBR
- Brass

Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel P. 221
- ▶ Thermoplastic P. 261

Couplings **RECTUS Series 76KB**

	Connection A	Hex SW	L mm	L1 mm	D mm	Valve	Working press. connected	Version	Seal	Part Number
<p>Female Thread</p>	G 1	41	105,5	24	62	with	100 bar	Brass	NBR	76KB IW33 MPX

Plugs **RECTUS Series 76KB**

	Connection A	Hex SW	L mm	L1 mm	D mm	Valve	Working press. connected	Version	Seal	Part Number
<p>Female Thread</p>	G 1	41	65	24		with	100 bar	Brass	NBR	76SB IW33 MPX




Nominal Diameter

4 = 12,5 mm²

RECTUS Series

204KL



actual size



red dot design award winner 2007

You will find the following alternative versions in our current catalogue on page:

► Stainless Steel

P. 222

Technical Description

Dry-break coupling systems, which stand out for their extremely low leakage rates and a minimum volume of dead space. No air locks whatsoever during connecting and negligible film of channelled medium on the valve bodies when disconnecting. Coupling systems for applications in sensitive environments, such as in analysis technology, cooling circuits, transport systems and many applications with aggressive medium.

Advantages

Single-handed operation. Easy handling. Ergonomic sleeve shape. Optimised size. Low connecting forces. Valve body protected by collar design.

Extremely low dead volume remainings.

Interchangeability

RECTUS Design

Working Pressure

PB = 15 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature

-20°C up to +100°C (NBR)
Other sealing materials available on request.

Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals

Standard


- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- AISI 303
- AISI 420
- NBR

Plug

- Plug Profile
- Back Body
- Valve
- Spring
- Seal

- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- AISI 303
- NBR

Chart





Couplings

RECTUS Series 204KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/8	14	45	19	7					Standard	204KL AW10 MPN
	G 1/4	17	47	19	9					Standard	204KL AW13 MPN
<p>Female Thread</p>	G 1/8	14	45	19	9					Standard	204KL IW10 MPN
	G 1/4	17	47	19	9					Standard	204KL IW13 MPN

Valved Plugs

RECTUS Series 204KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14	40	7						Standard	204SL AW10 MPN
	G 1/4	17	42	9						Standard	204SL AW13 MPN
 <p>Female Thread</p>	G 1/8	14	40	9						Standard	204SL IW10 MPN
	G 1/4	17	42	7						Standard	204SL IW13 MPN



Dry-Break

Nominal Diameter

5 = 20 mm²

RECTUS Series

21KL

actual size



Technical Description

Mini industrial coupling, internationally the most common profile for this nominal diameter, in double shut-off design. Above average flow performance for liquid and gaseous media. Large band width in materials and valve variants.

Dust Caps (P. 331)

for coupling Part.-No. SK16S



Advantages

Single handed operation.
Small dimensions. Minimum (hardly noticeable) leakage occurs when disconnecting.
Air is not trapped in during the connecting process.

Working Pressure

PB = 8 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*


-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM) depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Single Shut-off P. 34
- ▶ Brass/Steel Double Shut-off P. 125
- ▶ Stainless Steel P. 224
- ▶ Thermoplastics P. 242
- ▶ Safety P. 276
- ▶ Coded Systems P. 300

Chart



Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Inner Sleeve
Seal bonnet

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR
Brass
Brass

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR
Brass
Brass

Plug


Plug Profile
Back Body
Valve
Spring
Seal

Brass
Brass
Brass
AISI 301
NBR

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
AISI 301
NBR





Couplings

RECTUS Series 21KL





Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	36	16	7					Standard	21KL AW10 MPX
									Nickel Plated	21KL AW10 MPN
G 1/4	17	38	16	9					Standard	21KL AW13 MPX
									Nickel Plated	21KL AW13 MPN
G 3/8	19	38	16	9					Standard	21KL AW17 MPX
									Nickel Plated	21KL AW17 MPN
M 12 x 1,5	17	38	16	9					Standard	21KL AD12 MPX
									Nickel Plated	21KL AD12 MPN
M 14 x 1,5	17	38	16	9					Standard	21KL AD14 MPX
									Nickel Plated	21KL AD14 MPN

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Female Thread</p>	G 1/8	14	36	16	9					Standard	21KL IW10 MPX	
										Nickel Plated	21KL IW10 MPN	
	G 1/4	17	38	16	9					Standard	21KL IW13 MPX	
										Nickel Plated	21KL IW13 MPN	
	G 3/8	19	38	16	9					Standard	21KL IW17 MPX	
										Nickel Plated	21KL IW17 MPN	
	M 12 x 1,5	17	38	16	6					Standard	21KL IM12 MPX	
										Nickel Plated	21KL IM12 MPN	
	M 14 x 1,5	17	38	16	6					Standard	21KL IM14 MPX	
										Nickel Plated	21KL IM14 MPN	
	 <p>Hose Barb</p>	4 mm	14	46	16	17					Standard	21KL TF04 MPX
											Nickel Plated	21KL TF04 MPN
6 mm		14	46	16	17					Standard	21KL TF06 MPX	
										Nickel Plated	21KL TF06 MPN	
8 mm		14	46	16	17					Standard	21KL TF08 MPX	
										Nickel Plated	21KL TF08 MPN	
9 mm		14	46	16	17					Standard	21KL TF09 MPX	
										Nickel Plated	21KL TF09 MPN	
10 mm		14	46	16	17					Standard	21KL TF10 MPX	
										Nickel Plated	21KL TF10 MPN	
6 mm Parker		14	46	16	17					Standard	21KL TP06 MPX	
										Nickel Plated	21KL TP06 MPN	
 <p>Plastic Hose Connection</p>	4 x 6 mm	14	42	16	7	6			M 10 x 1	Standard	21KL KO06 MPX	
										Nickel Plated	21KL KO06 MPN	
	6 x 8 mm	14	42	16	7	6			M 12 x 1	Standard	21KL KO08 MPX	
										Nickel Plated	21KL KO08 MPN	
 <p>Panel Mount, Plastic Hose Connection</p>	4 x 6 mm	14	54	16	7	18	14	4	M 10 x 1	Standard	21KL KS06 MPX	
										Nickel Plated	21KL KS06 MPN	
	6 x 8 mm	17	54	16	7	18	17	4	M 12 x 1	Standard	21KL KS08 MPX	
										Nickel Plated	21KL KS08 MPN	


Couplings

RECTUS Series 21KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Panel Mount, Hose Barb</p>	4 mm	14	60	16	17	14	14	4	M 10 x 1	Standard	21KL TS04 MPX	
										Nickel Plated	21KL TS04 MPN	
	5 mm	17	60	16	17	14	17	4	M 12 x 1	Standard	21KL TS05 MPX	
										Nickel Plated	21KL TS05 MPN	
	6 mm	17	60	16	17	14	17	4	M 12 x 1	Standard	21KL TS06 MPX	
										Nickel Plated	21KL TS06 MPN	
	8 mm	17	60	16	17	14	17	4	M 12 x 1	Standard	21KL TS08 MPX	
										Nickel Plated	21KL TS08 MPN	
	10 mm	17	60	16	17	14	19	4	M 12 x 1	Standard	21KL TS10 MPX	
										Nickel Plated	21KL TS10 MPN	
	 <p>Plastic Hose Connection with Spring Guard</p>	4 x 6 mm	14	125	16	7	6			M 10 x 1	Standard	21KL KK06 MPX
											Nickel Plated	21KL KK06 MPN
6 x 8 mm		14	130	16	7	6			M 10 x 1	Standard	21KL KK08 MPX	
										Nickel Plated	21KL KK08 MPN	

Valved Plugs

RECTUS Series 21KL





	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	4 mm	14	50		17					Standard	21SL TF04 MPX
										Nickel Plated	21SL TF04 MPN
	6 mm	14	50		17					Standard	21SL TF06 MPX
										Nickel Plated	21SL TF06 MPN
	8 mm	14	50		17					Standard	21SL TF08 MPX
										Nickel Plated	21SL TF08 MPN
	9 mm	14	50		17					Standard	21SL TF09 MPX
										Nickel Plated	21SL TF09 MPN
	10 mm	14	50		17					Standard	21SL TF10 MPX
										Nickel Plated	21SL TF10 MPN
	6 mm Parker	14	54		20					Standard	21SL TP06 MPX
										Nickel Plated	21SL TP06 MPN

Valved Plugs

RECTUS Series 21KL


Brass/Steel

Low Pressure

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Plastic Hose Connection</p>	4 x 6 mm	14	46	7	6				M 10 x 1	Standard	21SL KO06 MPX	
										Nickel Plated	21SL KO06 MPN	
	6 x 8 mm	14	46	7	6					M 12 x 1	Standard	21SL KO08 MPX
											Nickel Plated	21SL KO08 MPN
 <p>Panel Mount, Plastic Hose Connection</p>	6 x 8 mm	14	58	7	18	17	4		M 12 x 1	Standard	21SL KS08 MPX	
										Nickel Plated	21SL KS08 MPN	
	4 mm	14	64	17	14	14	4		M 10 x 1	Standard	21SL TS04 MPX	
										Nickel Plated	21SL TS04 MPN	
 <p>Panel Mount, Hose Barb</p>	5 mm	14	64	17	14	14	4		M 12 x 1	Standard	21SL TS05 MPX	
										Nickel Plated	21SL TS05 MPN	
	6 mm	14	64	17	14	17	4		M 12 x 1	Standard	21SL TS06 MPX	
										Nickel Plated	21SL TS06 MPN	
 <p>Plastic Hose Connection with Spring Guard</p>	4 x 6 mm	14	130	7	6				M 10 x 1	Standard	21SL KK06 MPX	
										Nickel Plated	21SL KK06 MPN	
	6 x 8 mm	14	135	6						M 12 x 1	Standard	21SL KK08 MPX
											Nickel Plated	21SL KK09 MPN

Valved Plugs



RECTUS Series 21KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Male Thread</p>	G 1/8	14	40		7					Standard	21SL AW10 MPX	
										Nickel Plated	21SL AW10 MPN	
	G 1/4	17	42		9						Standard	21SL AW13 MPX
											Nickel Plated	21SL AW13 MPN

⚠ Please consider our security advices on the pages 12/13 ⚠

Valved Plugs

RECTUS Series 21KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	M 12 x 1,5	17	43		10					Standard	21SL AD12 MPX
										Nickel Plated	21SL AD12 MPN
 <p>Female Thread</p>	G 1/8	14	40		7					Standard	21SL IW10 MPX
										Nickel Plated	21SL IW10 MPN
	G 1/4	17	42		7					Standard	21SL IW13 MPX
										Nickel Plated	21SL IW13 MPN
	G 3/8	19	42		7					Standard	21SL IW17 MPX
										Nickel Plated	21SL IW17 MPN
	M 12 x 1,5	17	42		7					Standard	21SL IM12 MPX
										Nickel Plated	21SL IM12 MPN
M 14 x 1,5	17	42		7					Standard	21SL IM14 MPX	
									Nickel Plated	21SL IM14 MPN	



Technical Description

Dry-break coupling systems, which stand out for their extremely low leakage rates and a minimum volume of dead space. No air locks whatsoever during connecting and negligible film of channelled medium on the valve bodies when disconnecting. Coupling systems for applications in sensitive environments, such as in analysis technology, cooling circuits, transport systems and many applications with aggressive medium.

Advantages

Single handed operation. Easy handling. Ergonomic sleeve shape. Low connecting forces. Valve body protected by collar design.

Extremely low dead volume remainings.

Interchangeability

RECTUS Design

Working Pressure

PB = 15 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature

-20°C up to +100°C (NBR)
Other sealing materials available on request.

Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals

Standard

- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- AISI 303
- AISI 420
- NBR

Plug

- Plug Profile
- Back Body
- Valve
- Spring
- Seal

- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- AISI 303
- NBR



85 % of actual size




reddot design award winner 2007

You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel P. 228

Chart





Couplings

RECTUS Series 206KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 3/8	22	68,5	25,5	9					Standard	206KL AW17 MPN
	G 1/2	22	71,5	25,5	12					Standard	206KL AW21 MPN
<p>Female Thread</p>	G 3/8	22	68,5	25,5	7					Standard	206KL IW17 MPN
	G 1/2	24	71,5	25,5	10					Standard	206KL IW21 MPN

Valved Plugs

RECTUS Series 206KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 3/8	22	51		9					Standard	206SL AW17MPN
	G 1/2	22	54		12					Standard	206SL AW21MPN
 <p>Female Thread</p>	G 3/8	22	51		7					Standard	206SL IW17MPN
	G 1/2	24	54		10					Standard	206SL IW21MPN



Technical Description

3/8" - 1/2" brass coupling system. High flow performance. Notable for robust design and steel sleeve used with large pneumatic consumers.

Dust Caps (P. 331)

for coupling Part.-No. SK23S
for plug Part.-No. SK12S



Advantages

Single handed operation. Robust design. High flow valve. No damage to the valve body from collar design. Minimum (hardly noticeable) leakage occurs when disconnecting. Air is not trapped in during the connecting process.

Working Pressure

PB = 8 bar, maximum static working pressure with safety factor of 4 to 1.


Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.



Chart



Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Seal Bonnet
Inner Sleeve

Standard

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR
Brass
Brass

Nickel Plated

Plug

Plug Profile
Back Body
Valve
Spring
Seal

Brass
Brass
Brass
AISI 301
NBR

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
AISI 301
NBR

You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Single Shut-off P. 73
- ▶ Brass/Steel Double Shut-off P. 139
- ▶ Stainless Steel P. 230
- ▶ Safety P. 278
- ▶ Safety Self-Venting P. 290
- ▶ Coded Systems P. 303




Couplings

RECTUS Series 25KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	60	23	12					Standard	25KL AK13 BPN
	R 3/8	19	60	23	12					Standard	25KL AK17 BPN
	R 1/2	22	61	23	17					Standard	25KL AK21 BPN
<p>Female Thread</p>	G 1/4	19	56	23	10					Standard	25KL IW13 BPN
	G 3/8	19	55	23	9					Standard	25KL IW17 BPN
	G 1/2	24	58	23	12					Standard	25KL IW21 BPN
	M 14 x 1,5	19	55	23	9					Standard	25KL IM14 BPN
	M 16 x 1,5	19	55	23	9					Standard	25KL IM16 BPN
M 18 x 1,5	22	56	23	9					Standard	25KL IM18 BPN	


Couplings

RECTUS Series 25KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm	19	74	23	25					Standard	25KL TF06 BPN
	8 mm	19	74	23	25					Standard	25KL TF08 BPN
	9 mm	19	74	23	25					Standard	25KL TF09 BPN
	10 mm	19	74	23	25					Standard	25KL TF10 BPN
	13 mm	19	74	23	25					Standard	25KL TF13 BPN
 <p>Plastic Hose Connection</p>	6 x 8 mm	19	67	23	7	6		M 12 x 1	Standard	25KL KO08 BPN	
	8 x 10 mm	19	155	23	9	8		M 16 x 1	Standard	25KL KO10 BPN	
	9 x 12 mm	19	65	23	9	8		M 16 x 1	Standard	25KL KO12 BPN	
 <p>Plastic Hose Connection with Spring Guard</p>	6 x 8 mm	19	144	23	7	6		M 12 x 1	Standard	25KL KK08 BPN	
	8 x 10 mm	19	155	23	9	8		M 16 x 1	Standard	25KL KK10 BPN	
	9 x 12 mm	19	162	23	9	8		M 16 x 1	Standard	25KL KK12 BPN	




Valved Plugs

RECTUS Series 25KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Hose Barb</p>	9 mm	21	60	25						Standard	25SL TF09 MPX	
										Nickel Plated	25SL TF09 MPN	
	10 mm	21	60	25							Standard	25SL TF10 MPX
											Nickel Plated	25SL TF10 MPN
	13 mm	21	60	25							Standard	25SL TF13 MPX
											Nickel Plated	25SL TF13 MPN



Valved Plugs

RECTUS Series 25KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Plastic Hose Connection</p>	6 x 8 mm	21	47		7	6			M 12 x 1	Standard	25SL KO08 MPX
										Nickel Plated	25SL KO08 MPN
	8 x 10 mm	21	51		8,5	8,5			M 16 x 1	Standard	25SL KO10 MPX
										Nickel Plated	25SL KO10 MPN
	9 x 12 mm	21	51		8,5	8,5			M 16 x 1	Standard	25SL KO12 MPX
										Nickel Plated	25SL KO12 MPN
 <p>Panel Mount, Hose Barb</p>	6 mm	21	62		17	10	17	4	M 12 x 1	Standard	25SL TS06 MPX
										Nickel Plated	25SL TS06 MPN
	10 mm	21	74		25	14	7	3,5	G 1/4	Standard	25SL TS10 MPX
										Nickel Plated	25SL TS10 MPN
 <p>Plastic Hose Connection with Spring Guard</p>	6 x 8 mm	19	135		7	6			M 12 x 1	Standard	25SL KK08 MPX
										Nickel Plated	25SL KK08 MPN
	8 x 10 mm	19	145		8,5	8,5			M 16 x 1	Standard	25SL KK10 MPX
										Nickel Plated	25SL KK10 MPN
	9 x 12 mm	19	150		8,5	8,5			M 16 x 1	Standard	25SL KK12 MPX
										Nickel Plated	25SL KK12 MPN

Valved Plugs

RECTUS Series 25KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/4	22	43		9					Standard	25SL AW13 MPX
										Nickel Plated	25SL AW13 MPN
	G 3/8	22	43		9					Standard	25SL AW17 MPX
										Nickel Plated	25SL AW17 MPN
	G 1/2	22	46		12					Standard	25SL AW21 MPX
										Nickel Plated	25SL AW21 MPN
	M 14 x 1,5	22	44		10					Standard	25SL AD14 MPX
										Nickel Plated	25SL AD14 MPN
	M 16 x 1,5	22	45		11					Standard	25SL AD16 MPX
										Nickel Plated	25SL AD16 MPN
	M 18 x 1,5	22	45		11					Standard	25SL AD18 MPX
										Nickel Plated	25SL AD18 MPN
 <p>Female Thread</p>	G 1/4	22	43		10					Standard	25SL IW13 MPX
										Nickel Plated	25SL IW13 MPN
	G 3/8	22	43		9					Standard	25SL IW17 MPX
										Nickel Plated	25SL IW17 MPN
	G 1/2	24	46		12					Standard	25SL IW21 MPX
										Nickel Plated	25SL IW21 MPN
	M 14 x 1,5	22	43		9					Standard	25SL IM14 MPX
										Nickel Plated	25SL IM14 MPN
	M 16 x 1,5	22	43		9					Standard	25SL IM16 MPX
										Nickel Plated	25SL IM16 MPN
	M 18 x 1,5	22	43		9					Standard	25SL IM18 MPX
										Nickel Plated	25SL IM18 MPN

⚠ Please consider our security advices on the pages 12/13 ⚠



Nominal Diameter

8,1 = 52 mm²

RECTUS Series

93KL



75% of actual size



Technical Description

The 93 Series is a modular coupling and plug without an integrated locking system for installation in multi-coupling system. The complete multi-coupling is offered under our 08 Series product name. The important sliding parts are coated with PTFE to reduce frictional resistance as much as possible.

Advantages

Available in single shut-off, double shut-off with dry break or straight through versions.

Working Pressure

PB = 15 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
 -30°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 0°C up to +316°C (FFKM)
 depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

Material

Coupling

Back Body
 Valve Body

 Valve
 Spring and Locking Ring
 Seals

Standard

Brass, Nickel Plated
 Steel Hardened and PTFE coated
 Brass
 AISI 301
 FKM

Plug

Plug Profile

 Back Body
 Valve
 Spring and Locking Ring
 Seal

Steel Hardened and PTFE coated
 Brass, Nickel Plated
 Brass
 AISI 301
 FKM

You will find the following alternative versions in our current catalogue on page:



► Brass/Steel Single Shut-off P. 85

Couplings **RECTUS Series 93KL**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 1/2	24	48		10,1					Standard	93KL IW21 SVN
<p>Hose Barb</p>	9 mm	24	54		17					Standard	93KL TF09 SVN
	13 mm	24	62		25					Standard	93KL TF13 SVN



Valved Plugs

RECTUS Series 93KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 1/2	24	57,5		10,1					Standard	93SL IW21 SVN
 <p>Hose Barb</p>	9 mm	24	63,5		17					Standard	93SL TF09 SVN
	13 mm	24	68,5		25					Standard	93SL TF13 SVN

Locking Coupling and Bolt

RECTUS Series 93KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Locking Coupling</p>			45								94KX
 <p>Locking Bolt</p>		24	58		13						94SX



Nominal Diameter

8,1 = 52 mm²

RECTUS Series

08KL



Technical Description

Multi-coupling system as plate or individual components for connecting hose combinations. Special coupling body with PTFE coating giving greater robustness, lower coupling forces, and resistance to liquid media. The standard version consists of a floating plate fitted with 8 quick connect couplings, 2 handles and 2 locking couplings as well as a fixed plate fitted with 8 plugs and 2 locking bolts. The layout is asymmetrical to avoid mixing up the circulation systems.

Advantages

The safety locking system prevents unintentional disconnection. Minimum (hardly noticeable) leakage occurs when disconnecting. Air is not trapped in during the connecting process. Time saving by using a multi-coupling system.

Working Pressure

PB = 15 bar, maximum static working pressure with safety factor 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 0°C up to +316°C (FFKM) depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

Material

Coupling

- Plate with 2 Handles
- 8 Multi Couplings
 - Back Body
 - Plug
 - Inner Parts
 - Springs
 - Seals
 - Locking Rings
- 2 Locking Couplings

Standard

- Aluminium, elox.
- Brass, Nickel Plated
- Steel Hardened, DNC-PTFE coated
- Brass
- AISI 301
- FKM
- AISI 301
- Steel Hardened, Nickel Plated

Plug

- Plate
- 8 Multi-Plugs
 - Back Body
 - Plug
 - Inner Parts
 - Springs
 - Seals
 - Locking Rings
- 2 Locking Bolts

- Aluminium, elox.
- Brass, Nickel Plated
- Steel Hardened, DNC-PTFE coated
- Brass
- AISI 301
- FKM
- AISI 301
- Steel Hardened, Nickel Plated



You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Single Shut-off P. 87

Couplings

RECTUS Series 08KL

	Connection A	A mm	B mm	C mm	D mm	E mm				Version	Part Number
<p>Female Thread</p>	G 1/2	170	100	50	30	18				Standard	08KL IW21 SVN
<p>Hose Barb</p>	13 mm	170	100	50	44	18			Standard	08KL TF13 SVN	

	Connection A	A mm	B mm	C mm	D mm	E mm				Version	Part Number
 <p>Female Thread</p>	G 1/2	170	100	50	30	27				Standard	08SL IW21 SVN
 <p>Hose Barb</p>	13 mm	170	100	50	44	27				Standard	08SL TF13 SVN



Nominal Diameter

9 = 63,5 mm²

RECTUS Series

209KL



70 % of actual size



reddot design award
winner 2007

You will find the following alternative versions in our current catalogue on page:


► Stainless Steel

P. 234

Technical Description

Dry-break coupling systems, which stand out for their extremely low leakage rates and a minimum volume of dead space. No air locks whatsoever during connecting and negligible film of channelled medium on the valve bodies when disconnecting. Coupling systems for applications in sensitive environments, such as in analysis technology, cooling circuits, transport systems and many applications with aggressive medium.

Chart



Advantages

Single handed operation. Easy handling. Ergonomic sleeve shape. Low connecting forces. Valve body protected by collar design.

Extremely low dead volume remainings.

Interchangeability

RECTUS Design

Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals

Plug

- Plug Profile
- Back Body
- Valve
- Spring
- Seal

Working Pressure

PB = 15 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature

-20°C up to +100°C (NBR)
Other sealing materials available on request.


Standard

- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- AISI 303
- AISI 420
- NBR

- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- AISI 303
- NBR


Couplings

RECTUS Series 209KL



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/2	27	92	33	14					Standard	209KL IW21 MPN
G 3/4	32	94	33	14					Standard	209KL IW26 MPN



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/2	27	79,5		14					Standard	209SL IW21 MPN
G 3/4	32	81,5		14					Standard	209SL IW26 MPN



Dry-Break

Nominal Diameter

19 = 300 mm²

RECTUS Series

39KL

45% of actual size

**Technical Description**

Industrial brass profile.
Compact dimensions with high performance characteristics.
Coupling can be used with numerous gaseous and liquid media.

Advantages

Minimum leakage when disconnecting leaves only a slight film of the medium left on the front part of the plug. Air is not trapped in during the coupling process. Compact dimensions. Extremely high flow performance.

Working Pressure

PB = 8 bar, maximum static working pressure with safety factor of 4 to 1.


Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -20°C and above +150°C special seals are available on request.

You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Single Shut-off P. 117
- ▶ Brass/Steel Double Shut-off P. 158

Chart**Material****Coupling**

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Seal Bonnet
Inner Sleeve

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR
Brass
Brass

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR
Brass
Brass

Plug

Plug Profile
Back Body
Valve
Spring
Seal
Spring Plate

Brass
Brass
Brass
AISI 301
NBR
Brass

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
AISI 301
NBR
Brass

Couplings**RECTUS Series 39KL**


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 3/4	41	95	46	16					Standard	39KL AW26 MPX
										Nickel Plated	39KL AW26 MPN
	G 1	41	98	46	19					Standard	39KL AW33 MPX
										Nickel Plated	39KL AW33 MPN
G 1 1/4	41	98	46	19					Standard	39KL AW42 MPX	
									Nickel Plated	39KL AW42 MPN	
<p>Female Thread</p>	G 3/4	41	99	46	20					Standard	39KL IW26 MPX
										Nickel Plated	39KL IW26 MPN
	G 1/2	41	100	46	20					Standard	39KL IW33 MPX
										Nickel Plated	39KL IW33 MPN
	G 1 1/4	50	105	46	22					Standard	39KL IW42 MPX
										Nickel Plated	39KL IW42 MPN

Couplings

RECTUS Series 39KL


Brass/Steel

Low Pressure

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	19 mm	41	115	46	36					Standard	39KL TF19 MPX
										Nickel Plated	39KL TF19 MPN
	25 mm	41	125	46	48					Standard	39KL TF25 MPX
										Nickel Plated	39KL TF25 MPN



Valved Plugs


RECTUS Series 39KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	19 mm	41	114		36					Standard	39SL TF19 MPX
										Nickel Plated	39SL TF19 MPN
	25 mm	41	124		48					Standard	39SL TF25 MPX
										Nickel Plated	39SL TF25 MPN

Valved Plugs

RECTUS Series 39KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 3/4	41	92		16					Standard	39SL AW26 MPX
										Nickel Plated	39SL AW26 MPN
	G 1	41	95		19					Standard	39SL AW33 MPX
										Nickel Plated	39SL AW33 MPN
 <p>Female Thread</p>	G 1 1/4	41	95		19					Standard	39SL AW42 MPX
										Nickel Plated	39SL AW42 MPN
	G 3/4	41	96		16					Standard	39SL IW26 MPX
										Nickel Plated	39SL IW26 MPN
	G 1	41	97		24					Standard	39SL IW33 MPX
										Nickel Plated	39SL IW33 MPN
	G 1 1/4	50	102		26					Standard	39SL IW42 MPX
										Nickel Plated	39SL IW42 MPN



Nominal Diameter

2,7 = 6 mm²

RECTUS Series

20KA



actual size



Technical Description

Mini industrial coupling, internationally used profile. Notable for a high flow and numerous application options with various media. Frequent use in mini-pneumatics, medical technology and chemistry/pharmacy.

Advantages

Single handed operation.
Small dimensions.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability



RECTUS 91
WALTHER 06-003

Working Temperature*

-15°C up to +200°C (FKM) depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel Double Shut-off P. 200
- ▶ Brass/Steel Single Shut-off P. 26

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals

AISI 303

AISI 303
AISI 303
AISI 303
AISI 303
AISI 301
AISI 420
FKM

AISI 316 L

AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 Ti
AISI 420
FKM

Plug

Plug

AISI 303

AISI 316 L




Couplings

RECTUS Series 20KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	M 5	9	26	10	5					AISI 303	20KA AM05 RVX
										AISI 316 L	20KA AM05 EVX
<p>Female Thread</p>	G 1/8	11	28	10	7					AISI 303	20KA AW10 RVX
										AISI 316 L	20KA AW10 EVX
<p>Male Thread</p>	M 5	9	25	10	5					AISI 303	20KA IM05 RVX
										AISI 316 L	20KA IM05 EVX
<p>Female Thread</p>	G 1/8	12	28	10	7					AISI 303	20KA IW10 RVX
										AISI 316 L	20KA IW10 EVX



Couplings

RECTUS Series 20KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	3 mm		35	10	13					AISI 303	20KA TF03 RVX
	4 mm		35	10	13					AISI 303 AISI 316 L	20KA TF04 RVX 20KA TF04 EVX
	5 mm		35	10	13					AISI 303	20KA TF05 RVX
 <p>Plastic Hose Connection</p>	3 x 4 mm	9	34	10	7	5			M 7 x 0,5	AISI 303 AISI 316 L	20KA KO04 RVX 20KA KO04 EVX
	3 x 5 mm	9	34	10	7	5			M 7 x 0,5	AISI 303 AISI 316 L	20KA KO05 RVX 20KA KO05 EVX
	4 x 6 mm	9	34	10	7	5			M 8 x 0,5	AISI 303 AISI 316 L	20KA KO06 RVX 20KA KO06 EVX
 <p>Panel Mount, Plastic Hose Connection</p>	3 x 4 mm	12	45	10	7	17	11	3	M 7 x 0,5	AISI 303	20KA KS04 RVX
	3 x 5 mm	12	45	10	7	17	11	3	M 7 x 0,5	AISI 303	20KA KS05 RVX
	4 x 6 mm	12	45	10	7	17	11	3	M 8 x 0,5	AISI 303	20KA KS06 RVX

Plugs


RECTUS Series 20KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	3 mm		24	7	13					AISI 303 AISI 316 L	20SF TF03 RXX 20SF TF03 EXX
	4 mm		24	7	13					AISI 303 AISI 316 L	20SF TF04 RXX 20SF TF04 EXX
	5 mm		22	9	13					AISI 303 AISI 316 L	20SF TF05 RXX 20SF TF05 EXX
 <p>Plastic Hose Connection</p>	3 x 4 mm	8	25		7	5			M 7 x 0,5	AISI 303 AISI 316 L	20SF KO04 RXX 20SF KO04 EXX
	3 x 5 mm	8	25		7	5			M 7 x 0,5	AISI 303 AISI 316 L	20SF KO05 RXX 20SF KO05 EXX
	4 x 6 mm	8	25		7	5			M 8 x 0,5	AISI 303 AISI 316 L	20SF KO06 RXX 20SF KO06 EXX

⚠ Please consider our security advices on the pages 12/13 ⚠



Couplings


RECTUS Series 20KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Panel Mount, Plastic Hose Connection</p>	4 x 6 mm	12	38		7	17	12	3	M 8 x 0,5	AISI 303	20SF KS06 RXX

Plugs

RECTUS Series 20KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	M 5	7	18		5					AISI 303	20SF AM05 RXX
										AISI 316 L	20SF AM05 EXX
 <p>Female Thread</p>	G 1/8	11	20		7					AISI 303	20SF AW10 RXX
										AISI 316 L	20SF AW10 EXX
	M 5	7	17		5					AISI 303	20SF IM05 RXX
										AISI 316 L	20SF IM05 EXX
	G 1/8	12	19		7					AISI 303	20SF IW10 RXX
										AISI 316 L	20SF IW10 EXX



Technical Description



Mini industrial coupling, the world's most commonly used profile. Above average flow performance for liquid and gaseous media. Large band width in materials and valve variants.

Dust Caps (P. 331)

for coupling Part.-No SK16S



Chart



Advantages

Single handed operation.
Small dimensions.
All variants interchangeable.

Interchangeability

RECTUS 90
CAMMOZZI
EWO
KANI

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals

AISI 303

AISI 303
AISI 303
AISI 303
AISI 303
AISI 301
AISI 420
FKM

AISI 316 L

AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 Ti
AISI 420
FKM

Plug

Plug

AISI 303

AISI 316 L

actual size




You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel Double Shut-off P. 205
- ▶ Stainless Steel Dry-Break P. 224
- ▶ Thermoplastics P. 242
- ▶ Brass/Steel P. 34
- ▶ Safety P. 266
- ▶ Coded Systems P. 300

Couplings

RECTUS Series 21KA








Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	36	16	7					AISI 303	21KA AW10 RVX
									AISI 316 L	21KA AW10 EVX
G 1/4	17	38	16	9					AISI 303	21KA AW13 RVX
									AISI 316 L	21KA AW13 EVX
G 3/8	19	38	16	9					AISI 303	21KA AW17 RVX
									AISI 316 L	21KA AW17 EVX
M 12 x 1,5	14	38	16	9					AISI 303	21KA AM12 RVX
M 14 x 1,5	17	39	16	10					AISI 303	21KA AM14 RVX



Male Thread


Couplings

RECTUS Series 21KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 1/8	14	36	16	5					AISI 303	21KA IW10 RVX
										AISI 316 L	21KA IW10 EVX
	G 1/4	17	38	16	9					AISI 303	21KA IW13 RVX
										AISI 316 L	21KA IW13 EVX
	G 3/8	19	38	16	9					AISI 303	21KA IW17 RVX
										AISI 316 L	21KA IW17 EVX
 <p>Hose Barb</p>	M 12 x 1,5	17	38	16	9					AISI 303	21KA IM12 RVX
	M 14 x 1,5	17	38	16	9					AISI 303	21KA IM14 RVX
	4 mm	14	46	16	17					AISI 303	21KA TF04 RVX
										AISI 316 L	21KA TF04 EVX
	6 mm	14	46	16	17					AISI 303	21KA TF06 RVX
										AISI 316 L	21KA TF06 EVX
 <p>Hose Barb</p>	8 mm	14	46	16	17					AISI 303	21KA TF08 RVX
										AISI 316 L	21KA TF08 EVX
	9 mm	14	46	16	17					AISI 303	21KA TF09 RVX
										AISI 316 L	21KA TF09 EVX
	10 mm	14	46	16	17					AISI 303	21KA TF10 RVX
										AISI 316 L	21KA TF10 EVX
 <p>6 mm Parker</p>	6 mm Parker	14	50	16	20					AISI 303	21KA TP06 RVX
 <p>Plastic Hose Connection</p>	4 x 6 mm	14	42	16	7	6			M 10 x 1	AISI 303	21KA KO06 RVX
										AISI 316 L	21KA KO06 EVX
 <p>Plastic Hose Connection</p>	6 x 8 mm	14	42	16	7	6			M 12 x 1	AISI 303	21KA KO08 RVX
										AISI 316 L	21KA KO08 EVX
 <p>Panel Mount, Plastic Hose Connection</p>	4 x 6 mm	14	54	16	7	18	12	3	M 10 x 1	AISI 303	21KA KS06 RVX
										AISI 316 L	21KA KS06 EVX
	6 x 8 mm	17	54	16	7	18	17	4	M 12 x 1	AISI 303	21KA KS08 RVX

Couplings

RECTUS Series 21KA




Panel Mount,
Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
5 mm	17	60	16	17	14	17	4	M 12 x 1	AISI 303	21KA TS05 RVX
6 mm	17	60	16	17	14	17	4	M 12 x 1	AISI 303	21KA TS06 RVX
8 mm	17	60	16	17	14	17	4	M 12 x 1	AISI 303	21KA TS08 RVX


Plugs

RECTUS Series 21KA




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
4 mm		32	9	17					AISI 303	21SF TF04 RXX
5 mm		32	9	17					AISI 303	21SF TF05 RXX
6 mm		32	9	17					AISI 303 AISI 316 L	21SF TF06 RXX 21SF TF06 EXX
8 mm		32	9	17					AISI 303 AISI 316 L	21SF TF08 RXX 21SF TF08 EXX
9 mm		33	10	17					AISI 303 AISI 316 L	21SF TF09 RXX 21SF TF09 EXX
10 mm		33	12	17					AISI 303 AISI 316 L	21SF TF10 RXX 21SF TF10 EXX
6 mm Parker		36	12	20					AISI 303	21SF TP06 RXX



Plastic Hose Connection

4 x 6 mm	12	32		7	6	12		M 10 x 1	AISI 303 AISI 316 L	21SF KO06 RXX 21SF KO06 EXX
6 x 8 mm	14	32		7	6	14		M 12 x 1	AISI 303 AISI 316 L	21SF KO08 RXX 21SF KO08 EXX







Panel Mount,
Plastic Hose Connection

4 x 6 mm	14	43		7	18	12	3	M 10 x 1	AISI 303 AISI 316 L	21SF KS06 RXX 21SF KS06 EXX
6 x 8 mm	14	44		7	18	17	4	M 12 x 1	AISI 303	21SF KS08 RXX

Plugs

RECTUS Series 21KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Male Thread</p>	G 1/8	14	25		7					AISI 303	21SF AW10 RXX	
										AISI 316 L	21SF AW10 EXX	
	G 1/4	17	28		9						AISI 303	21SF AW13 RXX
											AISI 316 L	21SF AW13 EXX
	G 3/8	19	28		9						AISI 303	21SF AW17 RXX
											AISI 316 L	21SF AW17 EXX
	M 10 x 1	14	25		7						AISI 303	21SF AM10 RXX
	M 12 x 1,5	17	28		10						AISI 303	21SF AM12 RXX
M 14 x 1,5	17	28		10						AISI 303	21SF AD14 RXX	
 <p>Female Thread</p>	G 1/8	14	25		8					AISI 303	21SF IW10 RXX	
										AISI 316 L	21SF IW10 EXX	
	G 1/4	17	25		9						AISI 303	21SF IW13 RXX
											AISI 316 L	21SF IW13 EXX
	G 3/8	19	26		9						AISI 303	21SF IW17 RXX
											AISI 316 L	21SF IW17 EXX
	M 10 x 1	14	26		9						AISI 303	21SF IM10 RXX
	M 12 x 1,5	17	27		10						AISI 303	21SF IM12 RXX
M 14 x 1,5	17	27		10						AISI 303	21SF IM14 RXX	

**Technical Description**

Euro-Coupling-System made of AISI 303 for corrosion resistant applications. Plug Profile interchangeable to Euro-Profile.

Advantages

Single handed operation.



Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-15°C up to +100°C (FKM) depending on the medium.

*At a temperature below -15°C and above +100°C special seals are available on request.

Chart**Interchangeability**

RECTUS 25
European Profile

Material**Coupling**

Back Body
Valve Body
Sleeve
Valve
Spring
Balls, Pins
Seals
Distance Sleeve

AISI 303

AISI 303
AISI 303
AISI 303
AISI 303
AISI 301
AISI 316
FKM
PTFE

Plug

Plug

AISI 303

90% of actual size



You will find the following alternative versions in our current catalogue on page:


- ▶ Brass/Steel Single Shut-off P. 66
- ▶ Brass/Steel Double Shut-off P. 136
- ▶ Safety Self-Venting P. 288

Couplings**RECTUS Series 26KA**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/4	19	55,5	28	10,5					AISI 303	26KA AW13 RVX
	G 3/8	19	53,5	28	9					AISI 303	26KA AW17 RVX
	G 1/2	24	56,5	28	12					AISI 303	26KA AW21 RVX
<p>Female Thread</p>	G 1/4	19	51,5	28	10					AISI 303	26KA IW13 RVX
	G 3/8	19	53,5	28	9					AISI 303	26KA IW17 RVX
	G 1/2	24	56,5	28	12					AISI 303	26KA IW21 RVX

Couplings

RECTUS Series 26KA




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	19	69,5	28	25					AISI 303	26KA TF06 RVX
8 mm	19	69,5	28	25					AISI 303	26KA TF08 RVX
9 mm	19	69,5	28	25					AISI 303	26KA TF09 RVX
10 mm	19	69,5	28	25					AISI 303	26KA TF10 RVX
13 mm	19	69,5	28	25					AISI 303	26KA TF13 RVX


Plugs

RECTUS Series 25SF




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm		48	12	25					AISI 303 AISI 316 L	25SF TF06 RXX 25SF TF06 EXX
8 mm		48	12	25					AISI 303 AISI 316 L	25SF TF08 RXX 25SF TF08 EXX
9 mm		48	12	25					AISI 303 AISI 316 L	25SF TF09 RXX 25SF TF09 EXX
10 mm		48	12	25					AISI 303 AISI 316 L	25SF TF10 RXX 25SF TF10 EXX
13 mm		48	15	25					AISI 303 AISI 316 L	25SF TF13 RXX 25SF TF13 EXX




Plastic Hose Connection

4 x 6 mm		34	12	7	6			M 10 x 1	AISI 303 AISI 316 L	25SF KO06 RXX 25SF KO06 EXX
6 x 8 mm		34	12	7	6			M 12 x 1	AISI 303 AISI 316 L	25SF KO08 RXX 25SF KO08 EXX
8 x 10 mm	17	42		9	8			M 16 x 1	AISI 303	25SF KO10 RXX
9 x 12 mm	17	42		9	8			M 16 x 1	AISI 303 AISI 316 L	25SF KO12 RXX 25SF KO12 EXX




Panel Mount, Hose Barb

6 mm	14	56		17	14	17	4	M 12 x 1	AISI 303	25SF TS06 RXX
8 mm	14	56		17	14	17	4	M 12 x 1	AISI 303	25SF TS08 RXX
10 mm	17	56		17	14	19	4	M 14 x 1	AISI 303	25SF TS10 RXX




Male Thread



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	31		7					AISI 303	25SF AW10 RXX
									AISI 316 L	25SF AW10 EXX
G 1/4	17	33		9					AISI 303	25SF AW13 RXX
									AISI 316 L	25SF AW13 EXX
G 3/8	19	33		9					AISI 303	25SF AW17 RXX
									AISI 316 L	25SF AW17 EXX
G 1/2	24	38		12					AISI 303	25SF AW21 RXX
									AISI 316 L	25SF AW21 EXX
M 18 x 1,5	22	37		11					AISI 303	25SF AM18 RXX
G 1/8	14	30		7					AISI 303	25SF IW10 RXX
									AISI 316 L	25SF IW10 EXX
G 1/4	17	33		10					AISI 303	25SF IW13 RXX
									AISI 316 L	25SF IW13 EXX
G 3/8	19	33		10					AISI 303	25SF IW17 RXX
									AISI 316 L	25SF IW17 EXX
G 1/2	24	35		12					AISI 303	25SF IW21 RXX
									AISI 316 L	25SF IW21 EXX
M 14 x 1,5	17	33		10					AISI 303	25SF IM14 RXX
M 14 x 1,5	17	33		10					AISI 303	25SF IM14 RXX
M 14 x 1,5	17	33		13					AISI 303	25SF IM14 RXX




Nominal Diameter

7,8 = 48 mm²

RECTUS Series

25KA





Low Pressure

actual size



Technical Description
 3/8" - 1/2" European industrial profile with UltraFlo technology. High flow performance. Notable for robust design and steel sleeve used with large pneumatic consumers. Optimum use with liquids and aggressive media.

Dust Caps (P. 331)
 for coupling Part.-No. SK23S
 for plug Part.-No. SK12S



Advantages
 Single handed operation.
 Tough construction.
 UltraFlo technology.

Interchangeability
 RECTUS 26
 CEJN 320
 various German products

Working Pressure
 PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*
 -15°C up to +200°C (FKM) depending on the medium.
 *At a temperature below -15°C and above +200°C special seals are available on request.


Material	AISI 303	AISI 316 L
Coupling		
Back Body	AISI 303	AISI 316 L
Valve Body	AISI 303	AISI 316 L
Sleeve	AISI 303	AISI 316 L
Valve	AISI 303	AISI 316 L
Inner Sleeve	AISI 303	AISI 316 L
Spring Plate	AISI 303	AISI 316 L
Spring and Locking Ring	AISI 301	AISI 316 Ti
Locking Balls	AISI 316	AISI 316
Seals	FKM	FKM

Plug	AISI 303	AISI 316 L
Plug	AISI 303	AISI 316 L

You will find the following alternative versions in our current catalogue on page:





- ▶ Stainless Steel Double Shut-off P. 209
- ▶ Stainless Steel Dry-Break P. 230
- ▶ Safety P. 270
- ▶ Safety Self-Venting P. 290
- ▶ Coded Systems S. 303
- ▶ Brass/Steel P. 73

Couplings **RECTUS Series 25KA**



Male Thread


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW	B mm	G mm	Version	Part Number
G 1/4	19	59,5	23	10,5					AISI 303	25KA AW13 RVX
G 1/4	19	59,5	23	10,5					AISI 316 L	25KA AW13 EVX
G 3/8	19	57,5	23	9					AISI 303	25KA AW17 RVX
G 3/8	19	57,5	23	9					AISI 316 L	25KA AW17 EVX
G 1/2	24	60,5	23	12					AISI 303	25KA AW21 RVX
G 1/2	24	60,5	23	12					AISI 316 L	25KA AW21 EVX
M 18 x 1,5	19	59,5	23	11					AISI 303	25KA AM18 RVX

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Female Thread</p>	G 1/4	19	55,5	23	10					AISI 303	25KA IW13 RVX	
										AISI 316 L	25KA IW13 EVX	
	G 3/8	19	54,5	23	9						AISI 303	25KA IW17 RVX
											AISI 316 L	25KA IW17 EVX
	G 1/2	24	57,5	23	12						AISI 303	25KA IW21 RVX
											AISI 316 L	25KA IW21 EVX
 <p>Hose Barb</p>	6 mm	19	73,5	23	25					AISI 303	25KA TF06 RVX	
										AISI 316 L	25KA TF06 EVX	
	8 mm	19	73,5	23	25						AISI 303	25KA TF08 RVX
											AISI 316 L	25KA TF08 EVX
	9 mm	19	73,5	23	25						AISI 303	25KA TF09 RVX
											AISI 316 L	25KA TF09 EVX
	10 mm	19	73,5	23	25						AISI 303	25KA TF10 RVX
											AISI 316 L	25KA TF10 EVX
	13 mm	19	73,5	23	25						AISI 303	25KA TF13 RVX
											AISI 316 L	25KA TF13 EVX
 <p>Plastic Hose Connection</p>	6 x 8 mm	19	61	23	7	6			M 12 x 1	AISI 303	25KA KO08 RVX	
										AISI 316 L	25KA KO08 EVX	
	8 x 10 mm	19	64,5	23	9	8				M 16 x 1	AISI 303	25KA KO10 RVX
											AISI 316 L	25KA KO12 EVX
 <p>Panel Mount, Hose Barb</p>	6 mm	19	75,5	23	17	10	17	4	M 12 x 1	AISI 303	25KA TS06 RVX	
										AISI 316 L	25KA TS08 RVX	
	8 mm	19	79,5	23	17	14	17	4	M 12 x 1	AISI 303	25KA TS08 RVX	
										AISI 316 L	25KA TS10 RVX	
	10 mm	19	79,5	23	25	14	19	4	M 14 x 1	AISI 303	25KA TS10 RVX	
										AISI 316 L		


Plugs

RECTUS Series 25KA


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm		48	12	25					AISI 303	25SF TF06 RXX
									AISI 316 L	25SF TF06 EXX
8 mm		48	12	25					AISI 303	25SF TF08 RXX
									AISI 316 L	25SF TF08 EXX
9 mm		48	12	25					AISI 303	25SF TF09 RXX
									AISI 316 L	25SF TF09 EXX
10 mm		48	12	25					AISI 303	25SF TF10 RXX
									AISI 316 L	25SF TF10 EXX
13 mm		48	15	25					AISI 303	25SF TF13 RXX
									AISI 316 L	25SF TF13 EXX
4 x 6 mm		34	12	7	6			M 10 x 1	AISI 303	25SF KO06 RXX
									AISI 316 L	25SF KO06 EXX
6 x 8 mm		34	12	7	6			M 12 x 1	AISI 303	25SF KO08 RXX
									AISI 316 L	25SF KO08 EXX
8 x 10 mm		17	42	9	8			M 16 x 1	AISI 303	25SF KO10 RXX
6 mm		14	56	17	14	17	4	M 12 x 1	AISI 303	25SF TS06 RXX
10 mm		17	56	17	14	19	4	M 14 x 1	AISI 303	25SF TS10 RXX




Hose Barb




Plastic Hose Connection



Panel Mount, Hose Barb




Male Thread



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	31		7					AISI 303	25SF AW10 RXX
									AISI 316 L	25SF AW10 EXX
G 1/4	17	33		9					AISI 303	25SF AW13 RXX
									AISI 316 L	25SF AW13 EXX
G 3/8	19	33		9					AISI 303	25SF AW17 RXX
									AISI 316 L	25SF AW17 EXX
G 1/2	24	38		12					AISI 303	25SF AW21 RXX
									AISI 316 L	25SF AW21 EXX
M 18 x 1,5	22	37		11					AISI 303	25SF AM18 RXX
G 1/8	14	30		7					AISI 303	25SF IW10 RXX
									AISI 316 L	25SF IW10 EXX
G 1/4	17	33		10					AISI 303	25SF IW13 RXX
									AISI 316 L	25SF IW13 EXX
G 3/8	19	33		10					AISI 303	25SF IW17 RXX
									AISI 316 L	25SF IW17 EXX
G 1/2	24	35		12					AISI 303	25SF IW21 RXX
									AISI 316 L	25SF IW21 EXX
M 14 x 1,5	17	33		10					AISI 303	25SF IM14 RXX
M 16 x 1,5	19	33		10					AISI 303	25SF IM16 RXX
M 18 x 1,5	22	36		13					AISI 303	25SF IM18 RXX



Nominal Diameter

10 = 80 mm²

RECTUS Series

27KA



Low Pressure

actual size





Technical Description

1/2" European industrial profile with UltraFlo technology. High flow performance. Notable for robust design with steel sleeve in use with large pneumatic consumers. Particularly suitable for aggressive media.

Dust Caps (P. 331)

for coupling Part.-No. SK27S
for plug Part.-No. SK16S

Chart



Advantages

Single handed operation. Low pressure drop. No damage to the valve body from collar design. High flow valve.

Interchangeability

CEJN 410

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Inner Sleeve
- Spring Plate
- Spring and Lock Ring
- Locking Balls
- Seals

AISI 303

- AISI 303
- AISI 303
- AISI 303
- AISI 303
- AISI 303
- AISI 303
- AISI 301
- AISI 316
- FKM

AISI 316 L

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316
- FKM

Plug

Plug


AISI 303

AISI 316 L

You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel Double Shut-off P. 213
- ▶ Safety Self-Venting P. 292
- ▶ Brass/Steel P. 95

Couplings RECTUS Series 27KA





Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW	B mm	G mm	Version	Part Number
G 1/4	24	57,5	27	9					AISI 303	27KA AW13 RVX
G 3/8	24	57,5	27	9					AISI 303 AISI 316 L	27KA AW 17 RVX 27KA AW17 EVX
G 1/2	24	59,5	27	12					AISI 303 AISI 316 L	27KA AW21 RVX 27KA AW21 EVX
G 3/4	32	60,5	27	16					AISI 303 AISI 316 L	27KA AW26 RVX 27KA AW26 EVX


Couplings

RECTUS Series 27KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 3/8	24	56,5	27	11					AISI 303	27KA IW17 RVX
										AISI 316 L	27KA IW17 EVX
	G 1/2	24	56,5	27	12					AISI 303	27KA IW21 RVX
										AISI 316 L	27KA IW21 EVX
	G 3/4	32	60,5	27	16					AISI 303	27KA IW26 RVX
										AISI 316 L	27KA IW26 EVX
 <p>Hose Barb</p>	8 mm	24	76,5	27	25					AISI 316 L	27KA TF08 EVX
	9 mm	24	76,5	27	25					AISI 303	27KA TF09 RVX
										AISI 316 L	27KA TF09 EVX
	10 mm	24	76,5	27	25					AISI 316 L	27KA TF10 EVX
	13 mm	24	76,5	27	25					AISI 303	27KA TF13 RVX
										AISI 316 L	27KA TF13 EVX
	16 mm	24	76,5	27	25					AISI 303	27KA TF16 RVX
										AISI 316 L	27KA TF16 EVX
19 mm	24	76,5	27	25					AISI 303	27KA TF19 RVX	
									AISI 316 L	27KA TF19 EVX	



Plugs

RECTUS Series 27KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm		48	15	25					AISI 303	27SF TF06 RXX
	8 mm		48	15	25					AISI 303	27SF TF08 RXX
										AISI 316 L	27SF TF08 EXX
	9 mm		48	15	25					AISI 303	27SF TF09 RXX
										AISI 316 L	27SF TF09 EXX
	10 mm		48	15	25					AISI 303	27SF TF10 RXX
										AISI 316 L	27SF TF10 EXX
	13 mm		48	15	25					AISI 303	27SF TF13 RXX
										AISI 316 L	27SF TF13 EXX
	16 mm		49	18	25					AISI 303	27SF TF16 RXX
									AISI 316 L	27SF TF16 EXX	
19 mm		48	15	25					AISI 303	27SF TF19 RXX	
									AISI 316 L	27SF TF19 EXX	


⚠ Please consider our security advices on the pages 12/13 ⚠

Plugs **RECTUS Series 27KA**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Male Thread</p>	G 1/4	17	36,5		9					AISI 303	27SF AW13 RXX	
										AISI 316 L	27SF AW13 EXX	
	G 3/8	19	36,5		9						AISI 303	27SF AW17 RXX
											AISI 316 L	27SF AW17 EXX
	G 1/2	24	40		12						AISI 303	27SF AW21 RXX
											AISI 316 L	27SF AW21 EXX
	G 3/4	32	45		16						AISI 303	27SF AW26 RXX
											AISI 316 L	27SF AW26 EXX
 <p>Female Thread</p>	G 3/8	19	33		9					AISI 303	27SF IW17 RXX	
										AISI 316 L	27SF IW17 EXX	
	G 1/2	24	37		12						AISI 303	27SF IW21 RXX
											AISI 316 L	27SF IW21 EXX
	G 3/4	32	42		16						AISI 303	27SF IW26 RXX
											AISI 316 L	27SF IW26 EXX



Transport for hazardous goods.



Our dry-break stainless steel coupling system in series 99KL stands up for its robustness and the safety of 8-way coding, which reliably prevents mix-ups.






Nominal Diameter

2,7 = 5 mm²

RECTUS Series

20KB



actual size



Technical Description

Mini industrial coupling, internationally used profile. Notable for a high flow and numerous application options with various media. Frequent use in medical technology and chemistry/pharmacy.

Advantages

Single handed operation. Small dimensions. Minimal pressure drop.

Working Pressure



PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM) depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

Chart



You will find the following alternative versions in our current catalogue on page:

- Stainless Steel Single Shut-off P. 182
- Brass/Steel Double Shut-off P. 120

Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals

AISI 303

- AISI 303
- AISI 303
- AISI 303
- AISI 303
- AISI 301
- AISI 316
- FKM

AISI 316 L

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316
- FKM

Plug

- Plug Profile
- Back Body
- Valve
- Spring
- Seal

- AISI 303
- AISI 303
- AISI 303
- AISI 301
- FKM

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- FKM




Couplings

RECTUS Series 20KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	M 5	9	26	10	5					AISI 303	20KB AM05 RVX
										AISI 316 L	20KB AM05 EVX
<p>Female Thread</p>	G 1/8	11	28	10	7					AISI 303	20KB AW10 RVX
										AISI 316 L	20KB AW10 EVX
	M 5	9	25	10	5					AISI 303	20KB IM05 RVX
										AISI 316 L	20KB IM05 EVX
	G 1/8	12	28	10	7					AISI 303	20KB IW10 RVX
										AISI 316 L	20KB IW10 EVX




Couplings

RECTUS Series 20KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	3 mm		35	10	13					AISI 303	20KB TF03 RVX
	4 mm		35	10	13					AISI 303 AISI 316 L	20KB TF04 RVX 20KB TF04 EVX
	5 mm		35	10	13					AISI 303	20KB TF05 RVX
 <p>Plastic Hose Connection</p>	3 x 4 mm	9	34	10	7	5			M 7 x 0,5	AISI 303 AISI 316 L	20KB KO04 RVX 20KB KO04 EVX
	3 x 5 mm	9	34	10	7	5			M 7 x 0,5	AISI 303 AISI 316 L	20KB KO05 RVX 20KB KO05 EVX
	4 x 6 mm	9	34	10	7	5			M 8 x 0,5	AISI 303 AISI 316 L	20KB KO06 RVX 20KB KO06 EVX
 <p>Panel Mount, Plastic Hose Connection</p>	3 x 4 mm	12	45	10	7	17	11	3	M 7 x 0,5	AISI 303	20KB KS04 RVX
	3 x 5 mm	12	45	10	7	17	11	3	M 7 x 0,5	AISI 303	20KB KS05 RVX
	4 x 6 mm	12	45	10	7	17	12	3,5	M 8 x 0,5	AISI 303	20KB KS06 RVX

Valved Plugs



RECTUS Series 20KB


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	3 mm	8	37		13					AISI 303	20SB TF03 RVX
	4 mm	8	37		13					AISI 303 AISI 316 L	20SB TF04 RVX 20SB TF04 EVX
	5 mm	8	37		13					AISI 303	20SB TF05 RVX
 <p>Plastic Hose Connection</p>	3 x 4 mm	9	36		7	5			M 7 x 0,5	AISI 303 AISI 316 L	20SB KO04 RVX 20SB KO04 EVX
	3 x 5 mm	9	36		7	5			M 7 x 0,5	AISI 303 AISI 316 L	20SB KO05 RVX 20SB KO05 EVX
	4 x 6 mm	9	36		7	5			M 8 x 0,5	AISI 303 AISI 316 L	20SB KO06 RVX 20SB KO06 EVX
 <p>Panel Mount, Plastic Hose Connection</p>	3 x 4 mm	12	47		7	17	11	3	M 7 x 0,5	AISI 303	20SB KS04 RVX
	3 x 5 mm	12	47		7	17	11	3	M 7 x 0,5	AISI 303	20SB KS05 RVX
	4 x 6 mm	12	47		7	17	12	3,5	M 8 x 0,5	AISI 303	20SB KS06 RVX

⚠ Please consider our security advices on the pages 12/13 ⚠

Valved Plugs

RECTUS Series 20KB



	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	M 5	9	28		5					AISI 303	20SB AM05 RVX
										AISI 316 L	20SB AM05 EVX
	G 1/8	11	30		7					AISI 303	20SB AW10 RVX
										AISI 316 L	20SB AW10 EVX
 <p>Female Thread</p>	M 5	9	27		5					AISI 303	20SB IM05 RVX
										AISI 316 L	20SB IM05 EVX
	G 1/8	12	30		7					AISI 303	20SB IW10 RVX
										AISI 316 L	20SB IW10 EVX



Technical Description

Mini industrial coupling with plug profile according to ISO 6150 C. Popular profile in analytical and medical technology. Above average flow rate performance for liquid and gaseous media.

Chart



Interchangeability

ISO 6150 C

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM) depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

Material

AISI 316 L

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring
- Balls, Pins
- Seals
- Distance Sleeve

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316
- FKM
- AISI 316 L

Plug

Plug

AISI 316 L

actual size





Couplings

RECTUS Series 303KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/8	14	43	18	7					AISI 316 L	303KB AW10 EVX
	G 1/4	17	45	18	9					AISI 316 L	303KB AW13 EVX
<p>Female Thread</p>	G 1/8	14	43	18	9					AISI 316 L	303KB IW10 EVX
	G 1/4	17	45	18	9					AISI 316 L	303KB IW13 EVX





Couplings


RECTUS Series 303KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	4 mm	14	53	18	17					AISI 316 L	303KB TF04 EVX
	6 mm	14	53	18	17					AISI 316 L	303KB TF06 EVX
	4 x 6 mm	14	49	18	7	6	12		M 10 x 1	AISI 316 L	303KB KO06 EVX
 <p>Plastic Hose Connection</p>	6 x 8 mm	14	49	18	7	6	14		M 12 x 1	AISI 316 L	303KB KO08 EVX

Valved Plugs

RECTUS Series 303KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14	48,5		7					AISI 316 L	303SB AW10 EVX
	G 1/4	17	50,5		9					AISI 316 L	303SB AW13 EVX
	G 1/8	14	48,5		9					AISI 316 L	303SB IW10 EVX
 <p>Female Thread</p>	G 1/4	17	50,5		9					AISI 316 L	303SB IW13 EVX
 <p>Hose Barb</p>	4 mm	14	58,5		17					AISI 316 L	303SB TF04 EVX
	6 mm	14	58,5		17					AISI 316 L	303SB TF06 EVX
	4 x 6 mm	14	54,5		7	6	12		M 10 x 1	AISI 316 L	303SB KO06 EVX
 <p>Plastic Hose Connection</p>	6 x 8 mm	14	54,5		7	6	14		M 12 x 1	AISI 316 L	303SB KO08 EVX





Technical Description

Mini industrial coupling, internationally the most common profile for this nominal diameter, in double shut-off design. Above average flow performance for liquid and gaseous media. Large band width in materials and valve variants.

Dust Caps (P. 323)

for coupling Part.-No. SK16S 

Chart



Advantages

Single handed operation.
Small dimensions.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals

Plug

Plug Profile
Back Body
Valve
Spring
Seal

AISI 303

AISI 303
AISI 303
AISI 303
AISI 303
AISI 301
AISI 420
FKM

AISI 316 L

AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 Ti
AISI 316
FKM

AISI 303
AISI 303
AISI 303
AISI 301
FKM

AISI 306 L
AISI 316 L
AISI 316 L
AISI 316 Ti
FKM

actual size




You will find the following alternative versions in our current catalogue on page:

- Stainless Steel Single Shut-off P. 185
- Stainless Steel Dry-Break P. 224
- Thermoplastics P. 242
- Brass/Steel Double Shut-off P. 125
- Safety P. 276
- Coded Systems P. 300

Couplings

RECTUS Series 21KB





Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	36	16	7					AISI 303	21KB AW10 RVX
									AISI 316 L	21KB AW10 EVX
G 1/4	17	38	16	9					AISI 303	21KB AW13 RVX
									AISI 316 L	21KB AW13 EVX
G 3/8	19	38	16	9					AISI 303	21KB AW17 RVX
									AISI 316 L	21KB AW17 EVX



Male Thread


Couplings

RECTUS Series 21KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Female Thread</p>	G 1/8	14	36	16	9					AISI 303	21KB IW10 RVX	
										AISI 316 L	21KB IW10 EVX	
	G 1/4	17	38	16	9						AISI 303	21KB IW13 RVX
											AISI 316 L	21KB IW13 EVX
	G 3/8	19	38	16	9						AISI 303	21KB IW17 RVX
											AISI 316 L	21KB IW17 EVX
 <p>Hose Barb</p>	4 mm	14	46	16	17					AISI 303	21KB TF04 RVX	
										AISI 316 L	21KB TF04 EVX	
	5 mm	14	46	16	17					AISI 303	21KB TF05 RVX	
	6 mm	14	46	16	17						AISI 303	21KB TF06 RVX
											AISI 316 L	21KB TF06 EVX
	8 mm	14	46	16	17						AISI 303	21KB TF08 RVX
											AISI 316 L	21KB TF08 EVX
	9 mm	14	46	16	17						AISI 303	21KB TF09 RVX
											AISI 316 L	21KB TF09 EVX
	10 mm	14	46	16	17						AISI 303	21KB TF10 RVX
AISI 316 L											21KB TF10 EVX	
6 mm Parker	14	50	16	20						AISI 303	21KB TP06 RVX	
 <p>Plastic Hose Connection</p>	4 x 6 mm	14	42	16	7	6			M 10 x 1	AISI 303	21KB KO06 RVX	
										AISI 316 L	21KB KO06 EVX	
	6 x 8 mm	14	42	16	7	6				M 12 x 1	AISI 303	21KB KO08 RVX
											AISI 316 L	21KB KO08 EVX
 <p>Panel Mount, Plastic Hose Connection</p>	4 x 6 mm	14	54	16	7	18	14	4	M 10 x 1	AISI 303	21KB KS06 RVX	
										AISI 316 L	21KB KS06 EVX	
	6 x 8 mm	17	54	16	7	18	14	4	M 12 x 1	AISI 303	21KB KS08 RVX	




Couplings

RECTUS Series 21KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Panel Mount, Hose Barb</p>	8 mm	17	60	16	17	14	17	4	M 12 x 1	AISI 303	21KB TS08 RVX	


Valved Plugs

RECTUS Series 21KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Hose Barb</p>	6 mm	14	50		17					AISI 303	21SB TF06 RVX	
										AISI 316 L	21SB TF06 EVX	
	8 mm	14	50		17					AISI 303	21SB TF08 RVX	
										AISI 316 L	21SB TF08 EVX	
	9 mm	14	50		17					AISI 303	21SB TF09 RVX	
										AISI 316 L	21SB TF09 EVX	
	10 mm	14	50		17					AISI 303	21SB TF10 RVX	
										AISI 316 L	21SB TF10 EVX	
	6 mm Parker	14	54		20					AISI 303	21SB TP06 RVX	
	 <p>Plastic Hose Connection</p>	4 x 6 mm	14	46		7	6			M 10 x 1	AISI 303	21SB KO06 RVX
											AISI 316 L	21SB KO06 EVX
		6 x 8 mm	14	46		7	6				M 12 x 1	AISI 303
										AISI 316 L	21SB KO08 EVX	
 <p>Panel Mount, Plastic Hose Connection</p>	4 x 6 mm	14	58		7	18	12	3	M 10 x 1	AISI 303	21SB KS06 RVX	
										AISI 316 L	21SB KS06 EVX	
	6 x 8 mm	17	58		7	18	17	4	M 12 x 1	AISI 303	21SB KS08 RVX	

Valved Plugs

RECTUS Series 21KB




Panel Mount,
Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	17	64		17	14	17	4	M 12 x 1	AISI 303	21SB TS06 RVX
9 mm	17	64		17	14	17	4	M 12 x 1	AISI 303	21SB TS09 RVX
10 mm	17	61		17	11	17	3,5	G 1/4	AISI 303	21SB TS10 RVX


Valved Plugs

RECTUS Series 21KB



Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	40		7					AISI 303	21SB AW10 RVX
									AISI 316 L	21SB AW10 EVX
G 1/4	17	42		9					AISI 303	21SB AW13 RVX
									AISI 316 L	21SB AW13 EVX
G 3/8	19	42		9					AISI 303	21SB AW17 RVX
									AISI 316 L	21SB AW17 EVX
M 14 x 1,5	17	43		10					AISI 303	21SB AM14 RVX



Female Thread

G 1/8	14	40		9					AISI 303	21SB IW10 RVX
									AISI 316 L	21SB IW10 EVX
G 1/4	17	42		9					AISI 303	21SB IW13 RVX
									AISI 316 L	21SB IW13 EVX
G 3/8	19	42		9					AISI 303	21SB IW17 RVX
									AISI 316 L	21SB IW17 EVX
M 10 x 1	14	40		9					AISI 303	21SB IM10 RVX
M 12 x 1,5	17	42		9					AISI 303	21SB IM12 RVX
M 14 x 1,5	17	42		9					AISI 303	21SB IM14 RVX



Technical Description



3/8" - 1/2" European industrial profile with UltraFlo technology. High flow performance. Notable for robust design and steel sleeve used with large pneumatic consumers. Optimum use with liquids and aggressive media.

Dust Caps (P. 323)

for coupling Part.-No. SK23S
for plug Part.-No. SK12S



Chart



Advantages

Single handed operation.
Robust design. High flow valve.
No damage to the valve body from collar design.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM) depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

actual size



Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Inner Sleeve
Spring Plate

Plug

Plug Profile
Back Body
Valve
Spring
Seal

AISI 303

AISI 303
AISI 303
AISI 303
AISI 303
AISI 301
AISI 316
FKM
AISI 303
AISI 303

AISI 303
AISI 303
AISI 303
AISI 301
FKM

AISI 316 L

AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 Ti
AISI 316 L
FKM
AISI 316 L
AISI 316 L

AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 Ti
FKM


You will find the following alternative versions in our current catalogue on page:

- Stainless Steel Single Shut-off P. 192
- Stainless Steel Dry-Break P. 230
- Brass/Steel Double Shut-off P. 139
- Safety P. 278
- Safety Self-Venting P. 290
- Coded Systems P. 303

Couplings





RECTUS Series 25KB

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/4	19	59,5	23	10,5					AISI 303	25KB AW13 RVX
									AISI 316 L	25KB AW13 EVX
G 3/8	19	57,5	23	9					AISI 303	25KB AW17 RVX
									AISI 316 L	25KB AW17 EVX
G 1/2	24	60,5	23	12					AISI 303	25KB AW21 RVX
									AISI 316 L	25KB AW21 EVX
M 16 x 1,5	19	59	23	10,5					AISI 303	25KB AM16 RVX
									AISI 316 L	25KB AM16 EVX






Male Thread

Couplings RECTUS Series 25KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Female Thread</p>	G 1/4	19	55,5	23	10					AISI 303	25KB IW13 RVX	
										AISI 316 L	25KB IW13 EVX	
	G 3/8	19	54,5	23	9						AISI 303	25KB IW17 RVX
											AISI 316 L	25KB IW17 EVX
	G 1/2	24	57,5	23	12						AISI 303	25KB IW21 RVX
											AISI 316 L	25KB IW21 EVX
	M 14 x 1,5	19	54,5	23	9						AISI 303	25KB IM14 RVX
M 16 x 1,5	19	54,5	23	9						AISI 303	25KB IM16 RVX	
M 18 x 1,5	22	54,5	23	9						AISI 303	25KB IM18 RVX	
 <p>Hose Barb</p>	6 mm	19	73,5	23	25					AISI 303	25KB TF06 RVX	
										AISI 316 L	25KB TF06 EVX	
	8 mm	19	73,5	23	25						AISI 303	25KB TF08 RVX
											AISI 316 L	25KB TF08 EVX
	9 mm	19	73,5	23	25						AISI 303	25KB TF09 RVX
											AISI 316 L	25KB TF09 EVX
10 mm	19	73,5	23	25						AISI 303	25KB TF10 RVX	
										AISI 316 L	25KB TF10 EVX	
13 mm	19	73,5	23	25						AISI 303	25KB TF13 RVX	
										AISI 316 L	25KB TF13 EVX	
 <p>Plastic Hose Connection</p>	6 x 8 mm	19	61	23	7	6		M 12 x 1		AISI 303	25KB KO08 RVX	
										AISI 316 L	25KB KO08 EVX	
	8 x 10 mm	19	64,5	23	9	8			M 16 x 1	AISI 303	25KB KO10 RVX	
9 x 12 mm	19	64,5	23	9	8			M 16 x 1		AISI 303	25KB KO12 RVX	
										AISI 316 L	25KB KO12 EVX	
 <p>Panel Mount, Hose Barb</p>	10 mm	19	79,5	23	25	14	19	4	M 14 x 1	AISI 303	25KB TS10 RVX	


Valved Plugs

RECTUS Series 25KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm	19	72	25						AISI 303	25SB TF06 RVX
										AISI 316 L	25SB TF06 EVX
	8 mm	19	72	25						AISI 303	25SB TF08 RVX
										AISI 316 L	25SB TF08 EVX
	9 mm	19	72	25						AISI 303	25SB TF09 RVX
										AISI 316 L	25SB TF09 EVX
 <p>Plastic Hose Connection</p>	4 x 6 mm	19	59	7	6			M 10 x 1	AISI 303	25SB KO06 RVX	
										AISI 316 L	25SB KO06 EVX
	6 x 8 mm	19	59	7	6			M 12 x 1	AISI 303	25SB KO08 RVX	
										AISI 316 L	25SB KO08 EVX
	8 x 10 mm	19	63	8,5	8,5			M 16 x 1	AISI 303	25SB KO10 RVX	
										AISI 316 L	25SB KO10 EVX
 <p>Panel Mount, Hose Barb</p>	6 mm	19	74	17	10	17	4	M 12 x 1	AISI 303	25SB TS06 RVX	
										AISI 316 L	25SB TS06 EVX
	8 mm	19	78	17	14	17	4	M 12 x 1	AISI 303	25SB TS08 RVX	
										AISI 316 L	25SB TS08 EVX
	10 mm	19	78	17	14	19	4	M 14 x 1	AISI 303	25SB TS10 RVX	
										AISI 316 L	25SB TS10 EVX



Valved Plugs


RECTUS Series 25KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	19	54	7						AISI 303	25SB AW10 RVX
										AISI 316 L	25SB AW10 EVX
	G 1/4	19	58	10,5						AISI 303	25SB AW13 RVX
										AISI 316 L	25SB AW13 EVX
	G 3/8	19	56	9						AISI 303	25SB AW17 RVX
										AISI 316 L	25SB AW17 EVX
<td>G 1/2</td> <td>24</td> <td>59</td> <td>12</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>AISI 303</td> <td>25SB AW21 RVX</td>	G 1/2	24	59	12						AISI 303	25SB AW21 RVX
										AISI 316 L	25SB AW21 EVX

Valved Plugs

RECTUS Series 25KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	M 16 x 1,5	19	57,5		10,5					AISI 303	25SB AM16 RVX
										AISI 316 L	25SB AM16 EVX
	M 18 x 1,5	19	58		11					AISI 303	25SB AM 18 RVX
 <p>Female Thread</p>	G 1/4	19	54		10					AISI 303	25SB IW13 RVX
										AISI 316 L	25SB IW13 EVX
	G 3/8	19	53		9					AISI 303	25SB IW17 RVX
										AISI 316 L	25SB IW17 EVX
	G 1/2	24	56		12					AISI 303	25SB IW21 RVX
										AISI 316 L	25SB IW21 EVX
	M 18 x 1,5	22	53		9					AISI 303	25SB IM18 RVX





Technical Description

1/2" European industrial profile with UltraFlo technology. High flow performance. Notable for robust design with steel sleeve in use with large pneumatic consumers. Particularly suitable for aggressive media.

Dust Caps (P. 323)

for coupling Part.-No. SK27S 

Chart



Advantages

Single handed operation. Low pressure drop. No damage to the valve body from collar design. High flow valve.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Inner Sleeve
Spring Plate

AISI 303

AISI 303
AISI 303
AISI 303
AISI 303
AISI 301
AISI 316
FKM
AISI 303
AISI 303

AISI 316 L

AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 Ti
AISI 316
FKM
AISI 316 L
AISI 316 L

Plug

Plug Profile
Back Body
Valve
Spring
Seal

AISI 303
AISI 303
AISI 303
AISI 301
FKM

AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 Ti
FKM

90% of actual size




You will find the following alternative versions in our current catalogue on page:

- Stainless Steel Single Shut-off P. 196
- Brass/Steel Double Shut-off P. 145
- Safety Self-Venting P. 292

Couplings



RECTUS Series 27KB

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/4	24	57,5	27	9					AISI 303	27KB AW13 RVX
G 3/8	24	57,5	27	9					AISI 303 AISI 316 L	27KB AW17 RVX 27KB AW17 EVX
G 1/2	24	59,5	27	12					AISI 303 AISI 316 L	27KB AW21 RVX 27KB AW21 EVX
G 3/4	32	60,5	27	16					AISI 303 AISI 316 L	27KB AW26 RVX 27KB AW26 EVX




Couplings



RECTUS Series 27KB


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 1/4	24	56,5	27	10					AISI 316 L	27KB IW13 EVX
	G 3/8	24	56,5	27	11					AISI 303	27KB IW17 RVX
										AISI 316 L	27KB IW17 EVX
	G 1/2	24	56,5	27	12					AISI 303	27KB IW21 RVX
										AISI 316 L	27KB IW21 EVX
	G 3/4	32	60,5	27	16					AISI 303	27KB IW26 RVX
										AISI 316 L	27KB IW26 EVX
 <p>Hose Barb</p>	13 mm	24	76,5	27	25					AISI 303	27KB TF13 RVX
										AISI 316 L	27KB TF13 EVX
	16 mm	24	76,5	27	25					AISI 303	27KB TF16 RVX
										AISI 316 L	27KB TF16 EVX
	19 mm	24	76,5	27	25					AISI 303	27KB TF19 RVX
										AISI 316 L	27KB TF19 EVX

Valved Plugs

RECTUS Series 27KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	9 mm	24	74,5		25					AISI 303	27SB TF09 RVX
										AISI 316 L	27SB TF09 EVX
	13 mm	24	74,5		25					AISI 303	27SB TF13 RVX
										AISI 316 L	27SB TF13 EVX
	16 mm	24	74,5		25					AISI 303	27SB TF16 RVX
										AISI 316 L	27SB TF16 EVX
	19 mm	24	74,5		25					AISI 303	27SB TF19 RVX
										AISI 316 L	27SB TF19 EVX

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/4	24	55,5		9					AISI 303	27SB AW13 RVX
	G 3/8	24	55,5		9					AISI 303 AISI 316 L	27SB AW17 RVX 27SB AW17 EVX
	G 1/2	24	57,5		12					AISI 303 AISI 316 L	27SB AW21 RVX 27SB AW21 EVX
	G 3/4	32	58,5		16					AISI 303 AISI 316 L	27SB AW26 RVX 27SB AW26 EVX
	G 1/4	24	54,5		10					AISI 303 AISI 316 L	27SB IW13 RVX 27SB IW13 EVX
	G 3/8	24	54,5		10					AISI 303 AISI 316 L	27SB IW17 RVX 27SB IW17 EVX
 <p>Female Thread</p>	G 1/2	24	54,5		12					AISI 303 AISI 316 L	27SB IW21 RVX 27SB IW21 EVX
	G 3/4	32	58,5		16					AISI 303 AISI 316 L	27SB IW26 RVX 27SB IW26 EVX



Nominal Diameter

4,3 = 15 mm²

RECTUS Series

71KB



Low Pressure

actual size



Technical Description

Smallest dimensions for a couplings series according to ISO 7241-1 series B. Particularly suitable for use with liquid media. This is a two-hand operation coupling system, i.e. the sleeve must be pushed back manually when coupling.

Advantages

High flow rate – marginal pressure drop. Plug Profile according to ISO-Norm.

Working Pressure



PB = 250 bar maximum static working pressure until 50°C with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

Chart



Material

Coupling

- Back Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals
- Spring Plate

AISI 303

- AISI 303
- AISI 303
- AISI 303
- AISI 301
- AISI 316
- FKM
- AISI 301

AISI 316 L

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316
- FKM
- AISI 316 L

Plug

- Plug Profile
- Valve
- Spring
- Spring Plate
- Seal

- AISI 303
- AISI 303
- AISI 301
- AISI 301
- FKM

- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316 L
- FKM

You will find the following alternative versions in our current catalogue on page:


- Thermoplastics P. 256
- Brass/Steel Double Shut-off P. 124

Couplings RECTUS Series 71KB

Diagram	Connection A	Hex	L	D	L1	L2	Hex1	B	G	Version	Part Number
		SW	mm	mm	mm	mm	SW1	mm	mm		
<p>Female Thread</p>	G 1/8	14	48,5	25	7					AISI 303	71KB IW10 RVX
										AISI 316 L	71KB IW10 EVX

Valved Plugs RECTUS Series 71KB

Diagram	Connection A	Hex	L	D	L1	L2	Hex1	B	G	Version	Part Number
		SW	mm	mm	mm	mm	SW1	mm	mm		
<p>Female Thread</p>	G 1/8	14	29,5		7					AISI 303	71SB IW10 RVX
										AISI 316 L	71SB IW10 EVX



Technical Description

Couplings series according to ISO 7241-1 series B. Particularly suitable for use with liquid media. This is a two-hand operation coupling system, i.e. the sleeve must be pushed back manually when coupling.

Advantages

High flow rate – marginal pressure drop. Plug Profile according to ISO-Norm.

Working Pressure

PB = 250 bar, maximum static working pressure until 50°C with safety factor of 4 to 1.



Working Temperature*

-15°C up to +200°C (FKM)
0°C up to +316 °C (FFKM)
depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.



Chart



Material

Coupling

Back Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Spring Plate

AISI 303

AISI 303
AISI 303
AISI 303
AISI 301
AISI 316
FKM
AISI 301

AISI 316 L

AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 Ti
AISI 316
FKM
AISI 316 L

Plug

Plug Profile
Valve
Spring
Spring Plate
Seal

AISI 303
AISI 303
AISI 301
AISI 301
FKM

AISI 316 L
AISI 316 L
AISI 316 Ti
AISI 316 L
FKM

You will find the following alternative versions in our current catalogue on page:

- Thermoplastics P. 257
- Brass/Steel Double Shut-off P. 134

Couplings


RECTUS Series 72KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 1/4	19	57,5	29	10					AISI 303	72KB IW13 RVX
										AISI 316 L	72KB IW13 EVX

Valved Plugs

RECTUS Series 72KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 1/4	19	35		10					AISI 303	72SB IW13 RVX
										AISI 316 L	72SB IW13 EVX



Nominal Diameter

7,5 = 44 mm²

RECTUS Series

73KB



Low Pressure



90% of actual size

Technical Description

Couplings series according to ISO 7241-1 series B. Particularly suitable for use with liquid media. This is a two-hand operation coupling system, i.e. the sleeve must be pushed back manually when coupling.

Advantages

High flow rate – marginal pressure drop. Plug Profile according to ISO-Norm.

Working Pressure



PB = 250 bar, maximum static working pressure until 50°C with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM)
0°C up to +316 °C (FFKM)
depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

Chart



You will find the following alternative versions in our current catalogue on page:

- Thermoplastics P. 258
- Brass/Steel Double Shut-off P. 144

Material

Coupling

- Back Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals
- Spring Plate

AISI 303

- AISI 303
- AISI 303
- AISI 303
- AISI 301
- AISI 316
- FKM
- AISI 301

AISI 316 L

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316
- FKM
- AISI 316 L

Plug

- Plug Profile
- Valve
- Spring
- Spring Plate
- Seal

- AISI 303
- AISI 303
- AISI 301
- AISI 301
- FKM

- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316 L
- FKM

Couplings RECTUS Series 73KB

Diagram	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
	<p>Female Thread</p>	G 3/8	22	64	35	11,5					AISI 303
										AISI 316 L	73KB IW17 EVX

Valved Plugs RECTUS Series 73KB

Diagram	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
	<p>Female Thread</p>	G 3/8	22	39		11,5					AISI 303
										AISI 316 L	73SB IW17 EVX



Technical Description

Couplings series according to ISO 7241-1 series B. Particularly suitable for use with liquid media. This is a two-hand operation coupling system, i.e. the sleeve must be pushed back manually when coupling.

Advantages

High flow rate – marginal pressure drop. Plug Profile according to ISO-Norm.

Working Pressure

PB = 250 bar, maximum static working pressure until 50°C with safety factor of 4 to 1.



Working Temperature

-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.



Chart



Material

Coupling

Back Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Spring Plate

AISI 303

AISI 303
AISI 303
AISI 303
AISI 301
AISI 316
FKM
AISI 316 L

AISI 316 L

AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 Ti
AISI 316
FKM
AISI 316 L

Plug

Plug Profile
Valve
Spring
Spring Plate
Seal

AISI 303
AISI 303
AISI 301
AISI 316 L
FKM

AISI 316 L
AISI 316 L
AISI 316 Ti
AISI 316 L
FKM

You will find the following alternative versions in our current catalogue on page:

- Thermoplastics P. 259
- Brass/Steel Double Shut-off P. 150

Couplings

RECTUS Series 74KB

	Connection A	Hex	L	D	L1	L2	Hex1	B	G	Version	Part Number
		SW	mm	mm	mm	mm	SW1	mm	mm		
<p>Female Thread</p>	G 1/2	27	76	44,5	16					AISI 303	74KB IW21 RVX
										AISI 316 L	74KB IW21 EVX

Valved Plugs

RECTUS Series 74KB

	Connection A	Hex	L	D	L1	L2	Hex1	B	G	Version	Part Number
		SW	mm	mm	mm	mm	SW1	mm	mm		
<p>Female Thread</p>	G 1/2	27	48		16					AISI 303	74SB IW21 RVX
										AISI 316 L	74SB IW21 EVX



Nominal Diameter

13 = 133 mm²

RECTUS Series

75KB



Low Pressure



60% of actual size

Technical Description

Couplings series according to ISO 7241-1 series B. Particularly suitable for use with liquid media. This is a two-hand operation coupling system, i.e. the sleeve must be pushed back manually when coupling.

Advantages

High flow rate – marginal pressure drop. Plug Profile according to ISO-Norm.

Working Pressure



PB =160 bar maximum static working pressure until 50°C with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM)
0°C bis +316°C (FFKM)
depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

Chart



You will find the following alternative versions in our current catalogue on page:

- Thermoplastics P. 260
- Brass/Steel Double Shut-off P. 154

Material

Coupling

- Back Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals
- Spring Plate

AISI 303

- AISI 303
- AISI 303
- AISI 303
- AISI 301
- AISI 316
- FKM
- AISI 301

AISI 316 L

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316
- FKM
- AISI 316 L

Plug


- Plug Profile
- Valve
- Spring
- Spring Plate
- Seal

- AISI 303
- AISI 303
- AISI 301
- AISI 301
- FKM

- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316 L
- FKM


Couplings


RECTUS Series 75KB

 Female Thread	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
	G 3/4	34	96	55	24						AISI 303
										AISI 316 L	75KB IW26 EVX

Valved Plugs

RECTUS Series 75KB

 Female Thread	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
	G 3/4	36	60		24						AISI 303
										AISI 316 L	75SB IW26 EVX



Technical Description

Couplings series according to ISO 7241-1 series B. Particularly suitable for use with liquid media. This is a two-hand operation coupling system, i.e. the sleeve must be pushed back manually when coupling.

Advantages

High flow rate – marginal pressure drop. Plug Profile according to ISO-Norm.

Working Pressure

PB = 100 bar, maximum static working pressure until 50°C with safety factor of 4 to 1.



Working Temperature*

-15°C up to +200°C (FKM)
0°C bis +316°C (FFKM)
depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.



Chart



Material

Coupling

Back Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Spring and Locking Ring

AISI 303

AISI 303
AISI 303
AISI 303
AISI 316 L
AISI 316
FKM
AISI 301

AISI 316 L

AISI 316 L
AISI 316 L
AISI 316 L
AISI 316 Ti
AISI 316
FKM
AISI 316 L

Plug

Plug Profile
Valve
Spring and Locking Ring
Spring Plate
Seal

AISI 303
AISI 303
AISI 316 L
AISI 301
FKM

AISI 316 L
AISI 316 L
AISI 316 Ti
AISI 316 L
FKM

You will find the following alternative versions in our current catalogue on page:

- Thermoplastics P. 261
- Brass/Steel Double Shut-off P. 160

Couplings

RECTUS Series 76KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 1	41	105,5	62	24					AISI 303	76KB IW33 RVX
										AISI 316 L	76KB IW33 EVX

Valved Plugs

RECTUS Series 76KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 1	14	43	18	7					AISI 303	76SB IW33 RVX
										AISI 316 L	76SB IW33 EVX



Nominal Diameter

4 = 12,5 mm²



RECTUS Series

204KL

actual size



red dot design award winner 2007

You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Dry-Break P. 162

Technical Description

Dry-break coupling systems, which stand out for their extremely low leakage rates and a minimum volume of dead space. No air locks whatsoever during connecting and negligible film of channelled medium on the valve bodies when disconnecting. Coupling systems for applications in sensitive environments, such as in analysis technology, cooling circuits, transport systems and many applications with aggressive medium.

Advantages

Single-handed operation. Easy handling. Ergonomic sleeve shape. Optimised size. Low connecting forces. Valve body protected by collar design.

Extremely low dead volume remaining.

Interchangeability

RECTUS Design

Working Pressure

PB = 15 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM)
Other sealing materials available on request.

Material

AISI 316 L

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals


- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316
- FKM

Plug

- Plug Profile
- Back Body
- Valve
- Spring
- Seal

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- FKM

Chart





Couplings

RECTUS Series 204KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/8	14	45	19	7					AISI 316 L	204KL AW10 EVX
	G 1/4	17	47	19	9					AISI 316 L	204KL AW13 EVX
<p>Female Thread</p>	G 1/8	14	45	19	9					AISI 316 L	204KL IW10 EVX
	G 1/4	17	47	19	9					AISI 316 L	204KL IW13 EVX

Valved Plugs

RECTUS Series 204KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14	40		7					AISI 316 L	204SL AW10 EVX
	G 1/4	17	42		9					AISI 316 L	204SL AW13 EVX
 <p>Female Thread</p>	G 1/8	14	40		9					AISI 316 L	204SL IW10 EVX
	G 1/4	17	42		9					AISI 316 L	204SL IW13 EVX




Nominal Diameter

5 = 20 mm²

RECTUS Series

21KL




actual size



Technical Description

Mini industrial coupling, internationally the most common profile for this nominal diameter, in double shut-off design. Above average flow performance for liquid and gaseous media. Large band width in materials and valve variants. To be used in small applications like laboratories and chemical processes with aggressive mediums.

Dust Caps (P. 331) 
for coupling Part.-No. SK16S

Advantages

Single handed operation. Small dimensions. Minimum (hardly noticeable) leakage occurs when disconnecting. Air is not trapped in during the connecting process.

Working Pressure

PB = 8 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*


-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM) depending on the medium.

*At a temperature below -15°C and above +200°C special seals are available on request.

You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel Single Shut-off P. 185
- ▶ Stainless Steel Double Shut-off P. 205
- ▶ Thermoplastics P. 242
- ▶ Brass/Steel Dry-Break P. 164
- ▶ Safety P. 276
- ▶ Coded Systems P. 300

Chart



Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals
- Inner Sleeve
- Seal bonnet

AISI 303

- AISI 303
- AISI 303
- AISI 303
- AISI 303
- AISI 301
- AISI 316
- FKM
- AISI 303
- AISI 303

AISI 316 L

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316
- FKM
- AISI 316 L
- AISI 316 L

Plug


- Plug Profile
- Back Body
- Valve
- Spring
- Seal

- AISI 303
- AISI 303
- AISI 303
- AISI 301
- FKM

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- FKM





Couplings

RECTUS Series 21KL




Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	36	16	7					AISI 303	21KL AW10 RVX
									AISI 316 L	21KL AW10 EVX
G 1/4	17	38	16	9					AISI 303	21KL AW13 RVX
									AISI 316 L	21KL AW13 EVX
G 3/8	19	38	16	9					AISI 303	21KL AW17 RVX
									AISI 316 L	21KL AW17 EVX

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Female Thread</p>	G 1/8	14	36	16	9					AISI 303	21KL IW10 RVX	
										AISI 316 L	21KL IW10 EVX	
	G 1/4	17	38	16	9						AISI 303	21KL IW13 RVX
											AISI 316 L	21KL IW13 EVX
 <p>Hose Barb</p>	5 mm	14	46	16	17					AISI 303	21KL TF05 RVX	
	6 mm	14	46	16	17					AISI 316 L	21KL TF08 EVX	
	8 mm	14	46	16	17						AISI 303	21KL TF09 RVX
											AISI 316 L	21KL TF09 EVX
	9 mm	14	46	16	17						AISI 303	21KL TF10 RVX
											AISI 316 L	21KL TF10 EVX
	10 mm	14	46	16	17						AISI 303	21KL TF06 RVX
											AISI 316 L	21KL TF06 EVX
	6 mm Parker	14	50	16	20						AISI 303	21KL TP06 RVX
	 <p>Plastic Hose Connection</p>	4 x 6 mm	14	42	16	7	6			M 10 x 1	AISI 303	21KL KO06 RVX
AISI 316 L											21KL KO06 EVX	
6 x 8 mm	14	42	16	7	6				M 12 x 1	AISI 303	21KL KO08 RVX	
										AISI 316 L	21KL KO08 EVX	
 <p>Panel Mount, Plastic Hose Connection</p>	4 x 6 mm	14	54	16	7	18	14	4	M 10 x 1	AISI 303	21KL KS06 RVX	
										AISI 316 L	21KL KS06 EVX	
	6 x 8 mm	17	54	16	7	18	17	4	M 12 x 1	AISI 303	21KL KS08 RVX	

Couplings

RECTUS Series 21KL




Panel Mount,
Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
8 mm	17	60	16	17	14	17	4	M 12 x 1	AISI 303	21KL TS08 RVX


Valved Plugs

RECTUS Series 21KL




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
5 mm	14	50		17					AISI 303	21SL TF06 RVX
									AISI 316 L	21SL TF06 EVX
6 mm	14	50		17					AISI 303	21SL TF08 RVX
									AISI 316 L	21SL TF08 EVX
9 mm	14	50		17					AISI 303	21SL TF10 RVX
									AISI 316 L	21SL TF10 EVX
10 mm	14	50		17					AISI 303	21SL TF10 RVX
									AISI 316 L	21SL TF06 EVX
6 mm Parker	14	54		20					AISI 303	21SL TP06 RVX





Plastic Hose Connection

4 x 6 mm	14	46		7	6			M 10 x 1	AISI 303	21SL KO06 RVX
									AISI 316 L	21SL KO06 EVX
6 x 8 mm	14	46		7	6			M 12 x 1	AISI 303	21SL KO08 RVX
									AISI 316 L	21SL KO08 EVX



Panel Mount,
Plastic Hose Connection

6 x 8 mm	17	58		7	18	17	4	M 12 x 1	AISI 303	21SL KS08 RVX

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Male Thread</p>	G 1/8	14	40			7				AISI 303	21SL AW10 RVX	
										AISI 316 L	21SL AW10 EVX	
	G 1/4	17	42			9				AISI 303	21SL AW13 RVX	
										AISI 316 L	21SL AW13 EVX	
	G 3/8	19	42			9				AISI 303	21SL AW17 RVX	
										AISI 316 L	21SL AW17 EVX	
 <p>Female Thread</p>	G 1/8	14	40			9				AISI 303	21SL IW10 RVX	
										AISI 316 L	21SL IW10 EVX	



Nominal Diameter

6 = 28 mm²

RECTUS Series

206KL



85 % of actual size



reddot design award winner 2007

You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Dry-Break P. 169

Technical Description

Dry-break coupling systems, which stand out for their extremely low leakage rates and a minimum volume of dead space. No air locks whatsoever during connecting and negligible film of channelled medium on the valve bodies when disconnecting. Coupling systems for applications in sensitive environments, such as in analysis technology, cooling circuits, transport systems and many applications with aggressive medium.

Advantages

Single-handed operation. Easy handling. Ergonomic sleeve shape. Low connecting forces. Valve body protected by collar design.

Extremely low dead volume remaining.

Interchangeability

RECTUS Design

Working Pressure

PB = 15 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM)
Other sealing materials available on request.

Material

AISI 316 L

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals


- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316
- FKM

Plug



- Plug Profile
- Back Body
- Valve
- Spring
- Seal

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- FKM

Chart





Couplings RECTUS Series 206KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 Male Thread	G 3/8	22	68,5	25,5	9					AISI 316 L	206KL AW17 EVX
	G 1/2	24	71,5	25,5	12					AISI 316 L	206KL AW21 EVX
 Female Thread	G 3/8	22	68,5	25,5	9					AISI 316 L	206KL IW17 EVX
	G 1/2	24	71,5	25,5	12					AISI 316 L	206KL IW21 EVX

Valved Plugs

RECTUS Series 206KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 3/8	22	51		9					AISI 316 L	206SL AW17 EVX
	G 1/2	24	54		12					AISI 316 L	206SL AW21 EVX
 <p>Female Thread</p>	G 3/8	22	51		9					AISI 316 L	206SL IW17 EVX
	G 1/2	24	54		12					AISI 316 L	206SL IW21 EVX




Nominal Diameter

7,4 = 42 mm²

RECTUS Series

25KL



actual size

Technical Description
 3/8" - 1/2" brass coupling system. High flow performance. Notable for robust design in critical and aggressive surrounding like laboratories, electronic cooling-system and semi conductor industry.

Advantages
 Single handed operation. Robust design. High flow valve. No damage to the valve body from collar design. Minimum (hardly noticeable) leakage occurs when disconnecting. Air is not trapped in during the connecting process.

Working Pressure
 PB = 8 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*
 -15°C up to +200°C (FKM)
 0°C up to +316°C (FFKM) depending on the medium.


*At a temperature below -15°C and above +200°C special seals are available on request.

Dust Caps (P. 331)
 for coupling Part.-No. SK23S
 for plug Part.-No. SK12S

You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel Single Shut-off P. 192
- ▶ Stainless Steel Double Shut-off P. 209
- ▶ Brass/Steel Dry-Break P. 171
- ▶ Safety P. 278
- ▶ Safety Self-Venting P. 290
- ▶ Coded Systems P. 303

Chart





Material	AISI 303	AISI 316 L
Coupling		
Back Body	AISI 303	AISI 316 L
Valve Body	AISI 303	AISI 316 L
Sleeve	AISI 303	AISI 316 L
Valve	AISI 303	AISI 316 L
Spring and Locking Ring	AISI 301	AISI 316 Ti
Locking Balls	AISI 416	AISI 416
Seals	FKM	FKM
Seal Bonnet	AISI 303	AISI 316 L
Inner Sleeve	AISI 303	AISI 316 L
Plug		
Plug Profile	AISI 303	AISI 316 L
Back Body	AISI 303	AISI 316 L
Valve	AISI 303	AISI 316 L
Spring	AISI 301	AISI 316 Ti
Seal	FKM	FKM

Couplings **RECTUS Series 25KL**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/4	19	59,5	23	10,5					AISI 303	25KL AW13 RVX
										AISI 316 L	25KL AW13 EVX
	G 3/8	19	57,5	23	9					AISI 303	25KL AW17 RVX
										AISI 316 L	25KL AW17 EVX
<p>Female Thread</p>	G 1/2	24	60,5	23	12					AISI 303	25KL AW21 RVX
										AISI 316 L	25KL AW21 EVX
	G 1/4	19	55,5	23	10					AISI 303	25KL IW13 RVX
										AISI 316 L	25KL IW13 EVX
	G 3/8	19	54,5	23	9					AISI 303	25KL IW17 RVX
										AISI 316 L	25KL IW17 EVX
	G 1/2	24	57,5	23	12					AISI 303	25KL IW21 RVX
										AISI 316 L	25KL IW21 EVX



Couplings

RECTUS Series 25KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	9 mm	19	73,5	23	25					AISI 303	25KL TF09 RVX
										AISI 316 L	25KL TF09 EVX
	13 mm	19	73,5	23	25					AISI 303	25KL TF13 RVX
										AISI 316 L	25KL TF13 EVX
 <p>Plastic Hose Connection</p>	8 x 10 mm	19	64,5	23	9	8		M 16 x 1	AISI 303	25KL KO10 RVX	



Valved Plugs

RECTUS Series 25KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm	19	75		25					AISI 303	25SL TF06 RVX
	9 mm	19	72		25					AISI 303	25SL TF09 RVX
										AISI 316 L	25SL TF09 EVX
	13 mm	19	72		25					AISI 303	25SL TF13 RVX
										AISI 316 L	25SL TF13 EVX
 <p>Plastic Hose Connection</p>	8 x 10 mm	19	63		8,5	8,5		M 16 x 1	AISI 303	25SL KO10 RVX	

Valved Plugs

RECTUS Series 25KL

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/4	19	58		10,5					AISI 303	25SL AW13 RVX
										AISI 316 L	25SL AW13 EVX
	G 3/8	19	56		9					AISI 303	25SL AW17 RVX
										AISI 316 L	25SL AW17 EVX
	G 1/2	24	59		12					AISI 303	25SL AW21 RVX
										AISI 316 L	25SL AW21 EVX
 <p>Female Thread</p>	G 1/4	19	54		10					AISI 303	25SL IW13 RVX
										AISI 316 L	25SL IW13 EVX
	G 3/8	19	53		9					AISI 303	25SL IW17 RVX
										AISI 316 L	25SL IW17 EVX
	G 1/2	24	56		12					AISI 303	25SL IW21 RVX
										AISI 316 L	25SL IW21 EVX



Nominal Diameter

8 = 50 mm²

RECTUS Series

99KL



Technical Description

Dry-Break, unmistakable system. During the connection process, the plug and the coupling seals before both valves open. The valves close simultaneously when disconnected, allowing the coupling and plug to be separated afterwards. This ensures minimum leakage. Coded via two lateral grooves on the plug and a similar guide in the coupling, which are arranged in different

angular degrees. Particularly suitable for liquid and aggressive media especially for High Purity Applications.

Advantages

Single handed operation.
8-way coding. All individual parts are electro-burnished.

Working Pressure



PB = 6 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-0°C up to +316°C (FFKM) depending on the medium.

Information about the Plug Protection Cap (Part-No. SK 99EXXS) on request.

Chart



Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals
- Valve Stem Guide
- Threaded Nut

AISI 316 L

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 301
- AISI 316 L
- FFKM
- PTFE
- AISI 316 L

Plug


- Plug Profile
- Valve Stem Guide
- Valve
- Spring
- Seals
- Threaded Nut

- AISI 316 L
- PTFE
- AISI 316 L
- AISI 301
- FFKM
- AISI 316 L

You will find the following alternative versions in our current catalogue on page:


- ▶ Coded Systems P. 308

Couplings RECTUS Series 99KL



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
M 30 x 2/30°	34	97	45	10					AISI 316 L	99KL IM30 EKX30
M 30 x 2/45°	34	97	45	10					AISI 316 L	99KL IM30 EKX45
M 30 x 2/60°	34	97	45	10					AISI 316 L	99KL IM30 EKX60
M 30 x 2/75°	34	97	45	10					AISI 316 L	99KL IM30 EKX75
M 30 x 2/90°	34	97	45	10					AISI 316 L	99KL IM30 EKX90
M 30 x 2/105°	34	97	45	10					AISI 316 L	99KL IM30 EKX105
M 30 x 2/120°	34	97	45	10					AISI 316 L	99KL IM30 EKX120
M 30 x 2/150°	34	97	45	10					AISI 316 L	99KL IM30 EKX150



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
M 30 x 2/30°	34	57		9					AISI 316 L	99SL IM30 EKX30
M 30 x 2/45°	34	57		9					AISI 316 L	99SL IM30 EKX45
M 30 x 2/60°	34	57		9					AISI 316 L	99SL IM30 EKX60
M 30 x 2/75°	34	57		9					AISI 316 L	99SL IM30 EKX75
M 30 x 2/90°	34	57		9					AISI 316 L	99SL IM30 EKX90
M 30 x 2/105°	34	57		9					AISI 316 L	99SL IM30 EKX105
M 30 x 2/120°	34	57		9					AISI 316 L	99SL IM30 EKX120
M 30 x 2/150°	34	57		9					AISI 316 L	99SL IM30 EKX150



Nominal Diameter

9 = 63,5 mm²



RECTUS Series
209KL



70 % of actual size



red dot design award
winner 2007

You will find the following alternative versions in our current catalogue on page:

- Brass/Steel Dry-Break P. 178

Technical Description

Dry-break coupling systems, which stand out for their extremely low leakage rates and a minimum volume of dead space. No air locks whatsoever during connecting and negligible film of channelled medium on the valve bodies when disconnecting. Coupling systems for applications in sensitive environments, such as in analysis technology, cooling circuits, transport systems and many applications with aggressive medium.

Advantages

Single-handed operation. Easy handling. Ergonomic sleeve shape. Low connecting forces. Valve body protected by collar design.

Extremely low dead volume remaining.

Compatibility

RECTUS Design

Working Pressure

PB = 15 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-15°C up to +200°C (FKM)
Other sealing materials available on request.

Material

AISI 316 L

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals


- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- AISI 316
- FKM

Plug

- Plug Profile
- Back Body
- Valve
- Spring
- Seal


- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 Ti
- FKM

Chart




Couplings

RECTUS Series 209KL



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/2	27	92	33	16					AISI 316 L	209KL IW21 EVX
G 3/4	32	94	33	16					AISI 316 L	209KL IW26 EVX



Female Thread


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/2	27	79,5		16					AISI 316 L	209SL IW21 EVX
G 3/4	32	81,5		16					AISI 316 L	209SL IW26 EVX

RectuChem / RectuPom

Resistance to Chemicals

RectuChem

This quick connect coupling system made of polyvinyl fluoride (PVDF) has been designed for increased resistance to chemicals. The stable spring made of high quality stainless steel guarantees a secure connection and permanent functionality.




RectuChem+

This quick connect coupling system completely made of solid plastic is extremely resistant to all organic and mineral media. The resistance of the sealing materials, the PVDF base material and the spring fittings made of PEEK offer virtually unlimited application possibilities. The system is excellently suited for media that must not be contaminated by metal radicals.



RectuPom

The well proven, quick connect coupling system made of thermoplastic polymer is distinguished by unequalled high mechanical strength and outstanding resistance to liquids and high temperatures. The plug is automatically locked in position when pushed in. To disconnect, simply pull back the sleeve.



This chart is intended as a guide only and is not to be considered as a recommendation to use Rectus couplings in a specific application or with specific fluid. For more information please ask the our experts.

Resistance to Chemicals / RectuChem (PVDF)

● = recommended

▲ = restricted usage

■ = not recommended

Chemicals	Temperature					
	20°C	50°C	70°C	100°C	110°C	120°C
Acetaldehyde	■					
Acetanhydride	■	■	■			
Acetic acid (50%)	●	●	●	●	●	
Acetic acid (80%)	●	●	●	●		
Acetic acid (100%)	●	●	▲	■	■	
Acetone	■	■				
Acetone (50% water)	▲	▲	■			
Acetone nitrile	●	●	▲			
Acetophenone	●	▲	■	■		
Acetyl acetone	■			■		
Acetyl chloride	■	■				
Acryl nitrile	●	▲				
Adipic acid, diluted	●	●	●			
Allyl chloride	●	●	●	●		
Aluminium chloride	●	●	●	●	●	●
Aluminium chloride (50%)	●	●	●			
Aluminium fluoride	●	●	●	●	●	●
Aluminium fluoride (50%)	●	●	●			
Aluminium hydroxide	●	●	●	●	●	●
Aluminium nitrate	●	●	●	●	●	●
Aluminium nitrate (50%)	●	●	●			
Aluminium potassium sulphate	●	●	●	●	●	●
Aluminium sulphate	●	●	●			
Ammonia (30%)	●	●	●	●		
Ammonia, enhydrous	●	●	●	●	●	●
Ammonium aluminium sulphate	●	●	●	●	●	●
Ammonium carbonate	●	●	●	●	●	●
Ammonium chloride	●	●	●	●	●	●
Ammonium fluoride	●	●	●	●	●	●
Ammonium hydroxide	●	●	●	●	●	●
Ammonium nitrate	●	●	●	●	●	●
Ammonium phosphate	●	●	●	●	●	●
Ammonium sulphate	●	●	●	●	●	●
Ammonium sulphide	●	●	●	●	●	●
Amyl acetate	●	●	▲	■	■	
Amyl alcohol	●	●	●	●	●	●
Amyl chloride	●	●	●	●	●	●
Amyl chloride (50%)	●	●	●	●	●	●
Aniline	●	▲	▲	■		
Antimonous chloride	●					
Aqua regia	●	●	●			
Arsenic acid	●	●	●	●	●	●
Barium carbonate	●	●	●	●	●	●
Barium chloride	●	●	●	●	●	●
Barium hydroxide	●	●	●	●	●	●
Barium sulphide	●	●	●	●	●	●
Benzaldehyde	▲	▲	■			
Benzene	●	▲	▲			
Benzene-sulphonic acid	●	■				
Benzoic acid	●	●	●	●	●	●
Benzyl methyl ester			■			
Benzyl alcohol	●	●	●	●	●	●
Benzyl chloride	●	▲	▲	■	■	■

Chemicals	Temperature					
	20°C	50°C	70°C	100°C	110°C	120°C
Borax	●	●	●	●	●	●
Boric cold	●	●	●	●	●	●
Bromic acid	●	●	●	●	●	
Bromina, dry	●	●	●			
Butadiene	●	●	●	●		
n-Butanol	●	●	●	●	●	●
sec-Butanol	●	●	●	●	●	●
tert-Butanol	●	●	●	●	●	●
Butene	●	●	●	●	●	●
Butyl acrylate	●	▲	■	■		
Butyl acetate	●	▲	■	■		
n-Butyl amine	■	■				
sec-Butyl amine	■	■				
tert-Butyl amine	●	▲	▲	■		
n-Butyl bromide	●	●	●	●	●	●
n-Butyl chloride	●	●	●	●	●	●
Butyl glycol	●	●	●	●	●	●
n-Butyl mercaptane	●	●	●	●	●	●
Butyl phenol	●	●	●	●		
Butyric acid	●	●	●	●	●	
γ-Butyrol acetone			■			
Calcium carbonate	●	●	●	●	●	●
Calcium chlorate/chloride	●	●	●	●	●	●
Calcium disulphate	●	●	●	●	●	●
Calcium hydrogen sulphite	●	●	●	●	●	●
Calcium hydroxide	●	●	●	●	●	●
Calcium hypochlorite	●	●	●	●	●	●
Calcium nitrate	●	●	●	●	●	●
Calcium sulphate	●	●	●	●	●	●
Capric acid	●	●	●			
Caprylic acid	●	●	●	▲		
Carbon dioxine, wet	●	●	●	●	●	●
Carbon dioxide, anhydros	●	●	●	●	●	●
Carbon disulfide	●					
Carbon tetrachloride	●	●	●	●	●	●
Caustic soda (10%)	●	●	●	●		
Caustic soda (50%)	●	●	●	●		
Chloric acid gas	●	●	●	●		
Chlorine (5% in CCl4)	●	●	●	●		
Chlorine dioxine (15%)	●	●	●			
Chlorine, wet	●	●	●	●		
Chlorine, dry	●	●	●	●		
(Mono-)chloroacetic acid (50%)	●	●	●	●		
(Mono-)chloroacetic acid (100%)	●	●	●	●		
Chlorobenzene	●	●	●	▲		
Chlorodifluoromethane	●	●	●	●		
Chloroform	●	●	●	●		
Chlorosulfonic acid	■	■				
Chromic acid (50%)	●	●	▲			
Chromyl chloride	●	●				
Citric acid	●	●	●	●	●	●
Citric acid (50%)	●	●	●	●	●	●
Coconut oil	●	●	●	●	●	●

Chemicals	Temperature					
	20°C	50°C	70°C	100°C	110°C	120°C
Coke oven gas	●	●	●	●		
Cooper chloride	●	●	●	●	●	●
Cooper cyanide	●	●	●	●	●	●
Cooper fluoride	●	●	●	●	●	●
Cooper nitrate	●	●	●	●	●	●
Cooper sulphate	●	●	●	●	●	●
Corn all	●	●	●	●	●	●
Crotonaldehyde	●	●	▲	■		
Crude oil	●	●	●	●	●	●
Mineral oil	●	●	●	●	●	
Cyclohexane	●	●	●	●	●	●
Cyclohexanol	●	●	●	▲		
Cyclohexanone	●	■	■	■		
Dextrine	●	●	●	●	●	●
Diacetone alcohol	●	▲	■	■		
o-Dichlorobenzene						
Dichlorodifluormethane	●	●	●	●		
Diesel fuel	●	●	●	●	●	●
Diethylamine	●	■	■			
Diethylenetriamine	●	●	▲	■		
Diethyl ether	●	▲				
Diglycolic acid	●					
Diisobutyl ketone	●	●	●	●		
Diisopropyl ether	●	●				
N, N-Dimethyl acetamide			■			
Dimethyl amine	■	■	■	■		
Dimethyl aniline	●	▲	■	■	■	
Dimethyl formamide			■			
Dimethyl phthalate	●	▲	■	■		
1, 4-Dioxane	■	■	■			
Epichlorohydrine	■	■				
Ethyl acetate	●	▲	■	■		
Ethyl acrylate	●	▲	■	■		
Ethyl alcohol	●	●	●	●	●	●
Ethyl chloride	●	●	●	●	●	●
Ethylene bromide (1, 2-Dibromoethane)	●	●	●	●	●	●
Ethylene chloride (1, 2-Dichlorethane)	●	●	●	●	●	●
Ethylene chlorhydrine	●	▲	■	■		
Ethylene diamine	■	■				
Ethylene glycol	●	●	●	●	●	●
Ethylene oxide	●	●				
Fats (triglycerides of long or medium chain fatty acids)	●	●	●	●		
Fatty acids (long chain)	●	●	●	●	●	●
Fatty acids (medium chain)	●	●	●			
Ferrous chloride	●	●	●	●	●	●
Ferric chloride (50%)	●	●	●	●	●	●
Ferrous nitrate	●	●	●	●	●	●
Ferric nitrate	●	●	●	●	●	●
Ferrous sulphate	●	●	●	●	●	●
Ferric sulphate	●	●	●	●	●	●
Ferric sulphate (50%)	●	●	●	●		
Fluorine	●					
Formaldehyde (37%, Formalin, Wz)	●	●				
Formic acid	●	●	●	●	●	●
Furane	■	■				
Furfural	▲	■	■	■		
Fuel oil (EL)	●	●	●	●		
Gallic acid	●	▲				
Gear oil ARAL Energol	●	●				

Chemicals	Temperature					
	20°C	50°C	70°C	100°C	110°C	120°C
Gear oil ARAL Montanol GM 220	●	●	●			
Gear oil BP Energol H-PC 220	●	●	●			
Gear oil Shell Tellusoil 32	●	●	●			
Gear oil Shell Tonna oil T 220	●	●	●			
Glucose	●	●	●	●	●	●
Glycerol	●	●	●	●	●	●
1, 2-Glycol	●	●	●	●	●	●
Glycolic acid (hydroxyacetic acid)	●	▲	■	■		
Heptane	●	●	●	●	●	●
Hexamethyldisilazan (HMDS)	●					
Hexane	●	●	●	●	●	●
Hydrazine UDMH 50/50	●	▲				
Hydriodic acid (48% + 12%J2)	●	●	●	●	●	●
Hydrogen	●	●	●	●	●	●
Hydrogen bromide	●	●	●	●		
Hydrogen cyanide	●	●	●	●	●	●
Hydrogen fluoride (35%)	●	●	●	●	●	●
Hydrogen fluoride (70%)	●	●	●	●		
Hydrogen fluoride (100%)	●	●	●	●		
Hydrogen peroxide (30%)	●	●	●	●	●	●
Hydrogen peroxide (90%)	●					
Hydrogen phosphide	●	●				
Hydrogen sulphide, wet	●	●	●	●	●	●
Hydrogen sulphide, anhydrous	●	●	●	●	●	●
Hypochlorous acid	●	●	●	●	●	●
Iodine, dry	●	●	●			
Iodine, wet	●	●	●			
Iodoform	●	●	●	●		
Isooctane	●	●	●	●	●	●
Jat propulsion fuel IP4 and IP5	●	●	●	●		
Kerosine	●	●	●	●	●	●
Lactic acid	●	▲	■	■		
Lauric acid	●	●	●	●		
Lauryl chloride	●	●	●	●		
Lead acetate	●	●	●	●	●	●
Lead tetraethyl	●	●	●	●	●	●
Linseed oil	●	●	●	●	●	●
Linoleic acid	●	●	●	●	●	●
Magnesium carbonate	●	●	●	●	●	●
Magnesium chloride	●	●	●	●	●	●
Magnesium hydroxide	●	●	●	●	●	●
Magnesium nitrate	●	●	●	●	●	●
Magnesium sulphate	●	●	●	●	●	●
Maleic acid	●	●	●	●	●	●
Mercury	●	●	●	●	●	●
Mercuric chloride	●	●	●	●	●	●
Mercuric cyanide	●	●	●	●	●	●
Mercuric nitrate	●	●	●	●	●	●
Methane	●	●	●	●	●	●
Methane sulfonic acid (50%)	●	●	●	●		
Methyl alcohol	●	●	●	●	●	●
Methyl bromide	●	●	●	●	●	●
Methyl chloride	●	●	●	●	●	●
Methylene chloride	▲	▲				
Methyl ethyl ketone	■	■	■	■		
Methyl isobutyl ketone	●	▲	■	■		
N-Methylpyrrolidone			■			
Milk	●	●	●	●		
Mineral Oil	●	●	●	●	●	●
Monoethanol amina	■	■				

Chemicals	Temperature					
	20°C	50°C	70°C	100°C	110°C	120°C
Morpholine	▲	■	■			
Naphtha	●	●	●	●	●	●
Naphthaline	●	●	●	▲		
Natriumbisulfat	●	●	●	●	●	●
Natural gas	●	●	●	●	●	●
Niacin (nicotinic acid)	●	●	●	●	●	●
Nickel chloride	●	●	●	●	●	●
Nickel nitrate	●	●	●	●	●	●
Nickel sulphate	●	●	●	●	●	●
Nicotine	●	▲	▲			
Nitrating acid	●	●	▲			
Nitric acid (15%/30%)	●	●	●	●		
Nitric acid (65%)	●	●	●			
Nitric acid (fuming)	▲	▲				
Nitrobenzone	●	▲	■			
Nitrogen dioxide	●	●	●	●		
Nitromethane	▲	■				
Nitrous acid	●	●	●	●		
Octane	●	●	●	●	●	●
Octene	●	●	●	●	●	●
Oil (triglyceride)	●	●	●	●		
Oleic acid	●	●	●	●	●	●
Oleum	■					
Oxalic acid	●	●	▲	■		
Oxygen	●	●	●	●	●	●
Ozone	●	●	●	●	●	●
Palmitic o. hexadacyclic acid	●	●	●	●	●	●
Paraldehyde	●	●	●			
Perchlorethylene	●	●	●	●	●	●
Perchloric acid (10%)	●	●	●	●		
Perchloric acid (72%)	●	●				
Petrol (Gasoline) (non-leaded)	●	●	●	●	●	●
Phenol (10%)	●	●	●	●		
Phenol (100%)	●	●	●	▲		
Phenylhydrazine	●	●				
Phosphorous pentoxide	●	●	●	●		
Phosphoric acid (30%)	●	●	●	●	●	●
Phosphoric acid (85%)	●	●	●	●	●	
Phosphorous chloride	●	●	●	●		
Phthalic acid	●	●	●	●		
Picric acid	●					
Potassium bromide/carbonate	●	●	●	●	●	●
Potassium chlorato/chloride	●	●	●	●	●	●
Potassium cyanide/dichromate	●	●	●	●	●	●
Potassium terrocyanide	●	●	●	●	●	●
Potassium hydroxide	●	●	●	●		
Potassium nitrate/permanganate	●	●	●	●	●	●
Potassium sulphate	●	●	●	●	●	●
Potassium sulphide	●	●	●	●	●	●
Propane	●	●	●	●	●	●
Propanol	●	●	▲	■		
Propylene carbonate			■			
Propylene oxida	■					
Pyridine	■	■	■			
Pyrogallic acid	●	●				
Salicylle acid	●	●	●	●		
Sea water	●	●	●	●	●	●
Silicon tetrachloride	●					
Silver cyanide	●	●	●	●	●	●
Silver nitrate	●	●	●	●	●	●

Chemicals	Temperature					
	20°C	50°C	70°C	100°C	110°C	120°C
Sodium acetate	●	●	●	●	●	●
Sodium benzoate	●	●	●	●	●	●
Sodium bicarbonate						
(Sodium nitrogen carbonate)	●	●	●	●	●	●
Sodium bisulphate						
(Sodium hydrogen sulphite)	●	●	●	●	●	●
Sodium bisulphite						
(Sodium hydrogen sulphate)	●	●	●	●	●	●
Sodium bromide	●	●	●	●	●	●
Sodium carbonate	●	●	●	●	●	●
Sodium carbonate (40%)	●	●	●			
Sodium chlorate	●	●	●	●	●	●
Sodium chloride	●	●	●	●	●	●
Sodium cyanide	●	●	●	●	●	●
Sodium hypochloride	●	●	●	●	●	●
Sodium nitrate	●	●	●	●	●	●
Sodium nitrite	●	●	●	●	●	●
Sodium peroxide	●	●	●	●	●	●
Sodium phosphate	●	●	●	●	●	●
Sodium silicate	●	●	●	●	●	●
Sodium sulphate	●	●	●	●	●	●
Sodium sulphide	●	●	●	●	●	●
Sodium sulphite	●	●	●	●	●	●
Sodium thiosulphate	●	●	●	●	●	●
Stearic acid	●	●	●	●	●	●
Sulphur	●	●	●	●	●	●
Sulphur chloride	●					
Sulphur dichloride	●					
Sulphur dioxide	●	●	●	●		
Sulphuric acid (50%)	●	●	●	●	●	
Sulphuric acid (60%)	●	●	●	●		
Sulphuric acid (80%)	●	●	●	●	●	▲
Sulphuric acid (95%)	●	●	▲	■		
Sulphuric acid (fuming/monohydrate)	■	■				
Sulphur trioxide	■	■				
Sulphurous acid	●	●	●	●		
Synthesis gas	●	●	●	●	●	●
Tall oil o. liquid rosin	●	●	●	●	●	●
Tetrachlorethylene	●	●	●	▲		
Tetrahydrofurane	▲	■				
Tetramethyl ammonium hydroxide (50%)	●	●	●	●		
Thionyl chloride	●	▲				
Titanium tetrachloride	●	●				
Toluol (toluene)	●	●	●	▲		
Tributyl phosphate	●	●	●	●		
Trichloroacetic acid	●	▲	■	■		
1.1.1-Trichloroethane	●	●	▲			
Trichloroethylene	●	●	●	●	●	●
Trichlorofluoromethane	●	●	●	●		
Triethyl amine	●	●	▲	■		
Urea (50%)	●	●	●	●	●	●
Vinyl acetate	●	●	●	●	●	●
Water	●	●	●	●	●	●
Xylol (xylene)	●	●	●			
Zin chloride	●	●	●	●	●	●
Zin chloride (50%)	●	●	●	●	●	●
Zin nitrate	●	●	●	●	●	●
Zin nitrate (50%)	●	●	●	●	●	●
Zin sulphate	●	●	●	●	●	●
Zin sulphate (50%)	●	●	●	●	●	●

Resistance to Chemicals / RectuPom

- = recommended
 ▲ = limited usage
 ■ = not recommended

weight increase < 3% or weight loss < 0,5% and/or decrease in tensile strength < 15%
 weight increase 3 - 8% or weight loss 0,5 - 3% and/or decrease in tensile strength 15 - 30%
 weight increase > 8% or weight loss > 3% and/or decrease in tensile strength > 30%

Chemicals	Temperature		Chemicals	Temperature		Chemicals	Temperature	
	20°C	60°C		20°C	60°C		20°C	60°C
Acetic acid (10%)	●	●	Fluorocarbons (partially halogenated)	■	■	Potassium hydroxide (caustic potash solution)	●	●
Acetic acid (80%)	▲	■	Fluorocarbons (perhalogenated)	●	●	Potassium permanganate (10%)*	●	●
Acetone	●	▲	Formaldehyde (40%)	●	●	refrigerant R 134 a (System Reclin)	●	●
Acetylene tetrabromide	▲	■	Formic acid (10%)*	●	■	Sea water (North sea)	●	●
Ammonia	●	●	Fuel oil EL	●	●	Sodium bicarbonate (10%)	●	●
Ammonium sulphate			Galbanum resin	●		Sodium bisulphite liquor (pH 4,5)	■	■
®Hoechst (10%) (pH 5,8)	●	■	®Genantin/tap water 1 : 1 (+1% ®Donax C, Shell)	●		Sodium carbonate (10%)	●	●
Benzene	▲	▲	Glacial acetic acid	▲	■	Sodium chloride	●	●
Benzene with 15 to 20% methanol	●	●	Glycerol	●	●	Sodium hydroxide (caustic soda solution)	●	●
Butanol	●	●	Glycol	●	●	Sodium hypochlorite (bleaching sol. about 12,5% active chlorine)	▲	■
Butyl acetate	●	▲	Glycol/distilled water 48 : 52	●	●	Sodium orthophosphate, monobasic (10%)	●	●
Buthyraldehyde	▲	▲	®Grison GBF 1 (5g to 100g H ₂ O)	●	●	Sodium orthophosphate, di-/tri-basic (10%)	●	●
Butyric acid (1%)*	●	●	Hydrochloric acid (10%)	■	■	Soya bean oil	●	●
Butyric acid (98%)	▲	▲	Hydrogen peroxide (30%)*	●	■	Sulphur dioxide gas	■	■
Calcium ammonium nitrate	●	●	Hydroxycitronellal	●	●	Sulphuric acid (10%)*	●	■
Calcium chloride (10%)	●	●	Ink (®Pelikan ink, blue-black)	●	■	Sulphuric acid (50%)	■	■
Calcium nitrate			Isopropyl alcohol	●	●	Tetrahydrofuran	▲	▲
®Hoechst (10%) (pH 6,4)	●	●	Jet fuel JP 1 + 4 (Shell)	●	●	®Tetralin (Henkel)	●	▲
Cananga oil	●	●	Lactic acid (10%)*	●	▲	Thiophene	▲	▲
Carbon disulphide	●	●	Lactic acid (90%)*	●	■	Toluene	●	●
Carbon tetrachloride	●	▲	Lavender oil, highest-quality	●	●	Transformer oil (®Univolt 36, Esso)	●	●
Chlorobenzene	▲	▲	Lemongrass oil	●	●	Trichloroethylene	▲	▲
Chloroform	■	■	Lime, chlorinated (approx. 10%)	■	■	Urine	●	●
Chromic acid (3%)	▲	▲	Methanol	●	●	Water, distilled	●	●
Citric acid (10%)	●	■	Methyl acetate	▲	▲	Xylene	●	●
®Clophen A 60 (Bayer)	●	●	Methyl bromide	■	■			
Coffee (®Nescafe)	●	●	Methyl ethyl ketone	▲	▲			
®Complezal Typ Blau 12 + 12 + 17 + 2 (10%, pH 5,8)	●	●	Methyl glycol	▲	▲			
®Complezal Typ Gelb 15 + 15 + 15 (10%, pH 5,8)	●	●	Methyl glycol acetate	▲	■			
®Complezal Typ NP 20 + 20 + 0 (10%, pH 5,7)	●	●	Methylene bromide	■	■			
®Complezal Typ Rot 13 + 13 + 21 (10%, pH 5,4)	●	●	Methylene chloride, technical	■	■			
Copper sulphate (10%)	●	●	Mineral oil	●	●			
Developer solution 1:100 (pH 10,4) (®Rodinal Agfa)	●	●	®Mobil oil SAE 20	●	●			
Developer solution 1:50 (pH 10,9) (®Rodinal Agfa)	●	●	Mobil oil HD SAE 20 after 3000 km	●	●			
Dibutyl phthalate	●	●	N-hexane	●	●			
Diesel oil	●	●	Natural gas	●	●			
Dimethyl phthalate	●	▲	Nickel sulphate (10%)	●	●			
Diocetyl sebacate	●	●	Nitric acid (10%)	■	■			
Dioxane	▲	▲	Nitrous gases	■	■			
Engine oil BP HP 20	●	●	Oil of cloves	●	●			
Engine oil SAE 40 (Caltrex)	●	●	Olive oil	●	■			
Ethanol (96%)	●	●	Ozone	■	■			
Ether (DAB 6)	●	●	Peat water (pH 3,7)	●	●			
Ethyl acetat	▲	▲	Perchloroethylene	●	■			
Ethyl chloride (DAB 6)	●	▲	Petrol, standard-grade	●	●			
Ethyl glycol	●	▲	Petrol/benzene mixture (super-grade petrol)	●	●			
Ferric chloride (10%)	▲	■	Petroleum	●	●			
			Petroleum fraction (boiling point 100-140°C)	●	●			
			Phenol	■	■			
			Phosphoric acid (25%)	●	■			

* Because of the acid or oxidizing nature of these chemicals, trials are recommended before prolonged contact with Rectus.



The results were obtained using injection-moulded, 1 mm thick test samples after a test duration of 60 days. During the test, the test samples were not under the influence of any external tension.

Media Chart O-Rings


- = little or no effect
- ▲ = weak to moderate effect
- = strong attack to complete destruction
- ◆ = no data available; probably suitable; test before use
- ✘ = no data available; probably not suitable

Media	Seals		
	NBR	FKM	EPDM
Acetone	■	■	●
Acetylene	●	●	●
Aero-engine oils JP 3/4/5/6	●	●	■
Ammonia, 100%	▲	■	●
Ammonium sulphate	●	●	●
Amyl acetate	■	■	●
Aniline	■	■	◆
Arsenic acid, aq.	●	●	●
Beer	●	●	●
Benzonic acid, aq.	●	●	●
Benzyl alcohol	◆	◆	✘
Black lye	▲	●	●
Borax, aq.	●	●	●
Boric acid, aq.	●	●	●
Brake fluids (glycol ether)	■	◆	●
Butadiene	●	●	■
Butane, gaseous	●	●	■
Butanol, aq.	●	▲	●
Butyl acetate	■	■	▲
Butyl alcohol	■	◆	●
Butyne diol	●	▲	●
Butyraldehyde	◆	◆	▲
Calcium nitrate, aq.	●	●	●
Calcium phosphate, aq.	●	●	●
Camphorated oil	●	▲	■
Carbon dioxide	●	●	●
Carbon dioxide, dry	●	●	●
Carbon disulphide	■	●	■
Carbon tetrachloride	■	●	■
Chloramine, aq.	●	◆	●
Chloride of lime, aq.	■	●	●
Chlorine	■	●	●
Chlorine water, saturated	■	●	●
Chromic acid, aq.	■	●	✘
Citric acid, aq.	●	●	●
Coconut fat	●	●	■
Coconut oil	●	●	■
Coking-oven gas	■	●	■
Crude oil	●	●	■
Cyclohexane	●	●	■
Cyclohexanol	●	◆	■
Desmophen 2000	●	✘	✘
Detergent, synthetic	●	●	●
Detergents	●	▲	●
Dextrin, aq.	●	●	●
Dichloroacetic acid	■	■	●
Diesel fuel	●	●	■
Diglycolic acid, aq.	▲	●	●
Dimethyl ether	■	■	●
Dimethylamine	■	■	●
Engine oils	●	●	■
Ethane	●	●	■
Ethyl acrylate	■	■	✘

	NBR	FKM	EPDM
Ethyl benzene	■	▲	■
Ethyl chloride	▲	▲	▲
Ethylene chloride	▲	▲	▲
Ethylene diamine	■	■	●
Ethylene glycol	●	●	●
Fatty acids	▲	●	◆
Fluorosilicic acid, aq.	●	●	●
Fish oil	●	●	▲
Formaldehyde, aq.	▲	◆	●
Formamide	■	▲	●
Gas oil	●	●	■
Glucose, aq.	●	●	●
Glycerol, aq.	●	●	●
Glycol, aq.	●	●	●
Glycolic acid, aq. 37%	●	●	●
Heptane	●	●	■
Hexachlorobutadiene	■	●	◆
Hexane	●	●	■
Hydrochloric acid	▲	●	●
Hydrogen	●	●	●
Hydrogen chloride gas	■	●	●
Hydrogen sulphide, dry aqueous	▲	●	●
Hydrosulphite, aq.	▲	◆	●
Isooctane	●	●	■
Isopropyl alcohol	▲	▲	●
Lactic acid, aq.	●	●	●
Lavender oil	▲	●	◆
Lead acetat, aq.	●	●	●
Lithium bromide, aq.	●	●	●
Machine oil, mineral	●	●	■
Magnesium sulphate, aq.	●	●	●
Mercury salts, aq.	●	●	●
Methane	●	●	▲
Methyl alcohol	▲	■	●
Mineral oil	●	●	■
Mustard gas	●	◆	●
Nitrogen tetroxide	◆	◆	■
Nitrogen	●	●	●
Nitroglycol, aq.	■	●	●
Octane	✘	●	◆
Oleic acid	●	●	■
Paraffin/Paraffin oil	●	●	■
Petrol	●	●	■
Petroleum	●	●	■
Propylene glycol	●	●	●
Sea water	●	●	●
Silicone grease/Silicone oil	●	●	●
Soda, aq.	●	●	●
Sodium chlorate	■	●	●
Sodium chloride	●	●	●
Sodium nitrate, aq.	●	●	●
Sodium phosphate, aq.	●	●	●
Steam	▲	●	●
Styrene	■	▲	■
Sulphur	◆	●	●
Sulphur trioxide	◆	●	▲
Sulphuric acid	▲	●	●
Sulphuryl chloride	■	●	▲
Tartaric acid, aq.	●	●	●
Titanium tetrachloride	●	▲	●
Town gas, benzene-free	●	●	■



Nominal Diameter

5 = 20 mm²

RECTUS Series

21KB



actual size



Technical Description

Mini industrial coupling made of POM and PVDF with the world's most commonly used profile. Above average flow performance for liquid and gaseous media. A new type of locking system made of thermoplastic with a non-slip sleeve considerably expands the application possibilities of this small quick connect coupling.

Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel Single shut-off P. 185
- ▶ Stainless Steel Double shut-off P. 205
- ▶ Brass/Steel P. 34
- ▶ Safety P. 266
- ▶ Coded Systems P. 300

Advantages

Single handed operation. Two different sleeve designs. The coupling is fitted with a double shut-off valve which enables it to be connected to a single shut-off (non-valved) plug as well as a double shut-off (valved) plug. The coupling is also available as a straight-through coupling (without a valve). The 21 series eliminates the danger of mix-ups by color coding of the coupling and the respective plug. This system guarantees the elimination of mix-ups when media are connected.

Working Pressure

PB = 10 bar (POM, 20°C)
PB = 8 bar (PVDF, 20°C)
maximum static working pressure with safety factor of 4 to 1.

Working Temperature

-20°C up to +80°C (POM)
-20°C up to +120 (PVDF)
depending on the medium.

Material

Coupling

Valve Body
Sleeve
Valve
Spring
Locking System
Seals
Back Body

RectuPom Standard

POM, black
POM, black
POM, black
AISI 301
POM, black
NBR
POM, black

RectuChem Standard

PVDF, white
PVDF, white
PVDF, white
AISI 316 Ti
PVDF, white
FKM
PVDF, white

Plug

Plug Profile
Valve
Spring
Adapter
Seal









POM, black
POM, black
AISI 301
POM, black
NBR

PVDF, white
PVDF, white
1.4571
PVDF, white
FKM









Couplings









RECTUS Series 21KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color Sleeve	Rectu POM Part Number	Rectu CHEM Part Number
Ergonomical Sleeve	G 1/8 o.	17	50	25,5	7					Standard	21KB AW10 DPX	21KB AW10 FXV
Male Thread												
Straight Sleeve	G 1/8 o.	17	50	21	7					Standard	21KB AW10 DPXG	21KB AW10 FXVG
										blue	21KB AW10 DPXGB	21KB AW10 FXVGB
Male Thread										green	21KB AW10 DPXGG	21KB AW10 FXVGG
										red	21KB AW10 DPXGR	21KB AW10 FXVGR
										yellow	21KB AW10 DPXGY	21KB AW10 FXVGY

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color Sleeve	Rectu POM Part Number	Rectu CHEM Part Number
Ergonomical Sleeve	G 1/4 o.	17	50	25,5	7					Standard	21KB AW13 DPX	21KB AW13 FVX
												
Male Thread												
Straight Sleeve	G 1/4 o.	17	50	21	7					Standard	21KB AW13 DPXG	21KB AW13 FVXG
										blue	21KB AW13 DPXGB	21KB AW13 FVXGB
Male Thread										green	21KB AW13 DPXGG	21KB AW13 FVXGG
										red	21KB AW13 DPXGR	21KB AW13 FVXGR
										yellow	21KB AW13 DPXGY	21KB AW13 FVXGY
Ergonomical Sleeve	G 1/8 i.	17	53	25,5	8					Standard	21KB IW10 DPX	21KB IW10 FVX
												
Female Thread												
Straight Sleeve	G 1/8 i.	17	53	21	8					Standard	21KB IW10 DPXG	21KB IW10 FVXG
										blue	21KB IW10 DPXGB	21KB IW10 FVXGB
Female Thread										green	21KB IW10 DPXGG	21KB IW10 FVXGG
										red	21KB IW10 DPXGR	21KB IW10 FVXGR
										yellow	21KB IW10 DPXGY	21KB IW10 FVXGY
Ergonomical Sleeve	G 1/4 i.	17	39	25,5	9					Standard	21KB IW13 DPX	21KB IW13 FVX
												
Female Thread												
Straight Sleeve	G 1/4 i.	17	39	21	9					Standard	21KB IW13 DPXG	21KB IW13 FVXG
										blue	21KB IW13 DPXGB	21KB IW13 FVXGB
Female Thread										green	21KB IW13 DPXGG	21KB IW13 FVXGG
										red	21KB IW13 DPXGR	21KB IW13 FVXGR
										yellow	21KB IW13 DPXGY	21KB IW13 FVXGY
for Front Panel Installation	4 x 6 mm	17	56	28	7	20,5	27	7	M 25 x 1	Standard	21KB KE06 DPX	21KB KE06 FVX
	6 x 8 mm	17	56	28	7	20,5	27	7	M 25 x 1	Standard	21KB KE08 DPX	21KB KE08 FVX
Panel Mount, Plastic Hose Connection												
for Front Panel Installation	4 x 6 mm	17	62	28	7	20,5	27	7	M 25 x 1	Standard		21KB FR06 FVX
	6 x 8 mm	17	66	28	7	20,5	27	7	M 25 x 1	Standard		21KB FR08 FVX
for PVDF- and PE-Hoses												



Couplings RECTUS Series 21KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color Sleeve	Rectu POM Part Number	Rectu CHEM Part Number
Ergonomical Sleeve	4 x 6 mm	17	62	25,5	17				M 10 x 1	Standard		21KB KP06 FVX
	6 x 8 mm	17	66	25,5	17				M 12 x 1	Standard		21KB KP08 FVX
												
for PVDF- and PE-Hoses												
Ergonomical Sleeve	4 x 6 mm	17	56	25,5	6	7			M 10 x 1	Standard	21KB KO06 DPX	21KB KO06 FVX
												
Plastic Hose Connection												
Straight Sleeve	4 x 6 mm	17	56	21	6	7			M 10 x 1	Standard	21KB KO06 DPXG	21KB KO06 FVXG
												
Plastic Hose Connection											21KB KO06 DPXGB	21KB KO06 FVXGB
											21KB KO06 DPXGG	21KB KO06 FVXGG
											21KB KO06 DPXGR	21KB KO06 FVXGR
											21KB KO06 DPXGY	21KB KO06 FVXGY
Ergonomical Sleeve	6 x 8 mm	17	56	21/25,5	6	7			M 12 x 1	Standard	21KB KO08 DPX	21KB KO08 FVX
												
Plastic Hose Connection												
Straight Sleeve	6 x 8 mm	17	56	21	6	7			M 12 x 1	Standard	21KB KO08 DPXG	21KB KO08 FVXG
												
Plastic Hose Connection										blue	21KB KO08 DPXGB	21KB KO08 FVXGB
										green	21KB KO08 DPXGG	21KB KO08 FVXGG
										red	21KB KO08 DPXGR	21KB KO08 FVXGR
										yellow	21KB KO08 DPXGY	21KB KO08 FVXGY
Ergonomical Sleeve	4 x 6 mm	17	68	25,5	7	18	14	4	M 10 x 1	Standard	21KB KS06 DPX	21KB KS06 FVX
												
Panel Mount, Plastic Hose Connection												
Straight Sleeve	4 x 6 mm	17	68	21	7	18	14	4	M 10 x 1	Standard	21KB KS06 DPXG	21KB KS06 FVXG
												
Panel Mount, Plastic Hose Connection										blue	21KB KS06 DPXGB	21KB KS06 FVXGB
										green	21KB KS06 DPXGG	21KB KS06 FVXGG
										red	21KB KS06 DPXGR	21KB KS06 FVXGR
										yellow	21KB KS06 DPXGY	21KB KS06 FVXGY
Ergonomical Sleeve	6 x 8 mm	17	68	25,5	7	18	17	4	M 12 x 1	Standard	21KB KS08 DPX	21KB KS08 FVX
												
Panel Mount, Plastic Hose Connection												

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color Sleeve	Rectu POM Part Number	Rectu CHEM Part Number
 Panel Mount, Plastic Hose Connection for Front Panel Installation	6 x 8 mm	17	68	21	7	18	17	4	M 12 x 1	Standard	21KB KS08 DPXG	21KB KS08 FVXG
										blue	21KB KS08 DPXGB	21KB KS08 FVXGB
										green	21KB KS08 DPXGG	21KB KS08 FVXGG
										red	21KB KS08 DPXGR	21KB KS08 FVXGR
										yellow	21KB KS08 DPXGY	21KB KS08 FVXGY
 Hose Barb	4 mm	17	60	28	17	20,5	27	7	M 25 x 1	Standard	21KB TE04 DPX	21KB TE04 FVX
	6 mm	17	60	28	17	20,5	27	7	M 25 x 1	Standard	21KB TE06 DPX	21KB TE06 FVX
 Hose Barb	4 mm	17	60	25,5	17					Standard	21KB TF04 DPX	21KB TF04 FVX
 Hose Barb	4 mm	17	60	21	17					Standard	21KB TF04 DPXG	21KB TF04 FVXG
										blue	21KB TF04 DPXGB	21KB TF04 FVXGB
										green	21KB TF04 DPXGG	21KB TF04 FVXGG
										red	21KB TF04 DPXGR	21KB TF04 FVXGR
										yellow	21KB TF04 DPXGY	21KB TF04 FVXGY
 Hose Barb	6 mm	17	60	25,5	17					Standard	21KB TF06 DPX	21KB TF06 FVX
 Hose Barb	6 mm	17	60	21	17					Standard	21KB TF06 DPXG	21KB TF06 FVXG
										blue	21KB TF06 DPXGB	21KB TF06 FVXGB
										green	21KB TF06 DPXGG	21KB TF06 FVXGG
										red	21KB TF06 DPXGR	21KB TF06 FVXGR
										yellow	21KB TF06 DPXGY	21KB TF06 FVXGY
 Hose Barb, Panel Mount	4 mm	17	74	25,5	17	14	14	4	M 10 x 1	Standard	21KB TS04 DPX	21KB TS04 FVX
 Hose Barb, Panel Mount	4 mm	17	74	21	17	14	14	4	M 10 x 1	Standard	21KB TS04 DPXG	21KB TS04 FVXG
										blue	21KB TS04 DPXGB	21KB TS04 FVXGB
										green	21KB TS04 DPXGG	21KB TS04 FVXGG
										red	21KB TS04 DPXGR	21KB TS04 FVXGR
										yellow	21KB TS04 DPXGY	21KB TS04 FVXGY





Couplings





RECTUS Series 21KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color Sleeve	Rectu POM Part Number	Rectu CHEM Part Number
Ergonomical Sleeve	6 mm	17	74	25,5	17	14	14	4	M 10 x 1	Standard	21KB TS06 DPX	21KB TS06 FVX
												
Hose Barb, Panel Mount												
Straight Sleeve	6 mm	17	74	21	17	14	17	4	M 12 x 1	Standard	21KB TS06 DPXG	21KB TS06 FVXG
										blue	21KB TS06 DPXGB	21KB TS06 FVXGB
										green	21KB TS06 DPXGG	21KB TS06 FVXGG
										red	21KB TS06 DPXGR	21KB TS06 FVXGR
										yellow	21KB TS06 DPXGY	21KB TS06 FVXGY
Hose Barb, Panel Mount												

Valved Plugs

RECTUS Series 21SB


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color	Rectu POM Part Number	Rectu CHEM Part Number
 Male Thread	G 1/8 o.	17	36		7					Standard	21SB AW10 DPX	21SB AW10 FVX
										blue	21SB AW10 DPXB	21SB AW10 FVXB
										green	21SB AW10 DPXG	21SB AW10 FVXG
										red	21SB AW10 DPXR	21SB AW10 FVXR
										yellow	21SB AW10 DPXY	21SB AW10 FVXY
 Female Thread	G 1/4 o.	17	38		7					Standard	21SB AW13 DPX	21SB AW13 FVX
										blue	21SB AW13 DPXB	21SB AW13 FVXB
										green	21SB AW13 DPXG	21SB AW13 FVXG
										red	21SB AW13 DPXR	21SB AW13 FVXR
										yellow	21SB AW13 DPXY	21SB AW13 FVXY
 Female Thread	G 1/8 i.	17	39		8					Standard	21SB IW10 DPX	21SB IW10 FVX
										blue	21SB IW10 DPXB	21SB IW10 FVXB
										green	21SB IW10 DPXG	21SB IW10 FVXG
										red	21SB IW10 DPXR	21SB IW10 FVXR
										yellow	21SB IW10 DPXY	21SB IW10 FVXY
 Female Thread	G 1/4 i.	17	42		10					Standard	21SB IW13 DPX	21SB IW13 FVX
										blue	21SB IW13 DPXB	21SB IW13 FVXB
										green	21SB IW13 DPXG	21SB IW13 FVXG
										red	21SB IW13 DPXR	21SB IW13 FVXR
										yellow	21SB IW13 DPXY	21SB IW13 FVXY

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color	Rectu POM Part Number	Rectu CHEM Part Number	
 <p>Plastic Hose Connection</p>	4 x 6 mm	17	42	7	6					Standard	21SB KO06 DPX	21SB KO06 FVX	
										blue	21SB KO06 DPXB	21SB KO06 FVXB	
										green	21SB KO06 DPXG	21SB KO06 FVXG	
										red	21SB KO06 DPXR	21SB KO06 FVXR	
										yellow	21SB KO06 DPXY	21SB KO06 FVXY	
	6 x 8 mm	17	42	7	6						Standard	21SB KO08 DPX	21SB KO08 FVX
											blue	21SB KO08 DPXB	21SB KO08 FVXB
											green	21SB KO08 DPXG	21SB KO08 FVXG
											red	21SB KO08 DPXR	21SB KO08 FVXR
											yellow	21SB KO08 DPXY	21SB KO08 FVXY
 <p>Panel Mount, Plastic Hose Connection</p>	4 x 6 mm	17	54	7	18	14	4	M 10 x 1		Standard	21SB KS06 DPX	21SB KS06 FVX	
										blue	21SB KS06 DPXB	21SB KS06 FVXB	
										green	21SB KS06 DPXG	21SB KS06 FVXG	
										red	21SB KS06 DPXR	21SB KS06 FVXR	
										yellow	21SB KS06 DPXY	21SB KS06 FVXY	
	6 x 8 mm	17	54	7	18	17	4	M 12 x 1			Standard	21SB KS08 DPX	21SB KS08 FVX
											blue	21SB KS08 DPXB	21SB KS08 FVXB
											green	21SB KS08 DPXG	21SB KS08 FVXG
											red	21SB KS08 DPXR	21SB KS08 FVXR
											yellow	21SB KS08 DPXY	21SB KS08 FVXY
 <p>Panel Mount, for PVDF- and PE-Hoses</p>	4 x 6 mm	17	48	28						Standard		21SB KP06 FVX	
										blue		21SB KP06 FVXB	
										green		21SB KP06 FVXG	
										red		21SB KP06 FVXR	
										yellow		21SB KP06 FVXY	
	6 x 8 mm	17	52	28							Standard		21SB KP08 FVX
											blue		21SB KP08 FVXB
											green		21SB KP08 FVXG
											red		21SB KP08 FVXR
											yellow		21SB KP08 FVXY
 <p>Hose Barb</p>	4 mm	17	46	17						Standard	21SB TF04 DPX	21SB TF04 FVX	
										blue	21SB TF04 DPXB	21SB TF04 FVXB	
										green	21SB TF04 DPXG	21SB TF04 FVXG	
										red	21SB TF04 DPXR	21SB TF04 FVXR	
										yellow	21SB TF04 DPXY	21SB TF04 FVXY	
	6 mm	17	46	17							Standard	21SB TF06 DPX	21SB TF06 FVX
											blue	21SB TF06 DPXB	21SB TF06 FVXB
											green	21SB TF06 DPXG	21SB TF06 FVXG
											red	21SB TF06 DPXR	21SB TF06 FVXR
											yellow	21SB TF06 DPXY	21SB TF06 FVXY

Valved Plugs

RECTUS Series 21SB

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color	Rectu POM Part Number	Rectu CHEM Part Number
4 mm	17	60		7	14	14	4	M 10 x 1	Standard	21SB TS04 DPX	21SB TS04 FVX
									blue	21SB TS04 DPXB	21SB TS04 FVXB
									green	21SB TS04 DPXG	21SB TS04 FVXG
									red	21SB TS04 DPXR	21SB TS04 FVXR
									yellow	21SB TS04 DPXY	21SB TS04 FVXY
6 mm	17	60		7	14	17	4	M 12 x 1	Standard	21SB TS06 DPX	21SB TS06 FVX
									blue	21SB TS06 DPXB	21SB TS06 FVXB
									green	21SB TS06 DPXG	21SB TS06 FVXG
									red	21SB TS06 DPXR	21SB TS06 FVXR
									yellow	21SB TS06 DPXY	21SB TS06 FVXY




Panel Mount, Hose Barb


Plugs

RECTUS Series 21SF





Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color	Rectu POM Part Number	Rectu CHEM Part Number
G 1/8 o.	14	25		7					Standard	21SF AW10 DXX	21SF AW10 FXX
									blue	21SF AW10 DPXB	21SF AW10 FVXB
									green	21SF AW10 DPXG	21SF AW10 FVXG
									red	21SF AW10 DPXR	21SF AW10 FVXR
									yellow	21SF AW10 DPXY	21SF AW10 FVXY
G 1/4 o.	17	28		9					Standard	21SF AW13 DXX	21SF AW13 FXX
									blue	21SF AW13 DPXB	21SF AW13 FVXB
									green	21SF AW13 DPXG	21SF AW13 FVXG
									red	21SF AW13 DPXR	21SF AW13 FVXR
									yellow	21SF AW13 DPXY	21SF AW13 FVXY
G 1/8 i.	14	24		8					Standard	21SF IW10 DXX	21SF IW10 FXX
									blue	21SF IW10 DPXB	21SF IW10 FVXB
									green	21SF IW10 DPXG	21SF IW10 FVXG
									red	21SF IW10 DPXR	21SF IW10 FVXR
									yellow	21SF IW10 DPXY	21SF IW10 FVXY
G 1/4 i.	17	25		9					Standard	21SF IW13 DXX	21SF IW13 FXX
									blue	21SF IW13 DPXB	21SF IW13 FXXB
									green	21SF IW13 DPXG	21SF IW13 FXXG
									red	21SF IW13 DPXR	21SF IW13 FXXR
									yellow	21SF IW13 DPXY	21SF IW13 FXXY




Male Thread





Female Thread

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color	Rectu POM Part Number	Rectu CHEM Part Number	
 <p>Plastic Hose Connection</p>	4 x 6 mm	14	32	7	6				M 10 x 1	Standard	21SF KO06 DX	21SF KO06 FX	
										blue	21SF KO06 DPXB	21SF KO06 FVXB	
										green	21SF KO06 DPXG	21SF KO06 FVXG	
										red	21SF KO06 DPXR	21SF KO06 FVXR	
										yellow	21SF KO06 DPXY	21SF KO06 FVXY	
	6 x 8 mm	14	32	7	6					M 12 x 1	Standard	21SF KO08 DX	21SF KO08 FX
											blue	21SF KO08 DPXB	21SF KO08 FVXB
											green	21SF KO08 DPXG	21SF KO08 FVXG
											red	21SF KO08 DPXR	21SF KO08 FVXR
											yellow	21SF KO08 DPXY	21SF KO08 FVXY
 <p>Panel Mount, for Plastic Hose Connection</p>	4 x 6 mm	14	44	7	18	14	4		M 10 x 1	Standard	21SF KS06 DX	21SF KS06 FX	
										blue	21SF KS06 DPXB	21SF KS06 FVXB	
										green	21SF KS06 DPXG	21SF KS06 FVXG	
										red	21SF KS06 DPXR	21SF KS06 FVXR	
										yellow	21SF KS06 DPXY	21SF KS06 FVXY	
	6 x 8 mm	14	44	7	18	14	4			M 12 x 1	Standard	21SF KS08 DX	21SF KS08 FX
											blue	21SF KS08 DPXB	21SF KS08 FVXB
											green	21SF KS08 DPXG	21SF KS08 FVXG
											red	21SF KS08 DPXR	21SF KS08 FVXR
											yellow	21SF KS08 DPXY	21SF KS08 FVXY
 <p>Panel Mount for PVDF- and PE-Hoses</p>	4 x 6 mm	17	48	28						Standard		21SF KP06 FV	
										blue		21SF KP06 FVXB	
										green		21SF KP06 FVXG	
										red		21SF KP06 FVXR	
										yellow		21SF KP06 FVXY	
	6 x 8 mm	17	52	28							Standard		21SF KP08 FV
											blue		21SF KP08 FVXB
											green		21SF KP08 FVXG
											red		21SF KP08 FVXR
											yellow		21SF KP08 FVXY
 <p>Hose Barb</p>	4 mm		32	17						Standard	21SF TF04 DX	21SF TF04 FX	
										blue	21SF TF04 DPXB	21SF TF04 FVXB	
										green	21SF TF04 DPXG	21SF TF04 FVXG	
										red	21SF TF04 DPXR	21SF TF04 FVXR	
										yellow	21SF TF04 DPXY	21SF TF04 FVXY	
	6 mm		32	17							Standard	21SF TF06 DX	21SF TF06 FX
											blue	21SF TF06 DPXB	21SF TF06 FVXB
											green	21SF TF06 DPXG	21SF TF06 FVXG
											red	21SF TF06 DPXR	21SF TF06 FVXR
											yellow	21SF TF06 DPXY	21SF TF06 FVXY

Plugs **RECTUS Series 21SF**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color	Rectu POM Part Number	Rectu CHEM Part Number
 <p>Panel Mount Hose Barb</p>	4 mm	14	50		17	14	14	4	M 10 x 1	Standard	21SF TS04 DXX	21SF TS04 FXX
										blue	21SF TS04 DPXB	21SF TS04 FVXB
										green	21SF TS04 DPXG	21SF TS04 FVXG
										red	21SF TS04 DPXR	21SF TS04 FVXR
										yellow	21SF TS04 DPXY	21SF TS04 FVXY
	6 mm	14	50		17	14	17	4	M 12 x 1	Standard	21SF TS06 DXX	21SF TS06 FXX
										blue	21SF TS06 DPXB	21SF TS06 FVXB
										green	21SF TS06 DPXG	21SF TS06 FVXG
										red	21SF TS06 DPXR	21SF TS06 FVXR
										yellow	21SF TS06 DPXY	21SF TS06 FVXY



Technical Description

The 48 series coupling system made of POM and PVDF has been developed for use in the medical, chemical, food handling, pharmaceutical and laboratory technology industries. The coupling is also available in a completely thermoplastic version (RectuChem+). Here the metal springs are replaced by springs made of PEEK, an extremely resistant synthetic material.

Advantages

Single handed operation.
No mix up due to our color coded sleeves and plugs.
The coupling is fitted with a double shut-off valve which enables it to be connected to a single shut-off (non-valved) plug as well as a double shut-off (i.e. plug with valve). The coupling is also available as a straight through coupling.



Working Pressure

PB = 0 - 10 bar (POM, at 20°C)
PB = 0 - 8 bar (PVDF, springs made of steel)
PB = 1 - 8 bar (PVDF, springs made of PEEK),
maximum static working pressure with safety factor of 4 to 1.

Working Temperature

-20°C up to +80°C (POM)
-20°C up to +120 (PVDF)
depending on the medium.

Chart



Material

Coupling

	RectuPom	RectuChem	RectuChem+
Valve Body	POM, black	PVDF, white	PVDF, white
Sleeve	POM, black	PVDF, white	PVDF, white
Valve	POM, black	PVDF, white	PVDF, white
Springs	AISI 316 Ti	AISI 316 Ti	PEEK 450G
Locking System	POM, black	PVDF, white	PEEK 450G
Seals	NBR	FKM	FKM
Back Body	POM, black	PVDF, white	PVDF, white

Plug

	RectuPom	RectuChem	RectuChem+
Plug Profile	POM, black	PVDF, white	PVDF, white
Valve	POM, black	PVDF, white	PVDF, white
Spring	AISI 316 Ti	AISI 316 Ti	PEEK 450G
Adapter	POM, black	PVDF, white	PVDF, white
Seal	NBR	FKM	FKM


75% of actual size



Couplings

RECTUS Series 48KB





Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color Sleeve	Rectu POM Part Number	Rectu CHEM Part Number	Rectu CHEM+ Part Number
G 1/4 o.	21	70,5	26	9					Standard	48KB AW13 DPX	48KB AW13 FVX	48KB AW13 FVP
									blue	48KB AW13 DPXB	48KB AW13 FVXB	48KB AW13 FVPB
									green	48KB AW13 DPXG	48KB AW13 FVXG	48KB AW13 FVPG
									red	48KB AW13 DPXR	48KB AW13 FVXR	48KB AW13 FVPR
									yellow	48KB AW13 DPXY	48KB AW13 FVXY	48KB AW13 FVPY
G 3/8 o.	21	67	26	9					Standard	48KB AW17 DPX	48KB AW17 FVX	48KB AW17 FVP
									blue	48KB AW17 DPXB	48KB AW17 FVXB	48KB AW17 FVPB
									green	48KB AW17 DPXG	48KB AW17 FVXG	48KB AW17 FVPG
									red	48KB AW17 DPXR	48KB AW17 FVXR	48KB AW17 FVPR
									yellow	48KB AW17 DPXY	48KB AW17 FVXY	48KB AW17 FVPY






Male Thread

Couplings

RECTUS Series 48KB


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color Sleeve	Rectu POM Part Number	Rectu CHEM Part Number	Rectu CHEM+ Part Number	
 <p>Male Thread</p>	G 1/2 o.	21	73,5	26	12					Standard	48KB AW21 DPX	48KB AW21 FVX	48KB AW21 FVP	
										blue	48KB AW21 DPXB	48KB AW21 FVXB	48KB AW21 FVPB	
										green	48KB AW21 DPXG	48KB AW21 FVXG	48KB AW21 FVPG	
										red	48KB AW21 DPXR	48KB AW21 FVXR	48KB AW21 FVPR	
										yellow	48KB AW21 DPXY	48KB AW21 FVXY	48KB AW21 FVPY	
 <p>Female Thread</p>	G 1/4 i.	21	63,5	26	10					Standard	48KB IW13 DPX	48KB IW13 FVX	48KB IW13 FVP	
										blue	48KB IW13 DPXB	48KB IW13 FVXB	48KB IW13 FVPB	
										green	48KB IW13 DPXG	48KB IW13 FVXG	48KB IW13 FVPG	
										red	48KB IW13 DPXR	48KB IW13 FVXR	48KB IW13 FVPR	
	G 3/8 i.	21	63,5	26	13						Standard	48KB IW17 DPX	48KB IW17 FVX	48KB IW17 FVP
											blue	48KB IW17 DPXB	48KB IW17 FVXB	48KB IW17 FVPB
											green	48KB IW17 DPXG	48KB IW17 FVXG	48KB IW17 FVPG
											red	48KB IW17 DPXR	48KB IW17 FVXR	48KB IW17 FVPR
	G 1/2 i.	21	74,5	26	13						Standard	48KB IW21 DPX	48KB IW21 FVX	48KB IW21 FVP
											blue	48KB IW21 DPXB	48KB IW21 FVXB	48KB IW21 FVPB
											green	48KB IW21 DPXG	48KB IW21 FVXG	48KB IW21 FVPG
											red	48KB IW21 DPXR	48KB IW21 FVXR	48KB IW21 FVPR
 <p>for PVDF- and PE-Hoses</p>	6 x 8 mm	21	80	26	21					Standard		48KB KP08 FVX	48KB KP08 FVP	
	9 x 12 mm	21	87	26	28					Standard		48KB KP12 FVX	48KB KP12 FVP	
	10 x 12 mm	21	87	26	28					Standard		48KB KP12 FVXS	48KB KP12 FVPS	
 <p>Hose Barb</p>	6 mm	21	81	26	22					Standard	48KB TF06 DPX	48KB TF06 FVX	48KB TF06 FVP	
										blue	48KB TF06 DPXB	48KB TF06 FVXB	48KB TF06 FVPB	
										green	48KB TF06 DPXG	48KB TF06 FVXG	48KB TF06 FVPG	
										red	48KB TF06 DPXR	48KB TF06 FVXR	48KB TF06 FVPR	
	9 mm	21	81	26	22						Standard	48KB TF09 DPX	48KB TF09 FVX	48KB TF09 FVP
											blue	48KB TF09 DPXB	48KB TF09 FVXB	48KB TF09 FVPB
											green	48KB TF09 DPXG	48KB TF09 FVXG	48KB TF09 FVPG
											red	48KB TF09 DPXR	48KB TF09 FVXR	48KB TF09 FVPR
	13 mm	21	84	26	25						Standard	48KB TF13 DPX	48KB TF13 FVX	48KB TF13 FVP
											blue	48KB TF13 DPXB	48KB TF13 FVXB	48KB TF13 FVPB
											green	48KB TF13 DPXG	48KB TF13 FVXG	48KB TF13 FVPG
											red	48KB TF13 DPXR	48KB TF13 FVXR	48KB TF13 FVPR
										yellow	48KB TF13 DPXY	48KB TF13 FVXY	48KB TF13 FVPY	

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color	Rectu POM Part Number	Rectu CHEM Part Number	Rectu CHEM+ Part Number	
 <p>Male Thread</p>	G 1/4 o.	21	55	9					Standard	48SB AW13 DPX	48SB AW13 FVX	48SB AW13 FVP	
									blue	48SB AW13 DPXB	48SB AW13 FVXB	48SB AW13 FVPB	
									green	48SB AW13 DPXG	48SB AW13 FVXG	48SB AW13 FVPG	
									red	48SB AW13 DPXR	48SB AW13 FVXR	48SB AW13 FVPR	
	G 3/8 o.	21	51,5	9						Standard	48SB AW17 DPX	48SB AW17 FVX	48SB AW17 FVP
										blue	48SB AW17 DPXB	48SB AW17 FVXB	48SB AW17 FVPB
										green	48SB AW17 DPXG	48SB AW17 FVXG	48SB AW17 FVPG
										red	48SB AW17 DPXR	48SB AW17 FVXR	48SB AW17 FVPR
	G 1/2 o.	21	58	12						Standard	48SB AW21 DPX	48SB AW21 FVX	48SB AW21 FVP
										blue	48SB AW21 DPXB	48SB AW21 FVXB	48SB AW21 FVPB
										green	48SB AW21 DPXG	48SB AW21 FVXG	48SB AW21 FVPG
										red	48SB AW21 DPXR	48SB AW21 FVXR	48SB AW21 FVPR
 <p>Female Thread</p>	G 1/4 i.	21	48	10					Standard	48SB IW13 DPX	48SB IW13 FVX	48SB IW13 FVP	
									blue	48SB IW13 DPXB	48SB IW13 FVXB	48SB IW13 FVPB	
									green	48SB IW13 DPXG	48SB IW13 FVXG	48SB IW13 FVPG	
									red	48SB IW13 DPXR	48SB IW13 FVXR	48SB IW13 FVPR	
	G 3/8 i.	21	48	10						Standard	48SB IW17 DPX	48SB IW17 FVX	48SB IW17 FVP
										blue	48SB IW17 DPXB	48SB IW17 FVXB	48SB IW17 FVPB
										green	48SB IW17 DPXG	48SB IW17 FVXG	48SB IW17 FVPG
										red	48SB IW17 DPXR	48SB IW17 FVXR	48SB IW17 FVPR
	G 1/2 i.	21	59	13						Standard	48SB IW21 DPX	48SB IW21 FVX	48SB IW21 FVP
										blue	48SB IW21 DPXB	48SB IW21 FVXB	48SB IW21 FVPB
										green	48SB IW21 DPXG	48SB IW21 FVXG	48SB IW21 FVPG
										red	48SB IW21 DPXR	48SB IW21 FVXR	48SB IW21 FVPR
 <p>for PVDF- and PE-Hoses</p>	6 x 8 mm	21	64,5	21					Standard		48SB KP08 FVX	48SB KP08 FVP	
	9 x 12 mm	21	71,5	28					Standard		48SB KP12 FVX	48SB KP12 FVP	
	10 x 12 mm	21	71,5	28					Standard		48SB KP12 FVXS	48SB KP12 FVPS	

Valved Plugs

RECTUS Series 48SB

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color	Rectu POM Part Number	Rectu CHEM Part Number	Rectu CHEM+ Part Number
6 mm	21	65,5		22					Standard	48SB TF06 DPX	48SB TF06 FVX	48SB TF06 FVP
									blue	48SB TF06 DPXB	48SB TF06 FVXB	48SB TF06 FVPB
									green	48SB TF06 DPXG	48SB TF06 FVXG	48SB TF06 FVPG
									red	48SB TF06 DPXR	48SB TF06 FVXR	48SB TF06 FVPR
									yellow	48SB TF06 DPXY	48SB TF06 FVXY	48SB TF06 FVPY
9 mm	21	65,5		22					Standard	48SB TF09 DPX	48SB TF09 FVX	48SB TF09 FVP
									blue	48SB TF09 DPXB	48SB TF09 FVXB	48SB TF09 FVPB
									green	48SB TF09 DPXG	48SB TF09 FVXG	48SB TF09 FVPG
									red	48SB TF09 DPXR	48SB TF09 FVXR	48SB TF09 FVPR
									yellow	48SB TF09 DPXY	48SB TF09 FVXY	48SB TF09 FVPY
13 mm	21	68,5		25					Standard	48SB TF13 DPX	48SB TF13 FVX	48SB TF13 FVP
									blue	48SB TF13 DPXB	48SB TF13 FVXB	48SB TF13 FVPB
									green	48SB TF13 DPXG	48SB TF13 FVXG	48SB TF13 FVPG
									red	48SB TF13 DPXR	48SB TF13 FVXR	48SB TF13 FVPR
									yellow	48SB TF13 DPXY	48SB TF13 FVXY	48SB TF13 FVPY




Hose Barb

Plugs

RECTUS Series 48SF

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color	Rectu POM Part Number	Rectu CHEM Part Number	Rectu CHEM+ Part Number
G 1/4 o.	17	38,5		9					Standard	48SF AW13 DXX	48SF AW13 FXX	
									blue	48SF AW13 DPXB	48SF AW13 FVXB	
									green	48SF AW13 DPXG	48SF AW13 FVXG	
									red	48SF AW13 DPXR	48SF AW13 FVXR	
									yellow	48SF AW13 DPXY	48SF AW13 FVXY	
G 3/8 o.	21	38,5		9					Standard	48SF AW17 DXX	48SF AW17 FXX	
									blue	48SF AW17 DPXB	48SF AW17 FVXB	
									green	48SF AW17 DPXG	48SF AW17 FVXG	
									red	48SF AW17 DPXR	48SF AW17 FVXR	
									yellow	48SF AW17 DPXY	48SF AW17 FVXY	
G 1/2 o.	21	41,5		12					Standard	48SF AW21 DXX	48SF AW21 FXX	
									blue	48SF AW21 DPXB	48SF AW21 FVXB	
									green	48SF AW21 DPXG	48SF AW21 FVXG	
									red	48SF AW21 DPXR	48SF AW21 FVXR	
									yellow	48SF AW21 DPXY	48SF AW21 FVXY	
G 1/4 i.	17	35,5		9					Standard	48SF IW13 DXX	48SF IW13 FXX	
									blue	48SF IW13 DPXB	48SF IW13 FVXB	
									green	48SF IW13 DPXG	48SF IW13 FVXG	
									red	48SF IW13 DPXR	48SF IW13 FVXR	
									yellow	48SF IW13 DPXY	48SF IW13 FVXY	




Male Thread



Female Thread



Plugs


RECTUS Series 48SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color	Rectu POM Part Number	Rectu CHEM Part Number	Rectu CHEM+ Part Number	
 <p>Female Thread</p>	G 3/8 i.	21	35,5	10						Standard	48SF IW17 DXX	48SF IW17 FXX		
										blue	48SF IW17 DXXB	48SF IW17 FXXB		
										green	48SF IW17 DXXG	48SF IW17 FXXG		
										red	48SF IW17 DXXR	48SF IW17 FXXR		
										yellow	48SF IW17 DXXY	48SF IW17 FXXY		
	G 1/2 i.	24	59	13							Standard	48SF IW21 DXX	48SF IW21 FXX	
											blue	48SF IW21 DPXB	48SF IW21 FVXB	
											green	48SF IW21 DPXG	48SF IW21 FVXG	
											red	48SF IW21 DPXR	48SF IW21 FVXR	
											yellow	48SF IW21 DPXY	48SF IW21 FVXY	

Plugs

RECTUS Series 48SF

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Color	Rectu POM Part Number	Rectu CHEM Part Number	Rectu CHEM+ Part Number	
 <p>for PVDF- and PE-Hoses</p>	6 x 8 mm	21	64,5	21						Standard		48SF KP08 FVX		
	9 x 12 mm	21	71,5	28						Standard		48SF KP12 FVX		
	10 x 12 mm	21	71,5	28						Standard		48SF KP12 FVXS		
 <p>Hose Barb</p>	6 mm		47	18	22					Standard	48SF TF06 DXX	48SF TF06 FXX		
										blue	48SF TF06 DPXB	48SF TF06 FVXB		
										green	48SF TF06 DPXG	48SF TF06 FVXG		
										red	48SF TF06 DPXR	48SF TF06 FVXR		
										yellow	48SF TF06 DPXY	48SF TF06 FVXY		
	9 mm		47	18	22						Standard	48SF TF09 DXX	48SF TF09 FXX	
											blue	48SF TF09 DPXB	48SF TF09 FVXB	
											green	48SF TF09 DPXG	48SF TF09 FVXG	
											red	48SF TF09 DPXR	48SF TF09 FVXR	
											yellow	48SF TF09 DPXY	48SF TF09 FVXY	
	13 mm		50	18	25						Standard	48SF TF13 DXX	48SF TF13 FXX	
											blue	48SF TF13 DPXB	48SF TF13 FVXB	
											green	48SF TF13 DPXG	48SF TF13 FVXG	
											red	48SF TF13 DPXR	48SF TF13 FVXR	
											yellow	48SF TF13 DPXY	48SF TF13 FVXY	



Nominal Diameter

4,3 = 15 mm²

RECTUS Series



71KB



actual size

**Technical Description**

The 71KB series is a double shut-off hydraulic coupling used for liquid media. The plug profile is manufactured in accordance with ISO-7241-1, series B. All versions mentioned below are manufactured from non-rusting stainless steel or POM. This coupling requires two handed operation (the sleeve must be manually pulled back when connecting).

Chart**Advantages**

Simple, yet rugged construction guarantees the highest safety.

Working Pressure

PB = 15 bar (at 50°C)
maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +90°C (NBR)
-40°C up to +90°C (EPDM)
-15°C up to +90°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +90°C special seals are available on request.

Material**Coupling**

Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Spring Plate

Standard

POM, white
POM, white
AISI 303
AISI 301
AISI 316
NBR
AISI 301

Plug

Plug Profile
Valve
Spring
Seal
Spring Plate

POM, white
AISI 303
AISI 301
NBR
AISI 301

You will find the following alternative versions in our current catalogue on page:


- ▶ Stainless Steel Double Shut-off P. 216
- ▶ Brass/Steel Double Shut-off P. 124

Coupling**RECTUS Series 71KB**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 1/8	14	48,5	24,5	7					Standard	71KB IW10 DPX

Valved Plug**RECTUS Series 71KB**



	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 1/8	14	29,5		7					Standard	71SB IW10 DPX



Technical Description

The 72KB series is a double shut-off hydraulic coupling used for liquid media. The plug profile is manufactured in accordance with ISO-7241-1, series B. All versions mentioned below are manufactured from non-rusting stainless steel or POM. This coupling requires two handed operation (the sleeve must be manually pulled back when connecting).

Chart



Advantages

Simple, yet rugged construction guarantees the highest safety.

Working Pressure

PB = 15 bar (at 50°C)
maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +90°C (NBR)
-40°C up to +90°C (EPDM)
-15°C up to +90°C (FKM)
0°C up to +90°C (FFKM)
depending on the medium.

*At a temperature below -20°C and above +90°C special seals are available on request.

Material

Coupling

Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Spring Plate

Standard

POM, white
POM, white
AISI 303
AISI 301
AISI 316
NBR
AISI 301

Plug

Plug Profile
Valve
Spring
Spring Plate
Seal

POM, white
AISI 303
AISI 301
AISI 301
NBR



actual size

You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel Double Shut-off P. 217
- ▶ Brass/Steel Double Shut-off P. 134

Coupling


RECTUS Series 72KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 1/4	19	57,5	28,5	10					Standard	72KB IW13 DPX

Valved Plug

RECTUS Series 72KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 1/4	19	35		10					Standard	72SB IW13 DPX



Nominal Diameter

7,5 = 44 mm²

RECTUS Series



73KB



85% of actual size

Technical Description

The 73KB series is a double shut-off hydraulic coupling used for liquid media. The plug profile is manufactured in accordance with ISO-7421-1, series B. All versions mentioned below are manufactured from non-rusting stainless steel or POM. This coupling requires two handed operation (the sleeve must be manually pulled back when connecting).

Chart**Advantages**

Simple, yet rugged construction guarantees the highest safety.

Working Pressure

PB = 15 bar (at 50°C)
maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +90°C (NBR)
-40°C up to +90°C (EPDM)
-15°C up to +90°C (FKM)
0°C up to 90°C (FFKM)
depending on the medium.

*At a temperature below -20°C and above +90°C special seals are available on request.

Material**Coupling**

Back Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Spring Plate

Standard

POM, white
POM, white
AISI 303
AISI 301
AISI 316
NBR
AISI 301

Plug

Plug Profile
Valve
Spring
Spring Plate
Seal

POM, white
AISI 303
AISI 301
AISI 301
NBR

You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel Double Shut-off P. 218
- ▶ Brass/Steel Double Shut-off P. 144

Coupling**RECTUS Series 73KB**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 3/8	22	64	35	11,5					Standard	73KB IW17 DPX

Valved Plug**RECTUS Series 73KB**



	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 3/8	22	39		11,5					Standard	73SB IW17 DPX



Technical Description

The 74KB series is a double shut-off hydraulic coupling used for liquid media. The plug profile is manufactured in accordance with ISO-7421-1, series B. All versions mentioned below are manufactured from non-rusting stainless steel or POM. This coupling requires two handed operation (the sleeve must be manually pulled back when connecting).

Chart



Advantages

Simple, yet rugged construction guarantees the highest safety.

Working Pressure

PB = 10 bar (at 50°C), maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C bis +90°C (NBR)
 -40°C bis +90 (EPDM)
 -15°C bis +90°C (FKM)
 0°C bis +90°C (FFKM)
 depending on the medium.

*At a temperature below -20°C and above +90°C special seals are available on request.

Material

Coupling
 Valve Body
 Sleeve
 Valve
 Spring and Locking Ring
 Locking Balls
 Seals
 Spring Plate

Standard

POM, white
 POM, white
 AISI 303
 AISI 301
 AISI 316
 NBR
 AISI 301

Plug

Plug Profile
 Valve
 Spring
 Spring Plate
 Seal



75% of actual size

You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel Double Shut-off P. 219
- ▶ Brass/Steel Double Shut-off P. 150

Coupling


RECTUS Series 74KB

	Connection A	Hex	L	D	L1	L2	Hex1	B	G	Version	Part Number
		SW	mm	mm	mm	mm	SW1	mm	mm		
<p>Female Thread</p>	G 1/2	27	76	44,5	16					Standard	74KB IW21 DPX

Valved Plug

RECTUS Series 74KB

	Connection A	Hex	L	D	L1	L2	Hex1	B	G	Version	Part Number
		SW	mm	mm	mm	mm	SW1	mm	mm		
<p>Female Thread</p>	G 1/2	27	48		16					Standard	74SB IW21 DPX



Nominal Diameter

13 = 133 mm²

RECTUS Series

75KB


55% of actual size





You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel Double Shut-off P. 220
- ▶ Brass/Steel Double Shut-off P. 154

Technical Description

The 75KB series is a double shut-off hydraulic coupling used for liquid media. The plug profile is manufactured in accordance with ISO-7421-1, series B. All versions mentioned below are manufactured from non-rusting stainless steel or POM. This coupling requires two handed operation (the sleeve must be manually pulled back when connecting).

Chart



Advantages

Simple, yet rugged construction guarantees the highest safety.

Working Pressure

PB = 10 bar (at 50°C), maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +90°C (NBR)
-40°C up to +90 (EPDM)
-15°C up to +90°C (FKM)
0°C up to + 90°C (FFKM)
depending on the medium.

*At a temperature below -20°C and above +90°C special seals are available on request.

Material

Coupling

Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Spring Plate

Standard

POM, white
POM, white
AISI 303
AISI 301
AISI 316
NBR
AISI 301

Plug

Plug Profile
Valve
Spring
Spring Plate
Seal

POM, white
AISI 303
AISI 301
AISI 301
NBR

Coupling


RECTUS Series 75KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 3/4	34	96	55	24					Standard	75KB IW26 DPX

Valved Plug

RECTUS Series 75KB



	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 3/4	36	60		24					Standard	75SB IW26 DPX



Technical Description

The 76KB series is a double shut-off hydraulic coupling used for liquid media. The plug profile is manufactured in accordance with ISO-7421-1, series B. All versions mentioned below are manufactured from non-rusting stainless steel or POM. This coupling requires two handed operation (the sleeve must be manually pulled back when connecting).

Chart



Advantages

Simple, yet rugged construction guarantees the highest safety.

Working Pressure

PB = 10 bar (at 50°C), maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +90°C (NBR)
 -40°C up to +90°C (EPDM)
 -15°C up to +90°C (FKM)
 0°C up to +90°C (FFKM)
 depending on the medium

*At a temperature below -20°C and above +90°C special seals are available on request.

Material

Coupling
 Valve Body
 Sleeve
 Valve
 Spring and Locking Ring
 Locking Balls
 Seals
 Spring Plate, Locking Ring

Plug

Plug Profile
 Valve
 Spring
 Spring Plate
 Seal

Standard

POM, white
 POM, white
 AISI 303
 AISI 316 Ti

 AISI 316
 NBR
 AISI 301

POM, white
 AISI 303
 AISI 316 Ti
 AISI 301
 NBR



You will find the following alternative versions in our current catalogue on page:

- ▶ Stainless Steel Double Shut-off P. 221
- ▶ Brass/Steel Double Shut-off P. 160

Coupling


RECTUS Series 76KB

	Connection A	Hex	L	D	L1	L2	Hex1	B	G	Version	Part Number
		SW	mm	mm	mm	mm	SW1	mm	mm		
<p>Female Thread</p>	G 1	41	105,5	62	24					Standard	76KB IW33 DPX

Valved Plug

RECTUS Series 76KB

	Connection A	Hex	L	D	L1	L2	Hex1	B	G	Version	Part Number
		SW	mm	mm	mm	mm	SW1	mm	mm		
<p>Female Thread</p>	G 1	41	65		24					Standard	76SB IW33 DPX



Nominal Diameter

30 = 707 mm²

RECTUS Series



77KB



35% of actual size

**Technical Description**

The 77KB series is a double shut-off hydraulic coupling used for liquid media. The plug profile is manufactured in accordance with ISO-7421-1, series B. All versions mentioned below are manufactured from non-rusting stainless steel or POM. This coupling requires two handed operation (the sleeve must be manually pulled back when connecting).

Chart**Advantages**

Simple, yet rugged construction guarantees the highest safety.

Working Pressure

PB = 10 bar (at 50°C), maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +90°C (NBR)
-40°C up to +90°C (EPDM)
-15°C up to +90°C (FKM)
0°C up to +90°C (FFKM)
depending on the medium

*At a temperature below -20°C and above +90°C special seals are available on request.

Material**Coupling**

Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Spring Plate, Locking Ring

Standard

POM, white
POM, white
AISI 303
AISI 316 Ti
AISI 316
EPDM
AISI 301

Plug

Plug Profile
Valve
Spring
Spring Plate
Seal

POM, white
AISI 303
AISI 316 Ti
AISI 301
EPDM

Coupling**RECTUS Series 77KB**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 1 1/2	60	133	76	23					Standard	77KB IW48 DEXS


Valved Plug**RECTUS Series 77KB**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
<p>Female Thread</p>	G 1 1/2	60	132		23					Standard	77SB IW48 DEX

Male x Male Nipple

RECTUS Fittings


Connection A	Hex SW	L mm	L1 mm	L2 mm	L3 mm	Hex1 SW1	B mm	G mm	Rectu POM Part Number	Rectu CHEM Part Number
G 1/4 x G 1/8	14	19	8	7					DN 13/10DX	DN 13/10FX
G 1/4 x G 1/4	14	19	8	7					DN 13/13DX	DN 13/13FX
G 3/8 x G 1/4	17	28,5	9	9					DN 17/13DX	DN 17/13FX
G 3/8 x G 3/8	21	25	9	9					DN 17/17DX	DN 17/17FX
G 3/8 x G 1/2	21	31,5	9	12					DN 17/21DX	DN 17/21FX



Male x Female Nipple

RECTUS Fittings


Connection A	Hex SW	L mm	L1 mm	L2 mm	L3 mm	Hex1 SW1	B mm	G mm	Rectu POM Part Number	Rectu CHEM Part Number
G 1/4 x G 1/8	14	22	8	8					RL 13/10DX	RL 13/10FX
G 1/4 x G 1/4	17	25	8	10					RL 13/13DX	RL 13/13FX
G 3/8 x G 1/4	17	21,5	9	10					RL 17/13DX	RL 17/13FX
G 3/8 x G 3/8	21	21,5	9	10					RL 17/17DX	RL 17/17FX
G 3/8 x G 1/2	17	32,5	9	13					RL 17/21DX	RL 17/21FX



Hose Tale Adaptor

RECTUS Fittings


Connection A	Hex SW	L mm	L1 mm	L2 mm	L3 mm	Hex1 SW1	B mm	G mm	Rectu POM Part Number	Rectu CHEM Part Number
G 1/4 x 4 mm	14	29	8	17					GT 13/04DX	GT 13/04FX
G 1/4 x 6 mm	14	29	8	17					GT 13/06DX	GT 13/06FX
G 3/8 x 6 mm	17	39	9	22					GT 17/06DX	GT 17/06FX
G 3/8 x 9 mm	17	39	9	22					GT 17/09DX	GT 17/09FX
G 3/8 x 10 mm	17	39	9	22					GT 17/10DX	
G 3/8 x 13 mm	17	42	9	25					GT 17/13DX	GT 17/13FX



Plastic Screw Connector

RECTUS Fittings


Connection A	Hex SW	L mm	L1 mm	L2 mm	L3 mm	Conn. A1 mm	G mm	Rectu POM Part Number	Rectu CHEM Part Number
G 1/4	14	25	8	13		4 x 6	M 10 x 1	EV 13/06 DX	EV 13/06 FX
G 1/4	14	25	8	13		6 x 8	M 12 x 1	EV 13/08 DX	EV 13/08 FX




Screw Connection for PVDF or PE Hoses

RECTUS Fittings

Connection A	Hex SW	L mm	L1 mm	L2 mm	L3 mm	Conn. A1 mm	G mm	Rectu POM Part Number	Rectu CHEM Part Number
G 1/4	17	31	17	8		4 x 6	M 10 x 1		EV 13/06 FX04
G 1/4	17	35	21	8		6 x 8	M 12 x 1		EV 13/08 FX06
G 3/8	22	38	21	9		6 x 8	M 12 x 1		EV 17/08 FX06
G 3/8	22	45	28	9		9 x 12	M 12 x 1		EV 17/12 FX09
G 3/8	22	45	28	9		10 x 12	M 12 x 1		EV 17/12 FX10




Panel Mount, Standard Hose Connection **RECTUS Fittings**



Connection A	Hex SW	L mm	L1 mm	L2 mm	L3 mm	Hex1 SW1	B mm	G mm	Rectu POM Part Number	Rectu CHEM Part Number
G 1/4 x 4 mm	14	43	7	8	14	14	4	M 10 x 1	ET 13/04 DX	ET 13/04 FX
G 1/4 x 6 mm	14	43	8	8	14	17	4	M 12 x 1	ET 13/06 DX	ET 13/06 FX

Panel Mount, Plastic Hose Connection **RECTUS Fittings**



Connection A	Hex SW	L mm	L1 mm	L2 mm	L3 mm	Hex1 SW1	B mm	G mm	Rectu POM Part Number	Rectu CHEM Part Number
G 1/4 x 4 x 6 mm	14	37	7	8	18	14	4	M 10 x 1	EK 13/06 DX	EK 13/06 FX
G 1/4 x 6 x 8 mm	14	37	8	8	18	17	4	M 12 x 1	EK 13/08 DX	EK 13/08 FX




For the toughest demands.



Our thermoplastic coupling systems in series 21 and 48 help to prevent mixing of media by the use of colour coding.





Nominal Diameter

5 = 20 mm²



RECTUS Series

21KS

actual size



Technical Description

Mini industrial coupling, the world's most commonly used profile. Above average flow performance for liquid and gaseous media. It also uses an additional safety locking system. This prevents unintentional disconnection. When being disconnected, the plug must first be pushed further into the coupling before it can be disconnected.

Advantages

Small dimensions. The safety locking system prevents unauthorized disconnection.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 0°C up to +316°C (FFKM)
 depending on the medium.



*At a temperature below -20°C and above +100°C special seals are available on request.

Dust Caps (P. 331)

for coupling Part.-No. SK16S



Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Safety Double Shut-off P. 276
- ▶ Coded Systems P. 300
- ▶ Brass/Steel P. 34
- ▶ Stainless Steel P. 185
- ▶ Thermoplastics P. 242

Material

Coupling

Back Body
 Valve Body
 Sleeve
 Valve
 Spring and Locking Rings
 Locking Balls
 Seal

Standard

Brass
 Brass
 Brass
 Brass
 AISI 301
 AISI 420
 NBR

Nickel Plated

Brass, Nickel Plated
 Brass, Nickel Plated
 Brass, Nickel Plated
 Brass
 AISI 301
 AISI 420
 NBR

Plug


Plug

Brass

Brass, Nickel Plated

Couplings









RECTUS Series 21KS



Male Thread



Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/8	14	36	16	7					Standard	21KS AW10 MPX
									Nickel Plated	21KS AW10 MPN
G 1/4	17	38	16	9					Standard	21KS AW13 MPX
									Nickel Plated	21KS AW13 MPN
G 3/8	19	38	16	9					Standard	21KS AW17 MPX
									Nickel Plated	21KS AW17 MPN
M 12 x 1,5	17	39	16	10					Standard	21KS AD12 MPX
									Nickel Plated	21KS AD12 MPN
M 14 x 1,5	17	39	16	10					Standard	21KS AD14 MPX
									Nickel Plated	21KS AD14 MPN

ISO 8434-1

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Female Thread</p>	G 1/8	14	36	16	9					Standard	21KS IW10 MPX	
										Nickel Plated	21KS IW10 MPN	
	G 1/4	17	38	16	9					Standard	21KS IW13 MPX	
										Nickel Plated	21KS IW13 MPN	
	G 3/8	19	38	16	6					Standard	21KS IW17 MPX	
										Nickel Plated	21KS IW17 MPN	
 <p>Hose Barb</p>	M 12 x 1,5	17	38	16	6					Standard	21KS IM12 MPX	
										Nickel Plated	21KS IM12 MPN	
	M 14 x 1,5	17	38	16	6					Standard	21KS IM14 MPX	
										Nickel Plated	21KS IM14 MPN	
	4 mm	14	46	16	17					Standard	21KS TF04 MPX	
										Nickel Plated	21KS TF04 MPN	
 <p>Plastic Hose Connection</p>	5 mm	14	46	16	17					Standard	21KS TF05 MPX	
										Nickel Plated	21KS TF05 MPN	
	6 mm	14	46	16	17					Standard	21KS TF06 MPX	
										Nickel Plated	21KS TF06 MPN	
	8 mm	14	46	16	17					Standard	21KS TF08 MPX	
										Nickel Plated	21KS TF08 MPN	
 <p>Panel Mount, Plastic Hose Connection</p>	9 mm	14	46	16	17					Standard	21KS TF09 MPX	
										Nickel Plated	21KS TF09 MPN	
	10 mm	14	46	16	17					Standard	21KS TF10 MPX	
										Nickel Plated	21KS TF10 MPN	
 <p>Panel Mount, Hose Barb</p>	4 x 6 mm	14	42	16	7	6		M 10 x 1		Standard	21KS KO06 MPX	
										Nickel Plated	21KS KO06 MPN	
	6 x 8 mm	14	42	16	7	6		M 12 x 1		Standard	21KS KO08 MPX	
										Nickel Plated	21KS KO08 MPN	
 <p>Panel Mount, Plastic Hose Connection</p>	4 x 6 mm	14	54	16	7	18	14	4	M 10 x 1		Standard	21KS KS06 MPX
										Nickel Plated	21KS KS06 MPN	
	6 x 8 mm	17	54	16	7	18	17	4	M 12 x 1		Standard	21KS KS08 MPX
										Nickel Plated	21KS KS08 MPN	
 <p>Panel Mount, Hose Barb</p>	4 mm	14	60	16	17	14	14	4	M 10 x 1		Standard	21KS TS04 MPX
										Nickel Plated	21KS TS04 MPN	
	5 mm	17	60	16	17	14	17	4	M 12 x 1		Standard	21KS TS05 MPX
										Nickel Plated	21KS TS05 MPN	
 <p>Panel Mount, Hose Barb</p>	6 mm	17	60	16	17	14	17	4	M 12 x 1		Standard	21KS TS06 MPX


Plugs


RECTUS Series 21KS

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Male Thread</p>	G 1/8	14	25	7						Standard	21SS AW10 MXX	
										Nickel Plated	21SS AW10 MXN	
	G 1/4	17	28	9							Standard	21SS AW13 MXX
											Nickel Plated	21SS AW13 MXN
 <p>Female Thread</p>	G 1/8	14	25	8						Standard	21SS IW10 MXX	
										Nickel Plated	21SS IW10 MXN	
	G 1/4	17	25	9							Standard	21SS IW13 MXX
											Nickel Plated	21SS IW13 MXN

Plugs

RECTUS Series 21KS

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Hose Barb</p>	4 mm		32	9	17					Standard	21SS TF04 MXX	
										Nickel Plated	21SS TF04 MXN	
	6 mm		32	9	17						Standard	21SS TF06 MXX
											Nickel Plated	21SS TF06 MXN
	8 mm		32	9	17						Standard	21SS TF08 MXX
											Nickel Plated	21SS TF08 MXN
	9 mm		33	10	17						Standard	21SS TF09 MXX
											Nickel Plated	21SS TF09 MXN
	10 mm		33	12	17						Standard	21SS TF10 MXX
											Nickel Plated	21SS TF10 MXN



Nominal Diameter

7,8 = 48 mm²



RECTUS Series

25KS

actual size



Technical Description

Safety coupling with UltraFlo technology. High flow performance. Notable for robust design and steel sleeve used with large pneumatic consumers. Additional safety locking system. This safety lock prevents unintentional disconnection. To disconnect, the plug must first be pushed further into the coupling before it can be unlocked.

Advantages

Quality coupling with small dimensions and high flow rates. Safety locking system. Double profiled plug design against wear of material during operation.

Working Temperature*



-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 0°C up to +316°C (FFKM)
 depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Working Pressure

PB = 35 bar (Brass)
 PB = 70 bar (with steel body and steel seal), maximum static working pressure with safety factor of 4 to 1.

Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Safety Double Shut-off P. 278
- ▶ Safety Self-Venting P. 290
- ▶ Coded Systems P. 303
- ▶ Brass/Steel P. 73
- ▶ Stainless Steel P. 192

Material Coupling

Back Body
 Valve Body
 Sleeve

Standard

Brass
 Steel, Nickel Pl.
 Steel Hardened, Nickel Plated
 Brass

Brass

Brass
 Brass
 Brass
 Brass

Brass, Nickel Pl.

Brass, Nickel Pl.
 Brass, Nickel Pl.
 Brass, Nickel Pl.

Valve
 Spring and Lock Ring
 Locking Balls
 Seals
 Distance Sleeve
 Spring Plate

AISI 301
 AISI 420
 NBR
 Brass
 Brass

AISI 301
 AISI 420
 NBR
 Brass
 Brass

AISI 301
 AISI 420
 NBR
 Brass
 Brass

Plug

Plug


Steel Hardened, Zinc-Plated

Brass

Brass, Nickel Pl.

Couplings

RECTUS Series 25KS





Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/4	19	60	23	12					Standard	25KS AK13 SPN
									Brass	25KS AK13 BPX
									Brass, Nickel Pl.	25KS AK13 BPN
R 3/8	19	60	23	12					Standard	25KS AK17 SPN
									Brass	25KS AK17 BPX
									Brass, Nickel Pl.	25KS AK17 BPN
R 1/2	22	61	23	17					Standard	25KS AK21 SPN
									Brass	25KS AK21 BPX
									Brass, Nickel Pl.	25KS AK21 BPN


Couplings

RECTUS Series 25KS


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Female Thread</p>	G 1/4	19	56	23	10					Standard	25KS IW13 SPN	
										Brass	25KS IW13 BPX	
										Brass, Nickel Pl.	25KS IW13 BPN	
	G 3/8	19	55	23	9					Standard	25KS IW17 SPN	
										Brass	25KS IW17 BPX	
										Brass, Nickel Pl.	25KS IW17 BPN	
	G 1/2	24	58	23	12					Standard	25KS IW21 SPN	
 <p>Hose Barb</p>	6 mm	19	74	23	25					Standard	25KS TF06 SPN	
	8 mm	19	74	23	25					Standard	25KS TF08 SPN	
										Brass	25KS TF08 BPX	
										Brass, Nickel Pl.	25KS TF08 BPN	
	9 mm	19	74	23	25					Standard	25KS TF09 SPN	
										Brass	25KS TF09 BPX	
										Brass, Nickel Pl.	25KS TF09 BPN	
	10 mm	19	74	23	25					Standard	25KS TF10 SPN	
										Brass	25KS TF10 BPX	
										Brass, Nickel Pl.	25KS TF10 BPN	
	13 mm	19	74	23	25					Standard	25KS TF13 SPN	
										Brass	25KS TF13 BPX	
										Brass, Nickel Pl.	25KS TF13 BPN	

Plugs


RECTUS Series 25KS


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	
 <p>Male Thread</p>	R 1/8	13	33		9					Standard	25SS AK10 SXZ	
	R 1/4	14	37		12					Standard	25SS AK13 SXZ	
	G 1/4	17	33		9					Brass	26SS AW13 MXX	
	G 1/4	17	33		9					Brass, Nickel Pl.	26SS AW13 MXN	
	R 3/8	17	37		12					Standard	25SS AK17 SXZ	
	R 1/2	22	43		17					Standard	25SS AK21 SXZ	

Plugs **RECTUS Series 25KS**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Female Thread</p>	G 1/4	17	33		9					Standard	25SS IW13 SXZ
	G 3/8	19	33		9					Standard	25SS IW17 SXZ
	G 1/2	24	36		12					Standard	25SS IW21 SXZ

Plugs **RECTUS Series 25KS**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm		48	12	25					Standard	25SS TF06 SXZ
	8 mm		48	12	25					Standard	25SS TF08 SXZ
			48	12	25					Brass, Nickel Pl.	26SS TF08 MXN
	9 mm		48	12	25					Standard	25SS TF09 SXZ
	10 mm		48	12	25					Standard	25SS TF10 SXZ
	13 mm		48	15	25					Standard	25SS TF13 SXZ



Technical Description

The 28KS safety coupling is the largest version of our safety range. The plug must be pushed further into the coupling before it can be disconnected, which prevents unintentional disconnection. The plug profile conforms with the CETOP RP 59 P-15 standard.

Advantages

Single handed operation. High quality coupling made of steel. Safety locking system. High flow rate due to the UltraFlo valve. Double profiled plug design against wear of material during operation.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.



Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Rings
- Locking Balls
- Seals


Standard

- Brass, Nickel Plated
- Steel, Nickel Plated
- Steel Hardened, Nickel Plated
- Brass
- AISI 301
- AISI 420
- NBR

Plug




- Plug
- Steel Hardened,
- Nickel Plated

Chart





Couplings

RECTUS Series 28KS

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/2	24	69,5	28	17					Standard	28KS AK21 SPN
	R 3/4	27	69,5	28	17					Standard	28KS AK26 SPN
 <p>Female Thread</p>	G 3/8	24	61,5	28	12					Standard	28KS IW17 SPN
	G 1/2	24	61,5	28	12					Standard	28KS IW21 SPN
	G 3/4	32	65,5	28	16					Standard	28KS IW26 SPN
 <p>Hose Barb</p>	13 mm	24	81,5	28	25					Standard	28KS TF13 SPN
	16 mm	24	81,5	28	25					Standard	28KS TF16 SPN
	19 mm	24	81,5	28	25					Standard	28KS TF19 SPN


Plugs

RECTUS Series 28KS

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 Male Thread	R 3/8	17	45		12					Standard	28SS AK17 SXN
	R 1/2	22	50		17					Standard	28SS AK21 SXN
 Female Thread	G 3/8	19	39		9					Standard	28SS IW17 SXN
	G 1/2	24	42		12					Standard	28SS IW21 SXN
	G 3/4	32	47		16					Standard	28SS IW26 SXN

Plugs

RECTUS Series 28KS

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 Hose Barb	10 mm		54	15	25					Standard	28SS TF10 SXN
	13 mm		54	15	25					Standard	28SS TF13 SXN
	16 mm		56	18	25					Standard	28SS TF16 SXN
	19 mm		56	21	25					Standard	28SS TF19 SXN



Allow us to present: your new safety representative.



Our self-venting coupling system in series 26KE reliably prevents the dangerous whiplash effect.



Nominal Diameter

5 = 20 mm²

RECTUS Series

21KD



actual size



Technical Description

Mini industrial coupling, the world's most commonly used profile. Above average flow performance for liquid and gaseous media. It also uses an additional safety locking system. This prevents unintentional disconnection. When being disconnected, the plug must first be pushed further into the coupling before it can be disconnected.

Advantages

Small dimensions. The safety locking system prevents unauthorized disconnection.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 0°C up to +316°C (FFKM)
 depending on the medium.



*At a temperature below -20°C and above +100°C special seals are available on request.

Dust Caps (P. 331)

for coupling Part.-No. SK16S



Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Safety Single Shut-off P. 266
- ▶ Coded Systems P. 300
- ▶ Brass/Steel P. 34
- ▶ Stainless Steel P. 185
- ▶ Thermoplastics P. 242

Material

Coupling

Back body
 Valve body
 Sleeve
 Valve
 Spring and Locking Ring
 Locking Balls
 Seals

Standard

Brass, Nickel Plated
 Brass, Nickel Plated
 Brass, Nickel Plated
 Brass
 AISI 301
 AISI 420
 NBR


Plug

Plug Profile
 Back Body
 Valve
 Spring
 Seal


Brass, Nickel Plated
 Brass, Nickel Plated
 Brass
 AISI 301
 NBR

Couplings

RECTUS Series 21KD



Male Thread




Female Thread

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
Male Thread	G 1/8	14	36	16	7					Standard	21KD AW10 MPN
	G 1/4	17	38	16	9					Standard	21KD AW13 MPN
	G 3/8	19	38	16	9					Standard	21KD AW17 MPN
Female Thread	G 1/8	14	36	16	9					Standard	21KD IW10 MPN
	G 1/4	17	38	16	9					Standard	21KD IW13 MPN
	G 3/8	19	38	16	9					Standard	21KD IW17 MPN



Couplings

RECTUS Series 21KD

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm	14	46	16	17					Standard	21KD TF06 MPN
	10 mm	14	46	16	17					Standard	21KD TF10 MPN


Valved Plugs


RECTUS Series 21KD

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14	40		7					Standard	21SD AW10 MPN
	G 1/4	17	42		9					Standard	21SD AW13 MPN
	G 3/8	19	42		9					Standard	21SD AW17 MPN
 <p>Female Thread</p>	G 1/8	14	40		7					Standard	21SD IW10 MPN
	G 1/4	17	42		7					Standard	21SD IW13 MPN

Valved Plugs

RECTUS Series 21KD

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm	14	50		17					Standard	21SD TF06 MPN
	10 mm	14	50		17					Standard	21SD TF10 MPN



Nominal Diameter

7,4 = 43 mm²

RECTUS Series

25KD



actual size

Technical Description

Safety coupling with UltraFlo technology. High flow performance. Notable for robust design and steel sleeve used with large pneumatic consumers. Additional safety locking system. This safety lock prevents unintentional disconnection. To disconnect, the plug must first be pushed further into the coupling before it can be unlocked.

Advantages

Quality coupling with small dimensions and high flow rates. Safety locking system. Double profiled plug design against wear of material during operation. Non-slip sleeve can also be operated when wearing safety gloves.

Working Temperature*



-20°C up to +100°C (NBR)
 -40°C up to +120/150°C (EPDM)
 -15°C up to +200°C (FKM)
 0°C up to +316°C (KFFKM)
 depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Chart



Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals

Standard

- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass
- AISI 301
- AISI 420
- NBR

Plug

- Plug Profile
- Back Body
- Valve
- Spring
- Seal


- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass
- AISI 420
- NBR

You will find the following alternative versions in our current catalogue on page:


- ▶ Safety Single Shut-off P. 270
- ▶ Safety Self-Venting P. 290
- ▶ Coded Systems P. 303
- ▶ Brass/Steel P. 73
- ▶ Stainless Steel P. 209

Couplings

RECTUS Series 25KD



Male Thread




Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
R 1/4	19	60	30	12					Standard	25KD AK13 BPN
R 3/8	19	60	30	12					Standard	25KD AK17 BPN
R 1/2	22	61	30	17					Standard	25KD AK21 BPN
G 1/4	19	56	30	10					Standard	25KD IW13 BPN
G 3/8	19	55	30	9					Standard	25KD IW17 BPN
G 1/2	24	58	30	12					Standard	25KD IW21 BPN

Couplings

RECTUS Series 25KD




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
6 mm	19	74	30	25					Standard	25KD TF06 BPN
8 mm	19	74	30	25					Standard	25KD TF08 BPN
9 mm	19	74	30	25					Standard	25KD TF09 BPN
10 mm	19	74	30	25					Standard	25KD TF10 BPN
13 mm	19	74	30	25					Standard	25KD TF13 BPN


Valved Plugs

RECTUS Series 25KD



Male Thread


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/4	22	43		9					Standard	25SD AW13 MPN
G 3/8	22	43		9					Standard	25SD AW17 MPN
G 1/2	22	46		12					Standard	25SD AW21 MPN
G 1/4	22	43		10					Standard	25SD IW13 MPN
G 3/8	22	43		9					Standard	25SD IW17 MPN
G 1/2	24	46		12					Standard	25SD IW21 MPN



Female Thread

Valved Plugs

RECTUS Series 25KD



Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Material	Part Number
6 mm	21	60		25					Standard	25SD TF06 MPN
8 mm	21	60		25					Standard	25SD TF08 MPN
9 mm	21	60		25					Standard	25SD TF09 MPN
10 mm	21	60		25					Standard	25SD TF10 MPN
13 mm	21	60		25					Standard	25SD TF13 MPN



Self-Venting System

Nominal Diameter

5,5 = 25 mm²

RECTUS Series

14KE



90% of actual size



Technical Description

The connection is made the same way as with all other quick connect coupling series, by simply pushing the plug into the coupling. The audible latching when the plug is securely in place signifies that the coupling is locked. The sleeve must be pulled back to release the first locking system before it can be disconnected. This closes the coupling valve. The compressed downstream air can now escape from the plug (hose). Pulling the sleeve back a second time releases the second locking system. The connection can now be safely undone. This self-venting coupling, designed for bleeding off trapped air, is not suitable for direct connection to compressed air tools.

Advantages

The system fulfils the requirements of ISO 4414.
 - increased safety standards in the work place
 - the plastic sleeve does not scratch working surfaces

Caution

Not recommended for direct connection to compressed air tools. Reliable functioning can only be guaranteed in conjunction with original Rectus plugs made of steel.

Working Pressure

PB = 12 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature

-20°C up to +60°C (NBR) depending on the medium.

Material

Coupling

Back Body
 Valve Body
 Sleeve
 Valve
 Spring
 Locking Balls
 Seals
 Pins

Standard

Brass, Nickel Plated
 Brass, Nickel Plated
 Thermoplastic
 Brass
 AISI 301
 AISI 420
 NBR
 AISI 420


Plug

Steel Hardened, Nickel Plated

You will find the following alternative versions in our current catalogue on page:


► Brass/Steel Single Shut-off P. 44

Chart




Couplings

RECTUS Series 14KE



Male Thread




Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
R 1/4	22	58	31	9					Standard	14KE AK13 MPN
R 3/8	22	58	31	9					Standard	14KE AK17 MPN
R 1/2	24	63	31	12					Standard	14KE AK21 MPN
G 1/4	22	57	31	9					Standard	14KE IW13 MPN
G 3/8	22	57	31	9					Standard	14KE IW17 MPN
G 1/2	24	60	31	12					Standard	14KE IW21 MPN

Couplings


RECTUS Series 14KE




Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm	22	71	31	25					Standard	14KE TF06 MPN
8 mm	22	71	31	25					Standard	14KE TF08 MPN
9 mm	22	71	31	25					Standard	14KE TF09 MPN
10 mm	22	71	31	25					Standard	14KE TF10 MPN
13 mm	22	71	31	25					Standard	14KE TF13 MPN

Plugs

RECTUS Series 22SF




Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
R 1/8	12	35		9					Standard	22SF AK10 SXN
R 1/4	14	41		12					Standard	22SF AK13 SXN
R 3/8	17	41		12					Standard	22SF AK17 SXN
R 1/2	22	46		17					Standard	22SF AK21 SXN



G 1/4	17	35		9					Standard	22SF IW13 SXN
G 3/8	19	35		10					Standard	22SF IW17 SXN
G 1/2	24	38		12					Standard	22SF IW21 SXN

Valved Plugs

RECTUS Series 22SF



Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm		49	12	25					Standard	22SF TF06 SXN
8 mm		49	12	25					Standard	22SF TF08 SXN
9 mm		49	12	25					Standard	22SF TF09 SXN
10 mm		49	12	25					Standard	22SF TF10 SXN
13 mm		49	12	25					Standard	22SF TF13 SXN



Self-Venting System

Nominal Diameter

5,5 = 25 mm²



RECTUS Series

18KE

90% of actual size



You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Single Shut-off P. 46

Technical Description

The 18KE series is a safety coupling with a self-venting system. When the sleeve is pulled back the plug is released, however, it still remains locked to the coupling. The coupling's valve closes while the downstream air supply line is vented simultaneously. Afterward it can be disconnected without any danger by pulling the sleeve back a second time to completely release the plug from the coupling.

Advantages

Connected in the same manner as all standard couplings – single hand operation. The venting takes place without any danger to the operators during the disconnecting process – no danger of being hit by a whipping hose that is still pressurized. The system fulfils the requirements stipulated in ISO 4414 for increased safety standards in the working place.

Working Pressure

PB = 8 bar, maximum static working pressure with safety factor of 4 to 1.

Working temperature

-20°C up to +60°C (NBR) depending on the medium.

Caution

Not recommended for direct connection to compressed air tools. Reliable functioning can only be guaranteed in conjunction with original RECTUS plugs made of steel.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals
Pins


Standard

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR
AISI 420

Plug

Steel Hardened, Nickel Plated

Chart




Couplings

RECTUS Series 18KE

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	24	67	30	12					Standard	18KE AK13 BPN
	R 3/8	24	67	30	12					Standard	18KE AK17 BPN
	R 1/2	24	72	30	17					Standard	18KE AK21 BPN
<p>Female Thread</p>	G 1/4	24	63	30	10					Standard	18KE IW13 BPN
	G 3/8	24	60	30	9					Standard	18KE IW17 BPN
	G 1/2	24	65	30	12					Standard	18KE IW21 BPN

Couplings

RECTUS Series 18KE




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm	24	81	30	25					Standard	18KE TF06 BPN
8 mm	24	81	30	25					Standard	18KE TF08 BPN
9 mm	24	81	30	25					Standard	18KE TF09 BPN
10 mm	24	81	30	25					Standard	18KE TF10 BPN
13 mm	24	81	30	25					Standard	18KE TF13 BPN


Plugs

RECTUS Series 18KE



Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
G 1/4	17	41		9					Standard	18SF AW13 SXN
G 3/8	19	41		9					Standard	18SF AW17 SXN




Female Thread

G 1/4	17	43		9					Standard	18SF IW13 SXN
G 3/8	19	44		9					Standard	18SF IW17 SXN

Plugs

RECTUS Series 18KE



Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm		56	12	25					Standard	18SF TF06 SXN
8 mm		56	12	25					Standard	18SF TF08 SXN
9 mm		56	12	25					Standard	18SF TF09 SXN
10 mm		56	12	25					Standard	18SF TF10 SXN
13 mm		56	12	25					Standard	18SF TF13 SXN



Self-Venting System

Nominal Diameter

5,5 = 25 mm²



RECTUS Series

23KE

85% of actual size



Technical Description

The 23KE series is a safety coupling with a self venting system. When the sleeve is pulled back the plug is released, however, it still remains locked to the coupling. The coupling's valve closes while the downstream air supply line is vented simultaneously. Afterward it can be disconnected without any danger by pulling the sleeve back a second time to completely release the plug from the coupling.

Advantages

Connected in the same manner as all standard couplings – single hand operation. The venting takes place without any danger to the operators during the disconnecting process – no danger of being hit by a whipping hose that is still pressurized. The system fulfills the requirements stipulated in ISO 4414 for increased safety standards in the working place. Interchangeable with Rectus Series 24.

Working Pressure

PB = 8 bar, maximum static working pressure with safety factor of 4 to 1.

Working temperature

-20°C up to +60°C (NBR) depending on the medium.


Caution

Not recommended for direct connection to compressed air tools. Reliable functioning can only be guaranteed in conjunction with original RECTUS plugs made of steel.

You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Single Shut-off P. 52

Chart



Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals
- Pins

Standard


- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass, Nickel Plated
- Brass
- AISI 301
- AISI 420
- NBR
- AISI 420

Plug


Steel Hardened, Nickel Plated

Couplings

RECTUS Series 23KE



Male Thread




Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
R 1/4	24	65	30	12					Standard	23KE AK13 BPN
R 3/8	25	65	30	12					Standard	23KE AK17 BPN
R 1/2	24	69	30	17					Standard	23KE AK21 BPN
G 1/4	24	61	30	10					Standard	23KE IW13 BPN
G 3/8	24	58	30	9					Standard	23KE IW17 BPN
G 1/2	24	63	30	10					Standard	23KE IW21 BPN

Couplings

RECTUS Series 23KE




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm	24	79	30	25					Standard	23KE TF06 BPN
8 mm	24	79	30	25					Standard	23KE TF08 BPN
10 mm	24	79	30	25					Standard	23KE TF10 BPN
13 mm	24	79	30	25					Standard	23KE TF13 BPN


Plugs

RECTUS Series 23KE



Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
R 1/8	13	39		9					Standard	23SF AK10 SXN
R 1/4	14	42		12					Standard	23SF AK13 SXN
R 3/8	17	42		12					Standard	23SF AK17 SXN
R 1/2	22	48		17					Standard	23SF AK21 SXN




Female Thread

G 1/8	14	36		9					Standard	23SF IW10 SXN
G 1/4	17	36		9					Standard	23SF IW13 SXN
G 3/8	19	36		9					Standard	23SF IW17 SXN
G 1/2	24	36		12					Standard	23SF IW21 SXN

Plugs

RECTUS Series 23KE



Hose Barb

Conenction A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm		51	14	25					Standard	23SF TF06 SXN
8 mm		51	14	25					Standard	23SF TF08 SXN
9 mm		51	14	25					Standard	23SF TF09 SXN
10 mm		51	14	25					Standard	23SF TF10 SXN
13 mm		51	14	25					Standard	23SF TF13 SXN



Self-Venting System

Nominal Diameter

5,5

 = 25 mm²


RECTUS Series

24KE

85% of actual size




You will find the following alternative versions in our current catalogue on page:

► Brass/Steel Single Shut-off P. 58

Technical Description

The connection is made the same way as with all other quick connect coupling series, by simply pushing the plug in the coupling. The audible latching when the plug is securely in place signifies that the coupling is locked. The sleeve must be pulled back to release the first locking system before it can be disconnected. This closes the coupling valve. The compressed downstream air can now escape from the plug (hose). Pulling the sleeve back a second time releases the second locking system. The connection can now be safely undone. This self-venting coupling, designed for bleeding off trapped air, is not suitable for direct connection to compressed air tools.

Chart



Advantages

The system fulfils the requirements of ISO 4414.

- increased safety standards in the work place
- the plastic sleeve does not scratch working surfaces

Caution

Not recommended for direct connection to compressed air tools. Reliable functioning can only be guaranteed in conjunction with original Rectus plugs made of steel.

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Pins
Seals
Locking Balls

Plug

Working Pressure

PB = 12 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature

-20°C up to +60°C (NBR) depending on the medium.


Standard

Brass, Nickel Plated
Brass, Nickel Plated
Thermoplastic
Brass
AISI 301
AISI 420
NBR
AISI 420


Steel Hardened, Nickel Plated

Couplings

RECTUS Series 24KE



Male Thread




Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
R 1/4	22	58	31	9					Standard	24KE AK13 MPN
R 3/8	22	58	31	9					Standard	24KE AK17 MPN
R 1/2	24	63	31	12					Standard	24KE AK21 MPN
G 1/4	22	57	31	9					Standard	24KE IW13 MPN
G 3/8	22	57	31	9					Standard	24KE IW17 MPN

Couplings

RECTUS Series 24KE




Hose Barb

Connction A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm	22	71	31	25					Standard	24KE TF06 MPN
8 mm	22	71	31	25					Standard	24KE TF08 MPN
9 mm	22	71	31	25					Standard	24KE TF09 MPN
10 mm	22	71	31	25					Standard	24KE TF10 MPN
13 mm	22	71	31	25					Standard	24KE TF13 MPN


Plugs

RECTUS Series 23SF



Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
R 1/8	13	39		9					Standard	23SF AK10 SXN
R 1/4	14	42		12					Standard	23SF AK13 SXN
R 3/8	17	42		12					Standard	23SF AK17 SXN
R 1/2	22	48		17					Standard	23SF AK21 SXN




Female Thread

G 1/8	14	36		9					Standard	23SF IW10 SXN
G 1/4	17	36		9					Standard	23SF IW13 SXN
G 3/8	19	36		9					Standard	23SF IW17 SXN
G 1/2	24	36		12					Standard	23SF IW21 SXN

Plugs

RECTUS Series 23SF



Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm		51	14	25					Standard	23SF TF06 SXN
8 mm		51	14	25					Standard	23SF TF08 SXN
9 mm		51	14	25					Standard	23SF TF09 SXN
10 mm		51	14	25					Standard	23SF TF10 SXN
13 mm		51	14	25					Standard	23SF TF13 SXN



Self-Venting System

Nominal Diameter

7,4 = 43 mm²



RECTUS Series

26KE

90% of actual size




You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Single Shut-off P. 66
- ▶ Brass/Steel Double Shut-off P. 136
- ▶ Stainless Steel P. 189

Technical Description

The connection is made the same way as with all other quick connect coupling series, by simply pushing the plug in the coupling. The audible latching when the plug is securely in place signifies that the coupling is locked. The sleeve must be pulled back to release the first locking system before it can be disconnected. This closes the coupling valve. The compressed downstream air can now escape from the plug (hose). Pulling the sleeve back a second time releases the second locking system. The connection can now be safely undone. This self-venting coupling, designed for bleeding off trapped air, is not suitable for direct connection to compressed air tools.

Chart



Advantages

The system fulfils the requirements of ISO 4414.

- increased safety standards in the work place
- the plastic sleeve does not scratch working surfaces

Caution

Not recommended for direct connection to compressed air tools. Reliable functioning can only be guaranteed in conjunction with original Rectus plugs made of steel.

Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring
- Locking Balls
- Seals
- Pin

Plug

Working Pressure

PB = 12 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +60°C (NBR) depending on the medium.

*At a temperature below -20°C and above +60°C special seals are available on request.

Standard

- Brass, Nickel Plated
- Brass, Nickel Plated
- Thermoplastic
- Brass
- AISI 301
- AISI 420
- NBR
- AISI 420

Steel Hardened, Zinc Plated


Couplings

RECTUS Series 26KE

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/4	22	55	31	9					Standard	26KE AW13 MPN
	G 3/8	22	55	31	9					Standard	26KE AW17 MPN
	G 1/2	24	58	31	12					Standard	26KE AW21 MPN
<p>Female Thread</p>	G 1/4	22	57	31	9					Standard	26KE IW13 MPN
	G 3/8	22	57	31	9					Standard	26KE IW17 MPN
	G 1/2	24	60	31	12					Standard	26KE IW21 MPN

Couplings


RECTUS Series 26KE




Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm	22	71	31	25					Standard	26KE TF06 MPN
8 mm	22	71	31	25					Standard	26KE TF08 MPN
9 mm	22	71	31	25					Standard	26KE TF09 MPN
10 mm	22	71	31	25					Standard	26KE TF10 MPN
13 mm	22	71	31	25					Standard	26KE TF13 MPN

Plugs

RECTUS Series 25SF




Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
R 1/8	13	33		9					Standard	25SF AK10 SXZ
R 1/4	14	37		12					Standard	25SF AK13 SXZ
R 3/8	17	37		12					Standard	25SF AK17 SXZ
R 1/2	22	43		17					Standard	25SF AK21 SXZ



G 1/8	14	30		7					Standard	25SF IW10 SXZ
G 1/4	17	33		9					Standard	25SF IW13 SXZ
G 3/8	19	33		9					Standard	25SF IW17 SXZ
G 1/2	24	36		12					Standard	25SF IW21 SXZ

Plugs

RECTUS Series 25SF



Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm		48	12	25					Standard	25SF TF06 SXZ
8 mm		48	12	25					Standard	25SF TF08 SXZ
9 mm		48	12	25					Standard	25SF TF09 SXZ
10 mm		48	12	25					Standard	25SF TF10 SXZ
13 mm		48	12	25					Standard	25SF TF13 SXZ



Self-Venting System

Nominal Diameter

7,8 = 48 mm²

RECTUS Series

25KE

85% of actual size



You will find the following alternative versions in our current catalogue on page:

- ▶ Safety Single Shut-off P. 270
- ▶ Safety Double Shut-off P. 278
- ▶ Coded Systems P. 303
- ▶ Brass/Steel P. 73
- ▶ Stainless Steel P. 192

Technical Description

The 25KE series is a safety coupling with a self venting-system. When the sleeve is pulled back the plug is released, however, it still remains locked to the coupling. The coupling's valve closes while the downstream air supply line is vented simultaneously. Afterward it can be disconnected without any danger by pulling the sleeve back a second time to completely release the plug from the coupling.

Advantages

Connected in the same manner as all standard couplings – single hand operation. The venting takes place without any danger to the operators during the dis-connecting process – no danger of being hit by a whipping hose that is still pressurized. The system fulfils the requirements stipulated in ISO 4414 for increased safety standards in the working place.

Working Pressure


PB = 8 bar, maximum static working pressure with safety factor of 4 to 1.

Working temperature

-20°C up to +60°C (NBR) depending on the medium.

Caution

Not recommended for direct connection to compressed air tools. Reliable functioning can only be guaranteed in conjunction with original Rectus plugs made of steel.

Chart**Material****Coupling**


Back Body
Valve Body
Sleeve
Valve
Spring
Locking Balls
Seals
Pins

Standard


Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
AISI 301
AISI 420
NBR
AISI 420

Plug

Steel Hardened, Zinc Plated

Couplings**RECTUS Series 25KE**

Male Thread




Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
R 1/4	24	62	30	12					Standard	25KE AK13 BPN
R 3/8	24	62	30	12					Standard	25KE AK17 BPN
R 1/2	24	67	30	17					Standard	25KE AK21 BPN
G 1/4	24	59	30	10					Standard	25KE IW13 BPN
G 3/8	24	56	30	9					Standard	25KE IW17 BPN
G 1/2	24	61	30	12					Standard	25KE IW21 BPN

Couplings


RECTUS Series 25KE




Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm	24	76	30	25					Standard	25KE TF06 BPN
8 mm	24	76	30	25					Standard	25KE TF08 BPN
9 mm	24	76	30	25					Standard	25KE TF09 BPN
10 mm	24	76	30	25					Standard	25KE TF10 BPN
13 mm	24	76	30	25					Standard	25KE TF13 BPN

Plugs

RECTUS Series 25KE




Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
R 1/8	13	33		9					Standard	25SF AK10 SXZ
R 1/4	14	37		12					Standard	25SF AK13 SXZ
R 3/8	17	37		12					Standard	25SF AK17 SXZ
R 1/2	22	43		17					Standard	25SF AK21 SXZ



G 1/8	14	30		7					Standard	25SF IW10 SXZ
G 1/4	17	38,5		9					Standard	25SF IW13 SXZ
G 3/8	19	39,5		9					Standard	25SF IW17 SXZ
G 1/2	24	44		12					Standard	25SF IW21 SXZ

Plugs

RECTUS Series 25KE



Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm		48	12	25					Standard	25SF TF06 SXZ
8 mm		48	12	25					Standard	25SF TF08 SXZ
9 mm		48	12	25					Standard	25SF TF09 SXZ
10 mm		48	12	25					Standard	25SF TF10 SXZ
13 mm		48	12	25					Standard	25SF TF13 SXZ



Self-Venting System

Nominal Diameter

10

 = 80 mm²


RECTUS Series

27KE

70% of actual size



You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Single Shut-off P. 95
- ▶ Brass/Steel Double Shut-off P. 145
- ▶ Stainless Steel P. 196

Technical Description

With nominal diameter 10, one of the largest range in a new generation of couplings with ventilation technology. Two-stage uncoupling prevents occurrence of the whiplash effect.

Advantages

Connected in the same manner as all standard couplings – single hand operation. The venting takes place without any danger to the operators during the disconnecting process – no danger of being hit by a whipping hose that is still pressurized. The system fulfils the requirements stipulated in ISO 4414 for increased safety standards in the working place.

Working Pressure

PB = 12 bar, maximum static working pressure with safety factor of 4 to 1.

Working temperature

-20°C up to +60°C (NBR) depending on the medium.

Caution

Not recommended for direct connection to compressed air tools. Reliable functioning can only be guaranteed in conjunction with original RECTUS plugs made of steel.

Material Coupling

Back Body
Valve Body
Sleeve
Valve
Spring
Locking Balls
Seals


Standard

Brass, Nickel Plated
Brass, Nickel Plated
Polyamide, fiber glass reinforced
Brass
AISI 301
AISI 420
NBR

Plug

Steel Hardened, Nickel Plated

Chart



Couplings

RECTUS Series 27KE


	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 3/8	27	79	38	9					Standard	27KE AK17 MPN
	R 1/2	27	80,5	38	12					Standard	27KE AK21 MPN
	R 3/4	32	86	38	16					Standard	27KE AK26 MPN
<p>Female Thread</p>	G 3/8	27	83	38	14					Standard	27KE IW17 MPN
	G 1/2	27	84	38	14					Standard	27KE IW21 MPN
	G 3/4	32	86	38	14					Standard	27KE IW26 MPN

Plugs

RECTUS Series 27KE

Safety

Low Pressure




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
6 mm		48	15	25					Standard	27SF TF06 SXN
8 mm		48	15	25					Standard	27SF TF08 SXN
9 mm		48	15	25					Standard	27SF TF09 SXN
10 mm		48	15	25					Standard	27SF TF10 SXN
13 mm		48	15	25					Standard	27SF TF13 SXN
16 mm		49	18	25					Standard	27SF TF16 SXN
19 mm		49	18	25					Standard	27SF TF19 SXN

Plugs

RECTUS Series 27KE



Male Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
R 1/4	17	40		12					Standard	27SF AK13 SXN
R 3/8	17	40		12					Standard	27SF AK17 SXN
R 1/2	22	45		17					Standard	27SF AK21 SXN
R 3/4	27	48		19					Standard	27SF AK26 SXN
G 1/4	17	33		9					Standard	27SF IW13 SXN
G 3/8	19	33		9					Standard	27SF IW17 SXN
G 1/2	24	37		12					Standard	27SF IW21 SXN
G 3/4	32	42		16					Standard	27SF IW26 SXN



Female Thread



Self-Venting System

Nominal Diameter

11 = 95 mm²

RECTUS Series

37KE



70% of actual size



Technical Description

The 37KE series is a single shut-off one-hand operating self-venting coupling. The large nominal diameter makes the 37KE especially suited to mains and supply pipes. Coupling is achieved in the same way as with all series couplings – simply by pushing the plug into the coupling. When uncoupling, the first lock is released by pulling the sleeve forward in the direction of the plug. This allows the compressed air to escape from the plug. The second locking system is released by pushing the sleeve back – it is only now, that the plug can be taken out safely.

Advantages

The system fulfils the requirements of ISO 4414.
 - increased safety standards in the work place
 - the plastic sleeve does not scratch working surfaces

Caution

Not recommended for direct connection to compressed air tools. Reliable functioning can only be guaranteed in conjunction with original Rectus plugs made of steel.

Working Pressure

PB = 12 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature


-20°C up to +60°C (NBR) depending on the medium.

You will find the following alternative versions in our current catalogue on page:

► Brass/Steel

S. 109

Chart



Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring
- Locking Balls
- Seals
- Pins

Standard


- Brass, Nickel Plated
- Brass, Nickel Plated
- Thermoplastic
- Brass
- AISI 301
- AISI 420
- NBR
- AISI 420

Plug

Steel Zinc Plated, Thick Layer Passivation, Yellow Colored

Couplings

RECTUS Series 37KE





Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
G1/2	30	93	43	14					Standard	37KE IW21 MPNS_01
G 3/4	32	95	43	16					Standard	37KE IW26 MPNS_01


Plugs

RECTUS Series 37KE

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 3/8	17	53	12						Standard	37SF AK17 SXG
	R 1/2	22	60	17						Standard	37SF AK21 SXG
	R 3/4	27	61	19						Standard	37SF AK26 SXG
 <p>Female Thread</p>	G 3/8	19	47	8						Standard	37SF IW17 SXG
	G 1/2	24	50	10						Standard	37SF IW21 SXG
	G 3/4	32	57	14						Standard	37SF IW26 SXG

Plugs

RECTUS Series 37KE

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	H mm	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	10 mm		62	17	25					Standard	37SF TF10 SXG
	13 mm		62	17	25					Standard	37SF TF13 SXG
	19 mm		72	21	35					Standard	37SF TF19 SXG



Breathing Air

Nominal Diameter

7,4 = 43 mm²

RECTUS Series

95KS



90% of actual size



Technical Description

The 95KS coupling system has a safety lock. To disconnect, the plug must first be pushed further into the coupling before it can be unlocked. This prevents unintentional disconnection.

Dust Caps (P. 331)
for coupling Part.-No. SK23S



Advantages

Disconnecting the safety coupling is only possible after the plug has first been pushed further into the coupling. Cannot be interconnected with the 96KS series. Single handed operation with a multitude of connecting possibilities. High flow rates due to the UltraFlo valve. Tested according EN 139 standard.

Working Pressure


PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



Material

Standard

AISI 303 / Brass

Coupling

Back Body
Valve Body
Sleeve
Valve

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Zinc Diecasting,
Nickel Plated

Brass, Nickel Plated
AISI 303
Brass, Nickel Plated
Zinc Diecasting,
Nickel Plated

Spring and Locking
Ring
Locking Balls
Seals
Distance Sleeve
Spring Plate

AISI 301
AISI 420
NBR
Brass
Brass

AISI 301
AISI 420
NBR
AISI 303
Brass

Plug

Plug

Brass, Nickel Plated


Couplings

RECTUS Series 95KS

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	61	23	12					Standard	95KS AK13 BPN
										AISI 303/Brass	95KS AK13 RPN
	R 3/8	19	60	23	12					Standard	95KS AK17 BPN
										AISI 303/Brass	95KS AK17 RPN
<p>Female Thread</p>	R 1/2	22	61	23	17					Standard	95KS AK21 BPN
										AISI 303/Brass	95KS AK21 RPN
	G 1/4	19	56	23	10					Standard	95KS IW13 BPN
										AISI 303/Brass	95KS IW13 RPN
	G 3/8	19	55	23	9					Standard	95KS IW17 BPN
										AISI 303/Brass	95KS IW17 RPN
	G 1/2	24	58	23	12					Standard	95KS IW21 BPN
										AISI 303/Brass	95KS IW21 RPN

Couplings

RECTUS Series 95KS




Hose Barb


Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW	B mm	G mm	Version	Part Number
6 mm	19	74	23	25					Standard	95KS TF06 BPN
									AISI 303/Brass	95KS TF06 RPN
7 mm	20	77	23	22					Standard	95KS TF07 BPN
									AISI 303/Brass	95KS TF07 RPN
8 mm	19	74	23	25					Standard	95KS TF08 BPN
									AISI 303/Brass	95KS TF08 RPN
9 mm	19	74	23	25					Standard	95KS TF09 BPN
									AISI 303/Brass	95KS TF09 RPN
10 mm	19	74	23	25					Standard	95KS TF10 BPN
									AISI 303/Brass	95KS TF10 RPN
13 mm	19	74	23	25					Standard	95KS TF13 BPN
									AISI 303/Brass	95KS TF13 RPN

Plugs

RECTUS Series 95KS



Male Thread




Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW	B mm	G mm	Version	Part Number
R 1/4	14	38,5		12					Standard	95SS AK13 MXN
R 3/8	17	38,5		12					Standard	95SS AK17 MXN
G 1/4	17	33		9					Standard	95SS IW13 MXN
G 3/8	19	33		9					Standard	95SS IW17 MXN

Plugs

RECTUS Series 95KS



Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW	B mm	G mm	Version	Part Number
6 mm		47,5	14	25					Standard	95SS TF06 MXN
9 mm		47,5	14	25					Standard	95SS TF09 MXN
10 mm		47,5	14	25					Standard	95SS TF10 MXN



Breathing Air

Nominal Diameter

7,4 = 43 mm²

RECTUS Series

96KS



90% of actual size



Technical Description

The 96KS coupling system has a safety lock. To disconnect, the plug must first be pushed further into the coupling before it can be unlocked. This prevents unintentional disconnection.

Dust Caps (P. 331)

for coupling Part.-No. SK23S
for plug Part.-No. SK12S



Advantages

Disconnecting the safety coupling is only possible after the plug has first been pushed further into the coupling. Single handed operation with a multitude of connecting possibilities. High flow rates due to the UltraFlo valve. Tested according EN 139 standard.

Working Pressure


PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
0°C up to +316°C (FFKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



Material

Coupling

Back Body
Valve Body
Sleeve
Valve

Spring and Locking Ring
Locking Balls
Seals
Distance Sleeve
Spring Plate

Plug

Plug

Standard

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Zinc Diecasting, Nickel Plated
AISI 301
AISI 420
NB
Brass
Brass

AISI 303

AISI 303
AISI 303
AISI 303
AISI 303
AISI 301
AISI 316
FKM
AISI 303
AISI 303

Brass, Nickel Plated

AISI 303

Couplings


RECTUS Series 96KS

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19	65	23	12					Standard	96KS AK13 BPN
	R 3/8	19	64	23	12					Standard	96KS AK17 BPN
	G 3/8	19	62	23	9					AISI 303	96KS AW17 RVX
	R 1/2	22	66	23	17					Standard	96KS AK21 BPN
<p>Female Thread</p>	G 1/4	19	60	23	10					Standard	96KS IW13 BPN
	G 3/8	19	59	23	9					Standard	96KS IW17 BPN

Couplings

RECTUS Series 96KS



Connection A	Hex	L	D	L1	L2	Hex1	B	G	Version	Part Number
	SW	mm	mm	mm	mm	SW	mm	mm		
6 mm	19	78	23	25					Standard	96KS TF06 BPN
7 mm	20	77	23	22					Standard	96KS TF07 BPN
9 mm	19	78	23	25					Standard	96KS TF09 BPN
10 mm	19	78	23	25					Standard	96KS TF10 BPN
13 mm	19	78	23	25					Standard	96KS TF13 BPN



Plugs

RECTUS Series 96KS


Connection A	Hex	L	D	L1	L2	Hex1	B	G	Version	Part Number
	mm	mm	mm	mm	mm	mm	mm	mm		
R 1/4	14	42		12					Standard	96SS AK13 MXN
R 3/8	17	42		12					Standard	96SS AK17 MXN
G 3/8	19	38		9					AISI 303	96SS AW17 RXX
G 1/4	17	38		10					Standard	96SS IW13 MXN
G 3/8	19	38		10					Standard	96SS IW17 MXN



Plugs

RECTUS Series 96KS

Connection A	Hex	L	D	L1	L2	Hex1	B	G	Version	Part Number
	SW	mm	mm	mm	mm	SW	mm	mm		
6 mm		51	12	25					Standard	96SS TF06 MXN
9 mm		51	12	25					Standard	96SS TF09 MXN
13 mm		53	12	25					Standard	96SS TF13 MXN





Nominal Diameter

5 = 20 mm²

RECTUS Series

21KA





50% of actual size



Technical Description

The 21 KA series is a small, single hand operated quick connect coupling with high air flow. This series has excellent capabilities wherever space plays a major role. The 21 series provides an excellent solution for the connecting of different media with the inherent danger of making the wrong connection. Four standard codes with matching colors for the coupling and the respective plugs make sure there is no mix-up of the media

Chart



You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel P. 34
- ▶ Stainless Steel P. 185
- ▶ Thermoplastics P. 242
- ▶ Safety P. 266

when connecting. Double shut-off and straight through couplings are available on request.

Advantages

A quality coupling with small dimensions. Single handed operation, high flow rate for its size. Multiple connection options. Cannot be inter-connected with the standard 21 series.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature

-20°C up to +100°C (NBR) depending on the medium.

Dust Caps (P. 331)

for coupling Part.-No. SK16S

Material

Coupling

Back Body
Valve Body
Sleeve
Valve
Spring and
Locking Ring
Locking Balls
Seals

Standard

Brass
Brass
Aluminium, elox.
Brass
AISI 301

AISI 420
NBR

Brass, Nickel plated

Brass, Nickel Plated
Brass, Nickel Plated
Aluminium, elox.
Brass
AISI 301

AISI 420
NBR

Plug

Brass
with anodized aluminium designation

Brass, Nickel Plated
with anodized aluminium designation

see Part Number
MPX, MXX

see Part Number
MPN, MXN




Couplings

RECTUS Series 21KA

	A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	○	△	◇	○	
										green Part Number	brown Part Number	blue Part Number	red Part Number	
<p>Male Thread</p>	G 1/8	14	44,9	16	7					21KA AW10 MPX0	21KA AW10 MPX3	21KA AW10 MPX6	21KA AW10 MPX8	
										21KA AW10 MPN0	21KA AW10 MPN3	21KA AW10 MPN6	21KA AW10 MPN8	
	G 1/4	17	47	16	9						21KA AW13 MPX0	21KA AW13 MPX3	21KA AW13 MPX6	21KA AW13 MPX8
											21KA AW13 MPN0	21KA AW13 MPN3	21KA AW13 MPN6	21KA AW13 MPN8
<p>Female Thread</p>	G 1/8	14	44,9	16	7					21KA IW10 MPX0	21KA IW10 MPX3	21KA IW10 MPX6	21KA IW10 MPX8	
										21KA IW10 MPN0	21KA IW10 MPN3	21KA IW10 MPN6	21KA IW10 MPN8	
	G 1/4	17	47	16	9						21KA IW13 MPX0	21KA IW13 MPX3	21KA IW13 MPX6	21KA IW13 MPX8
											21KA IW13 MPN0	21KA IW13 MPN3	21KA IW13 MPN6	21KA IW13 MPN8




Couplings

RECTUS Series 21KA

	A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	○ green Part Number	△ brown Part Number	⬡ blue Part Number	○ red Part Number
 <p>Hose Barb</p>	4 mm	14	69	16	17					21KA TF04 MPX0	21KA TF04 MPX3	21KA TF04 MPX6	21KA TF04 MPX8
	4 mm	14	69	16	17					21KA TF04 MPN0	21KA TF04 MPN3	21KA TF04 MPN6	21KA TF04 MPN8
	6 mm	14	69	16	17					21KA TF06 MPX0	21KA TF06 MPX3	21KA TF06 MPX6	21KA TF06 MPX8
	6 mm	14	69	16	17					21KA TF06 MPN0	21KA TF06 MPN3	21KA TF06 MPN6	21KA TF06 MPN8
	8 mm	14	69	16	17					21KA TF08 MPX0	21KA TF08 MPX3	21KA TF08 MPX6	21KA TF08 MPX8
	8 mm	14	69	16	17					21KA TF08 MPN0	21KA TF08 MPN3	21KA TF08 MPN6	21KA TF08 MPN8
	9 mm	14	69	16	17					21KA TF09 MPX0	21KA TF09 MPX3	21KA TF09 MPX6	21KA TF09 MPX8
	9 mm	14	69	16	17					21KA TF09 MPN0	21KA TF09 MPN3	21KA TF09 MPN6	21KA TF09 MPN8
	10 mm	14	69	16	17					21KA TF10 MPX0	21KA TF10 MPX3	21KA TF10 MPX6	21KA TF10 MPX8
	10 mm	14	69	16	17					21KA TF10 MPN0	21KA TF10 MPN3	21KA TF10 MPN6	21KA TF10 MPN8
 <p>Plastic Hose Connection</p>	4x6mm	14	51	16	7	6			M 10 x 1	21KA KO06 MPX0	21KA KO06 MPX3	21KA KO06 MPX6	21KA KO06 MPX8
										21KA KO06 MPN0	21KA KO06 MPN3	21KA KO06 MPN6	21KA KO06 MPN8
	6x8mm	14	51	16	7	6			M 12 x 1	21KA KO08 MPX0	21KA KO08 MPX3	21KA KO08 MPX6	21KA KO08 MPX8
										21KA KO08 MPN0	21KA KO08 MPN3	21KA KO08 MPN6	21KA KO08 MPN8
 <p>Bulkhead Fitting for Hose Barb</p>	4 mm	14	69	16	14	17	14	4	M 10 x 1	21KA TS04 MPX0	21KA TS04 MPX3	21KA TS04 MPX6	21KA TS04 MPX8
										21KA TS04 MPN0	21KA TS04 MPN3	21KA TS04 MPN6	21KA TS04 MPN8
	5 mm	14	69	16	14	17	17	4	M 12 x 1	21KA TS05 MPX0	21KA TS05 MPX3	21KA TS05 MPX6	21KA TS05 MPX8
										21KA TS05 MPN0	21KA TS05 MPN3	21KA TS05 MPN6	21KA TS05 MPN8
	6 mm	14	69	16	14	17	17	4	M 12 x 1	21KA TS06 MPX0	21KA TS06 MPX3	21KA TS06 MPX6	21KA TS06 MPX8
										21KA TS06 MPN0	21KA TS06 MPN3	21KA TS06 MPN6	21KA TS06 MPN8
	8 mm	14	69	16	14	17	17	4	M 12 x 1	21KA TS08 MPX0	21KA TS08 MPX3	21KA TS08 MPX6	21KA TS08 MPX8
										21KA TS08 MPN0	21KA TS08 MPN3	21KA TS08 MPN6	21KA TS08 MPN8



Plugs


RECTUS Series 21KA

	A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	○ green Part Number	△ brown Part Number	⬡ blue Part Number	○ red Part Number
 <p>Hose Barb</p>	4 mm		47	15	17					21SF TF04 MXX0	21SF TF04 MXX3	21SF TF04 MXX6	21SF TF04 MXX8
										21SF TF04 MXN0	21SF TF04 MXN3	21SF TF04 MXN6	21SF TF04 MXN8
	6 mm		47	15	17					21SF TF06 MXX0	21SF TF06 MXX3	21SF TF06 MXX6	21SF TF06 MXX8
										21SF TF06 MXN0	21SF TF06 MXN3	21SF TF06 MXN6	21SF TF06 MXN8
 <p>Plastic Hose Connection</p>	4x6 mm		43	15	7	6			M 10 x 1	21SF KO06 MXX0	21SF KO06 MXX3	21SF KO06 MXX6	21SF KO06 MXX8
										21SF KO06 MXN0	21SF KO06 MXN3	21SF KO06 MXN6	21SF KO06 MXN8
	6x8 mm		43,5	15	7	6			M 12 x 1	21SF KO08 MXX0	21SF KO08 MXX3	21SF KO08 MXX6	21SF KO08 MXX8
										21SF KO08 MXN0	21SF KO08 MXN3	21SF KO08 MXN6	21SF KO08 MXN8
 <p>Bulkhead Fitting for Hose Barb</p>	4 mm	17	63		17	14	14	4	M 10 x 1	21SF TS04 MXX0	21SF TS04 MXX3	21SF TS04 MXX6	21SF TS04 MXX8
										21SF TS04 MXN0	21SF TS04 MXN3	21SF TS04 MXN6	21SF TS04 MXN8
	6 mm	17	63		17	14	17	4	M 12 x 1	21SF TS06 MXX0	21SF TS06 MXX3	21SF TS06 MXX6	21SF TS06 MXX8
										21SF TS06 MXN0	21SF TS06 MXN3	21SF TS06 MXN6	21SF TS06 MXN8

⚠ Please consider our security advices on the pages 12/13 ⚠

Plugs **RECTUS Series 21KA**

	A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	○ green Part Number	△ brown Part Number	⬡ blue Part Number	⬢ red Part Number
 Male Thread	G 1/8	17	39,5	7						21SF AW10 MXX0	21SF AW10 MXX3	21SF AW10 MXX6	21SF AW10 MXX8
										21SF AW10 MXN0	21SF AW10 MXN3	21SF AW10 MXN6	21SF AW10 MXN8
	G 1/4	17	41,5	9						21SF AW13 MXX0	21SF AW13 MXX3	21SF AW13 MXX6	21SF AW13 MXX8
										21SF AW13 MXN0	21SF AW13 MXN3	21SF AW13 MXN6	21SF AW13 MXN8
 Female Thread	G 1/8	17	38,5	5						21SF IW10 MXX0	21SF IW10 MXX3	21SF IW10 MXX6	21SF IW10 MXX8
										21SF IW10 MXN0	21SF IW10 MXN3	21SF IW10 MXN6	21SF IW10 MXN8
	G 1/4	17	39	7						21SF IW13 MXX0	21SF IW13 MXX3	21SF IW13 MXX6	21SF IW13 MXX8
										21SF IW13 MXN0	21SF IW13 MXN3	21SF IW13 MXN6	21SF IW13 MXN8



Technical Description

The 25 series UltraFlo valve enables this single handed, quick connect coupling to be used in applications where higher flow rates are required. Although similar to the 21 series, the 25 series is an excellent solution for the problem of connecting different media. Four standard codes matching the coupling and the respective plug ensure that media are not mixed up

when connecting. Double shut-off and straight- through couplings are available upon request. Cannot be interconnected with the Rectus standard 25 series.

Advantages

A quality coupling with compact dimensions. Single handed operation, high flow rate for its size. Multiple options for connecting.



Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature

-20°C up to +100°C (NBR) depending on the medium.

Chart



Material

Coupling

Back Body
Valve Body
Sleeve
Valve

Spring and Locking Ring
Locking Balls
Seals

Plug

Standard

Brass
Brass
Aluminium, elox.
Zinc Diecasting, Nickel Plated
AISI 301

AISI 420
NBR

**see Part Number
BPX, MXX**

Brass, Nickel plated

Brass, Nickel Plated
Brass, Nickel Plated
Aluminium, elox.
Zinc Diecasting, Nickel Plated
AISI 301

AISI 420
NBR

Brass, Nickel Plated with anodized aluminium designation

**see Part Number
BPN, MXN**





You will find the following alternative versions in our current catalogue on page:


- ▶ Brass/Steel P. 73
- ▶ Stainless Steel P. 192
- ▶ Safety P. 270
- ▶ Safety Self-Venting P. 290

Couplings



RECTUS Series 25KA

	A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	○ green Part Number	△ brown Part Number	◇ blue Part Number	○ red Part Number
 <p>Male Thread</p>	G 1/4	19	57,5	23	12					25KA AW13 BPX0	25KA AW13 BPX3	25KA AW13 BPX6	25KA AW13 BPX8
										25KA AW13 BPN0	25KA AW13 BPN3	25KA AW13 BPN6	25KA AW13 BPN8
	G 3/8	19	57,5	23	12					25KA AW17 BPX0	25KA AW17 BPX3	25KA AW17 BPX6	25KA AW17 BPX8
										25KA AW17 BPN0	25KA AW17 BPN3	25KA AW17 BPN6	25KA AW17 BPN8
	G 1/2	22	61	23	17					25KA AW21 BPX0	25KA AW21 BPX3	25KA AW21 BPX6	25KA AW21 BPX8
										25KA AW21 BPN0	25KA AW21 BPN3	25KA AW21 BPN6	25KA AW21 BPN8
 <p>Female Thread</p>	G 1/4	19	55	23	10					25KA IW13 BPX0	25KA IW13 BPX3	25KA IW13 BPX6	25KA IW13 BPX8
										25KA IW13 BPN0	25KA IW13 BPN3	25KA IW13 BPN6	25KA IW13 BPN8
	G 3/8	19	55	23	9					25KA IW17 BPX0	25KA IW17 BPX3	25KA IW17 BPX6	25KA IW17 BPX8
										25KA IW17 BPN0	25KA IW17 BPN3	25KA IW17 BPN6	25KA IW17 BPN8
	G 1/2	24	58	23	12					25KA IW21 BPX0	25KA IW21 BPX3	25KA IW21 BPX6	25KA IW21 BPX8
										25KA IW21 BPN0	25KA IW21 BPN3	25KA IW21 BPN6	25KA IW21 BPN8


Couplings RECTUS Series 25KA

	A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	○ green Part Number	△ brown Part Number	⬡ blue Part Number	⊙ red Part Number
 <p>Hose Barb</p>	6 mm	19	74	23	25					25KA TF06 BPX0 25KA TF06 BPN0	25KA TF06 BPX3 25KA TF06 BPN3	25KA TF06 BPX6 25KA TF06 BPN6	25KA TF06 BPX8 25KA TF06 BPN8
	9 mm	19	74	23	25					25KA TF09 BPX0 25KA TF09 BPN0	25KA TF09 BPX3 25KA TF09 BPN3	25KA TF09 BPX6 25KA TF09 BPN6	25KA TF09 BPX8 25KA TF09 BPN8
	13 mm	19	74	23	25					25KA TF13 BPX0 25KA TF13 BPN0	25KA TF13 BPX3 25KA TF13 BPN3	25KA TF13 BPX6 25KA TF13 BPN6	25KA TF13 BPX8 25KA TF13 BPN8
	6x8mm	19	61	23	7	6			M 12 x 1	25KA KO08 BPX0 25KA KO08 BPN0	25KA KO08 BPX3 25KA KO08 BPN3	25KA KO08 BPX6 25KA KO08 BPN6	25KA KO08 BPX8 25KA KO08 BPN8
	8x10mm		65		9	8			M 16 x 1	25KA KO10 BPX0 25KA KO10 BPN0	25KA KO10 BPX3 25KA KO10 BPN3	25KA KO10 BPX6 25KA KO10 BPN6	25KA KO10 BPX8 25KA KO10 BPN8
	10x12mm		65		9	8			M 16 x 1	25KA KO12 BPX0 25KA KO12 BPN0	25KA KO12 BPX3 25KA KO12 BPN3	25KA KO12 BPX6 25KA KO12 BPN6	25KA KO12 BPX8 25KA KO12 BPN8

Plugs RECTUS Series 25KA


	A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	○ green Part Number	△ brown Part Number	⬡ blue Part Number	⊙ red Part Number
 <p>Hose Barb</p>	6 mm		50,5	15	25					26SF TF06 MXX0 26SF TF06 MXN0	26SF TF06 MXX3 26SF TF06 MXN3	26SF TF06 MXX6 26SF TF06 MXN6	26SF TF06 MXX8 26SF TF06 MXN8
	9 mm		50,5	15	25					26SF TF09 MXX0 26SF TF09 MXN0	26SF TF09 MXX3 26SF TF09 MXN3	26SF TF09 MXX6 26SF TF09 MXN6	26SF TF09 MXX8 26SF TF09 MXN8
	13 mm		50,5	15	25					26SF TF13 MXX0 26SF TF13 MXN0	26SF TF13 MXX3 26SF TF13 MXN3	26SF TF13 MXX6 26SF TF13 MXN6	26SF TF13 MXX8 26SF TF13 MXN8
	6x8 mm		43,5		7	6			M 12 x 1	26SF KO08 MXX0 26SF KO08 MXN0	26SF KO08 MXX3 26SF KO08 MXN3	26SF KO08 MXX6 26SF KO08 MXN6	26SF KO08 MXX8 26SF KO08 MXN8
	8x10 mm	17	43,5		8,5	8,5			M 16 x 1	26SF KO10 MXX0 26SF KO10 MXN0	26SF KO10 MXX3 26SF KO10 MXN3	26SF KO10 MXX6 26SF KO10 MXN6	26SF KO10 MXX8 26SF KO10 MXN8
	8x10 mm												
 <p>Plastic Hose Connection</p>	6 mm		60		17	14	17	4	M 12 x 1	26SF TS06 MXX0 26SF TS06 MXN0	26SF TS06 MXX3 26SF TS06 MXN3	26SF TS06 MXX6 26SF TS06 MXN6	26SF TS06 MXX8 26SF TS06 MXN8
	9 mm		60		17	14	17	4	M 14 x 1	26SF TS09 MXX0 26SF TS09 MXN0	26SF TS09 MXX3 26SF TS09 MXN3	26SF TS09 MXX6 26SF TS09 MXN6	26SF TS09 MXX8 26SF TS09 MXN8
	13 mm		60		25	14	19	4	M 16 x 1	26SF TS13 MXX0 26SF TS13 MXN0	26SF TS13 MXX3 26SF TS13 MXN3	26SF TS13 MXX6 26SF TS13 MXN6	26SF TS13 MXX8 26SF TS13 MXN8
	6 mm	17	60		17	14	17	4	M 12 x 1	26SF TS06 MXX0 26SF TS06 MXN0	26SF TS06 MXX3 26SF TS06 MXN3	26SF TS06 MXX6 26SF TS06 MXN6	26SF TS06 MXX8 26SF TS06 MXN8
	9 mm	17	60		17	14	17	4	M 14 x 1	26SF TS09 MXX0 26SF TS09 MXN0	26SF TS09 MXX3 26SF TS09 MXN3	26SF TS09 MXX6 26SF TS09 MXN6	26SF TS09 MXX8 26SF TS09 MXN8
	13 mm	17	60		25	14	19	4	M 16 x 1	26SF TS13 MXX0 26SF TS13 MXN0	26SF TS13 MXX3 26SF TS13 MXN3	26SF TS13 MXX6 26SF TS13 MXN6	26SF TS13 MXX8 26SF TS13 MXN8

Plugs RECTUS Series 25KA

	A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	○ green Part Number	△ brown Part Number	⬡ blue Part Number	⊙ red Part Number	
 <p>Male Thread</p>	G 1/4	17	36,5		9					26SF AW13 MXX0 26SF AW13 MXN0	26SF AW13 MXX3 26SF AW13 MXN3	26SF AW13 MXX6 26SF AW13 MXN6	26SF AW13 MXX8 26SF AW13 MXN8	
	G 3/8	19	41,5		12					26SF AW17 MXX0 26SF AW17 MXN0	26SF AW17 MXX3 26SF AW17 MXN3	26SF AW17 MXX6 26SF AW17 MXN6	26SF AW17 MXX8 26SF AW17 MXN8	


Plugs

RECTUS Series 25KA



Female Thread

A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	○ green Part Number	△ brown Part Number	⬡ blue Part Number	⊙ red Part Number
G 1/4	17	36,5	8						26SF IW13 MXX0	26SF IW13 MXX3	26SF IW13 MXX6	26SF IW13 MXX8
									26SF IW13 MXN0	26SF IW13 MXN3	26SF IW13 MXN6	26SF IW13 MXN8
G 3/8	19	36,5	8						26SF IW17 MXX0	26SF IW17 MXX3	26SF IW17 MXX6	26SF IW17 MXX8
									26SF IW17 MXN0	26SF IW17 MXN3	26SF IW17 MXN6	26SF IW17 MXN8



Nominal Diameter

7,4 = 42 mm²



RECTUS Series

65-67

35% of actual size



Technical Description

The 65-67 series are quick connect couplings designed for use as pressure regulators for fuel, gas and oxygen as well as welding torches.

Advantages

Our „RectuKey“ coding system prevents mixing up media. Up to three different media can be safely (non-interchangeable) connected with the standard version. The 65 - 67 series can be equipped with both a safety locking system (ensures that an unintentional disconnection cannot occur) as well as without a safety locking system.



Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature

-20°C up to +100°C (NBR) depending on the medium.

Chart



Material

Coupling

- Valve Body
- Sleeve
- Back Body
- Valve
- Spring and Locking Ring
- Locking Balls

Standard


- Brass, ungreased
- Brass, ungreased
- Brass, ungreased
- Brass, ungreased
- AISI 301
- AISI 420

Plug

- Brass, ungreased
- Dust Cap on request

Couplings

RECTUS Series 65-67




Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
Oxygen										
G 1/4 right	19	69,5	22	10					Standard	65KS IW13 MVX
G 3/8 right	19	69,5	22	9					Standard	65KS IW17 MVX
Fuel gas										
G 1/4 left	19	69,5	22	10					Standard	66KS IL13 MEX
G 3/8 left	19	69,5	22	10					Standard	66KS IL17 MEX
Var. Media										
G 1/4 left	19	69,5	22	10					Standard	67KS IL13 MVX
G 3/8 left	19	69,5	22	10					Standard	67KS IL17 MVX

Couplings

RECTUS Series 65-67




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
Oxygen										
6 mm	19	90	22	33					Standard	65KS TF06 MVX
9 mm	19	90	22	33					Standard	65KS TF09 MVX
Fuel gas										
6 mm	19	90	22	33					Standard	66KS TF06 MEX
9 mm	19	90	22	33					Standard	66KS TF09 MEX
Var. Media										
6 mm	19	90	22	33					Standard	67KS TF06 MVX
9 mm	19	90	22	33					Standard	67KS TF09 MVX

Plugs

RECTUS Series 65-67




Hose Barb

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
Oxygen										
6 mm		60		28					Standard	65SS TF06 MXX
9 mm		60		28					Standard	65SS TF09 MXX
Fuel gas										
6 mm		60		28					Standard	66SS TF06 MXX
9 mm		60		28					Standard	66SS TF09 MXX
Var. Media										
6 mm		60		28					Standard	67SS TF06 MXX
9 mm		60		28					Standard	67SS TF09 MXX

Plugs

RECTUS Series 65-67



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
Oxygen										
G 1/4 right	17	46		10					Standard	65SS IW13 MXX
G 3/8 right	19	46		10					Standard	65SS IW17 MXX
Fuel gas										
G 1/4 left	17	46		10					Standard	66SS IL13 MXX
G 3/8 left	19	46		10					Standard	66SS IL17 MXX
Var. Media										
G 1/4 left	17	46		10					Standard	67SS IL13 MXX
G 3/8 left	19	46		10					Standard	67SS IL17 MXX



Nominal Diameter

8 = 50 mm²

RECTUS Series

99KL



60% of actual size



Technical Description

Dry-Break, unmistakable system. During the connection process, the plug and the coupling seals before both valves open. The valves close simultaneously when disconnected, allowing the coupling and plug to be separated afterward. This ensures minimum leakage. Coded via two lateral grooves on the plug and a similar guide in the coupling, which are arranged in different angular

degrees. Particularly suitable for liquid and aggressive media especially for High Purity Applications.

Advantages

Single handed operation. 8-way coding. All individual parts are electro-burnished.

Working Pressure



PB = 6 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-0°C up to +316°C (FFKM) depending on the medium.

Information about the plug Protection Cap (Part-No. SK 99 EXXS) on request.

Chart



You will find the following alternative versions in our current catalogue on page:

► Stainless Steel Dry-Break P. 232

Material

Coupling

- Back Body
- Valve Body
- Sleeve
- Valve
- Spring and Locking Ring
- Locking Balls
- Seals
- Valve Stem Guide
- Threaded Nut

AISI 316 L

- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 316 L
- AISI 301
- AISI 316 L
- FFKM 4079
- PTFE
- AISI 316 L


Plug

- Plug Profile
- Valve Stem Guide
- Valve
- Spring
- Seals
- Threaded Nut

- AISI 316 L
- PTFE
- AISI 316 L
- AISI 301
- FFKM 4079
- AISI 316 L


Couplings

RECTUS Series 99 KL



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
M 30 x 2/30°	34	97	45	10					AISI 316 L	99KL IM30 EKX30
M 30 x 2/45°									AISI 316 L	99KL IM30 EKX45
M 30 x 2/60°									AISI 316 L	99KL IM30 EKX60
M 30 x 2/75°									AISI 316 L	99KL IM30 EKX75
M 30 x 2/90°									AISI 316 L	99KL IM30 EKX90
M 30 x 2/105°									AISI 316 L	99KL IM30 EKX105
M 30 x 2/120°									AISI 316 L	99KL IM30 EKX120
M 30 x 2/150°									AISI 316 L	99KL IM30 EKX150



Female Thread

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
M 30 x 2/30°	34	57		9					AISI 316 L	99SL IM30 EKX30
M 30 x 2/45°									AISI 316 L	99SL IM30 EKX45
M 30 x 2/60°									AISI 316 L	99SL IM30 EKX60
M 30 x 2/75°									AISI 316 L	99SL IM30 EKX75
M 30 x 2/90°									AISI 316 L	99SL IM30 EKX90
M 30 x 2/105°									AISI 316 L	99SL IM30 EKX105
M 30 x 2/120°									AISI 316 L	99SL IM30 EKX120
M 30 x 2/150°									AISI 316 L	99SL IM30 EKX150

RectuTest



Detect power losses. Cut costs. Assign the true consumption to the right cost centre. Keep your compressed air system under control with RectuTest.

Determining the exact consumption of compressed air used to be a costly venture and was often rejected for investment reasons. It was also difficult to assess the effectiveness and level of efficiency of the compressed air tools used.

The RectuTest RT02 unit measures the flow of compressed air through pipelines. It determines the current volume flow with an accuracy level of approx. 2,5% of the measured value.

A specially developed nozzle is used to create a small pressure drop in the through-flow. This so-called effective pressure is a

measure of the current flow volume. The exact standard volume flow is determined through simultaneous measurement of the medium temperature and the system pressures in the pressure line.

With its integrated display, the microprocessor-controlled RectuTest RT02 shows either the current volume flow in standard l/min or standard m³/h. Further display options are: compressed air consumption in m³/h, system pressure in bar and system temperature in °C.

The network function is specially integrated for several permanently installed devices. This permits the simple remote control and remote scanning of an almost unlimited number of RectuTest RT02 units through a linked-up PC.

Technical data

Housing: ABS grey (IP 65), W 80 x L 240 x H 60 mm

Power supply: 220 V/5 watts

Operating temperature: 0°C up to 60°C

Pressure drop: 0,1 bar (in the nozzle)


Measuring accuracy: ± 2,5% of measured value (flow rate and consumption measurement in the specified operating temperature and measuring ranges, according to table)

Permissible operating pressure: max. 10 bar

Resistance to pressure: max. 16 bar (without measurement)

Network: Any number of measuring units can be linked up using network socket

RectuTest RECTUS Measuring-Systems

	Description	Part Number
Standard Design: 	RectuTest with following equipment:	RT 02 Set
	- 1/2" measuring nozzle	
	- 2 pcs. 2 m plastic hose	
	- temperature sensor with cable	
	- software for PC port	
	- PC connecting cable	
	- connection coupling	
	- operating instructions	
	- equipment case	
Optional equipment:	Measuring diaphragm Ø 2 with 1/4" pipe thread*	RD 13/02
	Measuring diaphragm Ø 4 with 1/4" pipe thread*	RD 13/04
	1" measuring nozzle with 1" pipe thread*	RD 33
	2" measuring nozzle with 2" pipe thread*	RD 60
	Network cable for connecting several meters (standard 5 m, other lengths on request)	RTZ_01

* made of nickel-plated brass incl. CD-ROM with calibration data.

Scope of delivery

The RectuTest RT02 is supplied in a sturdy case with plastic inserts. The standard equipment includes the following:

- RectuTest RT02 measuring unit with power cable
- 1/2" nozzle (calibrated)
- measuring hoses made of PA, each 2 m long
- temperature sensor with 2 m connecting cable
- one set of quick connect couplings complete with connectors
- PC connecting cable 5 m for parallel port
- software on 3,5" disk for remote control of the RectuTest RT02
- operating instructions

The following are available as optional extras:

- 16-bit software (Win 3, 1x)
- PC cable for serial port
- measuring nozzles, 2 mm and 4 mm**
- 1" nozzle, 2" nozzle**
- other measuring nozzles on request
- network cable, length at customer's request
- analog interface, 4-20 mA, 0-1 V
- ** with calibration data on CD-ROM

Software for Windows 95 + Win 98 + Win NT 4.0 allowing remote control of all functions of an individual unit or of all networked units through a PC is supplied with the RectuTest RT02. The measured results can be continuously stored, with time stamp. The stored data can be printed out or further processed using other software programs, such as Word or Excel. Hardware requirements: PC with Windows 95 or higher, with CD-ROM-drive. In this way, the compressed air consumption can be assigned to the individual cost centres in the company.

Further applications are, for example, checking volume flows for values that are too high or too low.

Measuring ranges for compressed air


Output pressure	Volume flow, standardised in l/min.				
	2 mm nozzle	4 mm nozzle	1/2" nozzle	1" nozzle	2" nozzle
1 bar	3,2 to 48	14 to 210	102 to 1530	287 to 4300	1136 to 17000
6 bar	6,3 to 95	27 to 410	200 to 3000	567 to 8500	2200 to 33000
10 bar	8,0 to 120	34 to 510	250 to 3750	700 to 10500	2760 to 41500



Components / Blow-Guns

Threaded Nut

RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number
 <p>DIN EN 560 (left handed thread marked)</p>	G 1/8 right	12	11	Brass	UR 10
		12	11	AISI 303	UR 10 R
	G 1/4 right	17	15,5	Brass	UR 13
		17	15,5	AISI 303	UR 13 R
		17	15,5	AISI 316 L	UR 13 E
	G 3/8 right	19	16,5	Brass	UR 17
		19	14,5	Brass	UR 17 S***
		19	16,5	AISI 303	UR 17 R
		19	16,5	AISI 316 L	UR 17 E
	G 1/4 r. f. 9 mm	17	15,5	Brass	UR 13/9*
		17	15,5	AISI 303	UR 13/9 R*
	G 1/2 right	24	20,5	Brass	UR 21
		24	20,5	AISI 303	UR 21 R
		24	20,5	AISI 316 L	UR 21 E
	G 1/4 left	17	15,5	Brass	UL 13
		17	15,5	AISI 303	UL 13 R
	G 3/8 left	19	16,5	Brass	UL 17**
		19	16,5	AISI 303	UL 17 R
		19	16,5	AISI 316 L	UL 17 E
	G 1/2 left	24	20,5	Brass	UL 21


* only for STP 13/09

** only to use with male x male nipples marked

*** shortened version, useable for all sizes

Hose Tail, Short


RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number
	4 mm for G 1/8		27,5	Brass	STP 10/04
			27,5	AISI 303	STP 10/04 R
	6 mm for G 1/8		28	Brass	STP 10/06
			28	AISI 303	STP 10/06 R
	4 mm for G 1/4		30,5	Brass	STP 13/04
			30,5	AISI 303	STP 13/04 R
	6 mm for G 1/4		35,5	Brass	STP 13/06
			35,5	AISI 303	STP 13/06 R
			35,5	AISI 316 L	STP 13/06 E
	9 mm for G 1/4		35,5	Brass	STP 13/09*
			35,5	AISI 303	STP 13/09 R*
	4 mm for G 3/8		31	Brass	STP 17/04
	6 mm for G 3/8		36	Brass	STP 17/06
			36	AISI 303	STP 17/06 R
			36	AISI 316 L	STP 17/06 E

* UR 13/9 required


Hose Tail, short

RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number	
	9 mm for G 3/8		36	Brass	STP 17/09	
				36	AISI 303	STP 17/09 R
				36	AISI 316 L	STP 17/09 E
	6 mm for G 1/2			38	Brass	STP 21/06
		9 mm for G 1/2		38	Brass	STP 21/09
					38	AISI 303
				38	AISI 316 L	STP 21/09 E
	13 mm for G 1/2			44	Brass	STP 21/13


Hose Tail, long

RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number
 DIN EN 560	4 mm for G 1/4		47	Brass	STD 13/04
	6 mm for G 1/4		47	Brass	STD 13/06
	4 mm for G 3/8		47,5	Brass	STD 17/04
	6 mm for G 3/8		47,5	Brass	STD 17/06
	9 mm for G 3/4		47,5	Brass	STD 17/09


Hose Tail Barb

RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number
 with Male Thread (* inner cone 45°)	M 5, 3 mm	7	15,5	Brass	GT 05/03
		7	15,5	AISI 303	GT 05/03 R
		7	15,5	AISI 316 L	GT 05/03 E
	M 5, 4 mm	7	15,5	Brass	GT 05/04
		7	15,5	AISI 303	GT 05/04 R
		7	15,5	AISI 316 L	GT 05/04 E
	M 6, 4 mm	8	23	Brass	GT 06/04
	G 1/8, 4 mm*	14	28	Brass	GT 10/04
		14	28	AISI 303	GT 10/04 R
		14	28	AISI 316 L	GT 10/04 E
	G 1/8, 6 mm*	14	33	Brass	GT 10/06
		14	33	AISI 303	GT 10/06 R
		14	33	AISI 316 L	GT 10/06 E

Hose Tail Barb

RECTUS Components




with Male Thread
(* inner cone 45°)

Connection	Hex mm	Length mm	Version	Part Number
G 1/8, 8 mm*	14	33	Brass	GT 10/08
G 1/8, 9 mm*	14	33	Brass	GT 10/09
	14	33	AISI 303	GT 10/09 R
	14	33	AISI 316 L	GT 10/09 E
G 1/4, 4 mm*	17	29,5	Brass	GT 13/04
	17	29,5	AISI 303	GT 13/04 R
	17	29,5	AISI 316 L	GT 13/04 E
G 1/4, 6 mm*	17	34,5	Brass	GT 13/06
	17	34,5	AISI 303	GT 13/06 R
	17	34,5	AISI 316 L	GT 13/06 E
G 1/4, 8 mm*	17	34,5	Brass	GT 13/08
G 1/4, 9 mm*	17	34,5	Brass	GT 13/09
	17	34,5	AISI 303	GT 13/09 R
	17	34,5	AISI 316 L	GT 13/09 E
G 1/4, 13 mm*	17	34,5	Brass	GT 13/13
G 3/8, 6 mm*	19	36	Brass	GT 17/06
	19	36	AISI 303	GT 17/06 R
	19	36	AISI 316 L	GT 17/06 E
G 3/8, 8 mm*	19	36	Brass	GT 17/08
G 3/8, 9 mm*	19	36	Brass	GT 17/09
	19	36	AISI 303	GT 17/09 R
	19	36	AISI 316 L	GT 17/09 E
G 3/8, 13 mm*	19	42	Brass	GT 17/13
	19	42	AISI 303	GT 17/13 R
	19	42	AISI 316 L	GT 17/13 E
G 1/2, 6 mm*	24	39	Brass	GT 21/06
G 1/2, 9 mm*	24	39	Brass	GT 21/09
	24	39	AISI 303	GT 21/09 R
	24	39	AISI 316 L	GT 21/09 E
G 1/2, 13 mm*	24	45	Brass	GT 21/13
	24	45	AISI 303	GT 21/13 R
	24	45	AISI 316 L	GT 21/13 E
G 3/4, 13 mm*	32	48,5	Brass	GT 26/13
G 3/4, 16 mm*	32	56,5	Brass	GT 26/16
G 3/4, 19 mm*	32	56,5	Brass	GT 26/19
G 1, 25 mm*	36	67,5	Brass	GT 33/25

Hose Tail Barb

RECTUS Components



Female Thread

Connection	Hex mm	Length mm	Version	Part Number
G 1/8, 6 mm	12	31	Brass	GI 10/06
G 1/8, 8 mm	12	31	Brass	GI 10/08
G 1/4, 6 mm	17	33	Brass	GI 13/06
G 1/4, 8 mm	17	33	Brass	GI 13/08
G 1/4, 9 mm	17	33	Brass	GI 13/09
G 1/4, 13 mm	17	39	Brass	GI 13/13
G 3/8, 6 mm	19	33	Brass	GI 17/06
G 3/8, 8 mm	19	33	Brass	GI 17/08
G 3/8, 9 mm	19	33	Brass	GI 17/09
G 3/8, 13 mm	19	40	Brass	GI 17/13
G 1/2, 6 mm	24	36	Brass	GI 21/06
G 1/2, 8 mm	24	36	Brass	GI 21/08
G 1/2, 9 mm	24	36	Brass	GI 21/09
G 1/2, 13 mm	24	43	Brass	GI 21/13

Hose Repairer

RECTUS Components



* DIN EN 560
** for hard hoses

Connection	Hex mm	Length mm	Version	Part Number
4 mm		50	Brass	DS 04/04 P**
6 mm		72	Brass	DS 06/06*
8 mm		72	Brass	DS 08/08*
9 mm		72	Brass	DS 09/09*
13 mm		74	Brass	DS 13/13

Hose Repairer, short


RECTUS Components



Connection	Hex mm	Length mm	Version	Part Number
4 mm		19	Brass	DK 04/04
6 mm		19	Brass	DK 06/06

Male x Male Nipple

RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number
	M 5 x M 5	7	13	Brass	DN 05/05
		7	13	AISI 303	DN 05/05 R
		7	13	AISI 316 L	DN 05/05 E
	M 5 x G 1/8	14	17	Brass	DN 05/10
		14	17	AISI 303	DN 05/10 R
		14	17	AISI 316 L	DN 05/10 E
	M 5 x G 1/4	17	18,5	Brass	DN 05/13
	G 1/8 x G 1/8*	14	19	Brass	DN 10/10
		14	19	AISI 303	DN 10/10 R
		14	19	AISI 316 L	DN 10/10 E
	R 1/8 x R 1/8 con	12	21	Brass	DN 10/10 K
	G 1/8 x G 1/4*	17	19,5	Brass	DN 10/13
		17	19,5	AISI 303	DN 10/13 R
		17	19,5	AISI 316 L	DN 10/13 E
	G 1/8 x G 3/8**	19	21	Brass	DN 10/17
	G 1/4 x G 1/4*	17	22	Brass	DN 13/13
		17	22	AISI 303	DN 13/13 R
		17	22	AISI 316 L	DN 13/13 E
	R 1/4 x R 1/4 con	14	30	Brass	DN 13/13 K
	G 1/4 x G 3/8 **	19	22,5	Brass	DN 13/17
		19	22,5	AISI 303	DN 13/17 R
		19	22,5	AISI 316 L	DN 13/17 E
	G 1/4 x G 3/8 ext.***	19	24,5	Brass	DN 13/17 V
	G 1/4 x G 1/2*	24	25,5	Brass	DN 13/21
	G 3/8 x G 3/8**	19	23	Brass	DN 17/17
		19	23	AISI 303	DN 17/17 R
		19	23	AISI 316 L	DN 17/17 E
	G 3/8 x G 3/8 long***	19	27	Brass	DN 17/17 V
	R 3/8 x R 3/8 con.	17	30	Brass	DN 17/17 K
	G 3/8 x G 1/2**	24	26	Brass	DN 17/21
		24	26	AISI 303	DN 17/21 R
		24	26	AISI 316 L	DN 17/21 E
	G 3/8 x G 3/4**	32	29,5	Brass	DN 17/26
	G 1/2 x G 1/2*	24	28	Brass	DN 21/21
		24	28	AISI 303	DN 21/21 R
		24	28	AISI 316 L	DN 21/21 E
	R 1/2 x R 1/2 con	22	34	Brass	DN 21/21 K
	G 1/2 x G 3/4*	32	31,5	Brass	DN 21/26
	G 1/2 x G 1*	36	36,5	Brass	DN 21/33
	G 3/4 x G 3/4*	32	33	Brass	DN 26/26
G 3/4x G 1*	36	34	Brass	DN 26/33	
G 1 x G1*	36	37	Brass	DN 33/33	
G 1/4 l. x G 1/4 l.*	14	34	Brass	DN 13/13 L	
G 1/4 l. x G 3/8 l.*	17	35,5	Brass	DN 13/17 L	
G 3/8 l. x G 3/8 l.*	17	37	Brass	DN 17/17 L	


* inner cone 45°

** inner cone 45°, useable only together with threaded nut UR 17 S

*** inner cone 45°, useable with threaded nut UR17

Male x Male Nipples adjustable

RECTUS Components



Connection	Hex mm	Length mm	Version	Part Number
R 1/8 x R 1/8	15	27	Brass	LD 10/10 K
R 1/4 x R 1/4	19	34	Brass	LD 13/13 K
R 3/8 x R 3/8	22	37	Brass	LD 17/17 K
R 1/2 x R 1/2	27	44,5	Brass	LD 21/21 K
R 3/4 x R 3/4	36	53	Brass	LD 26/26 K
R 1 x R 1	46	64	Brass	LD 33/33 K

Reducing Bush, Short

RECTUS Components




Connection	Hex mm	Length mm	Version	Part Number
M 5 i. x G 1/8 o.	14	11	Brass	RK 05/10
	14	11	AISI 303	RK 05/10 R
	14	11	AISI 316 L	RK 05/10 E
M 5 i. x G 1/4 o.	17	12,5	Brass	RK 05/13
G 1/8 i. x G 1/4 o.	17	12,5	Brass	RK 10/13
	17	12,5	AISI 303	RK 10/13 R
	17	12,5	AISI 316 L	RK 10/13 E
G 1/8 i. x G 3/8 o.	19	13	Brass	RK 10/17
G 1/8 i. x G 1/2 o.	24	17	Brass	RK 10/21
G 1/4 i. x G 3/8 o.	19	14	Brass	RK 13/17
	19	14	AISI 303	RK 13/17 R
	19	14	AISI 316 L	RK 13/17 E
G 1/4 i. x G 1/2 o.	24	17	Brass	RK 13/21
G 3/8 i. x G 1/2 o.	24	17	Brass	RK 17/21
	24	17	AISI 303	RK 17/21 R
	24	17	AISI 316 L	RK 17/21 E
G 3/8 i. x G 3/4 o.	32	18	Brass	RK 17/26
G 1/2 i. x G 3/4 o.	32	20,5	Brass	RK 21/26
G 1/2 i. x G 1 o.	36	21,5	Brass	RK 21/33
G 3/4 i. x G 1 o.	36	21,5	Brass	RK 26/33

⚠ Please consider our security advices on the pages 12/13 ⚠

Reducing Bush, Long

RECTUS Components



* inner cone 45°

Connection	Hex mm	Length mm	Version	Part Number
M 5 o. x M 5 i.	8	15	Brass	RL 05/05
M 5 o. x G 1/8 i.	14	17	Brass	RL 05/10
G 1/8 o. x M 5 i.	14	17	Brass	RL 10/05
G 1/8 o. x G 1/8 i.*	14	23	Brass	RL 10/10
G 1/8 o. x G 1/4 i.*	17	26	Brass	RL 10/13
G 1/4 o. x G 1/8 i.*	17	26	Brass	RL 13/10
G 1/4 o. x G 1/4 i.*	17	28	Brass	RL 13/13
G 1/4 o. x G 3/8 i.*	19	29	Brass	RL 13/17
G 3/8 o. x G 1/4 i.*	19	29	Brass	RL 17/13
G 3/8 o. x G 3/8 i.*	19	29	Brass	RL 17/17
G 3/8 o. x G 1/2 i.*	24	32	Brass	RL 17/21
G 1/2 o. x G 3/8 i.*	24	34	Brass	RL 21/17
G 1/2 o. x G 1/2 i.*	24	34	Brass	RL 21/21
G 1/2 o. x G 3/4 i.*	32	31	Brass	RL 21/26

Female x Female Socket

RECTUS Components



Connection	Hex mm	Length mm	Version	Part Number
M 5	8	12	Brass	MU 05
M 5	8	12	AISI 303	MU 05 R
G 1/8	14	22	Brass	MU 10
	14	22	AISI 303	MU 10 R
	14	22	AISI 316 L	MU 10 E
G 1/4	17	26	Brass	MU 13
	17	26	AISI 303	MU 13 R
	17	26	AISI 316 L	MU 13 E
G 3/8	22	26	Brass	MU 17
	22	26	AISI 303	MU 17 R
	22	26	AISI 316 L	MU 17 E
G 1/2	27	30	Brass	MU 21
	27	30	AISI 303	MU 21 R
	27	30	AISI 316 L	MU 21 E
G 3/4	32	36	Brass	MU 26
G 1	41	40	Brass	MU 33

90° Elbow


RECTUS Components



Connection	Hex mm	Version	Part Number
M 5	10	Brass	WS 05
M 5	10	Aluminium elox.	WS 05 A
G 1/8	16	Brass	WS 10
G 1/8	16	Aluminium elox.	WS 10 A
G 1/4	22	Brass	WS 13
G 1/4	22	Aluminium elox.	WS 13 A
G 3/8	27	Brass	WS 17
G 3/8	27	Aluminium elox.	WS 17 A

Tee

RECTUS Components



Connection	Hex mm	Version	Part Number
M 5	10	Brass	TK 05
M 5	10	Aluminium elox.	TK 05 A
G 1/8	15	Brass	TK 10
G 1/8	16	Aluminium elox.	TK 10 A
G 1/4	22	Brass	TK 13
G 1/4	22	Aluminium elox.	TK 13 A
G 3/8	27	Brass	TK 17
G 3/8	27	Aluminium elox.	TK 17 A

4 Port Manifold


RECTUS Components



Connection	Hex mm	Version	Part Number
G 1/8	30	Aluminium	VB 10
G 1/4	30	Aluminium	VB 13
G 3/8	43	Aluminium	VB 17
G 1/2	52	Aluminium	VB 21


Multi-Port Manifold

RECTUS Components

	Connection	1 Entry	9 Exit	Hex mm	Version	Part Number
	G 1/8 x M 5	G 1/8	M 5	20	Aluminium elox.	VL 10/05
	G 3/8 x G 1/8	G 3/8	G 1/8	30	Aluminium elox.	VL 17/10
	G 1/2 x G 1/4	G 1/2	G 1/4	36	Aluminium elox.	VL 21/13


Bulkhead Lock Nut

RECTUS Components

	Connection	Hex mm	Version	Part Number
	G 1/8	15	Brass	KM 10 W
	G 1/4	17	Brass	KM 13 W
	G 3/8	22	Brass	KM 17 W
	G 1/2	27	Brass	KM 21 W
	G 3/4	30	Brass	KM 26 W
	M 6 x 0,75	9	Brass	KM 06 M
	M 8 x 1	12	Brass	KM 08 M
	M 10 x 1	12	Brass	KM 10 M
	M 12 x 1	17	Brass	KM 12 M
	M 14 x 1	19	Brass	KM 14 M

Blanking Plug

RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number
 Socket Pipe (DIN 908)	M 5 (head pipe)	8	8	Brass	VZ 05
		8	8	AISI 303	VZ 05 R
	G 1/8	5	11	Brass	VZ 10
		5	11	AISI 303	VZ 10 R
		5	11	AISI 316 L	VZ 10 E
	G 1/4	6	15	Brass	VZ 13
		6	5	AISI 303	VZ 13 R
		6	5	AISI 316 L	VZ 13 E
	G 3/8	8	15	Brass	VZ 17
		8	15	AISI 303	VZ 17 R
		8	15	AISI 316 L	VZ 17 E
	G 1/2	10	18	Brass	VZ 21
		10	18	AISI 303	VZ 21 R
		10	18	AISI 316 L	VZ 21 E
	G 3/4	12	20	Brass	VZ 26

Blanking Plug

RECTUS Components



Connection	Hex mm	Version	Part Number
R 1/8	5	Brass	VK 10
R 1/4	7	Brass	VK 13
R 3/8	8	Brass	VK 17

Washer, PVC

RECTUS Components



(Captive version page 329)

Connection	Hex mm	Version	Part Number
for M5			PD 05
for G 1/8			PD 10
for G 1/4			PD 13
for G 3/8			PD 17
for G 1/2			PD 21
for G 3/4			PD 26

Washer, Fiber

RECTUS Components



Connection	Hex mm	Part Number
for M5		FD 05
for G 1/8		FD 10
for G 1/4		FD 13
for G 3/8		FD 17
for G 1/2		FD 21
for G 3/4		FD 26


Washer, Aluminium

RECTUS Components




Connection	Hex mm	Part Number
for G 1/8		AD 10
for G 1/4		AD 13
for G 3/8		AD 17
for G 1/2		AD 21
for G 3/4		AD 26
for G 1		AD 33


Female Stud Fitting **RECTUS Components**

	Connection	Hex mm	Length mm	Version	Part Number
	G 1/8, 4 x 6 mm	14	23	Brass	MV 10/06
G 1/4, 4 x 6 mm	17	25	Brass	MV 13/06	
G 1/4, 6 x 8 mm	17	25	Brass	MV 13/08	
G 1/4, 8 x 10 mm	17	29	Brass	MV 13/10	
G 3/8, 6 x 8 mm	19	25	Brass	MV 17/08	
G 3/8, 8 x 10 mm	19	29	Brass	MV 17/10	


Swivelling Spring Guard **RECTUS Components**

	Connection	Hex mm	Length mm	Version	Part Number
	R 1/8, 3,1 x 4,7 mm	11		Brass	DV 10/05
R 1/4, 4,8 x 6,3 mm	14		Brass	DV 13/06	
R 1/4, 6,3 x 7,9 mm	14		Brass	DV 13/08	
R 1/4, 7,9 x 9,5 mm	15		Brass	DV 13/10	
R 3/8, 9,5 x 11,8 mm	19		Brass	DV 17/12	
R 1/2, 12,7 x 15,8 mm	22		Brass	DV 21/16	

Equal Ended Tee **RECTUS Components**

	Connection	Hex mm	Length mm	Version	Part Number
	4 x 6 mm			Brass	TSK 06
6 x 8 mm			Brass	TSK 08	
8 x 10 mm			Brass	TSK 10	

Equal Ended Cross **RECTUS Components**

	Connection	Hex mm	Length mm	Version	Part Number
	4 x 6 mm			Brass	KS 06
6 x 8 mm			Brass	KS 08	
8 x 10 mm			Brass	KS 10	

Equal Ended Cross

RECTUS Components



Connection	Hex mm	Length mm	Version	Part Number
G 1/8	19		AISI 316	VB 10 E
G 1/4	19		AISI 316	VB 13 E
G 3/8	20		AISI 316	VB 17 E
G 1/2	23		AISI 316	VB 21 E
G 3/4	25		AISI 316	VB 26 E
G 1	29		AISI 316	VB 33 E


Swivelling Single Banjo Fitting

RECTUS Components



Connection	Hex mm	Length mm	Version	Part Number
M 5, 3 x 4 mm	8	18,5	Brass	WV 05/04
M 5, 3 x 5 mm	8	18,5	Brass	WV 05/05
M 5, 4 x 6 mm	8	18,5	Brass	WV 05/06
G 1/8, 4 x 6 mm	14	28	Brass	WV 10/06
G 1/8, 6 x 8 mm	14	28	Brass	WV 10/08
G 1/4, 4 x 6 mm	17	33	Brass	WV 13/06
G 1/4, 6 x 8 mm	17	33	Brass	WV 13/08
G 1/4, 8 x 10 mm	17	33	Brass	WV 13/10


⚠ Please consider our security advices on the pages 12/13 ⚠

Bulkhead Fitting**RECTUS Components**

Connection	Hex mm	Length mm	Version	Part Number
3 x 4 mm	11	34	Brass	SC 05/04
3 x 5 mm	11	34	Brass	SC 05/05
4 x 6 mm	12	38	Brass	SC 10/06
6 x 8 mm	17	46	Brass	SC 10/08
8 x 10 mm	19	46	Brass	SC 14/10

Hose Tail Elbow, Swivelling**RECTUS Components**


Connection	Hex mm	Length mm	Version	Part Number
M 5, f. LW 3 mm	8	18,5	Brass	WT 05/03
M 5, f. LW 4 mm	8	18,5	Brass	WT 05/04

Stud Fitting**RECTUS Components**

Connection	Hex mm	Length mm	Version	Part Number
M 5, 3 x 4 mm	7	20	Brass	EV 05/04
M 5, 3 x 5 mm	7	20	Brass	EV 05/05
	7	20	AISI 303	EV 05/05 R
	7	20	AISI 316 L	EV 05/05 E
M 5, 4 x 6 mm	8	21	Brass	EV 05/06
	8	21	AISI 303	EV 05/06 R
	8	21	AISI 316 L	EV 05/06 E
G 1/8, 4 x 6 mm	12	25	Brass	EV 10/06
	12	25	AISI 303	EV 10/06 R
	12	25	AISI 316 L	EV 10/06 E
G 1/8, 6 x 8 mm	14	24	Brass	EV 10/08
	14	24	AISI 303	EV 10/08 R
	14	24	AISI 316 L	EV 10/08 E
G 1/4, 4 x 6 mm	17	26	Brass	EV 13/06
	17	26	AISI 303	EV 13/06 R
	17	26	AISI 316 L	EV 13/06 E
G 1/4, 6 x 8 mm	17	26	Brass	EV 13/08
	17	26	AISI 303	EV 13/08 R
	17	26	AISI 316 L	EV 13/08 E

Stud Fitting

RECTUS Components



* inner cone 45°

Connection	Hex mm	Length mm	Version	Part Number
G 1/4, 8 x 10 mm	17	31	Brass	EV 13/10
G 1/4, 9 x 12 mm	17	31	Brass	EV 13/12
	17	31	AISI 303	EV 13/12 R
G 3/8, 6 x 8 mm*	19	27	Brass	EV 17/08
G 3/8, 8 x 10 mm*	19	31	Brass	EV 17/10
	19	31	AISI 303	EV 17/10 R
G 3/8, 9 x 12 mm*	19	31	Brass	EV 17/12
	19	31	AISI 303	EV 17/12 R

Fixed Spring Guard

RECTUS Components



for Nylon hoses

* inner cone 45°

Connection	Hex mm	Length mm	Version	Part Number
M 5, 4 x 6 mm	8	103	Brass	SV 05/06
G 1/8, 4 x 6 mm	12	103	Brass	SV 10/06
G 1/8, 6 x 8 mm	12	106	Brass	SV 10/08
G 1/4, 4 x 6 mm	17	103	Brass	SV 13/06
G 1/4, 6 x 8 mm	17	106	Brass	SV 13/08
G 1/4, 8 x 10 mm	17	119	Brass	SV 13/10
G 1/4, 9 x 12 mm	17	123	Brass	SV 13/12
G 3/8, 6 x 8 mm*	19	106	Brass	SV 17/08
G 3/8, 8 x 10 mm*	19	119	Brass	SV 17/10
G 3/8, 9 x 12 mm*	19	123	Brass	SV 17/12

Male Stud Run Tee

RECTUS Components




Tapered Thread

Connection	Hex mm	Length mm	Version	Part Number
R 1/8, 4 x 6 mm			Brass	TE 10/06
R 1/8, 6 x 8 mm			Brass	TE 10/08
R 1/8, 8 x 10 mm			Brass	TE 10/10
R 1/4, 4 x 6 mm			Brass	TE 13/06
R 1/4, 6 x 8 mm			Brass	TE 13/08
R 1/4, 8 x 10 mm			Brass	TE 13/10


Male Stud Elbow

RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number
 <p>Tapered Thread</p>	R 1/8, 4 x 6 mm	12		Brass	WE 10/06
	R 1/8, 6 x 8 mm	14		Brass	WE 10/08
	R 1/8, 8 x 10 mm	16		Brass	WE 10/10
	R 1/4, 4 x 6 mm	12		Brass	WE 13/06
	R 1/4, 6 x 8 mm	14		Brass	WE 13/08
	R 1/4, 8 x 10 mm	16		Brass	WE 13/10


Male Stud Elbow

RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number
 <p>with Spring Guard, Tapered Thread</p>	R 1/8, 4 x 6 mm	12	107	Brass	WK 10/06
	R 1/8, 6 x 8 mm	14	112	Brass	WK 10/08
	R 1/8, 8 x 10 mm	17	125	Brass	WK 10/10
	R 1/4, 4 x 6 mm	12	109	Brass	WK 13/06
	R 1/4, 6 x 8 mm	14	114	Brass	WK 13/08
	R 1/4, 8 x 10 mm	17	127	Brass	WK 13/10


Spring Guard

RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number
 <p>completely with Tube Nut</p>	(M 10 x 1) 4 x 6 mm	12	94	Brass	KN 06
	(M 12 x 1) 6 x 8 mm	14	97	Brass	KN 08
	(M 16 x 1) 8 x 10 mm	17	110	Brass	KN 10
	(M 16 x 1) 9 x 12 mm	17	114	Brass	KN 12

Tube Nut

RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number
 <p>for Plastic Hoses</p>	(M 7 x 0,5) 3 x 4 mm	–	8,5	Brass	SM 04
	(M 7 x 0,5) 3 x 5 mm	–	8,5	Brass	SM 05
	(M 10 x 1) 4 x 6 mm	12	11	Brass	SM 06
	(M 12 x 1) 6 x 8 mm	14	11	Brass	SM 08
	(M 14 x 1) 8 x 10 mm	17	12,5	Brass	SM 10 S
	(M 16 x 1) 8 x 10 mm	17	12,5	Brass	SM 10
	(M 16 x 1) 9 x 12 mm	17	12,5	Brass	SM 12

Female Tee

RECTUS Components



* without Inner Cone
** with Inner Cone

Connection	Hex mm	Length mm	Version	Part Number
R 1/8 o.	10	37	Brass	TA 10*
R 1/4 o.	13	47	Brass	TA 13*
R 3/8 o.	17	52	Brass	TA 17*
R 1/2 o.	19	60	Brass	TA 21**

Male Elbow

RECTUS Components



* without Inner Cone
** with Inner Cone

Connection	Hex mm	Length mm	Version	Part Number
R 1/8 o.	10	23	Brass	WA 10*
R 1/4 o.	13	30	Brass	WA 13*
R 3/8 o.	17	33,5	Brass	WA 17*
R 1/2 o.	19	39	Brass	WA 21**

Female Tee

RECTUS Components



Connection	Hex mm	Length mm	Version	Part Number
G 1/8		34	Brass	TI 10
		28	AISI 316	TI 10 E
G 1/4		38,5	Brass	TI 13
		35	AISI 316	TI 13 E
G 3/8		44	Brass	TI 17
		43	AISI 316	TI 17 E
G 1/2		44	Brass	TI 21
		49	AISI 316	TI 21 E
G 3/4		50	Brass	TI 26
		59	AISI 316	TI 26 E
G 1		64,5	Brass	TI 33

Female Elbow **RECTUS Components**



Female Thread

Connection	Hex mm	Length mm	Version	Part Number
G 1/8		25	Brass	WI 10
		22	AISI 316	WI 10 E
G 1/4		29	Brass	WI 13
		27	AISI 316	WI 13 E
G 3/8		35	Brass	WI 17
		32	AISI 316	WI 17 E
G 1/2		40	Brass	WI 21
		40	AISI 316	WI 21 E
G 3/4		47	Brass	WI 26
		48	AISI 316	WI 26 E
G 1		55	Brass	WI 33

Male-/Female Elbow **RECTUS Components**



Female Thread
Male Thread

Connection	Hex mm	Length mm	Version	Part Number
G 1/8		26	AISI 316	WAI 10 E
G 1/4		28	AISI 316	WAI 13 E
G 3/8		32	AISI 316	WAI 17 E
G 1/2		37	AISI 316	WAI 21 E
G 3/4		43	AISI 316	WAI 26 E

Female Y **RECTUS Components**



2x Female Thread
1x Male Thread con.

Connection	Hex mm	Length mm	Version	Part Number
R 1/8 o./G 1/8 i.	13		Brass	YA 10
R 1/4 o./G 1/4 i.	17		Brass	YA 13
R 3/8 o./G 3/8 i.	20		Brass	YA 17
R 1/2 o./G 1/2 i.	25		Brass	YA 21

Female Y

RECTUS Components



3x Female Thread

Connection	Hex mm	Length mm	Version	Part Number
G 1/8	13		Brass	YI 10
G 1/4	17		Brass	YI 13
G 3/8	20		Brass	YI 17
G 1/2	25		Brass	YI 21

2 Way Manifold

RECTUS Components



Connection	Hex mm	Length mm	Version	Part Number
G 3/8 i.		47	Brass	ZO 17
G 1/2 i.		55	Brass	ZO 21

3 Way Manifold

RECTUS Components



Connection	Hex mm	Length mm	Version	Part Number
G 3/8 i.		61	Brass	DO 17
G 1/2 i.		67	Brass	DO 21

⚠ Please consider our security advices on the pages 12/13 ⚠

2 Way Manifold Assembly **RECTUS Components**



with Couplings
26 Series

Conenction	Hex mm	Length mm	Version	Part Number
G 1/4 o.			Brass	ZM 13 A
G 3/8 o.			Brass	ZM 17 A
G 1/2 o.			Brass	ZM 21 A
G 1/4 i.			Brass	ZM 13 I
G 3/8 i.			Brass	ZM 17 I
G 1/2 i.			Brass	ZM 21 I

3 Way Manifold Assembly **RECTUS Components**



with Couplings
26 Series

Connection	Hex mm	Length mm	Version	Part Number
G 1/4 o.			Brass	DM 13 A
G 3/8 o.			Brass	DM 17 A
G 1/2 o.			Brass	DM 21 A
G 1/4 i.			Brass	DM 13 I
G 3/8 i.			Brass	DM 17 I
G 1/2 i.			Brass	DM 21 I


Manifold Assembly **RECTUS Components**



Connection	Hex mm	Length mm	Version	Part Number
G 3/8 i.			Brass	WD 17-26
G 1/2 i.			Brass	WD 21-26


Manifold

RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number
	G 3/8 i.			Aluminium, elox.	WD 17
	G 1/2 i.			Aluminium, elox.	WD 21


Pressure Reducing Valve

RECTUS Components

	Connection	Hex mm	Length mm	Version	Max. Supply Pressure	Const. Supply Pressure	Part Number
	G 1/4 i x R 1/4 o.	17	34	Brass	15 bar	3,0 bar	DRV 13/30
	G 1/4 i x R 1/4 o.	17	34	Brass	15 bar	4,0 bar	DRV 13/40
	G 1/4 i x R 1/4 o.	17	34	Brass	15 bar	5,0 bar	DRV 13/50
	G 1/4 i x R 1/4 o.	17	34	Brass	15 bar	6,0 bar	DRV 13/60


Swivel Joint

RECTUS Components

	Connection	Hex mm	Length mm	Version	Part Number
	G 1/4 i x G 1/4 o.	17	52	Steel, Nickel Plated	FA 13A 13I SPN
	G 3/8 i x G 3/8 o.	21	58	Steel, Nickel Plated	FA 17A 17I SPN

Dust Caps for Couplings and Plugs

RECTUS Components

	Material	Flame Resistance	Temperature Range	Color	Part Number
	Thermo Flex	UL-VO	-25 up to 120°C	Blue	SK12S
	Euro Flex	UL-VO	-25 up to 120°C	Red	SK16S
	Thermo Flex	UL-VO	-25 up to 120°C	Blue	SK23S
	Thermo Flex	UL-VO	-25 up to 120°C	Blue	SK27S

⚠ Please consider our security advices on the pages 12/13 ⚠

Blow-Gun Technology



Short nozzle

Directed air jet. Ideal for blowing out blind holes and workpieces.

Safety nozzle

With center bore and lateral annular gap. In blowing operation, a protective shield is formed against rebounding shavings. The noise level is also significantly reduced. When the center bore is held closed, the air escapes through the annular gap.

Extension pipe

Made of aluminium, therefore rustproof. For blowing out deep holes and in inaccessible locations.

Protective shield

Is mounted behind the nozzle being used. Prevents shavings from rebounding.

Venturi nozzle

Saves energy, since 2/3 of the surrounding air is sucked in thanks to the Venturi principle. Wide blow-out effect thanks to the large nozzle effect. When the nozzle hole is held closed, the air escapes through the lateral holes.

Nozzle with sintered metal insert

Low noise level (63-73 dB(A)) yet with exceedingly good blow-out performance (up to 380 l/min).

AJ 13-Set

RECTUS Blow-Guns



Connection	Extension Tube	Part Number
G 1/4 i.	6 mm bent	AJ 13/06 SET
G 1/4 i.	8 mm bent	AJ 13/08 SET
including 10 Blow-Guns AJ 13		

AK 13-Set


RECTUS Blow-Guns



Connection		Part Number
G 1/4 i.		AK 13 SET
including 10 Blow-Guns AK 13		


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of aluminium, with standard nozzle</p>	G 1/4 i.	AA 13
	6 mm	AA 06 TF
	9 mm	AA 09 TF
	Plug 21 Series	AA 21 SF
	Plug 26 Series	AA 26 SF


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of aluminium, with safety nozzle</p>	G 1/4 i.	AS 13
	6 mm	AS 06 TF
	9 mm	AS 09 TF
	Plug 21 Series	AS 21 SF
	Plug 26 Series	AS 26 SF


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of aluminium, with sintered metal insert</p>	G 1/4 i.	AR 13


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of aluminium, with extension tube</p>	G 1/4 i.	AV 13
	6 mm	AV 06 TF
	9 mm	AV 09 TF
	Plug 21 Series	AV 21 SF
	Plug 26 Series	AV 26 SF


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of aluminium, with Venturi nozzle</p>	G 1/4 i.	AT 13
	6 mm	AT 06 TF
	9 mm	AT 09 TF
	Plug 21 Series	AT 21 SF
	Plug 26 Series	AT 26 SF


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of aluminium, lever operated with safety nozzle</p>	1/4 i. NPSF	ASG-1


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of impact resistant plastic with standard nozzle fixed nozzle, impossible to replace</p>	G 1/4 i.	AN 13
	6 mm	AN 06 TF
	9 mm	AN 09 TF
	Plug 21 Series	AN 21 SF
	Plug 26 Series	AN 26 SF

Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of impact resistant plastic with standard nozzle fixed nozzle, impossible to replace</p>	G 1/4 i.	AL 13
	6 mm	AL 06 TF
	9 mm	AL 09 TF
	Plug 21 Series	AL 21 SF
	Plug 26 Series	AL 26 SF


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of impact resistant plastic with sintered metal insert</p>	G 1/4 i.	AF 13


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of impact resistant plastic with aluminium extension tube fixed nozzle, impossible to replace</p>	G 1/4 i.	AK 13
	6 mm	AK 06 TF
	9 mm	AK 09 TF
	Plug 21 Series	AK 21 SF
	Plug 26 Series	AK 26 SF


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of impact resistant plastic extension tube brass nickel plated with a star tip nozzle - meets OSHA standards - light weight - rugged extension tube - fixed nozzle, impossible to replace</p>	G 1/4 i.	AZ 13
	Plug 26 Series	AZ 26 SF


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of impact resistant plastic extension tube brass nickel plated - rugged extension tube - fixed nozzle, impossible to replace</p>	G 1/4 i.	AC 13
	6 mm	AC 06 TF
	9 mm	AC 09 TF
	Plug 21 Series	AC 21 SF
	Plug 26 Series	AC 26 SF


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of impact resistant plastic with Venturi nozzle</p>	G 1/4 i.	AX 13


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of impact resistant plastic with R 1/8" i. without nozzle</p>	G 1/4 i.	AI 13


Blow-Gun

RECTUS Blow-Guns

	Connection	Part Number
 <p>made of impact resistant plastic with M 12 x 1,25 IG without nozzle</p>	G 1/4 i.	AM 13


Blow-Gun

RECTUS Blow-Guns

	Connection	Extension tube	Part Number
 <p>made of red impact resistant plastic with aluminium extension tube</p>	G 1/4 i.	6 mm bent	AJ 13/06 B
	G 1/4 i.	8 mm straight	AJ 13/08
	G 1/4 i.	8 mm bent	AJ 13/08 B
	G 1/4 i.	8 x 300 mm straight	AJ 13-300
	G 1/4 i.	8 x 500 mm straight	AJ 13-500
	G 1/4 i.	8 x 1000 mm straight	AJ 13-1000


Standard Nozzle

RECTUS Blow-Guns

	Connection	Part Number
 <p>for blow-gun made of aluminium</p>	M 12 x 1,25	KD 12


Safety Nozzle

RECTUS Blow-Guns

	Connection	Part Number
 <p>for blow-gun made of aluminium</p> <p>With center bore and lateral annular gap. In blowing operation a protection shield against kicking chips is formed, and noise level is clearly reduced. When the center bore is held locked, air escapes through the annular gap.</p>	M 12 x 1,25	SD 12


Extension Tube, 150 mm long

RECTUS Blow-Guns

	Connection	Part Number
 <p>for blow-gun made of aluminium</p> <p>For blowing-out deep holes and blind spots.</p>	M 12 x 1,25	VR 12


Venturi-Nozzle

RECTUS Blow-Guns

	Connection	Part Number
 <p>Energy saving as 2/3 of environmental air is aspirated due to the Venturi principle. Wide blow-out effect due to high nozzle performance. When the center bore is held locked, air escapes through the lateral holes.</p>	M 12 x 1,25	AT 12


Nozzle with sintered metal insert

RECTUS Blow-Guns

	Connection	Part Number
 <p>Low noise level (63-73 dB(A)), thus extremely good blowing effectivity (up to 380 l/min.)</p>	M 12 x 1,25	AR 12


Protective Shield

RECTUS Blow-Guns

	Connection	Part Number
		ST 12

Blow-Gun Set

RECTUS Blow-Guns

	Part Number
	with Blow-Gun made of aluminium
	SE 26 A
	with Blow-Gun made of impact resistant thermoplastic
	SE 26 K
including	
- Blow-Gun	
- Hose 6 x 8 mm, length 2,5 m	
- Couplings and plugs Series 26 (DN 7,2)	



For the true heroes of today.



The high quality blow guns from Rectus are used in trade and industry, in the widest range of different areas. With the broad variety of different types, you will find a suitable variant for every conceivable application.




Nycoil

Hoses and tubing range

Always ideally connected.

Media

All liquid or gaseous media which flow through the hose or influence it from outside must be taken into account when choosing the hose. Chemicals can have detrimental effects (swelling, stress-cracking, etc.) on the hose materials. A prior test is therefore important. Your technical advisor will be happy to help you. For non-standard requirements, we advise you to test the hoses under operating conditions. In this way you can ensure that there are no adverse effects on the hose strength arising from extreme temperatures or chemical mixtures and the concentration thereof.



Flexibility

All thermoplastic materials are flexible up to a certain degree. Depending on the type, our hoses can therefore be used for a wide range of tasks. Ultraflexible hoses are suitable for applications with small bend radii and a high degree of movement. For example, relatively rigid or stronger tubing is the better choice for static applications with little movement but higher working pressures are required.



Flow


The flow quantity required by the attached consumer is an important criterion for hose selection. The appropriate choice of hose cross-section for the medium and flow volume is dependent on this.

As a rule of thumb: the flow rate of the hose must always be greater than the flow rate of all consumers in the circuit.



Working Pressure

From the established bursting pressure at room temperature (20°C), integration of a working pressure safety factor can be calculated. For the max. working pressure, all criteria affecting the hose when in use must be observed. The most important criteria include overload through bending and stretching, and hose fatigue caused by use, as well as maintenance of extruder tolerances and production variables. Nycoil works with the highest grade polymer materials and to the latest production standards. In order to guarantee the high standard of quality, all relevant parameters and hose characteristics are checked both during and after the production process.





Working temperature

The working temperature, i.e. the temperature range in which the hose is used, is also a major factor in hose selection. A point to note is that the burst pressure – and therefore also the safe working pressure – falls significantly as temperatures rise.

Space-Saving Storage


Our straight hoses are rolled, packed on cardboard holders, and delivered in boxes – for space-saving storage and quick materials access.



Our hose qualities at a glance.



RECTULASTIC Nylon 12 (Polyamid)

Straight hoses or coiled hoses; multicolored dual and quadruple; unprecedented return force; small twists and therefore requires minimum space; light weight; resistant to organic and inorganic materials.



RECTUFLEX Polyurethan



Straight hoses or coiled hoses; multicolored dual and quadruple; extremely flexible; resistant to buckling; no change in cross-section; max. working length equal to 80% of stretch length; coiled hoses are supplied with swivel fittings and buckling protection on both ends.



SUPERBRAID®

Polyurethane Inner Braided Hose


Straight hoses or coiled hoses; as flexible as the conventional PU hose – from -40°C to +75°C – even with fabric inlay; extremely small twist diameter; coiled hoses are supplied with pre-assembled swivel fittings and buckling protection.



ULTRA-LITE SUPERBRAID®

Polyurethane Inner Braided Hose


Straight hoses; fittings for easy self-assembly; much lighter than the SUPERBRAID® hose and therefore even more flexible and easy to use; highly resistant to temperature (-40°C to +75°C); extremely small twist diameter.





RECTUSPARK® Polyurethane on Polyester Basis, with Protection against Welding Sparks

Straight hoses or coiled hoses; the non-flammable coating provides the hose with reliable protection against welding sparks; extremely flexible, pliable and resistant to buckling and ideally suited to harsh industrial applications.



RECTUSOFT Highly Flexible PVC, with Polyester Fibre Reinforcement (TÜV-tested)

Straight hoses or coiled hoses; extremely flexible, even at ultra-low temperatures; highly resistant to tears and pressure; light weight and easy operation makes this hose ideal for operating compressed air tools.



RECTUCHEM® PVDF

Straight hoses or coiled hoses; the perfect solution for chemical technology, especially clean applications; structurally resistant to many chemicals and therefore useful in a broad range of applications.


Fittings

Many hoses are available completely assembled with different fittings. Please check article description.





RECTULASTIC



Technical Description

RECTULASTIC hoses from Nycoil for safer, more efficient air power transmission.

Special Physical Features

- Light weight (specific weight 9x lower as copper)
- Wide temperature range
- High resistance against moisture
- Saltwater insensitive
- Long service time
- Highly elasticity

Mechanical Features

- High vibration prevention
- Perfect abrasion resistance
- High compression characteristics
- Low flow reduction for all kind of media
- Precise tolerances
- Constant solidity
- Resists kinking

Advantages

- Quick assembly possible
- Straight hoses ideal for Push-In-System
- Light weight
- Low pressure drop
- Different colors for identification
- Good storage possibility due to box packing (straight hoses)
- High abrasion resistance
- Self-retracting. Coiled Hose automatically recoils to a fraction of its working length
- Small bending diameter
- Resistant to oil, gasoline, grease and abrasion

Technical Data

Temperature range:
-40°C up to +90°C
Maximum operating pressure:
see chart

Tubing assembled:
-20°C up to +70°C



Applications

- Compressed air
- lubrication grease/oil
- gasoline
- hydraulic
- vacuum
- chemicals (on request)

All technical data refers to air applications. We will gladly assist you for other media

Relation Working Pressure / Temperature

(only for hoses, not for the fittings!)



Straight

Nycoil RECTULASTIC

	Inside x Outside Ø mm	Coil Outside Diameter mm	Working Length	Part Number Blue	Part Number Red
	2,0 x 4,0		25 m	PA040/025/03	PA040/025/02
			50 m	PA040/050/03	PA040/050/02
			100 m	PA040/100/03	PA040/100/02
	2,7 x 4,0		25 m	PA047/025/03	PA047/025/02
			50 m	PA047/050/03	PA047/050/02
			100 m	PA047/100/03	PA047/100/02
	4,0 x 6,0		25 m	PA060/025/03	PA060/025/02
			50 m	PA060/050/03	PA060/050/02
			100 m	PA060/100/03	PA060/100/02
	6,0 x 8,0		25 m	PA080/025/03	PA080/025/02
			50 m	PA080/050/03	PA080/050/02
			100 m	PA080/100/03	PA080/100/02
	8,0 x 10,0		25 m	PA100/025/03	PA100/025/02
	9,5 x 12,0		25 m	PA120/025/03	PA120/025/02
	12,0 x 14,0		25 m	PA140/025/03	PA140/025/02

Hoses in black or transparent available on request.



Inside x Outside Ø mm	Coil Outside Diameter mm	Max. Working Length	Approx. Coils	Part Number
3,1 x 4,7	38	2,5 m	36	SP 05/025
		5,0 m	72	SP 05/050
		7,5 m	108	SP 05/075
		10,0 m	144	SP 05/100
4,8 x 6,3	75	2,5 m	15	SP 06/025
		5,0 m	30	SP 06/050
		7,5 m	45	SP 06/075
		10,0 m	60	SP 06/100
		15,0 m	90	SP 06/150
		22,5 m	140	SP 06/225
6,3 x 7,9	75	2,5 m	15	SP 08/025
		5,0 m	30	SP 08/050
		7,5 m	45	SP 08/075
		10,0 m	60	SP 08/100
		15,0 m	90	SP 08/150
		22,5 m	135	SP 08/225
7,9 x 9,5	115	2,5 m	10	SP 10/025
		5,0 m	20	SP 10/050
		7,5 m	30	SP 10/075
		10,0 m	40	SP 10/100
		15,0 m	60	SP 10/150
		22,5 m	90	SP 10/225
9,5 x 11,8	140	2,5 m	8	SP 12/025
		5,0 m	15	SP 12/050
		7,5 m	23	SP 12/075
		10,0 m	31	SP 12/100
		15,0 m	46	SP 12/150
		22,5 m	70	SP 12/225
12,7 x 15,8	220	5,0 m	10	SP 16/050
		7,5 m	15	SP 16/075
		10,0 m	20	SP 16/100
		15,0 m	30	SP 16/150
		22,5 m	56	SP 16/225

Completely assembled with Swivel Fittings **Nycoil RECTULASTIC**



with swivel fittings and spring guards (Type DV)

Inside x Outside Ø mm	Coil Outside Diameter mm	Max. Working Length	Approx. Coils	Part Number
3,1 x 4,7 R1/8	38	2,5 m	36	SP 05/025/DV
		5,0 m	72	SP 05/050/DV
		7,5 m	108	SP 05/075/DV
		10,0 m	144	SP 05/100/DV
4,8 x 6,3 R1/4	75	2,5 m	15	SP 06/025/DV
		5,0 m	30	SP 06/050/DV
		7,5 m	45	SP 06/075/DV
		10,0 m	60	SP 06/100/DV
		15,0 m	90	SP 06/150/DV
		22,5 m	140	SP 06/225/DV
6,3 x 7,9 R1/4	75	2,5 m	15	SP 08/025/DV
		5,0 m	30	SP 08/050/DV
		7,5 m	45	SP 08/075/DV
		10,0 m	60	SP 08/100/DV
		15,0 m	90	SP 08/150/DV
		22,5 m	135	SP 08/225/DV
7,9 x 9,5 R 1/4	115	2,5 m	10	SP 10/025/DV
		5,0 m	20	SP 10/050/DV
		7,5 m	30	SP 10/075/DV
		10,0 m	40	SP 10/100/DV
		15,0 m	60	SP 10/150/DV
		22,5 m	90	SP 10/225/DV
9,5 x 11,8 R3/8	140	2,5 m	8	SP 12/025/DV
		5,0 m	15	SP 12/050/DV
		7,5 m	23	SP 12/075/DV
		10,0 m	31	SP 12/100/DV
		15,0 m	46	SP 12/150/DV
		22,5 m	70	SP 12/225/DV
12,7 x 15,8 R1/2	220	5,0 m	10	SP 16/050/DV
		7,5 m	15	SP 16/075/DV
		10,0 m	20	SP 16/100/DV
		15,0 m	30	SP 16/150/DV
		22,5 m	47	SP 16/225/DV




with 26 series coupling and plug with spring guards

	Inside x Outside Ø mm	Coil Outside Diameter mm	Max. Working Length	Approx. Coils	Part Number	
6,3 x 7,9	75	2,5 m	15	SP 08/025/K+S		
		5,0 m	30	SP 08/050/K+S		
		7,5 m	45	SP 08/075/K+S		
		10,0 m	60	SP 08/100/K+S		
		15,0 m	90	SP 08/150/K+S		
		22,5 m	135	SP 08/225/K+S		
		7,9 x 9,5	115	2,5 m	10	SP 10/025/K+S
				5,0 m	20	SP 10/050/K+S
				7,5 m	30	SP 10/075/K+S
				10,0 m	40	SP 10/100/K+S
15,0 m	60			SP 10/150/K+S		
9,5 x 11,8	140	2,5 m	8	SP 12/025/K+S		
		5,0 m	15	SP 12/050/K+S		
		7,5 m	23	SP 12/075/K+S		
		10,0 m	31	SP 12/100/K+S		
		15,0 m	46	SP 12/150/K+S		
		22,5 m	70	SP 12/225/K+S		





RECTUFLEX



Relation Working Pressure / Temperature

(only for hoses, not for the fittings!)



Technical Description

Nycoil polyurethane hose was developed to eliminate the two most common limitations of nylon self-storing hoses, kinking and abrasion resistance.

This lightweight, yet extremely durable hose is ideal for use in tough work areas or highly mobile applications.

Special Physical Features

- Light weight (specific weight 9x lower as copper)
- Wide temperature range
- High resistance against moisture
- Saltwater insensitive
- Long service

Mechanical Features

- High vibration prevention
- Perfect abrasion resistance
- High compression characteristics
- Low flow reduction for all kind of media
- Constant solidity

Applications

- Compressed Air
- Lubrication grease/oil
- Gasoline
- Hydraulics
- Vacuum
- Chemicals (on request)
- Food and beverage (on request)

Advantages

- Quick assembly possible
- Light weight
- Low pressure drop
- Different colors for identification
- Good storage possibility due to box packing (straight hoses)
- High abrasion resistance
- Very small bending radius and tight coil diameter economizes on work and storage space
- Working length is 80% of total hose length
- 25 % lighter than rubber
- Specially developed swivel fittings offer lowest possible air flow restrictions
- Superior elasticity and coil memory

Technical Data

Temperature range:

-40°C up to +75°C

Assembled: -20°C up to +70°C

Maximum operating pressure:

see chart

Durometer 95 shore A

All technical data refers to air applications. We will gladly assist you for other media.

Straight

Nycoil RECTUFLEX

	Inside x Outside Ø mm	Coil Outside Diameter mm	Working length	Part Number Blue*	Part Number Red*
	2,5 x 4,0		25 m	PU040/025/03	PU040/025/02
			50 m	PU040/050/03	PU040/050/02
			100 m	PU040/100/03	PU040/100/02
	4,0 x 6,0		25 m	PU060/025/03	PU060/025/02
			50 m	PU060/050/03	PU060/050/02
			100 m	PU060/100/03	PU060/100/02
	6,0 x 8,0		25 m	PU080/025/03	PU080/025/02
			50 m	PU080/050/03	PU080/050/02
			100 m	PU080/100/03	PU080/100/02
	6,5 x 10,0		25 m	PU100/025/03	PU100/025/02
	9,0 x 12,0		25 m	PU120/025/03	PU120/025/02

*Hoses in black or transparent available on request.

Multicolor straight

Nycoil RECTUFLEX

	Inside x Outside Ø mm	Coil Outside Diameter mm	Working length	Part Number 2-color	Part-Number 4-color
	4,0 x 6,0		25 m	MPS02/06/025	MPS04/06/025
	6,0 x 8,0		25 m	MPS02/08/025	MPS04/08/025

Completely assembled

Nycoil RECTUFLEX

	Inside x Outside Ø mm	Coil Outside Diameter mm	Working length	Connection	Part Number
with straight extensions 508 mm and 127mm 	5,0 x 8,0	40	2,0 m	G 1/4	PU08/020/DV
			3,0 m		PU08/030/DV
			4,0 m		PU08/040/DV
			6,0 m		PU08/060/DV
	6,3 x 9,5	60	7,5 m	G 1/4	PU08/075/DV
			2,0 m		PU10/020/DV
			3,0 m		PU10/030/DV
			4,0 m		PU10/040/DV
	8,0 x 12,0	80	6,0 m	G 3/8	PU10/060/DV
			7,5 m		PU10/075/DV
			3,0 m		PU12/030/DV
			4,0 m		PU12/040/DV
	9,5 x 15,0	110	6,0 m	G 3/8	PU12/060/DV
			7,5 m		PU12/075/DV
			4,0 m		PU15/030/DV
			6,0 m		PU15/040/DV
	12,0 x 19,0	110	7,5 m	R 1/2	PU15/060/DV
			6,0 m		PU15/075/DV
6,0 m			PU19/060/DV		
7,5 m			PU19/075/DV		

Multicolor coiled

Nycoil RECTUFLEX

	Inside x Outside Ø mm	Coil Outside Diameter mm	Working length	Part Number 2-color	Part-Number 4-color
	4,0 x 6,0	60	2,5 m	MPC02/06/025	MPC04/06/025
			6,0 m	MPC02/06/060	MPC04/06/060
			7,5 m	MPC02/06/075	MPC04/06/075
	6,0 x 8,0	60	2,5 m	MPC02/08/025	MPC04/08/025
			6,0 m	MPC02/08/060	MPC04/08/060
			7,5 m	MPC02/08/075	MPC04/08/075

⚠ Please consider our security advices on the pages 12/13 ⚠




Polyurethane Hose with Straight Extension

RECTUFLEX

Relation Working Pressure / Temperature

(only for hoses, not for the fittings!)


Description

The extremely elastic Nycoil polyurethane hose with straight extension (100 mm at the connecting end, coils in various lengths, 2000 mm at the tool connection end) has the same favourable properties as our conventional coiled hoses: high shape recovery, low looping tendency, higher abrasion resistance, outstanding stability with very low empty weight. In addition, the straight extensions guarantee more freedom of movement and easier handling in the hard working process.

Advantages

- Extremely flexible – resists kinking
- Impervious to abrasions, heat and oil
- Specially developed swivel fittings offer lowest possible air flow restrictions
- Specially designed retainer sleeve also provides strain relief
- Superior elasticity and coil memory

- Working length is 80% of total hose length
- Very small bending radius and tight coil diameter economizes on work and storage space
- 25% lighter than rubber – easy handling
- Highly resistant to wear – five times the life of rubber
- Low tension – easy to work with
- Eases user fatigue
- Swivel fittings nickel plated
- Greater freedom of movement and easy handling through straight extensions at both ends
- Easy do-it-yourself assembly of couplings, plugs or fixed screw connections (on request with protective sleeve)

Applications

- Pneumatic control
- Air tools
- Assembly workstations
- Laboratories
- Electronic assemblies
- Robotics
- Machine tools
- Instrumentation
- Automobile Industry

Technical Data

Temperature range:
Hose: -40°C up to +75°C
Assembled: -20°C up to +70°C
Maximum operating pressure: see chart
Durometer 95 shore A
Color: blue

Other colors available on request.

All technical data refers to air applications. We will gladly assist you for other media.

Polyurethane Hose with Straight Extension

Nycoil RECTUFLEX

	Inside x Outside Ø mm	Nominal Outside Diameter mm	3 m* Part Number	6 m* Part Number	7,5 m* Part Number
	6,3 x 9,5	60	PU 10/230	PU 10/260	PU 10/275
	8,0 x 12,0	80	PU 12/230	PU 12/260	PU 12/275

Fittings

	Easy do-it-yourself assembly for coupling and plug 25 Series for PU 10 and PU 12 hoses	Part Number
	coupling and spring guard for PU 10	25KAKU10 SPN
	coupling and spring guard for PU 12	25KAKU12 SPN
	plug and spring guard for PU 10	26SFKU10 MXN
	plug and spring guard for PU 12	26SFKU12 MXN
	fixed screw connection and spring guard for PU 10	SV17/10 AN
	fixed screw connection and spring guard for PU 12	SV17/12 AN
	protective sleeve (black)	T1300-351 BK

* total hose length



Straight extension

The straight hose extensions attached to the coils optimise the handling of the complete hose unit and offer the user more freedom of movement in the working process. It combines the advantages of the straight hose connection on the tool with the high level of elasticity of the coil system.



Bend protection

Couplings and nipples are supplied with plastic bend protection – this provides lasting protection against the hose snapping.



Easy do-it-yourself assembly

Thanks to the highly user-friendly design of the connecting technology, you can assemble the couplings, plugs or fitting connections yourself in no time. You automatically have maximum flexibility and save time and costs.



Protective sleeve

After assembly of the connecting material, a protective sleeve (flush with the front side of the coupling) can be pushed on to prevent metal parts from scratching sensitive surfaces.




SUPERBRAID®



Relation Working Pressure / Temperature

(only for hoses, not for the fittings!)



Technical Description

Superbraid polyurethane recoiled hose is extruded with an inner braid for additional strength. This „integral piece“ process eliminates the need of bonding individual layers of hoses, braiding and cover which tend to separate overtime due to bending, flexing and pulsating. Superbraid combines the durability of bulkier hoses with the kink resistance and elasticity of polyurethane to make a tough, long lasting hose that is user friendly. Superbraid can be used with either our barb and sleeve fittings or reusable polyurethane fittings.

Technical Data

Temperature range:
-40°C up to +75°C

Maximum operating pressure:
see chart

Durometer: 85 shore A

Color: light blue transparent

Advantages

- Same flexibility as a polyurethane hose
- Usable at 15 bar (safety factor of 4 to 1)
- Flexible even at -40°C
- Highly kinking resistant; virtually undamaged by twisting or crushing
- Extremely flexible and easy to use; minimizes worker fatigue
- Superior elasticity and coil memory
- Excellent abrasion resistance; 6 to 10 times better than rubber or nylon
- Factory applied thread sealant supplied on male swivel fitting
- Very small bending radius and tight coil diameter economizes on work and storage space
- Both fittings nickel plated

All technical data refers to air applications. We will gladly assist you for other media.

Straight

Nycoil SUPERBRAID


	Inside x Outside Ø mm	Coil Outside Diameter mm	Working Length	Connection	Part Number
	6,3 x 9,5		25 m		PG10/025
	7,9 x 11,7		25 m		PG12/025

Coiled

Nycoil SUPERBRAID

	Inside x Outside Ø mm	Coil Outside Diameter mm	Working Length	Connection	Part Number
	6,3 x 9,5	42	3,0 m	G 1/4	PG 10/030/DV
			6,0 m		PG 10/060/DV
			7,5 m		PG 10/075/DV
	7,9 x 11,7	55	3,0 m	G 3/8	PG 12/030/DV
			6,0 m		PG 12/060/DV
			7,5 m		PG 12/075/DV

assembled with nickel plated swivel fittings on both ends



Technical Description

Thanks to the special production techniques, this hose keeps what it promises, even after frequent use and under extreme conditions. Ultra-Lite is made of polyurethane which is reinforced by a hose braid made of Dacron Polyester. Unlike conventional 3-layer textile hoses where the individual layers are not permanently bonded to each other, our Nycoil Ultra-Lite is specially made. The hose is heated and the different layers, textile and PU, melt to form a permanent bond with each other. Thanks to this process, the Ultra-Lite is extremely flexible and, above all, extremely durable. Its high level of flexibility and low weight make for easy handling. The Ultra-Lite retains its properties down to temperatures as low as -40°C.

Advantages

- Approx. 20% lighter than comparable hoses
- Further weight reduction through production of threaded couplings and hose nuts in light aluminium
- This allows us to reduce the total weight of the hose system, with all advantages of easy hose handling
- Extremely flexible even down to -40°C
- Anti-kink
- Highly temperature-resistant
- Easy do-it-yourself assembly of couplings, plugs or fixed screw connections from various Rectus series (available with protective sleeve on request)

Technical Data


Temperature range:
-40°C up to +75°C
Maximum operating pressure:
see chart
Color: yellow

All technical data refers to air applications. We will gladly assist you for other media.



Relation Working Pressure / Temperature

(only for hoses, not for the fittings!)



Straight

Nycoil ULTRA-LITE SUPERBRAID

	Inside x Outside Ø mm	Coil Outside Diameter mm	Working Length	Weight	Part Number
	9,5 x 13,0		25 m	75 g/m	SU13/025/05
	12,7 x 17,4		25 m	127 g/m	SU17/025/05

Fittings for Hose SU13

Nycoil ULTRA-LITE SUPERBRAID

	Series	Flow at 6 bar (Pressure drop 0.5 bar)	Weight	Part Number
	Coupling 1600 Series	2100 l/min	100 g	1600 KAKU13 SPN
	Coupling 31 Series	1060 l/min	90 g	31 KAKU13 SPN
	Coupling 1400 Series	960 l/min	90 g	1400 KAKU13 SPN
	Plug 26 Series (1600)		50 g	26 SFKU13 MXN
	Plug 31 Series		55 g	31 SFKU13 MXN
	Plug 23 Series (1400)		55 g	23 SFKU13 MXN
	fixed screw connection G 3/8 o.		50 g	SV 17/13 AN
	f. screw con. for hose SU17, G 1/2 o.		60 g	SV 21/17 AN

⚠ Please consider our security advices on the pages 12/13 ⚠




RECTUSPARK®



Relation Working Pressure / Temperature

(only for hoses, not for the fittings!)



Technical Description

The blue ether based 95 durometer polyurethane inner tubing is offered in two metric sizes. It is covered with a specially formulated black flame retardant cover which has excellent tear and tensile strength, yet is resistant to oils, greases, acids, bases, aqueous solutions, ozone, UV light and heat aging. This cover has strong insulative properties and meets UL-94-VO specifications.

Advantages

Black flame retardant cover protects tubing from incidental contact with welding sparks. The cover does not adhere to the inner tube, allowing the jacket to be easily skived back for connection with conventional compression or push-in fittings.

- Extremely flexible with excellent bend radius capability
- Very resistant to kink damage
- Broad range of chemical resistance
- Good aging resistance for long service life


Technical Data

Temperature range:
-25°C up to +70°C
Max. working pressure:
8 bar (depending on used temperature)

All technical data refers to air applications. We will gladly assist you for other media.


Straight

Nycoil RECTUSPARK

	Inside x Outside Ø mm	Protective Jacket Ø mm	Coil Outside Diameter mm	Working Length	Part Number
	5,0 x 8,0	10		25 m	WSS08/025/01

Coiled

Nycoil RECTUSPARK

	Inside x Outside Ø mm	Protective Jacket Ø mm	Coil Outside Diameter mm	Working Length	Part Number
	4,0 x 6,0	8	60	6,0 m	WSC06/060/01
				7,5 m	WSC06/075/01

RECTUSOFT



Technical Description

The new generation of highly flexible Rectus hoses consists of a textile-reinforced, 3-ply PVC hose with a smooth inner tube, polyester thread insert and abrasion-proof outer covering.

Advantages

Low weight, very high flexibility, highly resistant, high resistance to pressure, UV-resistant, long service life, shock and tread-resistant, non-buckling, manufacturer's imprint with technical specifications.

Technical Data

Working temperature:
-25°C up to +60°C

Maximum operating pressure:
at +23°C: 15 bar

Bursting pressure:
at +23°C: 63 bar

Color: light blue



Straight


Nycoil RECTUSOFT

	Inside x Outside Ø mm	Coil Outside Diameter mm	Package Unit	Part Number
	6,3 x 11,0	45	50 m	PVC06/050/03
	9,0 x 14,5	63	50 m	PVC09/050/03
	12,7 x 19,0	89	50 m	PVC12/050/03



Relation Working Pressure / Temperature

(only for hoses, not for fittings!)



Technical Description

PVDF tubing resists a broad range of chemicals, and its low permeability, out-gassing and extractable properties make it ideal for ultrapure applications. Unlike PTFE, PVDF withstands mechanical properties that resist creep and cold flow, while offering significant cost savings.

Special physical features

- Complies with USP Class VI Standards
- Acceptable for USDA
- Meets FDA Requirements and UL 94 V-O (Flame Retardant Requirements)
- Odorless & Tasteless
- Sterilizable by Gamma Radiation, Autoclave or Ozones
- Acceptable for 3-A Sanitary Standards for Dairy Equipment

Typical Chemical Applications:

Pesticides, petrochemical, wastewater treatment, pulp and paper bleaching operations

Chemical Resistance:

Oxidants, radiation, ultraviolet radiation, acids, alcohol, aliphatic, aromatics, mild basis, chloride, halogens, fungus, out-gassing

Technical Data

Temperature Range: -40°C up to +120°C

Maximum Operating Pressure: see chart


Color: opak

All technical data refers to air applications. We will gladly assist you for other media.

Useable with PVDF couplings 21 series + 48 series. (Page 232)


Straight

Nycoil RECTUCHEM

	Inside x Outside Ø mm	Coil Outside Diameter mm	Working Length	Part Number
	4,0 x 6,0		25 m	KYS06/025/00
	6,0 x 8,0		25 m	KYS08/025/00
	10,0 x 12,0		25 m	KYS12/025/00

Coiled

Nycoil RECTUCHEM

	Inside x Outside Ø mm	Coil Outside Diameter mm	Working Length	Part Number
	4,0 x 6,0	40	2,5 m	KYC06/025/00
			6,0 m	KYC06/060/00
	6,0 x 8,0	65	2,5 m	KYC08/025/00
			6,0 m	KYC08/060/00
	9,0 x 12,0	140	2,5 m	KYC12/025/00
			6,0 m	KYC12/060/00

Hose Accessories

Accessories

Hoses / Tubing

Low Pressure

Hose Cutter

Nycoil Accessories




(up to outside Diameter 14 mm)

	L	L1	Part Number
	79	25	RP 71-00

Swivelling Spring Guard


Nycoil Accessories



	Connection mm	Hex	Length	Material	Part Number
	R 1/8 3,1 x 4,7	11		Brass	DV 10/05
	R 1/4 4,8 x 6,3	14		Brass	DV 13/06
	R 1/4 6,3 x 7,9	14		Brass	DV 13/08
	R 1/4 7,9 x 9,5	15		Brass	DV 13/10
	R 3/8 9,5 x 11,8	19		Brass	DV 17/12
	R 1/2 12,7 x 15,8	22		Brass	DV 21/16

Fixed Spring Guard

Nycoil Accessories



with spring guard

* inner cone 45°

	Connection mm	Hex	Length	Material	Part Number
	M5 4,0 x 6,0	8	103	Brass	SV 05/06
	G 1/8 4,0 x 6,0	12	103	Brass	SV 10/06
	G 1/8 6,0 x 8,0	12	106	Brass	SV 10/08
	G 1/4 4,0 x 6,0	17	103	Brass	SV 13/06
	G 1/4 6,0 x 8,0	17	106	Brass	SV 13/08
	G 1/4 8,0 x 10,0	17	119	Brass	SV 13/10
	G 1/4 9,0 x 12,0	17	123	Brass	SV 13/12
	G 3/8 6,0 x 8,0*	19	106	Brass	SV 17/08
	G 3/8 8,0 x 10,0*	19	119	Brass	SV 17/10
	G 3/8 9,0 x 12,0*	19	123	Brass	SV 17/12

Reusable Swivel Fittings

Nycoil Accessories




	Connection mm	for PU Hose	Part Number
	G 1/4	PU 08	PV 13/08
		PU 10	PV 13/10
	G 3/8	PU 12	PV 17/12
		PU 15	PV 17/15

⚠ Please consider our security advices on the pages 12/13 ⚠


Worm Drive Hose Clips

Accessories

	Spread	Height	Part Number
	10 - 16 mm	8 mm	KA 1016
	12 - 22 mm	8 mm	KA 1222
	16 - 27 mm	8 mm	KA 1627
	23 - 35 mm	9 mm	KA 2335
	30 - 45 mm	9 mm	KA 3045
	32 - 50 mm	12 mm	KA 3250
	40 - 60 mm	12 mm	KA 4060
	50 - 70 mm	12 mm	KA 5070
	60 - 80 mm	12 mm	KA 6080


,O'-Clips


Accessories

	Spread	Height	Part Number
 <p>Steel, chromatized</p>	5 - 7 mm	6 mm	KB 0507
	7 - 9 mm	7 mm	KB 0709
	9 - 11 mm	7 mm	KB 0911
	11 - 13 mm	7 mm	KB 1113
	13 - 15 mm	7,5 mm	KB 1315
	15 - 18 mm	8 mm	KB 1518
	17 - 20 mm	8,5 mm	KB 1720
	20 - 23 mm	9 mm	KB 2023
	25 - 28 mm	10 mm	KB 2528
	28 - 31 mm	10 mm	KB 2831
	31 - 34 mm	10 mm	KB 3134
	34 - 37 mm	10 mm	KB 3437
	37 - 40 mm	10 mm	KB 3740
	40 - 43 mm	10 mm	KB 4043
	43 - 46 mm	10 mm	KB 4346

Hose Drum

Accessories

	Description	Connection	Working Length	Working Pressure	Part Number
	- PU-Hose (9,0 x 14,5), black	25KA Series	15 m	15 bar	DST 915-25
	- Casing made of polypropylene				
	- no mechanical guidance				
	- Completely assembled with coupling and plug 25 series				
	- CE-certified				



Lords of the air.



The Nycoil brand high-performance hose solutions have stood for innovation and reliability in the widest range of applications for decades. With our 4 material qualities, suitable products are available for every conceivable medium – whether straight or coiled hose.



Notices

A series of horizontal dotted lines for writing notices.

INDEX OF CONTENTS

Low-Pressure

Series	Material	Page
02KA	Brass/Steel	22
08KF	Brass/Steel	87
08KL	Brass/Steel	176
13KA	Brass/Steel	71
1400KA	Brass/Steel	54
1423KA	Brass/Steel	56
14KA	Brass/Steel	44
14KE	Self-Venting	280
1600KA	Brass/Steel	77
1625KA	Brass/Steel	79
1700KA	Brass/Steel	97
1700KB	Brass/Steel	148
1727KA	Brass/Steel	99
17KA	Brass/Steel	32
18KA	Brass/Steel	46
18KE	Self-Venting	282
19KA	Brass/Steel	48
20KA	Brass/Steel	26
20KA	Stainless Steel	182
20KB	Brass/Steel	120
20KB	Stainless Steel	200
204KL	Brass/Steel	162
204KL	Stainless Steel	222
206KL	Brass/Steel	169
206KL	Stainless Steel	228
209KL	Brass/Steel	178
209KL	Stainless Steel	234
21KA/21KB	Thermoplastic	242
21KA	Brass/Steel	34
21KA	Stainless Steel	185
21KA	Coded	300
21KB	Brass/Steel	125
21KB	Stainless Steel	205
21KD	Safety	276
21KL	Brass/Steel	164
21KL	Stainless Steel	224
21KS	Safety	266
22KA	Brass/Steel	50
23KA	Brass/Steel	52
23KE	Self-Venting	284
24KA	Brass/Steel	58
24KE	Self-Venting	286
25KA	Brass/Steel	73
25KA	Stainless Steel	192
25KA	Coded	303
25KB	Brass/Steel	139
25KB	Stainless Steel	209
25KD	Safety	278
25KE	Self-Venting	290
25KL	Brass/Steel	171
25KL	Stainless Steel	230
25KS	Safety	270
26KA	Brass/Steel	66
26KA	Stainless Steel	189
26KB	Brass/Steel	136
26KE	Self-Venting	288

Series	Material	Page
27KA	Brass/Steel	95
27KA	Stainless Steel	196
27KB	Brass/Steel	145
27KB	Stainless Steel	213
27KE	Self-Venting	292
28KS	Safety	273
29KA	Brass/Steel	113
303KB	Stainless Steel	203
30KA	Brass/Steel	91
31KA	Brass/Steel	60
32KA	Brass/Steel	101
33KA	Brass/Steel	81
34KA	Brass/Steel	103
37KA	Brass/Steel	109
37KE	Self-Venting	294
38KB	Brass/Steel	156
38KB/SF	Brass/Steel	115
39KB	Brass/Steel	158
39KB/SF	Brass/Steel	117
39KL	Brass/Steel	180
40KA	Brass/Steel	93
41KF	Brass/Steel	105
42KF	Brass/Steel	107
45KF	Brass/Steel	89
48KA/KB	Thermoplastic	251
50KA	Brass/Steel	24
51KB	Brass/Steel	130
51KB/SF	Brass/Steel	62
52KB	Brass/Steel	132
52KB/SF	Brass/Steel	64
57KB	Brass/Steel	152
57KB/SF	Brass/Steel	111
65-67	Coded	306
71KB	Brass/Steel	124
71KB	Stainless Steel	216
71KB	Thermoplastic	256
72KB	Brass/Steel	134
72KB	Stainless Steel	217
72KB	Thermoplastic	257
73KB	Brass/Steel	144
73KB	Stainless Steel	218
73KB	Thermoplastic	258
74KB	Brass/Steel	150
74KB	Stainless Steel	219
74KB	Thermoplastic	259
75KB	Brass/Steel	154
75KB	Stainless Steel	220
75KB	Thermoplastic	260
76KB	Brass/Steel	160
76KB	Stainless Steel	221
76KB	Thermoplastic	261
77KB	Thermoplastic	262
84KA	Brass/Steel	83
90KA	Brass/Steel	40
91KA	Brass/Steel	30
93KF	Brass/Steel	85

Series	Material	Page
93KL	Brass/Steel	174
95KS	Breathing Air	296
96KS	Breathing Air	298
99KL	Stainless Steel	232

Accessories

Description	Page
2 Way Manifold	329
2 Way Manifold Assembly	330
3 Way Manifold	329
3 Way Manifold Assembly	330
4 Port Manifold	319
90° Elbow	319
Blanking Plug	320
Blanking Plug, tapered	321
Blow-Guns	332
Bulkhead Fitting	324
Bulkhead Lock Nut	320
Dust Caps	331
Equal Ended Cross	322
Equal Ended Tee	322
Female Elbow	328
Female Stud Fitting	322
Female Tee	327
Female Tee	327
Female x Female Socket	318
Female Y	328
Fixed Spring Guard	325
Hose Repairer	315
Hose Repairer, short	315
Hose Tail Barb, Fem. Thread	315
Hose Tail Barb, Male Thread	313
Hose Tail Elbow	324
Hose Tail, long	313
Hose Tail, short	312
Male Elbow	327
Male Stud Elbow	326
Male Stud Run Tee	325
Male x Male Nipple	316
Male x Male Nipple adjust.	317
Male-/Female-Elbow	328
Manifold	330
Multi-Port Manifold	320
Pressure Reducing Valve	331
RectuTest	310
Reducing Bush, long	318
Reducing Bush, short	317
Single Banjo Fitting	323
Spring Guard	326
Stud Fitting	324
Swivel Joint	331
Swivelling Spring Guard	322
Tee	319
Threaded Nut	312
Washer, Aluminium	321

Accessories

Description	Page
--------------------	-------------

Washer, Fiber	321
Washer, PVC	321

Hoses and Tubing

Description	Page
--------------------	-------------

Nylon 12

RECTULASTIC	344
-------------	-----

Polyurethane

RECTUFLEX	348
with straight extension	350
SUPERBRAID	352
ULTRA-LITE	353
RECTUSPARK	354

PVC

RECTUSOFT	355
-----------	-----

PVDF

RECTUCHEM	356
-----------	-----

Accessories Hoses

Clips	358
Fittings	357
Hose Cutter	357
Hose Reels	358





Parker's Motion & Control Technologies

At Parker, we're guided by a relentless drive to help our customers become more productive and achieve higher levels of profitability by engineering the best systems for their requirements. It means looking at customer applications from many angles to find new ways to create value. Whatever the motion and control technology need, Parker has the experience, breadth of product and global reach to consistently deliver. No company knows more about motion and control technology than Parker. For further info call 1 800 C-Parker (1 800 272 7537)



Aerospace

Key Markets

Aftermarket services
Commercial transports
Engines
General & business aviation
Helicopters
Launch vehicles
Military aircraft
Missiles
Power generation
Regional transports
Unmanned aerial vehicles

Key Products

Control systems & actuation products
Engine systems & components
Fluid conveyance systems & components
Fluid metering, delivery & atomization devices
Fuel systems & components
Fuel tank inerting systems
Hydraulic systems & components
Thermal management
Wheels & brakes



Climate Control

Key Markets

Agriculture
Air conditioning
Construction Machinery
Food & beverage
Industrial machinery
Life sciences
Oil & gas
Precision cooling
Process
Refrigeration
Transportation

Key Products

Accumulators
Advanced actuators
CO₂ controls
Electronic controllers
Filter driers
Hand shut-off valves
Heat exchangers
Hose & fittings
Pressure regulating valves
Refrigerant distributors
Safety relief valves
Smart pumps
Solenoid valves
Thermostatic expansion valves



Electromechanical

Key Markets

Aerospace
Factory automation
Life science & medical
Machine tools
Packaging machinery
Paper machinery
Plastics machinery & converting
Primary metals
Semiconductor & electronics
Textile
Wire & cable

Key Products

AC/DC drives & systems
Electric actuators, gantry robots & slides
Electrohydraulic actuation systems
Electromechanical actuation systems
Human machine interface
Linear motors
Stepper motors, servo motors, drives & controls
Structural extrusions



Filtration

Key Markets

Aerospace
Food & beverage
Industrial plant & equipment
Life sciences
Marine
Mobile equipment
Oil & gas
Power generation & renewable energy
Process
Transportation
Water Purification

Key Products

Analytical gas generators
Compressed air filters & dryers
Engine air, coolant, fuel & oil filtration systems
Fluid condition monitoring systems
Hydraulic & lubrication filters
Hydrogen, nitrogen & zero air generators
Instrumentation filters
Membrane & fiber filters
Microfiltration
Sterile air filtration
Water desalination & purification filters & systems



Fluid & Gas Handling

Key Markets

Aerial lift
Agriculture
Bulk chemical handling
Construction machinery
Food & beverage
Fuel & gas delivery
Industrial machinery
Life sciences
Marine
Mining
Mobile
Oil & gas
Renewable energy
Transportation

Key Products

Check valves
Connectors for low pressure fluid conveyance
Deep sea umbilicals
Diagnostic equipment
Hose couplings
Industrial hose
Mooring systems & power cables
PTFE hose & tubing
Quick couplings
Rubber & thermoplastic hose
Tube fittings & adapters
Tubing & plastic fittings



Hydraulics

Key Markets

Aerial lift
Agriculture
Alternative energy
Construction machinery
Forestry
Industrial machinery
Machine tools
Marine
Material handling
Mining
Oil & gas
Power generation
Refuse vehicles
Renewable energy
Truck hydraulics
Turf equipment

Key Products

Accumulators
Cartridge valves
Electrohydraulic actuators
Human machine interfaces
Hybrid drives
Hydraulic cylinders
Hydraulic motors & pumps
Hydraulic systems
Hydraulic valves & controls
Hydrostatic steering
Integrated hydraulic circuits
Power take-offs
Power units
Rotary actuators
Sensors



Pneumatics

Key Markets

Aerospace
Conveyor & material handling
Factory automation
Life science & medical
Machine tools
Packaging machinery
Transportation & automotive

Key Products

Air preparation
Brass fittings & valves
Manifolds
Pneumatic accessories
Pneumatic actuators & grippers
Pneumatic valves & controls
Quick disconnects
Rotary actuators
Rubber & thermoplastic hose & couplings
Structural extrusions
Thermoplastic tubing & fittings
Vacuum generators, cups & sensors



Process Control

Key Markets

Alternative fuels
Biopharmaceuticals
Chemical & refining
Food & beverage
Marine & shipbuilding
Medical & dental
Microelectronics
Nuclear Power
Offshore oil exploration
Oil & gas
Pharmaceuticals
Power generation
Pulp & paper
Steel
Water/wastewater

Key Products

Analytical Instruments
Analytical sample conditioning products & systems
Chemical injection fittings & valves
Fluoropolymer chemical delivery fittings, valves & pumps
High purity gas delivery fittings, valves, regulators & digital flow controllers
Industrial mass flow meters/controllers
Permanent no-weld tube fittings
Precision industrial regulators & flow controllers
Process control double block & bleeds
Process control fittings, valves, regulators & manifold valves



Sealing & Shielding

Key Markets

Aerospace
Chemical processing
Consumer
Fluid power
General industrial
Information technology
Life sciences
Microelectronics
Military
Oil & gas
Power generation
Renewable energy
Telecommunications
Transportation

Key Products

Dynamic seals
Elastomeric o-rings
Electro-medical instrument design & assembly
EMI shielding
Extruded & precision-cut, fabricated elastomeric seals
High temperature metal seals
Homogeneous & inserted elastomeric shapes
Medical device fabrication & assembly
Metal & plastic retained composite seals
Shielded optical windows
Silicone tubing & extrusions
Thermal management
Vibration dampening

ENGINEERING YOUR SUCCESS.

Parker Worldwide

AE – UAE, Dubai

Tel: +971 4 8127100
parker.me@parker.com

AR – Argentina, Buenos Aires

Tel: +54 3327 44 4129

AT – Austria, Wiener Neustadt

Tel: +43 (0)2622 23501-0
parker.austria@parker.com

AT – Eastern Europe,

Wiener Neustadt
Tel: +43 (0)2622 23501 900
parker.easteurope@parker.com

AU – Australia, Castle Hill

Tel: +61 (0)2-9634 7777

AZ – Azerbaijan, Baku

Tel: +994 50 2233 458
parker.azerbaijan@parker.com

BE/LU – Belgium, Nivelles

Tel: +32 (0)67 280 900
parker.belgium@parker.com

BR – Brazil, Cachoeirinha RS

Tel: +55 51 3470 9144

BY – Belarus, Minsk

Tel: +375 17 209 9399
parker.belarus@parker.com

CA – Canada, Milton, Ontario

Tel: +1 905 693 3000

CH – Switzerland, Etoy

Tel: +41 (0)21 821 87 00
parker.switzerland@parker.com

CL – Chile, Santiago

Tel: +56 2 623 1216

CN – China, Shanghai

Tel: +86 21 2899 5000

CZ – Czech Republic, Klecany

Tel: +420 284 083 111
parker.czechrepublic@parker.com

DE – Germany, Kaarst

Tel: +49 (0)2131 4016 0
parker.germany@parker.com

DK – Denmark, Ballerup

Tel: +45 43 56 04 00
parker.denmark@parker.com

ES – Spain, Madrid

Tel: +34 902 330 001
parker.spain@parker.com

FI – Finland, Vantaa

Tel: +358 (0)20 753 2500
parker.finland@parker.com

FR – France, Contamine s/Arve

Tel: +33 (0)4 50 25 80 25
parker.france@parker.com

GR – Greece, Athens

Tel: +30 210 933 6450
parker.greece@parker.com

HK – Hong Kong

Tel: +852 2428 8008

HU – Hungary, Budapest

Tel: +36 1 220 4155
parker.hungary@parker.com

IE – Ireland, Dublin

Tel: +353 (0)1 466 6370
parker.ireland@parker.com

IN – India, Mumbai

Tel: +91 22 6513 7081-85

IT – Italy, Corsico (MI)

Tel: +39 02 45 19 21
parker.italy@parker.com

JP – Japan, Tokyo

Tel: +81 (0)3 6408 3901

KR – South Korea, Seoul

Tel: +82 2 559 0400

KZ – Kazakhstan, Almaty

Tel: +7 7272 505 800
parker.easteurope@parker.com

MX – Mexico, Apodaca

Tel: +52 81 8156 6000

MY – Malaysia, Shah Alam

Tel: +60 3 7849 0800

NL – The Netherlands,

Oldenzaal
Tel: +31 (0)541 585 000
parker.nl@parker.com

NO – Norway, Asker

Tel: +47 66 75 34 00
parker.norway@parker.com

NZ – New Zealand, Mt Wellington

Tel: +64 9 574 1744

PL – Poland, Warsaw

Tel: +48 (0)22 573 24 00
parker.poland@parker.com

PT – Portugal, Leca da Palmeira

Tel: +351 22 999 7360
parker.portugal@parker.com

RO – Romania, Bucharest

Tel: +40 21 252 1382
parker.romania@parker.com

RU – Russia, Moscow

Tel: +7 495 645-2156
parker.russia@parker.com

SE – Sweden, Spånga

Tel: +46 (0)8 59 79 50 00
parker.sweden@parker.com

SG – Singapore

Tel: +65 6887 6300

SK – Slovakia, Banská Bystrica

Tel: +421 484 162 252
parker.slovakia@parker.com

SL – Slovenia, Novo Mesto

Tel: +386 7 337 6650
parker.slovenia@parker.com

TH – Thailand, Bangkok

Tel: +662 717 8140

TR – Turkey, Istanbul

Tel: +90 216 4997081
parker.turkey@parker.com

TW – Taiwan, Taipei

Tel: +886 2 2298 8987

UA – Ukraine, Kiev

Tel: +380 44 494 2731
parker.ukraine@parker.com

UK – United Kingdom,

Warwick
Tel: +44 (0)1926 317 878
parker.uk@parker.com

US – USA, Cleveland

Tel: +1 216 896 3000

VE – Venezuela, Caracas

Tel: +58 212 238 5422

ZA – South Africa,

Kempton Park
Tel: +27 (0)11 961 0700
parker.southafrica@parker.com

European Product Information Centre

Free phone: 00 800 27 27 5374

(from AT, BE, CH, CZ, DE, EE, ES, FI, FR, IE, IL, IS, IT, LU, MT, NL, NO, PT, SE, SK, UK)

**Parker Hannifin Manufacturing
Germany GmbH & Co. KG**

Quick Coupling Division Europe
Daimlerstr. 7
71735 Eberdingen – Germany
Phone +49 7042 100 0
Fax +49 7042 100 147
www.rectus.de

